

GPVN-17.5kV Indoor AC High Voltage Vacuum Circuit Breaker

Summary

GPVN -15/17.5kV indoor AC high voltage vacuum circuit breaker is a type of holistic and completely sealed high voltage switchgear, it has compact dimension and small volume. The VCB applies to power system of rated voltage 13.8~17.5kV, three-phase and AC 50/60Hz. It is applicable in occasions with frequent operations, acting to protect and control line and electric apparatus. The product conforms to IEC62271-200, GB1984, JB3855 and DL1403 and passes type test.

Ambient condition

Ambient temperature: -25°C ~ 45°C , daily average: ≤ 35°C

Altitude: 1000m(Standard); can up to 4500m for special ordering;

Relative humidity: daily average ≤ 95%, monthly average ≤ 90%;

Earthquake intensity: ≤ 8 degree;

Applicable occasions should be free from inflammables, explosives, corrosives and severe vibration.



Model and its meaning

GP VN - 15 □ / 630 - 25

Rated short-circuit breaking current (kA)

Rated current (A)

Blank: Insulating sleeve type; E: Embedded type

Rated voltage (kV)

Indoor vacuum circuit breaker

Company feather code

Product feature

- 1) Holistic structure
- 2) Sealed spark chamber
- 3) Effective vacuum arc-extinguish
- 4) Good mechanical behavior
- 5) Various mounting approach

Main technical parameters table for 17.5kV vacuum circuit breaker

No.	Name		Unit	Data
1	Rated voltage		kV	15/17.5
2	Rated frequency		Hz	50/60
3	Rated current		A	630~4000
4	Rated short-circuit opening current		kA	50
5	Rated short-circuit making current (peak)		kA	130
6	Rated peak withstand current		kA	130
7	Rated short-time withstand current		kA	50
8	Electrical life		times	20
9	Rated short-time withstand current		s	4
10	Rated operating sequence			O-180s-CO-180s-CO
11	Rated insulation level	1 min Power frequency withstand voltage (RMS)	kV	38
		Lighting impulse withstand voltage (peak)	kV	95
12	Mechanical life		times	10000
13	Weight		kg	110~170