Machine Learning Basics: Supervised, Unsupervised and Reinforcement Learning

Knowledge document 002 of 100

Introduction to Machine Learning

Machine Learning (ML) is a part of Artificial Intelligence in which computers learn patterns from data instead of being explicitly programmed with rules. The American computer scientist Arthur Samuel, who built a self-learning checkers program at IBM, described machine learning in 1959 as giving computers the ability to learn without being explicitly programmed. In traditional programming a developer writes rules and the computer applies them to data to produce answers. In machine learning the computer is given data and the expected answers, and it works out the rules by itself. These learned rules are stored in a model, which can then make predictions on new data it has never seen.

Machine learning powers email spam filters, product recommendations, fraud detection, speech recognition, medical image analysis, language translation and many other applications. There are three main types of machine learning: supervised learning, unsupervised learning and reinforcement learning. Each differs in the kind of data it uses and the way it learns.

Supervised Learning

Supervised learning is a type of machine learning in which the model is trained on labelled data. Labelled data means each training example comes with the correct answer, called the label or target. For example, a set of house records may include the area, number of rooms and location (the inputs, called features) together with the actual selling price (the label). The model studies many examples, compares its predictions with the correct labels, measures its error using a loss function, and adjusts itself to reduce that error. It is called "supervised" because the labelled answers act like a teacher supervising the student.

Supervised learning has two major task types. Classification predicts a category, such as whether an email is spam or not spam, whether a tumour is benign or malignant, or whether an image shows a cat or a dog. Regression predicts a continuous number, such as the price of a house, tomorrow's temperature or the future sales of a shop. Popular supervised algorithms include linear regression, logistic regression, decision trees, random forests, support vector machines, k-nearest neighbours and neural networks.

Unsupervised Learning

Unsupervised learning works with unlabelled data. There are no correct answers provided; the algorithm must find hidden structure, groups or patterns in the data by itself. The most common unsupervised task is clustering, which groups similar items together. A classic example of unsupervised learning is customer segmentation: a retailer feeds the purchase history of thousands of customers into a clustering algorithm such as k-means, and the algorithm groups customers into segments like frequent buyers, bargain hunters and occasional visitors, without anyone telling it what the groups should be. Other examples include grouping news articles by topic, detecting unusual transactions as anomalies, and recommending items based on similar users.

Other unsupervised techniques include dimensionality reduction, such as Principal Component Analysis (PCA), which compresses data with many features into fewer features while keeping the important information, and association rule mining, which finds items often bought together, like bread and butter in a market basket analysis. A related approach called semi-supervised learning uses a small amount of labelled data together with a large amount of unlabelled data. Self-supervised learning, used to train large language models, creates labels automatically from the data itself, for example by hiding a word in a sentence and asking the model to predict it.

Reinforcement Learning

Reinforcement learning (RL) is learning by trial and error through interaction with an environment. A software agent observes the current state of the environment, chooses an action, and receives a reward (a positive number) or a penalty (a negative number) as feedback. The goal of the agent is to learn a policy, a strategy for choosing actions, that maximises the total reward it collects over time. Reinforcement learning uses rewards as its only guide: actions that lead to good outcomes are rewarded and become more likely, while actions that lead to bad outcomes are penalised and become less likely.

A simple way to understand how reinforcement learning uses rewards is to imagine training a dog. When the dog sits on command it gets a treat; when it does not, it gets nothing. Over many repetitions the dog learns which behaviour earns the treat. In the same way, a game-playing agent receives +1 for winning and -1 for losing and gradually learns winning strategies. An important idea is the balance between exploration (trying new actions to discover better rewards) and exploitation (using the best known action). Famous successes include DeepMind's AlphaGo, which defeated the Go champion Lee Sedol in 2016, robots that learn to walk, self-driving car research, data-centre cooling optimisation, and the use of reinforcement learning from human feedback (RLHF) to make chatbots more helpful. Common algorithms include Q-learning, Deep Q-Networks (DQN) and policy gradient methods.

Choosing the Right Type

The choice of learning type depends on the data available and the goal. If labelled examples exist and the aim is to predict a known outcome, supervised learning is used. If there are no labels and the aim is to explore the data, unsupervised learning is used. If an agent must make a sequence of decisions in an environment and can receive feedback, reinforcement learning is used. A typical machine learning workflow has these steps: collect data, clean and prepare it, split it into training and test sets, train a model, evaluate it, and deploy it. Two common problems are overfitting, where a model memorises the training data and performs poorly on new data, and underfitting, where it is too simple to capture the pattern.

Machine Learning in India

Machine learning is widely used in India. Banks and UPI payment apps use supervised models for fraud detection. E-commerce companies such as Flipkart use ML to recommend products and predict delivery times. Farmers receive crop-yield and pest predictions based on weather and satellite data. Hospitals use image classifiers to screen for diabetic retinopathy and tuberculosis. Chennai-based startups and IT firms build predictive maintenance systems for factories using ML on sensor data.

Challenges and Future

Machine learning needs good-quality data, can inherit bias from that data, and many models are hard to explain. Future directions include learning from smaller datasets, federated learning that protects privacy by training on devices, and AutoML that automates model building.

Quick Facts

- Supervised learning trains on labelled data, with correct answers provided for each example.
- Clustering of customers with k-means is a classic example of unsupervised learning.
- Reinforcement learning trains an agent using rewards and penalties to maximise total reward.
- Classification predicts categories while regression predicts continuous numbers.
- Arthur Samuel described machine learning in 1959 as computers learning without being explicitly programmed.