

Screenshots of created REST API

```
ubuntu@ip-172-31-29-225 × ubuntu@ip-172-31-29-225 × sintija-client.ipynb ×
ubuntu@ip-172-31-29-225:~/sintija-REST-API$ python3 sintija-rest-api.py
* Serving Flask app 'sintija-rest-api' (lazy loading)
* Environment: production
  WARNING: This is a development server. Do not use it in a production deployment.
  Use a production WSGI server instead.
* Debug mode: on
* Running on http://127.0.0.1:5000/ (Press CTRL+C to quit)
* Restarting with stat
* Debugger is active!
* Debugger PIN: 585-562-845
debug: sending full list
127.0.0.1 - - [27/Feb/2022 21:17:47] "GET /selection HTTP/1.1" 200 -
debug: added description with id 'icecream3'
127.0.0.1 - - [27/Feb/2022 21:18:05] "POST /selection HTTP/1.1" 201 -
debug: added description with id 'icecream4'
127.0.0.1 - - [27/Feb/2022 21:18:10] "POST /selection HTTP/1.1" 201 -
debug: added description with id 'icecream5'
127.0.0.1 - - [27/Feb/2022 21:18:15] "POST /selection HTTP/1.1" 201 -
debug: sending full list
127.0.0.1 - - [27/Feb/2022 21:18:20] "GET /selection HTTP/1.1" 200 -
127.0.0.1 - - [27/Feb/2022 21:18:24] "PUT /selection/icecream10 HTTP/1.1" 201 -
debug: deleting task with id 'icecream2'
127.0.0.1 - - [27/Feb/2022 21:18:29] "DELETE /selection/icecream2 HTTP/1.1" 204 -
debug: sending full list
127.0.0.1 - - [27/Feb/2022 21:18:34] "GET /selection HTTP/1.1" 200 -

ubuntu@ip-172-31-29-225 × ubuntu@ip-172-31-29-225 × sintija-client.ipynb ×
ubuntu@ip-172-31-29-225:~$ curl -s http://127.0.0.1:5000/selection
{
  "icecream1": {
    "description": "Chocolate ice cream with fudge brownies and milk chocolate ganache"
  },
  "icecream3": {
    "description": "Vanilla ice cream with salted caramel swirls"
  },
  "icecream4": {
    "description": "Mint ice cream with fudge brownies"
  },
  "icecream5": {
    "description": "Caramel ice cream"
  },
  "icecream10": {
    "description": "Cherry ice cream with cherries"
  }
}
ubuntu@ip-172-31-29-225:~$
```