

# GroundFlow: Multiple Flows Feedback for Enhancing Immersive Experience on the Floor in the Wet Scenes

Tzu-Hua Wang

National Taipei University of  
Technology  
Taipei, Taiwan

Tzu-Shan Lee

National Taipei University of  
Technology  
Taipei, Taiwan

Jr-Pin Pan

National Taipei University of  
Technology  
Taipei, Taiwan

Tzu-Yang Kuo


National Taipei University of  
Technology  
Taipei, Taiwan

Hui-Yang Yong

National Taipei University of  
Technology  
Taipei, Taiwan

Ping-Hsuan Han

National Taipei University of  
Technology  
Taipei, Taiwan



**Figure 1:** We introduce GroundFlow, a water recirculation system that provides multiple flows feedback, the users can also experience several kinds of fluid that have a corresponding scene in the immersive virtual reality. (a)We implement 5 virtual scenes which are possible in the real world to simulate the fluids. (e.g. the river scene with unidirectional flow.) (b)Users can experience the fluid simulation with no shoes. (c)Water will come from different directions. (d) The water can be over the ankle. (e)Simulate the places where there is no source direction of water flow.(e.g. the interpolated flow.)

## ABSTRACT

With haptic technology, the users can experience an enhanced immersion in virtual reality. Most haptic techniques focus on the upper body, such as the head, chest, and hands, to provide strength feedback when interacting in the virtual world. Thus, researchers have been exploring different techniques to simulate haptic feedback for walking around in virtual space, such as texture, height, vibration, shape, and resistance. However, those techniques can not provide a real wet sensation in the virtual scene. Therefore, we present GroundFlow, a water recirculation system that provides multiple flows feedback on the floor in immersive virtual reality. Our demonstration also implemented a virtual excursion that allows users to experience different water flows and their corresponding wet scenes.

## CCS CONCEPTS

• **Human-centered computing** → **Interaction paradigms**; Virtual Reality.

## KEYWORDS

Multisensory Feedback, Fluid Simulation, Liquid-based Haptic, Virtual Reality

### ACM Reference Format:

Tzu-Hua Wang, Tzu-Shan Lee, Jr-Pin Pan, Tzu-Yang Kuo, Hui-Yang Yong, and Ping-Hsuan Han. 2021. GroundFlow: Multiple Flows Feedback for Enhancing Immersive Experience on the Floor in the Wet Scenes. In *SIGGRAPH Asia 2021 Emerging Technologies (SA '21 Emerging Technologies)*, December 14-17, 2021. ACM, New York, NY, USA, 2 pages. <https://doi.org/10.1145/3476122.3484837>

## 1 INTRODUCTION

The first foot interaction has been a proposal by [Pearson and Weiser 1988], researchers explore diversification techniques to simulate the haptic feedback from the soles of our feet. One of the methods is wearable devices. Capsules [Matthies et al. 2017] contribute to utilizes capacitive sensing and machine learning technique to design an insole, which users can recognize texture and wet floor feedback. Level-Ups [Schmidt et al. 2015] present mechanical shoes which can simulate different heights of scenes. SnowWalking [Yokota et al. 2015] presents a boot that can simulate walking in the snow. RealWalk [Yang et al. 2020] utilizes magnetorheological fluid of shoes to simulate the wet desert. Although wearable device researches enable users to recognize different textures, wet and dry floors, they do not perceive the wet sensation from their feet. Besides, to have a good wearable experience, several sizes of shoes need to be provided. Instead of wearable devices, floor systems


Permission to make digital or hard copies of part or all of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for third-party components of this work must be honored. For all other uses, contact the owner/author(s).

SA '21 Emerging Technologies, December 14-17, 2021, Tokyo, Japan

© 2021 Copyright held by the owner/author(s).

ACM ISBN 978-1-4503-8685-2/21/12.

<https://doi.org/10.1145/3476122.3484837>



**Figure 2: Hardware Design:** (a)lower canvas ponds, (b)aluminum extrusions, (c)diatomaceous earth, (d)centrifugal pumps, (e)electric valve, and (f)upper canvas ponds.

can avoid wearing and taking off shoes, which is easy to adapt to different users. TilePoP [Teng et al. 2019] utilizes a pneumatically-actuated interface to operate 30 airbags, which can be inflated into an object in a virtual environment. Elevate [Je et al. 2021] utilizes a haptic floor base on a pin-array display, which can dynamically adjust the ups and downs of the terrain. Nevertheless, the users still can not perceive wet sensation or interact with water. Additionally, previous research has utilized the characteristics of liquids to deliver liquids into wearable devices through water pipes to achieve a variety of haptic feedback, such as temperature, gravity, or pressure feedback but not wet sensation. To interact with water, AquaTop [Koike et al. 2013] presents vision-based HCI of water surface display, in which the users can use their fingers to touch the projection on the stagnant water while taking a bath. This paper presents a water recirculation system that provides multiple flows feedback on the floor in immersive virtual reality. Our floor system can provide walking space for the users, or multi-users can sit at the edge. Users can take off shoes to experience multiple waters flows corresponding to the wet scenes in virtual reality.

## 2 DESIGN AND IMPLEMENTATION

GroundFlow is a water recirculation system that provides haptic feedback to the feet in virtual reality. By combining the haptic feedback system with virtual reality, our work allows the user to feel the fluid simulation corresponding to the virtual environment. GroundFlow hardware design is shown in figure 2. The total length and width of the installation is 260cm, and the height is 51cm, using 200cm\*200cm\*28cm raised floor(29.5cm height) and aluminum extrusions as support. We use centrifugal pumps (AQUA WAY JA150, flow rate: 350 L/min) to avoid users getting the electric shock to pump water from the lower canvas ponds to the upper one. We can store water in the lower large canvas ponds (260cm\*260cm\*30cm), and users can stand in the other canvas ponds for experience (220cm\*220cm\*46cm), thus achieving maximum space utilization. Besides, to make the wet floor dry when the canvas pond is without water, we use sixteen pieces of diatomaceous earth (40cm\*55cm\*1cm)on the floor.

The maximum water level of the system is 95mm, the rising water level speed is 100 mm/min with turn on two pumps, lowering water level speed is 74 mm/min with turn on eight electric valves. Our device utilizes the Linkit 7697 Bluetooth via the handmade wiring and Unity to operate the system with software. We have

eight electric valves to discharge the water from the upper canvas ponds back to the lower one to complete the water circulation. Thus, we can control the number of electric valves to increase or decrease the water discharge rate.

We use two centrifugal pumps and set them at opposite corners. The pump is paired with two normally closed electric valves installed on the left and right sides of the pump. When the pump is pumping water, we can control the electric valves to open one or two so that the water will come out in one direction or two directions. Thus, we implement the multiple fluid simulation. Our system can create (a)dry, (b)the unidirectional flow, (c)static, (d)2-way flow, (e)waving, (f)interpolated flow, (g)T-flow, and (h)4-way flow. For more detail, please refer to our video.

## 3 APPLICATION: VIRTUAL EXCURSION

To show that our device's possibility can be present, we implement a virtual excursion experience. Users can stand or sit in our device to relax in nature environments, even meditate. In this experience, we choose the general water flow and make the corresponding scene. Users can experience the waving pair to sea, unidirectional flow pair to the river, 2-way flow pair to forest SPA, 4-way flow pair to underground house, and static pair to temple. For more detail, please refer to the video.

## 4 SUMMARY AND FUTURE WORK

A water recirculation system provides multiple flows feedback on the floor in immersive virtual reality in this project, which can create diversified fluid simulations. We also implement a virtual excursion in which the users can experience multiple fluid simulations. In the future, we will further explore the human foot's perception of liquid interfaces and the utility of enhancing the immersion of virtual reality.

## REFERENCES

- Seungwoo Je, Hyunseung Lim, Kongpyung Moon, Shan-Yuan Teng, Jas Brooks, Pedro Lopes, and Andrea Bianchi. 2021. Elevate: A Walkable Pin-Array for Large Shape-Changing Terrains. In *Proceedings of the 2021 CHI Conference on Human Factors in Computing Systems*. 1–11.
- Hideki Koike, Yasushi Matoba, and Yoichi Takahashi. 2013. AquaTop display: interactive water surface for viewing and manipulating information in a bathroom. In *Proceedings of the 2013 ACM international conference on Interactive tabletops and surfaces*. 155–164.
- Denys JC Matthies, Thijs Roumen, Arjan Kuijper, and Bodo Urban. 2017. CapSoles: who is walking on what kind of floor?. In *Proceedings of the 19th International Conference on Human-Computer Interaction with Mobile Devices and Services*. 1–14.
- Glenn Pearson and Mark Weiser. 1988. Exploratory evaluation of a planar foot-operated cursor-positioning device. In *Proceedings of the SIGCHI conference on Human factors in computing systems*. 13–18.
- Dominik Schmidt, Rob Kovacs, Vikram Mehta, Udayan Umapathi, Sven Köhler, Lung-Pan Cheng, and Patrick Baudisch. 2015. Level-ups: Motorized stilts that simulate stair steps in virtual reality. In *Proceedings of the 33rd Annual ACM Conference on Human Factors in Computing Systems*. 2157–2160.
- Shan-Yuan Teng, Cheng-Lung Lin, Chi-huan Chiang, Tzu-Sheng Kuo, Liwei Chan, Da-Yuan Huang, and Bing-Yu Chen. 2019. Tilepop: Tile-type pop-up prop for virtual reality. In *Proceedings of the 32nd Annual ACM Symposium on User Interface Software and Technology*. 639–649.
- Tae-Heon Yang, Hyunki Son, Sangkyu Byeon, Hyunjae Gil, Inwook Hwang, Gwanghyun Jo, Seungmoon Choi, Sang-Youn Kim, and Jin Ryong Kim. 2020. Magnetorheological Fluid Haptic Shoes for Walking in VR. *IEEE Transactions on Haptics* 14, 1 (2020), 83–94.
- Tomohiro Yokota, Motohiro Ohtake, Yukihiro Nishimura, Toshiya Yui, Rico Uchikura, and Tomoko Hashida. 2015. Snow walking: motion-limiting device that reproduces the experience of walking in deep snow. In *Proceedings of the 6th Augmented Human International Conference*. 45–48.