

Part c Verification of FastAPI - Improve the documentation (organising the documentation)

```
ubuntu@ip-172-31-18-113:~/datascientest-data-engineering/fast-api$ uvicorn main:api --reload
INFO: Will watch for changes in these directories: ['/home/ubuntu/datascientest-data-engineering/fast-api']
INFO: Uvicorn running on http://127.0.0.1:8000 (Press CTRL+C to quit)
INFO: Started reloader process [1912] using StatReload
INFO: Started server process [1917]
INFO: Waiting for application startup.
INFO: Application startup complete.
```

Edit [main.py](#) file:

```
main.py M X
datascientest-data-engineering > fast-api > main.py > ...
1  from fastapi import FastAPI # type: ignore
2
3
4  api = FastAPI(openapi_tags = [
5      {
6          "name": "home",
7          "description": "default functions"
8      },
9      {
10         "name": "items",
11         "description": "functions that are used to deal with items"
12     }
13 ])
14
15 @api.get("/", tags = ["home"])
16 def get_index():
17     """returns greetings"""
18     return {
19         "greetings": "hello world"
20     }
21
22 @api.get("/items", tags = ["home", "items"])
23 def get_items():
24     """returns an item"""
25     return {
26         "item": "some item"
27     }
```

Open URL <http://localhost:8000/docs>

FastAPI 0.1.0 OAS 3.1
/openapi.json

home default functions

GET / Get Index

GET /items Get Items

items functions that are used to deal with items

GET /items Get Items

Run commands in new terminal:

```
ubuntu@ip-172-31-18-113:~/datascientest-data-engineering/fast-api$ curl -X GET -i http://127.0.0.1:8000/
HTTP/1.1 200 OK
date: Wed, 18 Jun 2025 13:12:45 GMT
server: uvicorn
content-length: 27
content-type: application/json

{"greetings":"hello world"}ubuntu@ip-172-31-18-113:~/datascientest-data-engineering/fast-api$ curl -X GET -i http://127.0.0.1:8000/items
HTTP/1.1 200 OK
date: Wed, 18 Jun 2025 13:12:50 GMT
server: uvicorn
content-length: 20
content-type: application/json

{"item":"some item"}ubuntu@ip-172-31-18-113:~/datascientest-data-engineering/fast-api$
```

Open URL <http://127.0.0.1:8000/>

```
{
  "greetings": "hello world"
}
```

Raw Parsed

Open URL <http://localhost:8000/items>

```
{
  "item": "some item"
}
```

Raw Parsed