

Hash tables

- hashing -- idea
- collision resolution
 - closed addressing (chaining)
 - open addressing techniques
- hash function
- Java **hashCode ()** for **HashMap** and **HashSet**
- big-O time bounds
- applications

Announcements

- Change to Claire's Thurs office hours this Thur:
10 – 11:50
- Midterm 2
 - Tue. 4/4, THH 101
 - closed book, closed note, bring USC ID card
- No lab assignment this Week
- Start early on PA4: more design involved (all based on material we have covered already)

Review: Map ADT

- A map stores a collection of (key,value) pairs
- keys are unique: a pair can be identified by its key

Operations:


- add a new (key, value) pair (called an entry)
- lookup an entry, given its key
- update the value of an entry, given its key
- remove an entry, given its key
- list all the entries
 - (order of visiting depends on the kind of map created)

Hashing idea

- [illegible]


Hashing idea (cont.)

- In Map ADT, keys might be strings, ints, ...



Problems

- More key values than indices in the array.
- How big is the set of one-word names of up to 20 characters?



Collisions

- Even if set of actual key values is small, the set of possible key values is large.
- The hash function maps the set of *possible* values, so you need to worry about collisions.
- But if the set of actual values is small, how soon do we need to really worry about this?

The Birthday Problem

How many people in a room before chance that any two have the same birthday is $> 50\%$?

What' s the implication?

- In general...
 - No matter what the table size
 - No matter what the hash function
 - No matter how many actual entries currently stored (>1)
- ...the hash address for key does ***not*** uniquely identify the map entry $\langle \text{key}, \text{value} \rangle$.
 - i.e., collisions can happen
- hash address just identifies a hash bin
 - assume you can store multiple entries in a bin

Collision resolution

- Recall: hash value does not uniquely identify the entry.
- Collision resolution:

Where to put the entries when two of them map to the same location (i.e., $\text{hash}(\text{key}_1) = \text{hash}(\text{key}_2)$)?

Collision resolution strategies

- Where to put the entries when two of them map to the same location?
 - Open addressing – put them in different hash buckets
 - linear probing: put in next empty bucket
 - Closed addressing – each bucket can hold multiple entries.
 - chaining: use a linked list for all entries in a bucket.
- We'll only discuss chaining in detail.

Collision resolution by chaining

- Each bucket stores multiple items -- using linked list.

John --> 3

Sam --> 6

Mary --> 3

Beth --> 4

Joe --> 4

Bob --> 3

HSIZE = 11

0	
1	
2	
3	
4	
5	
6	
7	
8	
9	
10	

- Insert, lookup, delete

Hash functions

- Required properties:
 - deterministic: value only depends on key
 - has to map to the indices of the array:
 - achieve with : **hashValue % HASH_SIZE**
- Desirable properties
 - easy to compute (i.e., fast)
 - promotes uniform distribution of key values over whole range of addresses

Hash functions

- General methods
 - truncation (e.g., key is a SSN)
 - folding
 - modulus (%)
 $\% \text{ HASHSIZE}$ (prime)

Hash functions: example

- Simple example of folding technique:
 - for a key that is a string: $c_1..c_n$
 $(\sum c_i) \% \text{HASHSIZE}$
- How many distinct values (addresses) can we get with this hash function? (before modulus)

Better string hash function

- Takes into account the position of the character.

α is a constant (prime better)

$$h_0 = 0$$

$$h_i = \alpha h_{i-1} + c_i \quad 1 \leq i \leq k$$

- Implement with a loop
- but to see what's happening, here's the whole computation
 - for three chars:

$$\alpha^2 c_1 + \alpha c_2 + c_3$$

- To find good hash functions:

The Art of Computer Programming, volume on Sorting and Searching,
by Don Knuth

Using Java **HashMap** (or **HashSet**)

- Recall: for **HashMap<KeyType, ValueType>**
 - **KeyType** must have
 - equals** and **hashCode** defined
 - Already defined for Java types such as **String**, **Integer**, **Double**
- How to use our own type as the **KeyType**?

Java `hashCode()` method

- Java **HashMap** / **HashSet** uses `hashCode()` method as the hash function.
- Many Java classes override it to do the right thing.
- For example **String**'s `hashCode()` uses the algorithm from the previous slide ($\alpha = 31$)
- Also defined for **LinkedList** and **ArrayList**, for example (see documentation for details)

Writing your own `hashCode()`

- Can be overridden from **Object**
- Doesn't depend on size of hash table:
 - **HASH_SIZE** is handled by `HashMap/HashSet` class
- Contract for **`hashCode()`**
 - if `a.equals(b)` then `a.hashCode() == b.hashCode()`
- Warning: `Object` version does not do the right thing – don't rely on inherited one.
 - object version returns a code based on the *address* of the object (i.e., object identity)
 - We want it to use the *value* of the object

Ex: Student class

```
public class Student {  
    private String theName;  
    private int score;  
    public boolean equals(Object other) {  
        // returns true iff they have the same name  
        // and the same score  
    }  
    public int hashCode() {  
        return theName.hashCode() + score;  
    }  
    . . .  
}
```

Danger of inheriting `hashCode()`

- Consider a **Term** class: (coefficient, exponent).
- Suppose we *override* `equals()` to be that the exponents and coefficients must be the same.
- but *inherit* `hashCode()` from **Object**.
- **Reminder: Contract for `hashCode()`**
 - if `a.equals(b)` then `a.hashCode() == b.hashCode()`

```
Term t = new Term(3,4);
```

```
Term t2 = new Term(3,4);
```

- `t.equals(t2)` // true or false?
- `t.hashCode() == t2.hashCode()` // true or false?

Why does this matter?

- What happens if you use these terms in a HashSet?

```
Term t = new Term(3,4) ;
```

```
. . .
```

```
hashSet.add(t) ;
```

```
. . .
```

```
Term target = new Term(3,4) ;
```

```
if (hashSet.contains(target)) . . .
```

- `t.equals(target)` – true or false?
- `t.hashCode() == target.hashCode()` – true or false?

Converse to contract not true

- Reminder: Contract for `hashCode()`
 - if `a.equals(b)` then `a.hashCode() == b.hashCode()`
- But, if `a.hashCode() == b.hashCode()`
 - what do we know about `a` and `b`?

Big-O time bounds

- Suppose chaining
 n = number of items in table
 b = size of table
 $\lambda = n / b$ average length of a list (uniform distr)
- $O(\lambda)$ search time
- On average, $O(1)$
- Inserts and deletes also take $O(\lambda)$

Performance in practice

- Performance depends on hash function, and load factor.
- Good hash function:
 - uniform distribution of keys over hash addresses
- Bad hash function:
 - worst case, all values could be in one bucket.
- Load factor:
 - HashMap / HashSet make the array bigger if it gets above 0.75 load factor. ($\text{numEntries} / \text{HASH_SIZE}$)
 - Involves rehashing everything.

Big-O for traversal

- Traversal (in no special order)
takes $O(n)$ -- but really $n + \text{size of the table (array)}$
- Ordered traversal involves sorting.
 - Best sorts are $O(n \log n)$
- hashing is an excellent Map representation,
providing that you aren't going to be
doing `traverseInOrder` operation much.
 - What representations are well suited for ordered traversal?

Applications of hash tables

- First: properties desired:
 - lookup
 - insert
 - (remove)
 - don't care about order of keys
- Examples of applications:
 - Database (master customer file)
 - Compilers: symbol tables
 - Games: look up board configuration to find the move that goes with it (e.g., chess, tic-tac-toe)
 - UNIX shell: quick command lookup.