

Introduction to functional programming with Java

Falk Sippach

 @sipsack

 <http://blog.oio.de>



BASEL | BERN | BRUGG | BUKAREST | DÜSSELDORF | FRANKFURT A.M. | FREIBURG I.B.R. | GENÈVE
HAMBURG | KOPENHAGEN | LAUSANNE | MANNHEIM | MÜNCHEN | STUTTGART | WIEN | ZÜRICH

nio
part of **trivadis** group

Falk Sippach

Trainer, Berater, Entwickler



Co-Organisator



Committer DukeCon

 @sipsack


 <http://blog.oio.de>



BASEL | BERN | BRUGG | BUKAREST | DÜSSELDORF | FRANKFURT A.M. | FREIBURG I.B.R. | GENÈVE
HAMBURG | KOPENHAGEN | LAUSANNE | MANNHEIM | MÜNCHEN | STUTTGART | WIEN | ZÜRICH

nio
part of **trivadis** group

OIO – Part of Trivadis




<http://www.oio.de>

OIO ist die Drehscheibe der Trivadis-Gruppe für Softwareentwicklung mit Java und JavaScript

Schulung, Beratung und Programmierung

3



<http://www.braintime.de>

OIO Braintime

Ihr Atlassian Platinum Solution Partner


Methoden, Werkzeuge und Lösungen

Abstract


Funktionale Programmierung ist im Moment in aller Munde. Seit Version 8 und Lambdas/Streams stehen auch Java-Anwendern diverse Werkzeuge zur Verfügung. Daher wird es Zeit, sich mit den grundlegenden Konzepten der funktionalen Programmierung auseinanderzusetzen.

Nach diesem Vortrag wirst Du verstehen, was eine pure Funktion ist und warum referentielle Transparenz bzw. Seiteneffektfreiheit wichtige Konzepte sind. Wir schauen zudem auf Value Types und wie funktionale Datenstrukturen aufgebaut sind und wie man dank Bedarfsauswertung auch mit sehr großen Datenmengen effizient umgehen kann. Weiterhin besprechen wir die Elemente der Wiederverwendung wie Funktionskomposition, Currying, partielle Funktionsaufrufe und Funktionen höherer Ordnung. Abschließend werfen wir noch ein Blick auf die Destrukturierung von Datenstrukturen mittels Pattern Matching, das Kapseln von Seiteneffekten und wie man in seiner Softwarearchitektur einen funktionalen Kern umsetzt.


4



5



6



trivadis


Your Bank

1234 5678 9876 5432

client-side testing


checksum
calculation
Luhn algorithm

8



Nummer	gültig
1465324567854823	<input checked="" type="checkbox"/>
1465324567851234	<input type="checkbox"/>
1465324567856604	<input checked="" type="checkbox"/>





trivadis

**“Construct [our]
programs using **pure
functions only**”**

12

Luhn-Algorithmus



```
static Function1<Long, Seq<Integer>> toDigits = number ->
    CharSeq.of(Long.toString(number)).map(c -> c - '0');

static Function1<Seq<Integer>, Seq<Integer>> reverse = Seq::reverse;

static Function1<Seq<Integer>, Seq<Integer>> double2nd =
    digits -> digits.zipWithIndex().map(t -> t._1 * (t._2 % 2 + 1));

static Function1<Seq<Integer>, Integer> sumDigits = digits ->
    digits.map(i -> i.longValue()).flatMap(toDigits).sum().intValue();

static Function1<Integer, Boolean> divisibleBy10 = number ->
    number % 10 == 0;
```

13



**“Pure functions have no
side effects”**

14

trivadis

Modifying a variable
Throwing an exception
Printing to the console
Writing to a file

Side effects

15


trivadis

“A function has a side
effect if it does
something **other than
simply return a result**”

16


```
int divide(int dividend, int divisor) {  
    return dividend / divisor;  
}
```

17



Side effects

18

**A purely functional
programmed application
is useless!**

19

FC & IS
Functional Core,
Imperative Shell

20

trivadis

“An expression is **referential transparent, if it can be replaced by its result without changing the meaning of the program”**

21

trivadis

“A function is **pure if calling it with referential transparent arguments is also **referential transparent**”**

22

`Math.random();`



`Math.max(1, 2);`



23

```
Function2<Integer, Integer, Integer> divide =
    (a, b) -> a / b;
```


```
Function2<Integer, Integer, Option<Integer>> safeDivide =
    Function2.lift(divide);
```

```
Option<Integer> result1 = safeDivide.apply(4, 0);
then(result1).isEqualTo(Option.none());
```

```
Option<Integer> result2 = safeDivide.apply(4, 2);
then(result2).isEqualTo(Option.some(2));
```

lifting

24



trivadis

Functions are values.

A function can be computed,
passed around and returned.

“A higher order function is a function that takes a function as an argument and/or returns a function.”

27

```
creditCardNumber
  .chars() // convert to int
  .map(in -> in - '0') // multiply by 1, 2 alternating
  .map(n -> n * (i[0] = i[0] == 1 ? 2 : 1)) // sum of digits
  .map(n -> n > 9 ? n - 9 : n)
  .sum() % 10 == 0;
```

higher order functions

28

1
2
Fizz
4
Buzz
Fizz
7
8
Fizz
Buzz
11
Fizz
13
14
FizzBuzz
16
...

```
final Stream<String> fizzes = Stream.of("", "", "Fizz").cycle();
final Stream<String> buzzes = Stream.of("", "", "", "", "Buzz").cycle();
final Stream<String> fizzBuzzes = fizzes.zipWith(buzzes, (t1, t2) -> t1 + t2);
final Stream<String> result = fizzBuzzes
    .zipWith(Stream.from(1), (_1, _2) -> _1.isEmpty() ? _2.toString() : _1);

result.take(20).forEach(System.out::println);
```


Beispiel von: <https://www.sitepoint.com/functional-fizzbuzz-with-vavr>

<https://pxhere.com/de/photo/487335>

Luhn: Zip to double each second digit



```
static Function1<Seq<Integer>, Seq<Integer>> double2nd =
    digits -> digits.zipWithIndex()
                    .map(t -> t._1 * (t._2 % 2 + 1));
```




```
Function0<Double> cachedRandom =
    Function0.of(Math::random).memoized();

double randomValue1 = cachedRandom.apply();
double randomValue2 = cachedRandom.apply();

then(randomValue1).isEqualTo(randomValue2);
```

memoization

31



32

trivadis

"... **function composition** is an act or mechanism to combine simple functions to build more complicated ones."


33

trivadis

```
static Function1<Long, Boolean> isValid =  
    toDigits.andThen(reverse)  
        .andThen(double2nd)  
        .andThen(sumDigits)  
        .andThen(divisibleBy10) ;
```

function composition

34



```

isValid n =
  divisibleBy10 (sumDigits (double2nd (reverse (toDigits(n)))))
  
```

35

Luhn Algorithmus in funktional

```

isValid n =
  divisibleBy10 (
    sumDigits (
      double2nd (
        reverse (
          toDigits(n)
        )
      )
    )
  )
  
```



Validierungsfunktion

Teilbar durch 10?

Aufsummieren

jede 2. verdoppeln

Ziffern umdrehen

Aufsplitten in Ziffern

Luhn: Individual steps



```
static Function1<Long, Seq<Integer>> toDigits = number ->
    CharSeq.of(Long.toString(number)).map(c -> c - '0');

static Function1<Seq<Integer>, Seq<Integer>> reverse = Seq::reverse;

static Function1<Seq<Integer>, Seq<Integer>> double2nd =
    digits -> digits.zipWithIndex().map(t -> t._1 * (t._2 % 2 + 1));

static Function1<Seq<Integer>, Integer> sumDigits = digits ->
    digits.map(i -> i.longValue()).flatMap(toDigits).sum().intValue();

static Function1<Integer, Boolean> divisibleBy10 = number ->
    number % 10 == 0;
```

37



"... **currying** is the technique of translating the evaluation of a function that takes multiple arguments into evaluating a sequence of functions, each with a single argument."

38

```

Function3<BiFunction<Integer, Integer, Integer>,
    List<Integer>,
    List<Integer>,
    List<Integer>>> myZip = ... // = myZip(function, list1, list2)

```

```

Function1<BiFunction<Integer, Integer, Integer>,
    Function1<List<Integer>,
        Function1<List<Integer>, List<Integer>>>>>> curriedMyZip
    = myZip.curried();

```

```

List<Integer> result = curriedMyZip.apply((a, b) -> a * b)
                                .apply(List(1, 2, 3))
                                .apply(List(4, 5, 6))

```

currying

39

“... **partial function**
 application refers to the
 process of fixing a number of
 arguments to a function,
 producing another function of
 smaller arity.”

40

```

Function3<BiFunction<Integer, Integer, Integer>,
    List<Integer>,
    List<Integer>,
    List<Integer>>> myZip = ... // = myZip(function, list1, list2)


Function1<List<Integer>, List<Integer>>> zipped =
    myZip.curried()
        .apply((a, b) -> a * b)
        .apply(List(1, 2, 3));

zipped.apply(List(4, 5, 6))

```

partial function application

41



42

```
Tuple2<String, Integer> java8 = Tuple.of("Java", 8);

Tuple2<String, Integer> vavr1 = java8.map(
    s -> s.substring(2) + "vr",
    i -> i / 8);

String vavr = vavr1._1;
int one = vavr1._2;
```

43

Try (Success, Failure)
Either (Left, Right)
Option (Some, None)
Validation (Valid, NotValid)

44

```
static CreditCardNumber from(String s) {
    return new CreditCardNumber(Long.parseLong(s));
}
```



```
static Try<CreditCardNumber> fromWithTry(String s) {
    return Try.of(() -> Long.parseLong(s))
        .map(n -> new CreditCardNumber(n));
}
```

```
System.out.println(CreditCardNumber.fromWithTry(s: "abc").getOrNull());
System.out.println(CreditCardNumber.fromWithTry(s: "abc").getCause().getClass().getName());
System.out.println(CreditCardNumber.fromWithTry(s: "123").get());
```

Try

45

```
static Either<String, CreditCardNumber> fromWithEither(String s) {
    try {
        return Either.right(new CreditCardNumber(Long.parseLong(s)));
    } catch (NumberFormatException e) {
        return Either.left(String.format("wrong credit card number format: %s", s));
    }
}
```

```
System.out.println(CreditCardNumber.fromWithEither(s: "abc").isLeft());
System.out.println(CreditCardNumber.fromWithEither(s: "123").isRight());
System.out.println(CreditCardNumber.fromWithEither(s: "123").left().getOrElse( other: "no error"));
System.out.println(CreditCardNumber.fromWithEither(s: "abc").left().get());
```

Either

46

```
String helloWorld = Option.of("Hello")
    .map(value -> value + " Falk")
    .peek(value -> LOG.debug("Value: {}", value))
    .getOrElse(() -> "Hello World");
```

Option


47

```
public class CreditCardValidator {
    public Validation<Seq<String>, CreditCard> validateNumber(String owner, String number) {
        final CreditCardNumber ccn = CreditCardNumber.from(number);
        return Validation.combine(
            owner == null || owner.isEmpty() ? Validation.invalid("Owner must not be empty!") : Validation.valid(owner),
            ccn.isValid() ? Validation.valid(ccn) : Validation.invalid("Credit card number is invalid: " + number)
        ).ap(CreditCard::new);
    }

    public static void main(String[] args) {
        final CreditCardValidator ccv = new CreditCardValidator();
        final Validation<Seq<String>, CreditCard> validation = ccv.validateNumber(owner: "John", number: "1234567");
        System.out.println(validation.isValid());
        System.out.println(validation.getError().intersperse(", "));
    }
}
```

Validation

48



Pattern Matching: Destrukturieren von Objekten


trivadis

```
final CreditCard cc = new CreditCard(owner: "John", ImmutableCreditCardNumber.builder().number(123456789L).build());

if (cc != null && "John".equals(cc.getOwner())) {
    final CreditCardNumber ccNumber = cc.getNumber();
    if (ccNumber != null) {
        System.out.println(String.format("Creditcard of %s with number %s", cc.getOwner(), ccNumber.getNumber()));
    }
}


Long number = Match(cc).of(
    Case($CreditCard($ (prototype: "John"), $CreditCardNumber($ ())), (name, no) -> no.getNumber(),
    Case($(), () -> 0L)
);
System.out.println(number);
```

50



trivadis

Immutability



Only one state
Thread Safety
Instances can be shared
Inner states can be used together

Benefits



Project Lombok

Immutableables

stars

1,662



Tools, libraries

Java Collections are mutable!

```
interface Collection<E> {
    void clear();
}
```


```
List<String> list = Collections
    .unmodifiableList(otherList);
```

```
list.add("Boom");
```

Persistent/Functional data structures in Vavr



```
List<Integer> list1 = List.of(1, 2, 3);
List<Integer> list2 = list1.tail().prepend(0);
```



57

http://www.vavr.io/vavr-docs/#_functional_data_structures

Persistent/Functional data structures in Vavr



```
Queue<Integer> queue = Queue.of(1, 2, 3)
    .enqueue(4) .enqueue(5) ;
Queue<Integer> queue2 = queue
    .dequeue() .dequeue() .dequeue()
```




58


http://www.vavr.io/vavr-docs/#_functional_data_structures

Persistent/Functional data structures in Vavr

```
// = TreeSet(1, 2, 3, 4, 6, 7, 8)
SortedSet<Integer> xs =
    TreeSet.of(6, 1, 3, 2, 4, 7, 8);
```



```
// = TreeSet(1, 2, 3, 4, 5, 6, 7, 8)
SortedSet<Integer> ys = xs.add(5);
```


http://www.vavr.io/vavr-docs/#_functional_data_structures

59

```
List<User> result = users.stream()
    .filter(user -> {
        try {
            return user.validate();
        } catch (Exception ex) {
            return false;
        }
    })
    .map(user -> user.name)
    .collect(Collectors.toList());
```

```
List<User> result = List.ofAll(users)
    .filter(user ->
        Try.of(user::validateAddress)
            .getOrElse(false)
    )
    .map(user -> user.name);
```

```
java.util.List<User> result2 =
    result.toJavaList();
```

java.util.List

60



FAZIT

```

3 public class LuhnAlgorithm {
4     public static boolean isValid(long number) {
5         int sum = 0;
6         boolean alternate = false;
7         while(number > 0) {
8             long digit = number % 10;
9             if (alternate) {
10                 sum += 2 * digit;
11                 if (digit >= 5) {
12                     sum -= 9;
13                 }
14             } else {
15                 sum += digit;
16             }
17             number = number / 10;
18             alternate = !alternate;
19         }
20         return sum % 10 == 0;
21     }
22 }


```

Split

Double second

Sum up

Validation check



Imperative:
How do I achieve
my goal?

Foto von tomwieden, [CC0 Public Domain Lizenz](https://pixabay.com/de/boule-kugeln-spielen-frankreich-141004/), <https://pixabay.com/de/boule-kugeln-spielen-frankreich-141004/>

Functional:
What do I want
to reach?

Foto von Mohamed Nuzrath, [CC0 Public Domain Lizenz](https://pixabay.com/de/kick-martial-arts-krieger-185384/), <https://pixabay.com/de/kick-martial-arts-krieger-185384/>

trivadis

Pros

- just works if compiles
- easy to understand, easy to conclude
- side-effect-free
- easy test/debugging
- easy to parallelize
- can be modularized and easily reassembled
- high code quality

Foto von tomwieden, [CC0 Public Domain Lizenz](https://pixabay.com/de/boule-kugeln-spielen-frankreich-141004/), <https://pixabay.com/de/boule-kugeln-spielen-frankreich-141004/>


trivadis

The image shows a central blue ring with the Java logo inside. Surrounding the ring are several logos for other technologies: JS (JavaScript), Groovy, f (F#), Camel, Spring, and others. This visualizes the concept of Java being at the center of a multi-language ecosystem.


66


Foto von Hans Braxmeier, [CC0 Public Domain Lizenz](https://pixabay.com/de/teller-suppteller-essteller-1365805/), <https://pixabay.com/de/teller-suppteller-essteller-1365805/>





**Java 8**


+

**VAVR**.io



Project Lombok

Immutableables  stars  1,662



68

Immutable data types + pure functions

key for better Java

69

Links

- Code-Beispiele
 - <https://github.com/sippsack/jvm-functional-language-battle>
- Learn You a Haskell for Great Good!
 - <http://learnyouahaskell.com/chapters>
- LYAH (Learn You a Haskell) adaptations for Frege
 - <https://github.com/Frege/frege/wiki/LYAH-adaptions-for-Frege>
- Onlinekurs TU Delft (FP 101):
 - <https://courses.edx.org/courses/DelftX/FP101x/3T2014/info>

70

Links



- Vavr
 - <http://www.vavr.io/>
- Immutables
 - <http://immutables.github.io/>
- Project Lombok
 - <https://projectlombok.org/>
- Functional Java
 - <http://www.functionaljava.org/>

71



Thank you

Questions?

