www.gansat.com.tr
sales@gansat.com.tr · +90 (541) 276 39 46



KU-BAND · GAN

# 400W SSPA

400W L-to-Ku Band Block Up Converter is based on GaN technology. Maximum power solution designed for reliable operation in the toughest outdoor environments.

| 400W | GaN | 42 kg | 2000W |
|---|---|---|---|
| OUTPUT POWER | TECHNOLOGY | WEIGHT | POWER DRAW |

### KEY FEATURES

- Output frequency 13.75 – 14.75 GHz (EXT) / 14.50 GHz (STD)
- Local oscillator: 12.80 GHz
- GaN technology: high efficiency, low power consumption and high reliability
- Power consumption: 2000W max.
- Auto-ranging power supply: 220V 50Hz AC
- Internal high-stability 10 MHz reference (optional)
- RoHS compliant · For civil use only

## Technical Specifications

GANSAT-400WKU

| | |
|---|---|
| RF Frequency | 13.75 – 14.50 GHz |
| Local Oscillator | 12.80 GHz |
| Output Power | 400W (+56 dBm) |
| IF Connector | N-type or F-type |
| Power Supply | 220V 50Hz AC, 2000W typ. |
| Output Interface | WR-75 G |
| Gain | 72 dB min, 78 dB nominal |
| IMD3 (Two Tones) | -26 dBc max. 2 signals 5 MHz apart at P-LINEAR |
| L.O. Leakage | -45 dBm max |
| Spurious | -50 dBc max |
| Spectral Regrowth | -30 dBc (QPSK at 1.5x and OQPSK at 1.0x symbol rate offset with 2dB back-off) |
| External Reference Requirement | Via IF cable — 10 MHz (sine-wave), -5 to +5 dBm @ input port |
| TX Gain Variation / Temperature Stability | ± 0.5 dB over 40 MHz / ± 1.8 dB over full band / ± 1.5 dB typ., ± 1.8 dB max. |

| | |
|---|---|
| Phase Noise (Intelsat IESS-308/309) | -55 dBc/Hz @ 10 Hz · -65 @ 100 Hz · -75 @ 1 kHz · -85 @ 10 kHz · -95 @ 100 kHz · -115 @ 1 MHz |
| Noise Power Density TX / RX | -80 dBm/Hz (max) / -125 dBm/Hz (max) |
| Noise Figure | 15 dB max |
| Input / Output V.S.W.R. | 2:1 max |
| Mute | SSPA Shutdown on L.O. Unlock |
| Operating / Storage Temperature | -40°C to +55°C / -55°C to +85°C |
| Dimensions | 450 (L) × 400 (W) × 220 (H) mm — 17.7" × 15.8" × 8.65" |
| Weight | 42 kg (92.59 lbs) max |

## GANSAT-400WEXTKU

| | |
|---|---|
| RF Frequency | 13.75 – 14.75 GHz |
| Local Oscillator | 12.80 GHz |
| Output Power | 400W (+56 dBm) |
| IF Connector | N-type or F-type |
| Power Supply | 220V 50Hz AC, 2000W typ. |
| Output Interface | WR-75 G |
| Gain | 72 dB min, 78 dB nominal |
| IMD3 (Two Tones) | -26 dBc max. 2 signals 5 MHz apart at P-LINEAR |
| L.O. Leakage | -45 dBm max |
| Spurious | -50 dBc max |
| Spectral Regrowth | -30 dBc (QPSK at 1.5x and OQPSK at 1.0x symbol rate offset with 2dB back-off) |
| External Reference Requirement | Via IF cable — 10 MHz (sine-wave), -5 to +5 dBm @ input port |
| TX Gain Variation / Temperature Stability | ± 0.5 dB over 40 MHz / ± 1.8 dB over full band / ± 1.5 dB typ., ± 1.8 dB max. |
| Phase Noise (Intelsat IESS-308/309) | -55 dBc/Hz @ 10 Hz · -65 @ 100 Hz · -75 @ 1 kHz · -85 @ 10 kHz · -95 @ 100 kHz · -115 @ 1 MHz |
| Noise Power Density TX / RX | -80 dBm/Hz (max) / -125 dBm/Hz (max) |
| Noise Figure | 15 dB max |
| Input / Output V.S.W.R. | 2:1 max |
| Mute | SSPA Shutdown on L.O. Unlock |
| Operating / Storage Temperature | -40°C to +55°C / -55°C to +85°C |
| Dimensions | 450 (L) × 400 (W) × 220 (H) mm — 17.7" × 15.8" × 8.65" |
| Weight | 42 kg (92.59 lbs) max |