

Programming Assignment 1: The perceptron learning algorithm.



6/6 得分 (100%)

测验通过！

[返回第 3 周课程](#)



1 / 1 分

1.

DISCLAIMER: Before beginning the actual quiz portion of the assignment, download the code and fill in the missing pieces. You do not have to submit the quiz until the deadline.

In this assignment you will take the provided starter code and fill in the missing details in order to create a working perceptron implementation.

To start, download the following code files:

- learn_perceptron.m
- plot_perceptron.m

And the following datasets:

- dataset1.mat
- dataset2.mat
- dataset3.mat
- dataset4.mat

Attention: some people have notified us that the provided datasets do not load under some versions of Octave. We are providing the same datasets in a different format that will hopefully work with more versions. You can find these files below.

And the following datasets:

- dataset1_ancient_octave.mat
- dataset2_ancient_octave.mat
- dataset3_ancient_octave.mat
- dataset4_ancient_octave.mat

For those who want to download all of the files together in a zip archive, you get get them here: Assignment1.zip

To run the code, you first need to load a dataset. To do so enter the following command in the Octave console (to load dataset 1):

```
load dataset1
```

This should load 4 variables:

- neg_examples_nobias - The matrix containing the examples belonging to class 0.
- pos_examples_nobias - The matrix containing the examples belonging to class 1.
- w_init - Some initial weight vector.
- w_gen_feas - A generously feasible weight vector (empty if one doesn't exist).

The variables have _nobias appended to their names because they do not have an additional column of 1's appended to them. This is done automatically in the learn_perceptron.m code already. Now that you have loaded a dataset, you can run the algorithm by entering the following at the Octave console:

```
w = learn_perceptron  
(neg_examples_nobias,pos_examples_nobias,w_init,w_gen_feas)
```

This will start the algorithm and plot the results as it proceeds. Until the algorithm converges you can keep pressing enter to run the next iteration. Pressing 'q' will terminate the program. At each iteration it should produce a plot that looks something like this.

The top left plot shows the data points. The circles represent one class while the squares represent the other. The line shows the decision boundary of the perceptron using the current set of weights. The green examples are those that are correctly classified while the red are incorrectly classified. The top-right plot will show the number of mistakes made by the perceptron. If a generously feasible weight vector is provided (and not empty), then the bottom left plot will show the distance of the learned weight vectors to the generously feasible weight vector.

Currently, the code doesn't do any learning. It is your job to fill this part in. Specifically, you need to fill in the lines under `learn_perceptron.m` marked %YOUR CODE HERE (lines 114 and 122). When you are finished, use this program to help you answer the questions below.

Ready to Begin?

☒ Yes

☐ No



1 / 1 分

2.

Which of the provided datasets are *not* linearly separable?
Check all that apply.

☒ Dataset 2



正确回答

☐ Dataset 1



正确回答

☒ Dataset 4



正确回答

☐ Dataset 3



正确答案



1 / 1 分

3.

True or false: if the dataset is *not* linearly separable, then it is possible for the number of classification errors to *increase* during learning.



True



正确答案

One training case might send the parameters off in a bad direction, that suddenly makes the perceptron misclassify many other training cases.



False



正确答案



1 / 1 分

4.

True or false: If a generously feasible region exists, then the distance between the current weight vector and a weight vector in the *generously feasible* region will monotonically decrease as the learning proceeds.



True



正确答案

This is part of the proof of convergence of the perceptron algorithm.



False



正确回答



1 / 1 分

5.

The perceptron algorithm as implemented and described in class implicitly uses a learning rate of 1. We can modify the algorithm to use a different learning rate α so that the update rule for an input x and target t becomes:

$$w^{(t)} \leftarrow w^{(t-1)} + \alpha(t - \text{prediction})x,$$

where **prediction** is the decision made by the perceptron using the current weight vector $w^{(t-1)}$, given by:

$$\text{prediction} = \begin{cases} 1 & \text{if } w^T x \geq 0 \\ 0 & \text{otherwise} \end{cases}$$

True or false: if we use a learning rate of 2, then the perceptron algorithm will always converge to a solution for linearly separable datasets.



True



正确回答

This is equivalent to doubling the magnitude of each training example, which will not change the fact that the dataset is still linearly separable.



False



正确回答



1 / 1 分

6.

According to the code, how many iterations does it take for the perceptron to converge to a solution on *dataset 3* using the provided initial weight vector w_{init} ?

Note: the program will output

Number of errors in iteration x : 0

You simply need to report x .

☐ 2



正确答案

☐ It doesn't converge.



正确答案

☐ 6



正确答案

☒ 9



正确答案

