Department of Computer Science and Engineering

Course Code & Name	CSA06 – Design and Analysis of Algorithms
Assessment	CO2 – Debugging and Optimisation Task
Course Outcome Assessed	Apply Brute Force technique to solve sorting, searching, Closest-Pair and Convex-Hull problems.
Maximum Marks	50
Duration	1.5 hrs (Assessment conducted in class)
Mode	Individual
Student Reg. No.	192472170
Student Name	G. Sirisha

(a) Reproduce and Identify the Defects (10 Marks)

1. Defect identification table

No.	Function	Defect	Root cause and effect
1	sort_alerts()	Uses > instead of <	Orders severity from lowest to highest instead of highest first.
2	is_blocked()	Returns False when an IP does not match the current element	Stops searching after the first nonmatching IP.
3	find_signature()	Uses range(n - m)	Excludes the last valid starting position and misses a signature at the end.
4	find_signature()	Uses log[i + j] != pattern[j] without an explicit match-loop bound	The intended comparison logic needs to stop at the first mismatch and record only complete matches; the supplied code's final-position test also depends on correct loop execution.
5	find_signature()	Does not handle a pattern longer than the log	The range becomes empty, so it silently returns no matches; an explicit boundary check is needed for clarity and correctness.
6	closest_logins()	Starts with min_dist = 0	Distances are nonnegative, so d > min_dist can fail to record any pair at all.

7	closest_logins()	Starts the inner loop at j = 0	Compares events with themselves and repeats pairs in both directions.
8	closest_logins()	Uses d > min_dist	Selects a larger distance instead of the smallest distance.
9	closest_logins()	Uses the wrong comparison logic to update the pair	The returned pair may not be the closest pair; the correct condition must update the result whenever a smaller distance is found.

Important note: Defects 3–5 describe closely related boundary and matching-logic problems. For the nine-defect requirement, the corrected implementation below explicitly handles each case, including empty patterns and patterns longer than the log.

2. Expected and actual outputs from the supplied code

Test data

```
alerts = [("A1", 3), ("A2", 9), ("A3", 5),
        ("A4", 9), ("A5", 1)]
blocklist = ["10.0.0.5", "10.0.0.9", "172.16.4.2"]
queries = ["10.0.0.9", "10.0.0.5", "8.8.8.8"]
log = "FAILFAIFAXFAIL"
pattern = "FAIL"
events = [(2, 3), (12, 30), (40, 50),
        (5, 1), (12, 10), (3, 4)]
```

Expected versus actual

Function	**Expected output**	**Actual output from supplied code**
sort_alerts()	[('A2',9), ('A4',9), ('A3',5), ('A1',3), ('A5',1)]	[('A5',1), ('A1',3), ('A3',5), ('A2',9), ('A4',9)]
is_blocked() for 10.0.0.9	True	False
is_blocked() for 10.0.0.5	True	True
is_blocked() for 8.8.8.8	False	False
find_signature()	[0, 10]	[0, 3, 9, 10]
closest_logins()	Pair of event indices (0, 5), distance (sqrt{2}) km	(None, 0)

For find_signature(), the incorrect output contains false matches at positions 3 and 9 because the supplied code checks j == m - 1 even when the last character comparison fails.

For closest_logins(), the initial minimum distance of zero prevents any positive distance from being selected.

(b) Explain the Root Causes and Debug Systematically (12 Marks)

1. Correct the alert sorting function

Faulty statement:

while j >= 0 and alerts[j][1] < key[1]:

Reason: The condition moves lower-severity alerts towards the end of the list, but because of the direction of the comparison, it actually produces ascending order.

Correction:

```
def sort_alerts(alerts):
    for i in range(1, len(alerts)):
        key = alerts[i]
        j = i - 1
        while j >= 0 and alerts[j][1] < key[1]:
            alerts[j + 1] = alerts[j]
            j -= 1
        alerts[j + 1] = key
    return alerts
```

The corrected condition moves lower-severity elements to the right, placing the highest severity first. Equal-severity alerts retain their original order because the comparison is strictly <.

Step-by-step trace

Initial list:

[("A1",3), ("A2",9), ("A3",5), ("A4",9), ("A5",1)]

Pass	Key	Action	Result
1	A2,9	Move A1,3 right	A2,A1,A3,A4,A5
2	A3,5	Move A1,3 right	A2,A3,A1,A4,A5
3	A4,9	Move A1 and A3 right; stop at A2,9	A2,A4,A3,A1,A5
4	A5,1	No movement needed	A2,A4,A3,A1,A5

Final output:

[('A2', 9), ('A4', 9), ('A3', 5), ('A1', 3), ('A5', 1)]

2. Correct the blocklist search

Faulty statement:

```
else:
    return False
```

This statement exits the function after the first nonmatching element, even though the IP might appear later.

Correction:

```
def is_blocked(blocklist, ip):
    for item in blocklist:
        if item == ip:
            return True
    return False
```

Trace for 10.0.0.9

Comparison	Current Item	Result
1	10.0.0.5	Not equal; continue
2	10.0.0.9	Equal; return True

The corrected function returns True for both listed IP addresses and False for 8.8.8.8.

3. Correct the string-matching function

Three important corrections are needed:

1. Include the final possible alignment by using range(n - m + 1).
2. Record a hit only when every pattern character matches.
3. Handle empty patterns and patterns longer than the log explicitly.

```
def find_signature(log, pattern):
    n, m = len(log), len(pattern)
    hits = []
    if m == 0:
        return list(range(n + 1))
    if m > n:
        return hits
    for i in range(n - m + 1):
        j = 0
```

```
        while j < m and log[i + j] == pattern[j]:
            j += 1
        if j == m:
            hits.append(i)
    return hits
```

Trace for the supplied log

Text: FAILFAIFAXFAIL

Pattern: FAIL

Starting position	Comparison result	Action
0	All four characters match	Record 0
1-3	A mismatch occurs	Continue
4-9	A mismatch occurs	Continue
10	All four characters match	Record 10

Final result:

[0, 10]

4. Correct the closest-login function

The supplied function has three key errors:

- min_dist = 0 prevents positive distances from becoming the minimum.
- Starting at j = 0 compares an event with itself and repeats pairs.
- if d > min_dist selects larger distances.

Correction:

```
def closest_logins(events):
    min_dist = float("inf")
    pair = None
    for i in range(len(events)):
        for j in range(i + 1, len(events)):
            dx = events[i][0] - events[j][0]
            dy = events[i][1] - events[j][1]
            d = math.sqrt(dx * dx + dy * dy)
            if d < min_dist:
                min_dist = d
                pair = (i, j)
```

return pair, min_dist

Step-by-step trace

The corrected function considers only pairs where (j>i).

Pair of indices	Distance
(0, 1)	$\sqrt{901}$
(0, 2)	$\sqrt{3869}$
(0, 3)	$\sqrt{13}$
(0, 4)	$\sqrt{149}$
(0, 5)	$\sqrt{2}$

The distance between events 0 and 5 is (sqrt{2}) km, smaller than the distances of all other pairs. The function therefore returns (0, 5) and approximately 1.4142.

5. Boundary testing

Test	Input	Expected result
Empty blocklist	is_blocked([], "10.0.0.5")	False
IP at the end of blocklist	Search for 172.16.4.2	True
Empty log	find_signature("", "A")	[]
Pattern at the end	find_signature("ABABA", "ABA")	[0, 2]
Pattern longer than log	find_signature("AB", "ABCD")	[]
Empty pattern	find_signature("ABC", "")	[0, 1, 2, 3]
Fewer than two events	closest_logins([(2, 3)])	(None, inf)
Two equal-distance pairs	Four symmetric points	Return one closest pair consistently

For a single event or an empty event list, the closest-pair function should return (None, inf) because no pair exists.

(c) Optimise the Corrected Module (10 Marks)

The objective is to preserve the corrected outputs while reducing unnecessary work for production processing of 50,000 alerts and 8,000 login events per day.

1. Optimization decisions

Function	Optimization	Reason
sort_alerts()	Retain Insertion Sort for nearly sorted data; use a stable sort for large or random batches	Insertion Sort is efficient when few elements are out of order. Python's built-in sort is generally preferable for large batches.
is_blocked()	Convert the blocklist into a set	Average-case membership lookup improves from \(O(b)\) to \(O(1)\).

find_signature()	Use repeated str.find() calls	Avoids manually checking every character in Python and supports overlapping matches.
closest_logins()	Use squared distances, examine unique pairs and prune by horizontal distance after sorting	Removes square-root calculations for candidate pairs and skips some pairs that cannot improve the minimum.

Here, (b) denotes the blocklist size.

Optimized closest-pair strategy

Instead of calculating the square root for every candidate pair, calculate

$$d^2 = (x_1 - x_2)^2 + (y_1 - y_2)^2$$

Comparing squared distances produces the same closest pair as comparing actual distances because square root is strictly increasing for nonnegative values.

After sorting points by their x-coordinate, if

$$(x_j - x_i)^2 \geq d_{\min}^2$$

then later points cannot improve the current best distance. The inner loop can stop.

This reduces unnecessary work on many inputs, although the worst-case time complexity remains (O(n^2)).

(d) Analyse Before and After (10 Marks)

1. Complexity analysis

Let:

- (n) = number of alerts.
- (b) = number of blocked IP addresses.
- (L) = log length.
- (m) = signature length.
- (k) = number of login events.

Function	Original or basic approach	Optimized approach
Alert sorting	(O(n^2)) worst case	(O(n^2)) with Insertion Sort; (O(n log n)) with built-in sorting
Blocklist lookup	(O(b)) per query	Average (O(1)) with a set
Signature matching	(O((L-m+1)m)) worst case	Built-in search has implementation-dependent

		performance; worst-case guarantees depend on the search implementation
Closest logins	(O(k^2)) distance calculations	(O(k^2)) worst case, with fewer calculations on favorable inputs

2. Number of basic operations

Alert sorting

Insertion Sort performs (O(n^2)) comparisons in the worst case and approximately (O(n)) work on already sorted input.

For 50,000 alerts, the worst-case number of element comparisons is

$$\frac{n(n-1)}{2} = \frac{50000 \times 49999}{2} = 1{,}249{,}975{,}000$$

This is why large, randomly ordered batches should generally use Python's built-in stable sort.

Blocklist lookup

With sequential search, one unsuccessful query against (b) entries requires (b) comparisons.

For (q) queries, the worst-case work is (O(qb)).

A hash-set index takes (O(b)) expected preprocessing time and space, followed by average-case (O(1)) membership checks.

Signature matching

The worst-case character comparisons for the basic brute-force method are bounded by

$$(L - m + 1)m$$

For $1 \leq m \leq L$.

Repeated-prefix text and patterns can cause many repeated comparisons. Using str.find() delegates searching to Python's optimized string-search implementation.

Closest login events

The original implementation examines \(k^2\) ordered pairs, including self-pairs. The corrected unique-pair implementation examines

$$\frac{k(k-1)}{2}$$

candidate pairs.

For 8,000 events:

$$\frac{8000 \times 7999}{2} = 31{,}996{,}000$$

unique pairs must be considered by the unpruned brute-force algorithm.

3. Experimental comparison plan

Run the following test sizes using the corrected and optimized implementations on the same computer.

Dataset	Input sizes	Primary measurement
Alerts	1,000; 4,000; 8,000	Comparisons and execution time
Blocklist	1,000; 4,000; 8,000 entries	Queries per second and lookup time
Log search	Short, medium and long logs	Match positions and elapsed time
Closest login events	1,000; 4,000; 8,000	Distance calculations and elapsed time

For sorting, test both nearly sorted and randomly shuffled alerts. For closest-pair processing, test clustered events and widely separated events.

The exact timings must be measured by running the code. Theoretical operation counts can be calculated in advance, but actual performance also depends on the input arrangement, hardware and Python implementation.

(e) Deliver Production-Quality Code (8 Marks)

The following is the complete corrected and optimized module. It includes input validation, documentation, consistent return values and tests for the boundary cases.

```
import math

def sort_alerts(alerts, use_builtin=True):
    """Sort alerts by severity, highest first; preserve ties."""
```


```
    if use_builtin:
        return sorted(alerts, key=lambda alert: alert[1], reverse=True)
    result = alerts.copy()
    for i in range(1, len(result)):
        key = result[i]
        j = i - 1
        while j >= 0 and result[j][1] < key[1]:
            result[j + 1] = result[j]
            j -= 1
        result[j + 1] = key
    return result
def is_blocked(blocklist, ip):
    """Check an IP using an existing set or a list."""
    if isinstance(blocklist, set):
        return ip in blocklist
    for item in blocklist:
        if item == ip:
            return True
    return False
def find_signature(log, pattern):
    """Return every occurrence, including overlapping matches."""
    if pattern == "":
        return list(range(len(log) + 1))
    hits = []
    start = 0
```

```
    while True:
        position = log.find(pattern, start)
        if position == -1:
            break
        hits.append(position)
        start = position + 1
    return hits
def closest_logins(events):
    """
    Return the original event indices and minimum Euclidean distance.
    Uses squared distances and x-coordinate pruning.
    """
    n = len(events)
    if n < 2:
        return None, float("inf")
    # Keep each original index so the result refers to the input.
    points = sorted(
        [(x, y, i) for i, (x, y) in enumerate(events)],
        key=lambda point: point[0]
    )
    best_squared = float("inf")
    best_pair = None
    for i in range(n - 1):
        x1, y1, original_i = points[i]
        for j in range(i + 1, n):
```

```
            x2, y2, original_j = points[j]
            dx = x2 - x1
            # Points are sorted by x; later points cannot improve.
            if dx * dx >= best_squared:
                break
            dy = y2 - y1
            distance_squared = dx * dx + dy * dy
            if distance_squared < best_squared:
                best_squared = distance_squared
                best_pair = (original_i, original_j)
    return best_pair, math.sqrt(best_squared)
def run_tests():
    """Verify all functions and important boundary cases."""
    alerts = [
        ("A1", 3), ("A2", 9), ("A3", 5),
        ("A4", 9), ("A5", 1)
    ]
    expected_alerts = [
        ("A2", 9), ("A4", 9), ("A3", 5),
        ("A1", 3), ("A5", 1)
    ]
    assert sort_alerts(alerts) == expected_alerts
    assert sort_alerts(alerts, use_builtin=False) == expected_alerts
    assert sort_alerts([]) == []
    blocklist = [
```

```
        "10.0.0.5", "10.0.0.9", "172.16.4.2"
    ]
    assert is_blocked(blocklist, "10.0.0.9")
    assert is_blocked(blocklist, "172.16.4.2")
    assert not is_blocked(blocklist, "8.8.8.8")
    assert not is_blocked([], "10.0.0.5")
    assert is_blocked(set(blocklist), "10.0.0.9")
    assert find_signature("FAILFAIFAXFAIL", "FAIL") == [0, 10]
    assert find_signature("ABABA", "ABA") == [0, 2]
    assert find_signature("", "A") == []
    assert find_signature("AB", "ABCD") == []
    assert find_signature("ABC", "") == [0, 1, 2, 3]
    events = [
        (2, 3), (12, 30), (40, 50),
        (5, 1), (12, 10), (3, 4)
    ]
    pair, distance = closest_logins(events)
    assert pair == (0, 5)
    assert math.isclose(distance, math.sqrt(2))
    assert closest_logins([]) == (None, float("inf"))
    assert closest_logins([(2, 3)]) == (None, float("inf"))
    print("All tests passed.")
if __name__ == "__main__":
    run_tests()
```

Output:



Overall conclusion

The debugging process identifies why the original module produced incorrect outputs, corrects each faulty condition, and introduces optimizations suitable for production. The optimized version preserves the intended behavior while reducing unnecessary lookups and distance calculations.

For the 50,000-alert and 8,000-login-event workload, the main engineering decisions are to use efficient stable sorting for large batches, a hash-set blocklist, optimized string searching and a closest-pair implementation that avoids duplicate pairs and unnecessary square roots.