

AIML LAB ASSIGNMENT-3

NAME: M. Siri Chandana

ROLL NO: 2203A51492

BATCH: CSE -12

Part-01: List of Tasks to Perform

1. Install the Python Libraries for Game Strategy

```
from collections import namedtuple, Counter, defaultdict
import random
import math
import functools
cache = functools.lru_cache(10**6)
```

2. Implement a Game Class Constructor with - actions, is_terminal, result, utility

```
class Game:
    """A game is similar to a problem, but it has a terminal test instead of
    a goal test, and a utility for each terminal state. To create a game,
    subclass this class and implement `actions`, `result`, `is_terminal`,
    and `utility`. You will also need to set the .initial attribute to the
    initial state; this can be done in the constructor."""

    def actions(self, state):
        """Return a collection of the allowable moves from this state."""
        raise NotImplementedError

    def result(self, state, move):
        """Return the state that results from making a move from a state."""
        raise NotImplementedError

    def is_terminal(self, state):
        """Return True if this is a final state for the game."""
        return not self.actions(state)

    def utility(self, state, player):
        """Return the value of this final state to player."""
        raise NotImplementedError
```

3. Implement a Player Game using game class function

```
def play_game(game, strategies: dict, verbose=False):
    """Play a turn-taking game. `strategies` is a {player_name: function} dict,
    where function(state, game) is used to get the player's move."""
    state = game.initial
    while not game.is_terminal(state):
        player = state.to_move
        move = strategies[player](game, state)
        state = game.result(state, move)
        if verbose:
            print('Player', player, 'move:', move)
            print(state)
    return state
```

Part-02: Implementation of Game Strategy Algorithm

1. MiniMax Tree

```
def minimax_search(game, state):
    """Search game tree to determine best move; return (value, move) pair."""

    player = state.to_move

    def max_value(state):
        if game.is_terminal(state):
            return game.utility(state, player), None
        v, move = -infinity, None
        for a in game.actions(state):
            v2, _ = min_value(game.result(state, a))
            if v2 > v:
                v, move = v2, a
        return v, move

    def min_value(state):
        if game.is_terminal(state):
            return game.utility(state, player), None
        v, move = +infinity, None
        for a in game.actions(state):
            v2, _ = max_value(game.result(state, a))
            if v2 < v:
                v, move = v2, a
        return v, move
```

```
return max_value(state)

infinity = math.inf
```

2. Alpha-Beta Search Algorithm

```
def alphabeta_search(game, state):
    """Search game to determine best action; use alpha-beta pruning.
    """Search all the way to the leaves."""

    player = state.to_move

    def max_value(state, alpha, beta):
        if game.is_terminal(state):
            return game.utility(state, player), None
        v, move = -infinity, None
        for a in game.actions(state):
            v2, _ = min_value(game.result(state, a), alpha, beta)
            if v2 > v:
                v, move = v2, a
                alpha = max(alpha, v)
            if v >= beta:
                return v, move
        return v, move

    def min_value(state, alpha, beta):
        if game.is_terminal(state):
            return game.utility(state, player), None
        v, move = +infinity, None
        for a in game.actions(state):
            v2, _ = max_value(game.result(state, a), alpha, beta)
            if v2 < v:
                v, move = v2, a
                beta = min(beta, v)
            if v <= alpha:
                return v, move
        return v, move

    return max_value(state, -infinity, +infinity)
```

Part-03: Implement the Game Strategy using TicTacToe

1.Implement TicToCToe game using init , actions, result, is terminal, utility,display constructors

```

class TicTacToe(Game):
    """Play TicTacToe on an `height` by `width` board, needing `k` in a row to win.
    'X' plays first against 'O'."""

    def __init__(self, height=3, width=3, k=3):
        self.k = k # k in a row
        self.squares = {(x, y) for x in range(width) for y in range(height)}
        self.initial = Board(height=height, width=width, to_move='X', utility=0)

    def actions(self, board):
        """Legal moves are any square not yet taken."""
        return self.squares - set(board)

    def result(self, board, square):
        """Place a marker for current player on square."""
        player = board.to_move
        board = board.new({square: player}, to_move=('O' if player == 'X' else 'X'))
        win = k_in_row(board, player, square, self.k)
        board.utility = (0 if not win else +1 if player == 'X' else -1)
        return board

    def utility(self, board, player):
        """Return the value to player; 1 for win, -1 for loss, 0 otherwise."""
        return board.utility if player == 'X' else -board.utility

    def is_terminal(self, board):
        """A board is a terminal state if it is won or there are no empty squares."""
        return board.utility != 0 or len(self.squares) == len(board)

    def display(self, board): print(board)

def k_in_row(board, player, square, k):
    """True if player has k pieces in a line through square."""
    def in_row(x, y, dx, dy): return 0 if board[x, y] != player else 1 + in_row(x + dx, y + dy, dx, dy)
    return any(in_row(*square, dx, dy) + in_row(*square, -dx, -dy) - 1 >= k
               for (dx, dy) in ((0, 1), (1, 0), (1, 1), (1, -1)))

```

2. Implement a Game Board using defaultdict using init , new, missing , hash ,repr

```

class Board(defaultdict):
    """A board has the player to move, a cached utility value,
    and a dict of {(x, y): player} entries, where player is 'X' or 'O'."""

```

```

empty = '.'
off = '#'

def __init__(self, width=8, height=8, to_move=None, **kwds):
    self.__dict__.update(width=width, height=height, to_move=to_move, **kwds)

def new(self, changes: dict, **kwds) -> 'Board':
    "Given a dict of {(x, y): contents} changes, return a new Board with the changes."
    board = Board(width=self.width, height=self.height, **kwds)
    board.update(self)
    board.update(changes)
    return board

def __missing__(self, loc):
    x, y = loc
    if 0 <= x < self.width and 0 <= y < self.height:
        return self.empty
    else:
        return self.off

def __hash__(self):
    return hash(tuple(sorted(self.items()))) + hash(self.to_move)

def __repr__(self):
    def row(y): return ' '.join(self[x, y] for x in range(self.width))
    return '\n'.join(map(row, range(self.height))) + '\n'

```

3. Implement random player(game,state) and player(search algorithm)

```

def random_player(game, state): return random.choice(list(game.actions(state)))

def player(search_algorithm):
    """A game player who uses the specified search algorithm"""
    return lambda game, state: search_algorithm(game, state)[1]

```

Part-04 Evaluate the Game Strategy using TicTokToe

1.Implement Game Strategy using play game(TicTacToe(), dict(X=random player,O=player(alphabeta search)), verbose=True).utility

```
play_game(TicTacToe(), dict(X=random_player, O=player(alpha_beta_search)), verbose=True).utility
```

```
... Player X move: (1, 0)
. X .
. . .
. . .

Player O move: (1, 2)
. X .
. . .
. O .

Player X move: (1, 1)
. X .
. X .
. O .

Player O move: (0, 0)
O X .
. X .
. O .

Player X move: (0, 1)
O X .
X X .
. O .
...
O X O
X X O
X O X

Output is truncated. View as a scrollable element or open in a text editor. Adjust cell output settings.
... 0
```

2. Implement Game strategy using `play_game(TicTacToe(), dict(X=player(alpha_beta_search), O=player(minimax_search)), verbose=True).utility`

```
play_game(TicTacToe(), dict(X=player(alpha_beta_search),
O=player(minimax_search)), verbose=True).utility
```

```
[2-3] ... Player X move: (0, 1)
```

```
... ..  
X . .  
... ..
```

```
Player O move: (2, 1)
```

```
... ..  
X . O  
... ..
```

```
Player X move: (1, 2)
```

```
... ..  
X . O  
. X .
```

```
Player O move: (0, 0)
```

```
O . .  
X . O  
. X .
```

```
Player X move: (1, 1)
```

```
O . .  
X X O  
. X .
```

```
... ..
```

```
O O X
```

```
X X O
```

```
O X X
```

Output is truncated. View as a [scrollable element](#) or open in a [text editor](#). Adjust cell output [settings...](#)

```
... 0
```