



# Compiler II: Code Generation



*Building a Modern Computer From First Principles*

[www.nand2tetris.org](http://www.nand2tetris.org)

# Course map



# The big picture


---

1. **Syntax analysis:** extracting the semantics from the source code

previous  
lecture

2. **Code generation:** expressing the semantics using the target language

this  
lecture



# Syntax analysis (review)

```
Class Bar {  
    method Fraction foo(int y) {  
        var int temp; // a variable  
        let temp = (xxx+12)*-63;  
        ...  
    }  
}
```

Syntax analyzer

```
<varDec>  
  <keyword> var </keyword>  
  <keyword> int </keyword>  
  <identifier> temp </identifier>  
  <symbol> ; </symbol>  
</varDec>  
<statements>  
  <letStatement>  
    <keyword> let </keyword>  
    <identifier> temp </identifier>  
    <symbol> = </symbol>  
    <expression>  
      <term>  
        <symbol> ( </symbol>  
        <expression>  
          <term>  
            <identifier> xxx </identifier>  
          </term>  
          <symbol> + </symbol>  
          <term>  
            <int.Const.> 12 </int.Const.>  
          </term>  
        </expression>  
      </term>  
    </expression>  
    ...
```

## The code generation challenge:

- ❑ Program = a series of operations that manipulate data
- ❑ Compiler: converts each “understood” (parsed) source operation and data item into corresponding operations and data items in the target language
- ❑ Thus, we have to generate code for
  - handling data
  - handling operations
- ❑ Our approach: morph the syntax analyzer (project 10) into a full-blown compiler: instead of generating XML, we'll make it generate VM code.

# Memory segments (review)

---

## VM memory Commands:

`pop segment i`

`push segment i`

Where *i* is a non-negative integer and *segment* is one of the following:

**static:** holds values of global variables, shared by all functions in the same class

**argument:** holds values of the argument variables of the current function

**local:** holds values of the local variables of the current function

**this:** holds values of the private ("object") variables of the current object

**that:** holds array values (silly name, sorry)


**constant:** holds all the constants in the range 0 ... 32767 (pseudo memory segment)

**pointer:** used to anchor *this* and *that* to various areas in the heap

**temp:** fixed 8-entry segment that holds temporary variables for general use;  
Shared by all VM functions in the program.


# Code generation example

```
method int foo() {  
  var int x;  
  let x = x + 1;  
  ...  
}
```



```
<letStatement>  
  <keyword> let </keyword>  
  <identifier> x </identifier>  
  <symbol> = </symbol>  
  <expression>  
    <term>  
      <identifier> x </identifier>  
    </term>  
    <symbol> + </symbol>  
    <term>  
      <constant> 1 </constant>  
    </term>  
  </expression>  
</letStatement>
```

Code  
generation



```
push local 0  
push constant 1  
add  
pop local 0
```

(note that *x* is the first local variable declared in the method)

# Handling variables

---

When the compiler encounters a variable, say  $x$ , in the source code, it has to know:

What is  $x$ 's data type?

Primitive, or ADT (class name) ?

(Need to know in order to properly allocate RAM resources for its representation)

What kind of variable is  $x$ ?

local, static, field, argument ?

( We need to know in order to properly allocate it to the right memory segment;  
this also implies the variable's life cycle ).

## Handling variables: mapping them on memory segments (example)

```
class BankAccount {  
    // Class variables  
    static int nAccounts;  
    static int bankCommission;  
    // account properties  
    field int id;  
    field String owner;  
    field int balance;
```

```
    method void transfer(int sum, BankAccount from, Date when) {  
        var int i, j;    // Some local variables  
        var Date due;    // Date is a user-defined type  
        let balance = (balance + sum) - commission(sum * 5);  
        // More code ...  
    }
```

- ❑ The target language uses 8 memory segments
- ❑ Each memory segment, e.g. static, is an indexed sequence of 16-bit values that can be referred to as static 0, static 1, static 2, etc.

When compiling this class, we have to create the following mappings:

The class variables	nAccounts , bankCommission	are mapped on	static 0,1
The object fields	id, owner, balance	are mapped on	this 0,1,2
The argument variables	sum, bankAccount, when	are mapped on	arg 0,1,2
The local variables	i, j, due	are mapped on	local 0,1,2.



# Handling variables: symbol tables

```
class BankAccount {  
    // Class variables  
    static int nAccounts;  
    static int bankCommission;  
    // account properties  
    field int id;  
    field String owner;  
    field int balance;
```

```
    method void transfer(int sum, BankAccount from, Date when) {  
        var int i, j;    // Some local variables  
        var Date due;    // Date is a user-defined type  
        let balance = (balance + sum) - commission(sum * 5);  
        // More code ...  
    }
```

Class-scope symbol table

Name	Type	Kind	#
nAccounts	int	static	0
bankCommission	int	static	1
id	int	field	0
owner	String	field	1
balance	int	field	2

## How the compiler uses symbol tables:

- ❑ The compiler builds and maintains a linked list of hash tables, each reflecting a single scope nested within the next one in the list
- ❑ Identifier lookup works from the current symbol table back to the list's head (a classical implementation).

Method-scope (transfer) symbol table

Name	Type	Kind	#
this	BankAccount	argument	0
sum	int	argument	1
from	BankAccount	argument	2
when	Date	argument	3
i	int	var	0
j	int	var	1
due	Date	var	2

# Handling variables: managing their life cycle

---

Class-scope symbol table

Name	Type	Kind	#
nAccounts	int	static	0
bankCommission	int	static	1
id	int	field	0
owner	String	field	1
balance	int	field	2

Method-scope (transfer) symbol table

Name	Type	Kind	#
this	BankAccount	argument	0
sum	int	argument	1
from	BankAccount	argument	2
when	Date	argument	3
i	int	var	0
j	int	var	1
due	Date	var	2

## Variables life cycle

- static variables: single copy must be kept alive throughout the program duration
- field variables: different copies must be kept for each object
- local variables: created on subroutine entry, killed on exit
- argument variables: similar to local variables.

Good news: the VM implementation already handles all these details !



# Handling objects: construction / memory allocation

## Java code

```
class Complex {
    // Fields (properties):
    int re; // Real part
    int im; // Imaginary part
    ...
    /** Constructs a new Complex number */
    public Complex (int re, int im) {
        this.re = re;
        this.im = im;
    }
    ...
}

class Foo {
    public void bla() {
        Complex a, b, c;
        ...
        a = new Complex(5,17);
        b = new Complex(12,192);
        ...
        c = a; // Only the reference is copied
        ...
    }
}
```

Following  
compilation:

RAM		
0		
	...	
326	6712	a
327	7002	b
328	6712	c
	...	
6712	5	} a object
6713	17	
	...	
7002	12	} b object
7003	192	
	...	

## How to compile:

`foo = new ClassName(...)` ?

The compiler generates code affecting:

`foo = Memory.alloc(n)`

Where `n` is the number of words necessary to represent the object in question, and `Memory.alloc` is an OS method that returns the base address of a free memory block of size `n` words.

# Handling objects: accessing fields

---

## Java code

```
class Complex {
    // Properties (fields):
    int re; // Real part
    int im; // Imaginary part
    ...
    /** Constructs a new Complex number */
    public Complex(int re, int im) {
        this.re = re;
        this.im = im;
    }
    ...
    /** Multiplies this Complex number
        by the given scalar */
    public void mult (int c) {
        re = re * c;
        im = im * c;
    }
    ...
}
```

## How to compile:

`im = im * c ?`


1. look up the two variables in the symbol table
2. Generate the code:

```
*(this + 1) = *(this + 1)
               times
               (argument 0)
```

This pseudo-code should be expressed in the target language.

# Handling objects: establishing access to the object's fields

Background: Suppose we have an object named *b* of type *Ball*. A *Ball* has *x,y* coordinates, a radius, and a color.



Assume that *b* and *r* were passed to the function as its first two arguments.

How to compile (in Java):

*b.radius = r* ?

```
// Get b's base address:  
push argument 0  
// Point the this segment to b:  
pop pointer 0  
// Get r's value  
push argument 1  
// Set b's third field to r:  
pop this 2
```

Virtual memory segments just before  
the operation *b.radius=17*:

argument		pointer	this
0	3012	0	
1	17	1	...
...			

Virtual memory segments just after  
the operation *b.radius=17*:

argument		pointer	this
0	3012	0	3012
1	17	1	
...			

(this 0  
is now  
aligned with  
RAM[ 3012 ])

# Handling objects: method calls

## Java code

```
class Complex {
    // Properties (fields):
    int re; // Real part
    int im; // Imaginary part
    ...
    /** Constructs a new Complex object. */
    public Complex(int re, int im) {
        this.re = re;
        this.im = im;
    }
    ...
}

class Foo {
    ...
    public void bla() {
        Complex x;
        ...
        x = new Complex(1,2);
        x.mult(5);
        ...
    }
}
```

## How to compile:

`x.mult(5)` ?

This method call can also be viewed as:

`mult(x,5)`

Generate the following code:

```
push x
push 5
call mult
```

General rule: each method call

`foo.bar(v1,v2,...)`

is translated into:

```
push foo
push v1
push v2
...
call bar
```

# Handling arrays: declaration / construction

## Java code

```
class Bla {  
    ...  
    void foo(int k) {  
        int x, y;  
        int[] bar; // declare an array  
        ...  
        // Construct the array:  
        bar = new int[10];  
        ...  
        bar[k]=19;  
    }  
    ...  
    Main.foo(2); // Call the foo method  
    ...  
}
```

Following  
compilation:

## RAM state

0		
	...	
275		x (local 0)
276		y (local 1)
277	4315	bar (local 2)
	...	
504	2	k (argument 0)
	...	
4315		} (bar array)
4316		
4317	19	
4318		
	...	
4324		
	...	

## How to compile:

`bar = new int(n) ?`

Generate code affecting:

`bar = Memory.alloc(n)`

# Handling arrays: accessing an array entry by its index

## Java code

```
class Bla {  
    ...  
    void foo(int k) {  
        int x, y;  
        int[] bar; // declare an array  
        ...  
        // Construct the array:  
        bar = new int[10];  
        ...  
        bar[k]=19;  
    }  
    ...  
    Main.foo(2); // Call the foo method  
    ...  
}
```

Following  
compilation:

RAM state, just after executing `bar[k] = 19`

0			
	...		
275		x	(local 0)
276		y	(local 1)
277	4315	bar	(local 2)
	...		
504	2	k	(argument 0)
	...		
4315		} (bar array)	
4316			
4317	19		
4318			
	...		
4324			
	...		

How to compile: `bar[k] = 19` ?

## VM Code (pseudo)

```
// bar[k]=19, or *(bar+k)=19  
push bar  
push k  
add  
// Use a pointer to access x[k]  
pop addr // addr points to bar[k]  
push 19  
pop *addr // Set bar[k] to 19
```

## VM Code (actual)

```
// bar[k]=19, or *(bar+k)=19  
push local 2  
push argument 0  
add  
// Use the that segment to access x[k]  
pop pointer 1  
push constant 19  
pop that 0
```




# Handling expressions

High-level code

```
((5+z)/-8)*(4^2)
```

syntax  
analysis



code  
generation

VM code

```
push 5
push z
add
push 8
neg
call div
push 4
push 2
call power
call mult
```

To generate VM code from a parse tree  $exp$ , use the following logic:

The  $codeWrite(exp)$  algorithm:

if  $exp$  is a constant  $n$  then output "push  $n$ "

if  $exp$  is a variable  $v$  then output "push  $v$ "

if  $exp$  is  $op(exp_1)$  then  $codeWrite(exp_1)$ ; output "op";

if  $exp$  is  $(exp_1 op exp_2)$  then  $codeWrite(exp_1)$ ;  $codeWrite(exp_2)$ ; output "op";

if  $exp$  is  $f(exp_1, \dots, exp_n)$  then  $codeWrite(exp_1)$ ; ...  $codeWrite(exp_n)$ ; output "call  $f$ ";


# Handling program flow

---

## High-level code

```
if (cond)
    s1
else
    s2
...
```

code  
generation




## VM code

```
VM code to compute and push !(cond)
if-goto L1
VM code for executing s1
goto L2
label L1
    VM code for executing s2
label L2
...
```

## High-level code

```
while (cond)
    s
...
```

code  
generation



## VM code

```
label L1
    VM code to compute and push !(cond)
    if-goto L2
    VM code for executing s
    goto L1
label L2
...
```

## High level code (BankAccount.jack class file)

```
/* Some common sense was sacrificed in this banking example in order
   to create a non trivial and easy-to-follow compilation example. */
class BankAccount {
    // Class variables
    static int nAccounts;
    static int bankCommission; // As a percentage, e.g., 10 for 10 percent
    // account properties
    field int id;
    field String owner;
    field int balance;

    method int commission(int x) { /* Code omitted */ }

    method void transfer(int sum, BankAccount from, Date when) {
        var int i, j; // Some local variables
        var Date due; // Date is a user-defined type
        let balance = (balance + sum) - commission(sum * 5);
        // More code ...
        return;
    }
    // More methods ...
}
```

## Pseudo VM code

```
function BankAccount.commission
    // Code omitted
function BankAccount.transfer
    // Code for setting "this" to point
    // to the passed object (omitted)
    push balance
    push sum
    add
    push this
    push sum
    push 5
    call multiply
    call commission
    sub
    pop balance
    // More code ...
    push 0
    return
```

## Final VM code

```
function BankAccount.commission 0
    // Code omitted
function BankAccount.transfer 3
    push argument 0
    pop pointer 0
    push this 2
    push argument 1
    add
    push argument 0
    push argument 1
    push constant 5
    call Math.multiply 2
    call BankAccount.commission 2
    sub
    pop this 2
    // More code ...
    push 0
    return
```

# Final example

Class-scope symbol table

Name	Type	Kind	#
nAccounts	int	static	0
bankCommission	int	static	1
id	int	field	0
owner	String	field	1
balance	int	field	2

Method-scope (transfer) symbol table

Name	Type	Kind	#
this	BankAccount	argument	0
sum	int	argument	1
from	BankAccount	argument	2
when	Date	argument	3
i	int	var	0
j	int	var	1
due	Date	var	2

# Perspective

---

Jack simplifications that are challenging to extend:

- ❑ Limited primitive type system
- ❑ No inheritance
- ❑ No public class fields, e.g. must use `r = c.getRadius()`  
rather than `r = c.radius`

Jack simplifications that are easy to extend :

- ❑ Limited control structures, e.g. no `for`, `switch`, ...
- ❑ Cumbersome handling of `char` types, e.g. cannot use `let x='c'`

Optimization

- ❑ For example, `c=c+1` is translated inefficiently into `push c, push 1, add, pop c`.
- ❑ Parallel processing
- ❑ Many other examples of possible improvements ...