

order table:

programiz.com/sql/online-compiler

Stop copy pasting code you don't actually understand
Build the coding confidence you need to become a developer companies will fight for

Become a PRO

Programiz Online SQL Editor

Interactive SQL Course

Customers [-]

customer_id [int]

first_name [varchar(100)]

last_name [varchar(100)]

age [int]

country [varchar(100)]

Orders [-]

order_id [integer]

item [varchar(100)]

amount [integer]

customer_id [integer]

Shippings [-]

shipping_id [integer]

status [integer]

customer [integer]

Input

Run SQL

-- Step 1: Create Table

CREATE TABLE orders (
ord_no INTEGER PRIMARY KEY,
purch_amt DECIMAL(10,2),
ord_date DATE,
customer_id INTEGER,
salesman_id INTEGER
);

-- Step 2: Insert Data

INSERT INTO orders VALUES
(70001, 150.50, '2013-10-05', 3005, 5001);

Output

first_name	age
John	31
Robert	22
David	22
John	25
Betty	28

Available Tables

Customers

customer_id	first_name	last_name	age	country
1	John	Doe	31	USA
2	Robert	Luna	22	USA
3	David	Robinson	22	UK
4	John	Reinhardt	25	UK
5	Betty	Doe	28	UAE

Orders

order_id	item	amount	customer_id
1	Keyboard	400	4
2	Mouse	300	4
3	Monitor	12000	3
4	Keyboard	400	1
5	Mousepad	250	2

Shippings

shipping_id	status	customer
-------------	--------	----------

Customers [-]

customer_id [int]

first_name [varchar(100)]

last_name [varchar(100)]

age [int]

country [varchar(100)]

Orders [-]

order_id [integer]

item [varchar(100)]

amount [integer]

customer_id [integer]

Shippings [-]

shipping_id [integer]

status [integer]

customer [integer]

-- Step 16: GROUP BY + HAVING

SELECT salesman_id,
SUM(purch_amt) AS total_sales
FROM orders
GROUP BY salesman_id
HAVING SUM(purch_amt) > 3000;

-- Step 17: GROUP BY + HAVING

SELECT customer_id,
SUM(purch_amt) AS total_purchase
FROM orders
GROUP BY customer_id
HAVING SUM(purch_amt) > 3000;

Output

first_name	age
John	31
Robert	22
David	22
John	25
Betty	28

Customers

customer_id	first_name	last_name	age	country
1	John	Doe	31	USA
2	Robert	Luna	22	USA
3	David	Robinson	22	UK
4	John	Reinhardt	25	UK
5	Betty	Doe	28	UAE

Orders

order_id	item	amount	customer_id
1	Keyboard	400	4
2	Mouse	300	4
3	Monitor	12000	3
4	Keyboard	400	1
5	Mousepad	250	2

Shippings

shipping_id	status	customer
1	Pending	2
2	Pending	4
3	Delivered	3

Customers [-]

customer_id [int]

first_name [varchar(100)]

last_name [varchar(100)]

age [int]

country [varchar(100)]

Orders [-]

order_id [integer]

item [varchar(100)]

amount [integer]

customer_id [integer]

Shippings [-]

shipping_id [integer]

status [integer]

customer [integer]

-- Step 14: GROUP BY Customer

SELECT customer_id,
SUM(purch_amt) AS total_purchase
FROM orders
GROUP BY customer_id;

-- Step 15: GROUP BY + MAX()

SELECT customer_id,
MAX(purch_amt) AS highest_purchase
FROM orders
GROUP BY customer_id;

Output

first_name	age
John	31
Robert	22
David	22
John	25
Betty	28

Customers

customer_id	first_name	last_name	age	country
1	John	Doe	31	USA
2	Robert	Luna	22	USA
3	David	Robinson	22	UK
4	John	Reinhardt	25	UK
5	Betty	Doe	28	UAE

Orders

order_id	item	amount	customer_id
1	Keyboard	400	4
2	Mouse	300	4
3	Monitor	12000	3
4	Keyboard	400	1
5	Mousepad	250	2

Shippings

shipping_id	status	customer
1	Pending	2
2	Pending	4
3	Delivered	3

Customers [-]

customer_id [int]

first_name [varchar(100)]

last_name [varchar(100)]

age [int]

country [varchar(100)]

Orders [-]

order_id [integer]

item [varchar(100)]

amount [integer]

customer_id [integer]

Shippings [-]

shipping_id [integer]

status [integer]

customer [integer]

SELECT COUNT(*) AS total_orders
FROM orders;

-- Step 13: GROUP BY Salesman

SELECT salesman_id,
SUM(purch_amt) AS total_sales
FROM orders
GROUP BY salesman_id;

-- Step 14: GROUP BY Customer

first_name	age
John	31
Robert	22
David	22
John	25
Betty	28

Customers

customer_id	first_name	last_name	age	country
1	John	Doe	31	USA
2	Robert	Luna	22	USA
3	David	Robinson	22	UK
4	John	Reinhardt	25	UK
5	Betty	Doe	28	UAE

Orders

order_id	item	amount	customer_id
1	Keyboard	400	4
2	Mouse	300	4
3	Monitor	12000	3
4	Keyboard	400	1
5	Mousepad	250	2

Shippings

shipping_id	status	customer
1	Pending	2
2	Pending	4
3	Delivered	3

Programiz Online SQL Editor

Interactive SQL Course

Customers [-]

customer_id [int]

first_name [varchar(100)]

last_name [varchar(100)]

age [int]

country [varchar(100)]

Orders [-]

order_id [integer]

item [varchar(100)]

amount [integer]

customer_id [integer]

Shippings [-]

shipping_id [integer]

status [integer]

customer [integer]

Input

WHERE purch_amt > 2000;

-- Step 4: WHERE with Date

SELECT *
FROM orders
WHERE ord_date = '2012-09-10';

-- Step 5: WHERE with Salesman

SELECT *
FROM orders

Output

first_name	age
John	31
Robert	22
David	22
John	25
Betty	28

Available Tables

Customers

customer_id	first_name	last_name	age	country
1	John	Doe	31	USA
2	Robert	Luna	22	USA
3	David	Robinson	22	UK
4	John	Reinhardt	25	UK
5	Betty	Doe	28	UAE

Orders

order_id	item	amount	customer_id
1	Keyboard	400	4
2	Mouse	300	4
3	Monitor	12000	3
4	Keyboard	400	1
5	Mousepad	250	2

Shippings

shipping_id	status	customer
1	Pending	2
2	Pending	4
3	Delivered	3

Eethikaaaaa

Correct MySQL Commans

WEEK7

siripanchajanya-netizen/

Online SQL Editor

Ask Gemini

programiz.com/sql/online-compiler

Dashboard | KLH L...KL University ERP | Codolio - Your All... | Learner dashboar... | Prime Video: Watc... | Home - Netflix | HTML Essentials | nuguri siri | LinkedIn | All Bookmarks

Stop copy pasting code you don't actually understand

Build the coding confidence you need to become a developer companies will fight for

Become a PRO

Programiz Online SQL Editor

Interactive SQL Course

Customers [-]

customer_id [int]

first_name [varchar(100)]

last_name [varchar(100)]

age [int]

country [varchar(100)]

Orders [-]

order_id [integer]

item [varchar(100)]

amount [integer]

customer_id [integer]

Shippings [-]

shipping_id [integer]

status [integer]

customer [integer]

Input

Run SQL

-- Step 1: Create Table

CREATE TABLE orders (
ord_no INTEGER PRIMARY KEY,
purch_amt DECIMAL(10,2),
ord_date DATE,
customer_id INTEGER,
salesman_id INTEGER
);

-- Step 2: Insert Data

INSERT INTO orders VALUES
(70001, 150.50, '2013-10-05', 3005, 5007);

Output

first_name	age
John	31
Robert	22
David	22
John	25
Betty	28

Available Tables

Customers

customer_id	first_name	last_name	age	country
1	John	Doe	31	USA
2	Robert	Luna	22	USA
3	David	Robinson	22	UK
4	John	Reinhardt	25	UK
5	Betty	Doe	28	UAE

Orders

order_id	item	amount	customer_id
1	Keyboard	400	4
2	Mouse	300	4
3	Monitor	12000	3
4	Keyboard	400	1
5	Mousepad	250	2

Shippings

shipping_id	status	customer
-------------	--------	----------