

Celestial Object Classification

Xiaoyang Wang Ziang Zeng

Outline

- 1 Astronomical Challenge
- 2 Data & Preprocessing
- 3 Methodology
- 4 Results
- 5 Conclusions

Section 1

Astronomical Challenge

Astronomical Challenge

Classifying celestial objects into stars, galaxies or quasars using their spectral characteristics.

Section 2

Data & Preprocessing

Image of the celestial objects



Figure 1: Galaxy



Figure 2: Star



Figure 3: Quasar

Table 1: Metadata of the celestial objects

vars	explanations
ra	Right Ascension angle (at J2000 epoch)
dec	Declination angle (at J2000 epoch)
u	Ultraviolet filter
g	Green filter
r	Red filter
i	Near Infrared filter
z	Infrared filter
run	Run Number
rerun	Rerun Number
camcol	Camera column
field	Field number
specobjid	Unique ID used for optical spectroscopic objects
class	Object class
redshift	Redshift value based on the increase in wavelength
plate	Plate
mjd	Modified Julian Date


- Missing Values: 3
- Samples for each category: 33333

Section 3

Methodology

Meta Data

- Explanatory Variables: u, g, r, i, z, redshift
- Response Variable: class
- STAR: 0
- GALAXY: 1
- QSO: 2
- kNN: $k = 3$
- Decision Tree
- Gini impurity,
- (para)
- Logistic Regression
- C:0.01
- penalty: l2
- iteration:2000



• Structure:

- 2 layers of convolution and 1 maxpooling
- 3 layers of full connecting
- output: $\vec{y} = (y_1, y_2, y_3)$

$$y_{pred} = \operatorname{argmax}_i \{\vec{y}\}$$


Probability through softmax

$$P(y = j | \mathbf{z}) = \frac{e^{z_j}}{\sum_{k=1}^3 e^{z_k}}$$

• Training:

SGD with different momentum, Adam, 10 epoch, batch size 64, lr 0.001

Voting Classifier



- Soft Voting:

- Models $\{C_1, \dots, C_n\}$
- For a given inputs, C_i has a prediction $P_i(y_j|x)$
- The predict probabilities for voting classifier
$$P(y_j|x) = \frac{1}{m} \sum_{i=1}^m P_i(y_j|x)$$
- $Thep(x) = \arg \max_{y_j} P(y_j|x)$

- Hard Voting:

- $p(x) = \text{mode}(p_1(x), p_2(x), \dots, p_m(x))$, mode identify the most frequent one

- Construction:

The candidate models are KNN, Logistic Regression, Classification Tree, CNN for image and CNN for spectrum image

Section 4

Results




Figure 7: Confusion Matrices for Metadata Models

Voting Classifier

Section 5

Conclusions

Table 2: Evaluation of Models

Data Model		M kNN	M DT	M LR	IC CNN	IS CNN	M+IC+IS VC
Accuracy		96.79%	97.68%	97.04%	93.91%	99.14%	97.8%
Precision	Star	95.59%	99.82%	95.95%	0%	0%	0%
	Galaxy	96.01%	96.45%	96.46%	0%	0%	0%
	Qso	98.84%	96.8%	98.77%	0%	0%	0%
Recall	Star	98.67%	99.82%	99.59%	0%	0%	0%
	Galaxy	94.61%	96.68%	95.06%	0%	0%	0%
	Qso	97.13%	96.56%	96.5%	0%	0%	0%
F1	Star	97.11%	99.82%	97.74%	0%	0%	0%
	Galaxy	95.31%	96.56%	95.76%	0%	0%	0%
	Qso	97.98%	96.68%	97.63%	0%	0%	0%

References I