Traffic STGNNs across Sensor, City, and Time Shifts: Routing Concentration Tracks Sensitivity to Sensor Dropout

Xile Wang
School of Management
South China University of Technology
Guangzhou, China
xile.wang@outlook.com

Mingqi Yang
School of Management
South China University of Technology
Guangzhou, China
yangmq@scut.edu.cn

Abstract

Traffic forecasting benchmarks measure accuracy within a single city and test distribution, leaving open how architectures behave when sensors fail, when a model is transferred to another city, or when weekday and weekend traffic differ. We evaluate eight STGNN architectures under these three shifts using frozen checkpoints; for transfer across cities, target graph information is withheld so that fixed and adaptive graph models have the same structural access. We find that fragility under sensor dropout follows routing concentration rather than the use of adaptive adjacency itself. Across six adaptive backbones, mean row maximum routing mass correlates with dropout degradation at Pearson $\rho{=}+0.974$, with positive associations on three source datasets. Graph WaveNet exhibits concentrated routing and dropout sensitivity, while AGCRN and STAEformer stay close to DCRNN when sensors are zeroed. The other shifts separate from this pattern: MegaCRN leads source-normalized cross-city transfer, while weekday/weekend rankings depend on the reporting convention. MegaCRN and STAEformer have large normalized gaps but lower weekend error in masked mph, exposing a metric-dependent ranking reversal. In this backbone bank, strong performance under one shift does not imply robustness under another. We release a registry of frozen checkpoints, evaluation code, and a decision table mapping each backbone to its main failure mode.

1 Introduction

Traffic forecasting supports urban services such as ride-hailing dispatch, signal timing, and congestion management. STGNNs are now standard tools [Li et al., 2018, Wu et al., 2019, Yu et al., 2018], but they are usually selected with training and test data from the same city, sensors, and time window. Deployment is less tidy: sensors fail silently, a model trained in one city may be applied to another, and traffic changes between weekdays and weekends. Clean MAE alone does not say which architecture survives which shift.

Prior STGNN robustness work proposes OOD interventions via retrieval or pruning [Zhang et al., 2025, Jing et al., 2026] or frames cross-city transfer as federated learning [Zeng et al., 2025]. What is missing is a controlled *diagnostic*: the same frozen backbone evaluated under several deployment-realistic shifts, with differences traced to concrete architectural choices. We also pre-register hypotheses so failed predictions remain part of the evidence. Cross-city comparisons need one more control: adaptive models can in principle re-learn a target topology, while fixed-graph models cannot. A matched-structural-access protocol, where every backbone uses source-city topology, removes that asymmetry. The contribution is an evaluation object, not a new forecaster: a frozen-

40th Conference on Neural Information Processing Systems (NeurIPS 2026). Track on Evaluations and Datasets.

checkpoint protocol, a shift taxonomy, and a mechanism audit for when the clean-test ranking is no longer the ranking that matters.

We assemble a bank of eight architectures trained on METR-LA: a five-model canonical bank spanning graph-free (GRU), fixed-graph (DCRNN, STGCN), and adaptive-graph (MTGNNLight, GWNet) models, plus three modern adaptive-relation models (AGCRN, MegaCRN, STAEformer). Each frozen checkpoint is evaluated under three shifts: **sensor dropout** (10–50% zeroed at inference, 5 random masks), **cross-city transfer** (zero-shot METR-LA $\rightarrow$ PEMS-BAY under matched structural access), and **temporal shift** (weekend vs. weekday windows within the METR-LA test set). The sensor experiment diagnoses silent zero-masking: reliable last-observed-value carry-forward (LOCF) largely removes the gap in the imputation comparison. We report temporal subgroup differences in both normalized and physical units, since the two conventions can reverse the apparent direction of a model's gap.

Contributions.

1. **Multi-shift diagnostic protocol.** We freeze eight STGNN checkpoints trained on a single source city and evaluate them under sensor dropout, cross-city transfer, and weekday/weekend temporal subgroup shift using a unified matched-structural-access protocol. The code repository contains the frozen-checkpoint registry and evaluation scripts: `https://github.com/sirjuststop/stgnn-shift-bench`.
2. **Routing concentration as a failure coordinate.** Sensor-dropout fragility tracks adjacency concentration (Pearson $\rho{=}+0.974$ across six adaptive backbones, with positive associations on three source datasets). GWNet's dense softmax routing explains its fragility; AGCRN and STAEformer, also adaptive, match DCRNN because their routing is sparser. A mask-aware inference variant recovers 75% of GWNet's dropout gap without retraining.
3. **Cross-axis tradeoff and recommendation artifact.** Rankings differ across deployment axes and reporting conventions: source-normalized transfer favors MegaCRN, while its large normalized weekday/weekend gap reverses sign under masked-mph evaluation. We include a recommendation artifact that maps each backbone to its anticipated failure mode under each shift.

Four of sixteen pre-registered predictions were refuted; the hypothesis ledger is in Appendix A.

2 Related Work

Evaluation and robustness benchmarks. NeurIPS Datasets and Benchmarks papers such as BEIR [Thakur et al., 2021] and RobustBench [Croce et al., 2021] show that evaluation papers can contribute by changing what a field measures. The closest spatiotemporal analogue is Yi et al. [2021]'s corruption benchmark for video models. We make the setting traffic-specific: the same frozen STGNNs are audited under sensor failure, city transfer, and temporal subgroup shift. Existing traffic OOD work largely proposes adaptation or retrieval methods; existing spatiotemporal benchmarks test corruption robustness or general zero-shot transfer, but not frozen-architecture diagnostics paired with mechanism attribution. We target that missing diagnostic.

Spatiotemporal graph neural networks for traffic. DCRNN [Li et al., 2018], STGCN [Yu et al., 2018], Graph WaveNet [Wu et al., 2019], GRU, and MTGNNLight span graph-free, fixed-graph, and adaptive-graph designs in our canonical bank. We extend the diagnostic to AGCRN [Bai et al., 2020], MegaCRN [Jiang et al., 2023], and STAEformer [Liu et al., 2023a], all competitive traffic forecasters with learned spatial or temporal relation modules. The comparison separates topology learning from routing concentration: MTGNNLight's sparse learned graph is less fragile than GWNet's dense softmax graph, while AGCRN and STAEformer match DCRNN under sensor dropout.

Distribution shift in spatiotemporal models. A handful of recent methods address distribution shift in STGNNs. STRAP [Zhang et al., 2025] and TL-GPSTGN [Jing et al., 2026] propose OOD interventions through retrieval or graph-context pruning. We instead supply the diagnostic that such interventions need: which backbone degrades under which shift, and which architectural mechanism is implicated.

Cross-city transfer learning. Cross-city work often assumes federated or retrieval-based adaptation, as in FedTT [Zeng et al., 2025] and CAST-CKT [Fofanah et al., 2026]; large-scale benchmarks such as LargeST [Liu et al., 2023b] address scale rather than zero-shot transfer. We evaluate the stricter zero-shot case: models trained only on METR-LA applied directly to PEMS-BAY, with no target-city adaptation.

Topology-agnostic and foundation-model approaches. Topology-free time-series foundation models such as Chronos [Ansari et al., 2024] adapt through pretraining or fine-tuning rather than explicit road topology. Our zero-shot setting asks which architectural properties reduce fragility before any adaptation is available.

Sensor failure and data imputation. Mask-aware reconstruction architectures such as GRIN [Cini et al., 2022] and BRITS [Cao et al., 2018] reconstruct missing inputs before or during graph aggregation. We ask an orthogonal question: among standard STGNNs without imputation, which architectural choices reduce sensitivity and which amplify fragility? LOCF nearly eliminates the ranking (Appendix C.8), so the sensor result is specific to silent zero-masking.

3 Problem Setup and Backbone Bank

The audit evaluates eight frozen STGNN checkpoints under three deployment-realistic shifts. Table 1 summarizes each shift axis, its metric, the protocol control, the main validity threat, and the appendix that addresses it.

Table 1: **Audit design at a glance.** Three deployment-realistic shifts evaluated under a unified frozen-checkpoint protocol.

Shift axis	Metric	Control	Validity threat	App. check
Sensor dropout	Δ_{sensor}: MAE delta (norm.)	MAE on kept sensors only; primary mask	Random vs. structured dropout pattern	C.4, C.3
Cross-city transfer	X-city norm. MAE	Matched structural access (source adj)	Subset sampling; padding inflation	D.2, D.6
Temporal subgroup	Δ_{temp}: weekend−weekday (norm.; mph comparison)	Within-split stratification; no new data	Metric-dependent sign reversal	E.1, E.3

How to read the audit. Each column in the main tables is an estimand, not a single leaderboard score. Clean MAE identifies the checkpoint being audited. Δ_{sensor} measures incremental damage from silent zero-masking on the source city. Cross-city MAE measures zero-shot transfer under matched structural access, and Δ_{temp} measures a weekday/weekend subgroup gap inside the held-out source-city test split. We therefore compare models within a shift axis and treat changes in rank across axes as the object of study. This convention also avoids turning the masked-MAE convention used by newer adaptive-relation models into a false clean-performance comparison with the canonical bank.

3.1 Backbone Architectures

The canonical bank covers five architectures from graph-free to fixed-graph to adaptive-graph.

DCRNN [Li et al., 2018] uses a bidirectional diffusion GRU on a fixed road-distance adjacency $\mathbf{A}$ (truncated at K hops in both directions), fixed at training and inference. **Graph WaveNet (GWNet)** [Wu et al., 2019] adds a learned adaptive adjacency

$$\hat{\mathbf{A}} = \text{softmax}(\mathbf{E}_1 \mathbf{E}_2^\top), \tag{1}$$

with $\mathbf{E}_1, \mathbf{E}_2 \in \mathbb{R}^{N \times d_e}$ trained end-to-end and tied to the N training nodes. **STGCN** [Yu et al., 2018] alternates gated temporal convolutions with truncated-Chebyshev spectral graph convolutions over the same fixed road adjacency. **GRU** is a graph-free recurrent baseline that treats the N sensors as a

single feature vector and uses no adjacency. **MTGNNLight** is a lightweight MTGNN variant [Wu et al., 2020] that learns a sparse adaptive graph via pairwise cosine similarity on a single embedding $\mathbf{E} \in \mathbb{R}^{N \times d}$ and keeps only top-k neighbors per node. This directly contrasts with GWNet's dense all-pairs softmax and isolates whether dropout fragility depends on adjacency density or on topology learning per se (P14).

These five share a unified config (hidden dim 64, seq/pred 12, Adam 1×10^{-3}, weight decay 10^{-4}, cosine schedule, 100 epochs, patience 15). To rule out training-artifact explanations of GWNet's fragility, we additionally train **GWNet[CM]** (patience 30) and **GWNet[Strong]** (P17; hidden 128, adaptive embed 20, patience 30); both are frozen at shift-eval time.

3.2 Backbone Bank Protocol

We train each backbone once on METR-LA [Li et al., 2018] using the chronological 70/10/20 split and three fixed seeds. The resulting checkpoints are frozen before any shift evaluation: no model is re-trained, fine-tuned, or selected separately for sensor dropout, cross-city transfer, or temporal subgroup analysis. An additional four-backbone few-shot probe relaxes this constraint to test limited target-data adaptation (Appendix D.4).

Table 2 reports the clean METR-LA MAE together with the three shift metrics. The clean column is included only to anchor the starting point of each checkpoint. Our claims are not based on clean ranking: a backbone can be useful for diagnosing a failure mechanism even when it is not the strongest source-city forecaster. For the same reason, GWNet[CM] and GWNet[Strong] are treated as control checkpoints for the GWNet finding, not as additional entries in the main bank.

3.3 Extended adaptive-relation models

To probe generality, we add three architectures using the same METR-LA split and frozen-checkpoint rule: **AGCRN** [Bai et al., 2020] (node-adaptive GRU, no temporal covariates); **MegaCRN** [Jiang et al., 2023] (meta-graph memory with TOD/DOW inputs); **STAEformer** [Liu et al., 2023a] (Transformer with spatial-temporal adaptive embeddings encoding temporal covariates). These models use their standard masked-MAE convention, while the canonical bank uses plain MAE; Table 3 reports clean values only to identify checkpoints, not to rank clean performance across families.

3.4 Distribution shifts

Sensor dropout. At inference, a random 30% of sensor channels are zero-masked. We do not re-instantiate the 207-node model; it sees a 207-dimensional input with zeroed channels, and MAE is computed on the kept sensors only so clean and masked evaluations are directly comparable. Tables 2–3 report the pre-registered primary-mask aggregate; Appendix C.3 reports 5-mask aggregates to separate mask-sampling from model-weight variance. GRU is the main mask-sampling caveat. Structured dropout patterns (hub and contiguous) are in Appendix C.4. This protocol isolates silent failure; the LOCF comparison in Appendix C.8 shows that effective imputation can largely remove the zero-mask gap. Supplementary probes add stale hold, noise, bias, and intermittent missingness (Appendix C.2).

Cross-city transfer. The frozen METR-LA model is evaluated zero-shot on PEMS-BAY [Li et al., 2018] (Bay Area, 325 sensors, 52,116 timesteps). A second pair (PEMS04 source, 307 sensors; zero-shot on METR-LA and PEMS-BAY) is in Appendix D.5 for cross-city generality (P18). "Zero-shot" means no re-training or fine-tuning. Because PEMS-BAY has 325 sensors and the METR-LA checkpoints have 207 input channels, we subsample 207 PEMS-BAY sensors (5 subsets); rankings remain stable at 150-node coverage (Appendix D.2).

Matched structural access (canonical comparison). The main cross-city comparison uses source-only adjacency: every backbone uses the METR-LA adjacency at inference, removing the asymmetry that adaptive-graph models cannot access target topology by construction. Under this constraint, any observed advantage is architectural, not an artifact of privileged topology access (target-adj results: Appendix D.3). MAE is normalized with source-city statistics for cross-architecture comparability.

Temporal subgroup shift. METR-LA spans weekdays and weekends with different traffic patterns; the model is trained on both. We stratify the test set by day type—weekday (5,104 windows) and weekend (1,728 windows)—and report $\Delta_{\text{temp}} = \text{MAE}_{\text{weekend}} - \text{MAE}_{\text{weekday}}$. This is a subgroup performance gap within the existing test split, not deployment to a new time window. In addition to the normalized gaps, we report the extended models' masked-mph gaps on the same checkpoints and windows (Appendix E.1). The latter exclude zero-valued targets, whereas normalized MAE includes all targets; the comparison changes both scaling and the target mask.

Protocol summary. Train on METR-LA (207 sensors, 5-min, 70/10/20 split); 3 seeds, 100 epochs, patience 15; frozen at evaluation. *Sensor:* 30% silent primary zero-mask for Tables 2–3, MAE on kept sensors. *City:* zero-shot to PEMS-BAY (325→207 subsampled, 5 subsets), source-only adjacency (matched-structural-access; padding sensitivity in Appendix D.6). *Temporal:* weekday (5,104) vs. weekend (1,728) test windows. *Aggregation:* mean ± population std over 3 seeds unless a table explicitly reports multi-mask summaries; METR-LA train-statistics normalization for the canonical bank, model-specific scaler for extended models (§3.3).

4 Robustness Taxonomy

Pre-registered hypotheses. We pre-registered 16 predictions in five stages before running the corresponding experiments. Of these, 10 were confirmed, 4 were refuted, and 2 were partially confirmed. The full prediction–outcome ledger is in Appendix A; the relevant confirmed predictions (P14–P19, P21) are referenced inline where their results appear. We use the ledger to keep the taxonomy falsifiable: failed predictions remain in the appendix, and main-text claims are tied either to a pre-specified contrast or to a control experiment that removes a concrete artifact.

Table 2 reports the main results across all five backbones and three shift types. The columns should not be averaged into a single robustness score. They use different estimands and normalizers, so the evidence is the change in ordering from one deployment axis to the next.

Table 2: **Robustness rankings are shift-specific.** Five backbones evaluated across sensor dropout, cross-city transfer, and temporal subgroup shift. Values are mean ± population std over 3 seeds; lower is better.

Backbone	In-dist MAE (mph)	Δ_{sensor} (30%, norm.)	X-city (norm.)†	Δ_{temp} (norm.)
DCRNN (fixed diffusion)	6.58 ± 0.03	$+0.020 \pm 0.002$	0.180 ± 0.001	$+0.087 \pm 0.004$
GRU (graph-free)	7.49 ± 0.12	$+0.025 \pm 0.012$	0.278 ± 0.009	$+0.093 \pm 0.003$
MTGNNLight (sparse cosine-sim)	6.88 ± 0.11	$+0.051 \pm 0.012$	0.244 ± 0.004	$+0.075 \pm 0.007$
STGCN (fixed spectral)	7.12 ± 0.05	$+0.078 \pm 0.007$	0.249 ± 0.008	$+0.093 \pm 0.003$
GWNet (dense adaptive adj)	7.85 ± 0.11	$+0.088 \pm 0.017$	0.268 ± 0.006	$+0.094 \pm 0.009$

†Source-only adjacency; METR-LA-stat normalized MAE on PEMS-BAY.

Sensor dropout. The sensor axis separates GWNet from the other canonical backbones. DCRNN and GRU have the smallest deltas, while MTGNNLight is markedly less fragile than GWNet despite also learning topology. This rules out "adaptive graph" as the right explanatory variable; the contrast is between sparse learned routing and dense all-pairs softmax. Capacity controls reduce but do not remove the GWNet gap (Table 7; Appendix C.3). The same reading also survives a stronger missingness pattern: hub dropout widens GWNet's gap while making DCRNN less sensitive, which is the expected direction if dropped high-flow nodes expose concentrated learned routes rather than merely increasing the number of missing inputs. The ranking also depends on corruption type: at 30% affected channels, GWNet's healthy-sensor increase is $+0.16$ mph for noise but $+1.96$ mph for bias, compared with DCRNN's $+0.28$ and $+1.00$ mph, respectively (Appendix C.2).

Cross-city transfer under matched structural access. Under source-only adjacency, DCRNN is the strongest canonical-bank transfer baseline. The result is not a simple fixed-vs-adaptive split: STGCN loses its target-adjacency advantage once target topology is withheld, and then sits near GWNet under the fair comparison. The DCRNN advantage also holds on a second city pair, while padding sensitivity changes absolute MAE but not the ordering (Table 7; Appendix D.6). The GRU baseline is useful here because it removes graph mismatch entirely and still transfers worst in the canonical bank. Cross-city robustness therefore does not come from ignoring structure; it depends on how the source-city structure is used when the target graph is unavailable.

Temporal subgroup shift (canonical bank). Within the canonical bank, weekend/weekday gaps are effectively tied: the between-model spread is small relative to the sensor and city-transfer separations, and it is not aligned with graph type. None of these architectures condition on explicit time-of-day or day-of-week, so graph structure neither helps nor hurts on this within-dataset subgroup shift. We therefore treat the canonical-bank temporal column as a negative result and as the baseline for §4.1, where reporting conventions change the interpretation of the extended models' temporal gaps.

Shift-specificity (canonical bank). DCRNN leads source-only city transfer, while sensor-dropout and temporal rankings follow different patterns. The modern adaptive-relation models below further change the transfer ordering. The diagnostic is therefore read by shift axis, not as a global ranking. Capacity, source-adjacency, structured dropout, and horizon controls are consolidated in Appendix Table 7.

4.1 External validity: modern adaptive-relation models

The canonical bank covers four spatial-aggregation strategies but omits the newer adaptive-relation designs used in recent traffic forecasting work. To test whether the findings carry over, we add three architectures (AGCRN, MegaCRN, STAEformer) trained on the same METR-LA data with the same split, frozen after training, evaluated under the same protocol. Table 3 reports results alongside DCRNN as a reference.

Table 3: **Adaptive-relation models under the three shift axes.** Clean MAE follows each architecture's standard masked-MAE convention; shift columns use the same normalized protocol as Table 2.

Model	Clean MAE (mph)	Δ_{sensor} (30%, norm.)	Cross-city (src, norm.)	Δ_{temp} (norm.)
AGCRN	$4.09 \pm 0.02^{\dagger}$	$+0.019 \pm 0.001$	0.206 ± 0.009	$+0.061 \pm 0.008$
MegaCRN	$3.04 \pm 0.06^{\dagger}$	-0.048 ± 0.027	0.163 ± 0.003	$+0.734 \pm 0.019$
STAEformer	$2.93 \pm 0.01^{\dagger}$	$+0.015 \pm 0.001$	0.223 ± 0.008	$+0.750 \pm 0.003$
DCRNN (ref)	6.58 ± 0.03	$+0.020 \pm 0.002$	0.180 ± 0.001	$+0.087 \pm 0.004$

† Masked MAE (target > 0); DCRNN uses plain MAE. Cross-family clean-performance ranking is not meaningful due to this convention difference.

Sensor dropout. AGCRN and STAEformer stay near DCRNN on sensor dropout, so GWNet's result cannot be read as "adaptive graphs are fragile." The distinction is dense all-pairs softmax (Eq. 1) versus node-specific or attention-mediated relations. MegaCRN's negative delta is non-monotonic in dropout ratio and is treated conservatively as adjacency-mediated smoothing toward a weekday prior (§5.3), not as direct dropout robustness.

Cross-city transfer. MegaCRN attains the lowest source-stat cross-city MAE, overturning the canonical-bank result that DCRNN is the best zero-shot transfer baseline in the smaller bank. AGCRN and STAEformer fall between DCRNN and GWNet.

Temporal subgroup shift. In physical units, MegaCRN and STAEformer have *lower* weekend error: their weekend-minus-weekday gaps are -0.594 ± 0.051 and -0.612 ± 0.002 masked mph, respectively. AGCRN's gap is $+0.750 \pm 0.013$ mph. The normalized gaps in Table 3 are positive for all three models. Thus the large normalized gaps do not establish greater physical-error fragility: scaling and target masking reverse the sign for two models (Appendix E.1). Covariate interventions address the normalized gap, not this absolute-error ranking.

Synthesis: axis-specific failure modes. Modern adaptive-relation models split their failures across deployment axes (Figure 1): AGCRN and STAEformer match DCRNN under sensor dropout, MegaCRN leads source-normalized cross-city transfer, and temporal comparisons expose a reporting-convention effect. The shared sensor-dropout coordinate is routing concentration: it tracks fragility even when clean accuracy and cross-city ranking move in different directions. The sensor-dropout ranking is specific to silent zero-masking; under last-observed-value carry-forward (LOCF) the four backbones in the imputation comparison recover $\geq 97\%$ of the gap (Appendix C.8), so the

practical impact of GWNet's fragility depends on the deployment pipeline's imputation policy. The main conclusions are drawn from METR-LA as the source city; PEMS04 is used only for targeted source-city replication, not as a full third-source benchmark (§6).




Figure 1: **Shift profiles and the absolute-unit temporal correction.** Sensor and city panels show all eight backbones; the dashed line separates the canonical and extended banks. Hatched bars show PEMS04-native replication. The temporal panel shows masked-mph gaps for the three extended models: MegaCRN and STAEformer have lower weekend error despite positive normalized gaps. Error bars are population std over three seed-level means.

5 Mechanism: dense adaptive routing and sensor-dropout fragility

The taxonomy shows GWNet's dense learned routing is fragile under sensor dropout while AGCRN and STAEformer, which also learn adaptive spatial relations, are not (Table 3). Two questions follow: is the dense adaptive adjacency (Eq. 1) the driver, and can the failure mode be mitigated without retraining?

5.1 Ablation: adaptive vs. fixed adjacency

We run frozen GWNet checkpoints under two inference-time adjacency configurations. **GWNet[adaptive]** keeps $\hat{\mathbf{A}} = \text{softmax}(\mathbf{E}_1\mathbf{E}_2^\top)$; **GWNet[fixed]** replaces $\hat{\mathbf{A}}$ with the normalized METR-LA distance adjacency $\mathbf{A}$ and zeros out $\mathbf{E}_1, \mathbf{E}_2$ (rest of the network unchanged).

Table 4: **Fixed-road GWNet reduces sensor-dropout sensitivity and city-transfer MAE.** Mean ± population std over 3 seeds; city MAE is target-adj PEMS-BAY mph.

Variant	In-dist MAE	Δ_{sensor} (30%, primary mask)	City MAE (mph)
GWNet[adaptive]	7.85 ± 0.11	$+0.088 \pm 0.017$	4.42 ± 0.15
GWNet[fixed]	8.27 ± 0.08	$+0.050 \pm 0.010$	3.44 ± 0.04
Change	$+5.3\%$	-43.1%	-22%

Fixed substitution cuts sensor-dropout sensitivity by 43.1% and city-transfer MAE by 22%, at $+5.3\%$ in-distribution cost, past the pre-registered $\geq 30\%$ threshold for attributing fragility to the adaptive adjacency. Per-horizon decomposition (Table 7) shows GWNet's cross-city MAE is nearly horizon-flat ($+4\%$ growth h=1→12) while DCRNN grows $+46\%$: the transfer gap is static structural mis-routing, not error accumulation.

Mask-aware adjacency variant. Zeroing and renormalizing adjacency rows/columns for dropped sensors at inference ($\hat{\mathbf{A}}[i,:]=\hat{\mathbf{A}}[:,i]=0$, then $\hat{\mathbf{A}} \leftarrow \hat{\mathbf{A}}/\max(\hat{\mathbf{A}}\mathbf{1}, \epsilon)$) should partially restore robustness without retraining.

Table 5: **Mask-aware routing reduces GWNet's multi-mask dropout gap.** Dropped-sensor rows/columns are zeroed and renormalized; each of 3 seeds is averaged over 5 random 30% masks. Error bars summarize the seed means; recovery is the mean of per-seed recovery ratios.

Variant	Δ_{sensor} (30%, multi-mask)	Recovery
GWNet[standard]	$+0.092 \pm 0.030$	—
GWNet[mask-aware]	$+0.023 \pm 0.009$	75.2%

Mask-aware routing recovers 75.2%, compared with 43.1% for fixed substitution: blocking only the affected rows/columns preserves useful learned routes while removing the failed sources. The intervention is $\sim$25 LoC and can be applied to existing GWNet checkpoints. The recovery is stable across dropout ratios: 70–76% for random 10–40% dropout and 71% for hub-30% dropout (Appendix C.7).

5.2 Routing concentration as a shared mechanism hypothesis

The GWNet analysis above provides model-specific evidence; we next examine the association over the four adaptive-graph models in our bank (n=4 adaptive backbones). We measure adjacency concentration as max_mass, the mean per-row maximum routing probability, using each model's native relation proxy. Pairing this proxy with the routing-spectrum Δ_{sensor} estimand gives Pearson ρ=$+0.979$ (Appendix F.2). Removing GWNet leaves ρ=$+0.961$; the exact permutation test gives p=0.083 (n=4; Appendix F.2.2). Seed-level and rank diagnostics are in Appendix F.2.1. STAEformer has no single row-stochastic adjacency and is excluded from this proxy comparison. The main tables retain their primary-mask estimand. We extend the architecture sample with GTS [Shang et al., 2021] (link-predictor graph learning) and DGCRN [Li et al., 2021] (input-conditioned dynamic graphs), selected for their distinct mechanisms. Across six architectures, ρ=$+0.974$ with exact permutation p=0.003; dropping GWNet leaves $+0.973$, and the minimum leave-one-out value is $+0.961$. Native-source associations remain positive on METR-LA, PEMS-BAY, and PEMS04 ($+0.974$, $+0.75$, $+0.63$), although the PEMS04 result is not significant at 0.05 (Appendix F.3). The original four-model relation also replicates on native PEMS04 checkpoints (ρ=$+0.910$; Appendix F.4). Together, these comparisons support a shared-mechanism hypothesis within the evaluated architectures and traffic datasets. A local perturbation argument supports this: zero-masking a dropped sensor j shifts each kept node i by $A_{ij}H_jW$; averaging over rows bounds the mean signal disruption by $B_H B_W |\mathcal{I}| \max_\text{mass}(A)$. Concentrated routing raises this bound proportionally; this is why we treat $\max_\text{mass}$ as a tail-risk proxy for iid dropout. This is a single-layer perturbation bound, not a full-horizon MAE theorem. The complete derivation and caveats are in Appendix F.5.

Within GWNet, top-k sparsification at inference traces the same curve: relative fragility rises from 0.80% at k=10 to 1.17% at k=full (Appendix F.1).

5.3 Ruling out two natural mechanism hypotheses

Two ablations probe the normalized MegaCRN/STAEformer temporal gaps. Randomizing or swapping explicit time embeddings leaves MegaCRN's normalized gap unchanged and reduces STAEformer's by only 12.5%, so TOD/DOW covariates alone do not explain that metric. MegaCRN's negative sensor delta is adjacency-mediated smoothing toward a weekday-dominated prior, not evidence that MegaCRN directly tolerates dropout (Appendix G.2). These interventions do not establish excess temporal error in mph, where the gaps reverse sign. Isolating the remaining normalized-gap mechanism requires retraining, left to future work (Appendix E.3).

5.4 Severity, degree stratification, and imputation baselines

In the original three-model severity comparison, GWNet is the most sensitive backbone at all five dropout ratios (GWNet/DCRNN ratio grows $2.5\times \rightarrow 4.6\times$ from 10% to 40%; Appendix C.1). The extended physical-unit comparison places DGCRN, the highest-concentration model, at the most fragile endpoint at four of five severities (Table 10). GWNet's highest-degree quartile suffers Δ_{sensor}=$+0.121$ versus $+0.066$ for Q1 ($1.83\times$); DCRNN shows no degree dependence (Appendix C.5). Last-observed-value carry-forward (LOCF) recovers $\geq$97% of the zero-mask gap across

the four backbones in that comparison, so the ranking is specific to silent-failure zero-masking (Appendix C.8).

6 Discussion

Deployment guidance. Within the shifts, source city, and masking model evaluated here, the data support conditional heuristics, not universal recommendations. Under silent-failure zero-mask dropout, DCRNN, AGCRN, and STAEformer degrade much less than GWNet; the GWNet gap is tied to dense softmax routing and the mask-aware variant recovers 75% without retraining. For zero-shot cross-city transfer on METR-LA/PEMS-BAY-style highway networks, MegaCRN and DCRNN are strong. Weekday/weekend comparisons require an explicit metric: MegaCRN and STAEformer have positive normalized gaps but negative masked-mph gaps. Their normalized values alone should not drive temporal deployment guidance.

Implications for robustness evaluation. A clean-test leaderboard is not enough when the deployment shift is unknown. More expressive relation learning changes which deployment axis is vulnerable rather than removing vulnerability, so benchmarks should report multi-shift robustness alongside in-distribution accuracy. GWNet controls rule out a simple training artifact: fixed-adjacency substitution, a 12-config capacity sweep, and MTGNNLight's lower fragility under adaptive topology all point to routing concentration rather than optimizer failure (Table 7).

Recommendation artifact. The release includes a small decision table and scripts built from the frozen checkpoint registry. Given a backbone name and anticipated deployment context (sensor reliability level, source/target city pairing, weekday/weekend exposure), the table returns the observed per-axis fragility profile and a matching mitigation, such as mask-aware routing for silent-failure settings or avoiding dense-softmax adjacency under high dropout rates. It does not generalize beyond the eight backbones, two source cities, and three shift axes evaluated. A $2\times2\times2$ deployment-profile decision table and conservative rankings (demoting MegaCRN on the sensor axis due to its smoothing-artifact negative delta) are in Appendix H. Its temporal axis uses the original normalized gap; weekend-related recommendations are therefore specific to that metric, rather than rankings of physical error.

Limitations. The study does not exhaust adaptive-relation traffic models (e.g., ASTGCN, DSTAGNN). MegaCRN's negative sensor delta is adjacency-mediated smoothing, and the normalized temporal gap is not explained by TOD/DOW covariates alone. Its sign reversal under masked-mph reporting makes the evaluation convention part of the finding. The main training source is METR-LA; PEMS04 is used as a targeted replication for cross-city transfer and routing concentration, not as a full source-city sweep. The fragility ranking is also specific to silent zero-masking: LOCF recovers most of the gap (Appendix C.8).

Scope of the zero-mask diagnostic. The zero-mask sensor-dropout protocol is a silent-outage diagnostic, not a prescription for reliable-imputation regimes. LOCF is a valid mitigation when recent readings are trustworthy, and the gap reported here applies to deployments where telemetry is delayed, where multi-source carry-forward is unreliable, or where sensors fail outright. We do not extrapolate the fragility ranking to settings in which last-observation backfill is broadly safe.

7 Conclusion

This audit does not identify a universally robust traffic STGNN. It identifies a failure coordinate. Sensor-dropout fragility tracks adaptive-adjacency concentration (Pearson $\rho{=}+0.974$ across six adaptive architectures on METR-LA, with positive associations on three source datasets); mask-aware inference recovers 75% of its gap without retraining. Cross-city and temporal evaluation reveal different effects: MegaCRN leads source-normalized transfer, while MegaCRN's and STAEformer's weekday/weekend gaps reverse sign under masked-mph reporting. Model assessment should state both the expected shift and the metric convention; the frozen-checkpoint protocol makes these distinctions visible.

Acknowledgments and Disclosure of Funding

This work was supported by the National Natural Science Foundation of China (Grant No. 62506134), the Guangdong-Hong Kong-Macao Applied Mathematics Center Project (Grant No. 2026A1515060008), and the Natural Science Foundation of Guangdong Province (Grant No. 2026A1515010171). The authors declare no competing interests.

References

A. F. Ansari, L. Stella, C. Turkmen, X. Zhang, P. Mercado, H. Shen, O. Shchur, S. S. Rangapuram, S. P. Arango, S. Kapoor, J. Zschiegner, D. C. Maddix, M. W. Mahoney, K. Torkkola, A. G. Wilson, M. Bohlke-Schneider, and Y. Wang. Chronos: Learning the language of time series. *arXiv preprint arXiv:2403.07815*, 2024. URL https://arxiv.org/abs/2403.07815.

L. Bai, L. Yao, C. Li, X. Wang, and C. Wang. Adaptive graph convolutional recurrent network for traffic forecasting. In *Advances in Neural Information Processing Systems*, 2020. URL https://arxiv.org/abs/2007.02842.

W. Cao, D. Wang, J. Li, H. Zhou, L. Li, and Y. Li. BRITS: Bidirectional recurrent imputation for time series. In *Advances in Neural Information Processing Systems*, 2018. URL https://proceedings.neurips.cc/paper/2018/hash/734e6bfcd358e25ac1db0a4241b95651-Abstract.html.

A. Cini, I. Marisca, and C. Alippi. Filling the gaps: Multivariate time series imputation by graph neural networks. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=kOu3-S3wJ7.

F. Croce, M. Andriushchenko, V. Sehwag, E. Debenedetti, N. Flammarion, M. Chiang, P. Mittal, and M. Hein. RobustBench: A standardized adversarial robustness benchmark. In *NeurIPS Datasets and Benchmarks Track*, 2021. URL https://datasets-benchmarks-proceedings.neurips.cc/paper/2021/hash/a3c65c2974270fd093ee8a9bf8ae7d0b-Abstract-round2.html.

A. J. Fofanah, L. Wen, D. Chen, A. A. Kamara, and Z. Zhang. CAST-CKT: Chaos-aware spatio-temporal and cross-city knowledge transfer for traffic flow prediction. arXiv preprint arXiv:2602.05133, 2026. URL https://arxiv.org/abs/2602.05133.

S. Guo, Y. Lin, N. Feng, C. Song, and H. Wan. Attention based spatial-temporal graph convolutional networks for traffic flow forecasting. In *AAAI Conference on Artificial Intelligence*, 2019.

R. Jiang, Z. Wang, J. Yong, P. Jeph, Q. Chen, Y. Kobayashi, X. Song, S. Fukushima, and T. Suzumura. MegaCRN: Meta-graph convolutional recurrent network for spatio-temporal modeling. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 37, pages 8078–8086, 2023.

Z. Jing, Y. Long, and G. Feng. Pruning for generalization: A transfer-oriented spatiotemporal graph framework. arXiv preprint arXiv:2602.04153, 2026. URL https://arxiv.org/abs/2602.04153.

F. Li, J. Feng, H. Yan, G. Jin, D. Jin, and Y. Li. Dynamic graph convolutional recurrent network for traffic prediction: Benchmark and solution. *arXiv preprint arXiv:2104.14917*, 2021. URL https://arxiv.org/abs/2104.14917.

Y. Li, R. Yu, C. Shahabi, and Y. Liu. Diffusion convolutional recurrent neural network: Data-driven traffic forecasting. In *International Conference on Learning Representations*, 2018. URL https://openreview.net/forum?id=SJiHXGWAZ.

H. Liu, Z. Dong, R. Jiang, J. Deng, J. Deng, Q. Chen, and X. Song. STAEformer: Spatio-temporal adaptive embedding makes vanilla transformer SOTA for traffic forecasting. In *Proceedings of the 32nd ACM International Conference on Information and Knowledge Management*, pages 4125–4129, 2023a.

X. Liu, Y. Xia, Y. Liang, J. Hu, Y. Wang, L. Bai, C. Huang, Z. Liu, B. Hooi, and R. Zimmermann. LargeST: A benchmark dataset for large-scale traffic forecasting. In *Advances in Neural Information Processing Systems*, 2023b.

C. Shang, J. Chen, and J. Bi. Discrete graph structure learning for forecasting multiple time series. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=WEHSlH5mOk.

N. Thakur, N. Reimers, A. Rücklé, A. Srivastava, and I. Gurevych. BEIR: A heterogeneous benchmark for zero-shot evaluation of information retrieval models. In *NeurIPS Datasets and Benchmarks Track*, 2021. URL https://openreview.net/forum?id=wCu6T5xFjeJ.

Z. Wu, S. Pan, G. Long, J. Jiang, and C. Zhang. Graph WaveNet for deep spatial-temporal graph modeling. In *International Joint Conference on Artificial Intelligence*, 2019. URL https://arxiv.org/abs/1906.00121.

Z. Wu, S. Pan, G. Long, J. Jiang, X. Chang, and C. Zhang. Connecting the dots: Multivariate time series forecasting with graph neural networks. In *ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, 2020. URL https://dl.acm.org/doi/10.1145/3394486.3403118.

C. Yi, S. Yang, H. Li, Y. peng Tan, and A. Kot. Benchmarking the robustness of spatial-temporal models against corruptions. In *NeurIPS Datasets and Benchmarks Track*, 2021. URL https://openreview.net/forum?id=MQlMIrm3Hv5.

B. Yu, H. Yin, and Z. Zhu. Spatio-temporal graph convolutional networks: A deep learning framework for traffic forecasting. In *International Joint Conference on Artificial Intelligence*, 2018.

Z. Zeng, Z. Fang, Y. Huang, L. Chen, and Y. Gao. Effective and efficient cross-city traffic knowledge transfer: A privacy-preserving perspective. arXiv preprint arXiv:2503.11963, 2025. URL https://arxiv.org/abs/2503.11963.

H. Zhang, W. Zhang, H. Miao, X. Jiang, Y. Fang, and Y. Zhang. STRAP: Spatio-temporal pattern retrieval for out-of-distribution generalization. arXiv preprint arXiv:2505.19547, 2025. URL https://arxiv.org/abs/2505.19547. Accepted at NeurIPS 2025.

A Pre-Registered Hypotheses

Table 6 records all 16 pre-registered predictions alongside experimental outcomes. Predictions were added in five stages before running the corresponding experiments.

Hosting and criteria. The ledger is hosted in the project notebook RESEARCH_JOURNEY_DEFENSE.md with stage-stamped entries; each stage was committed before the next round of training or evaluation began. A prediction is marked *confirmed* (✓) when its directional claim *and* any pre-stated quantitative threshold (e.g., "$\geq$ 30% reduction") hold; *refuted* (×) when either fails; *partial* when one holds and the other does not. Only secondary protocol details—mask seed indices, reporting-horizon choice, and figure formatting—were finalized post-hoc; the predictions themselves, including quantitative thresholds and the model bank, were frozen at registration time. Using the main-text categorization, the breakdown is ten confirmed, four refuted, and two partial; rows that miss the principal directional claim are counted as refuted even when a secondary threshold is informative. Verbatim re-statements are linked from each row of Table 6.

B Protocol and Transparency

B.1 Estimand-level crosswalk

Table 8 maps each reported estimand to its source table, units, normalization convention, and whether it is comparable across model families. Clean MAE is reported in canonical (mph) form for the primary table and in each family's standard masked convention for the extended bank; clean values are not directly cross-family-rankable because per-family training conventions differ. Shift estimands

(Δ_{sensor}, cross-city, Δ_{temp}) are normalized so that within-family and (where matched structural access holds) across-family comparisons are sound.

The "Cross-family?" column reflects whether the estimand can be ranked across model families without re-introducing a convention artifact: clean MAE cannot, the sensor and city comparisons follow their stated normalization protocols, and the temporal ranking depends on the scaling and target-mask convention (Table 24). Routing concentration is compared across the four row-stochastic backbones for which the proxy is identically defined.

B.2 Reproducibility, assets, and compute

All experiments use public traffic datasets and frozen checkpoints. The main numeric source for Tables 2–3 is `results/official_adaptive_relation/UPDATED_MERGED_COMPARISON_TABLE_2026-04-16.csv`; PEMS04 routing replication and mask-aware sweeps are read from `results/polish_v15/`. The checkpoint registry is `baselines/stgnn_protocol_registry.json`, and the unified training configuration is `configs/stgnn_unified.yaml`. Evaluation commands are listed in the repository README and mirror the commands used to generate the tables and figures. The code, configs, and frozen-checkpoint manifest are at `https://github.com/sirjuststop/stgnn-shift-bench`.

The released artifact contains the recommendation table and the scripts needed to regenerate the shift profiles from the canonical result files. It does not introduce a new dataset. METR-LA, PEMS-BAY, and PEMS04 remain under their original distribution terms; we cite the source papers and do not repackage the raw datasets in the submission. The runs were executed with one CUDA GPU per training/evaluation job. The April 16 extended-model evaluation log records roughly 3–9 minutes per seed for shift evaluation after training, depending on backbone; full retraining is not required to verify the frozen-checkpoint results.

C Sensor-Dropout Analysis

C.1 Severity curve: dropout ratios 10–50%

Table 9 reports Δ_{sensor} for three backbones across dropout ratios from 10% to 50%.

C.2 Additional corruption types

Table 11 reports the additional 30% corruption comparison on healthy sensors, alongside zero-fill. The evaluated types are stale/frozen hold, Gaussian noise, bias offset, and intermittent missingness. GWNet is sensitive to zero-fill and bias, but has the smallest noise increment among the models shown. Thus the silent-zero ranking does not extend unchanged to other corruptions. The reporting split matters too: under zero-fill, DCRNN's increase is $+0.39$ mph on healthy sensors and $+4.32$ mph on faulty sensors; GWNet's corresponding values are $+1.65$ and $+2.01$ mph.

C.3 Multi-mask aggregation

Table 12 reports Δ_{sensor} averaged over 5 random 30% zero-masks (seeds 42–46) per model checkpoint. The main-text results use the pre-registered primary mask per model seed. For DCRNN, MTGNN-Light, STGCN, and GWNet the 5-mask aggregate remains close to Table 2; GRU is a mask-sampling caveat.

C.4 Structured dropout patterns

Table 13 reports Δ_{sensor} under two topology-aware dropout patterns alongside the uniform random baseline. *Hub dropout* removes the k sensors with the highest adjacency-degree (most message-passing traffic); *contiguous dropout* removes a BFS-connected cluster seeded from the highest-degree node, mimicking a geographic outage.

The relative ordering GWNet $>$ STGCN $>$ DCRNN is preserved under all patterns. GWNet's hub-dropout sensitivity is **45% higher** than uniform random ($+0.127$ vs. $+0.088$, matched single-mask

protocol shared with Table 2): hub nodes feed GWNet's densest adaptive-routing pathways, so removing them is especially damaging. DCRNN and STGCN show *lower* Δ_{sensor} under hub/contiguous dropout ($+0.008$, $+0.026$) than under uniform random—an important methodological note: when hubs are dropped, the kept sensors are peripheral nodes with simpler traffic dynamics, making the prediction task inherently easier. The clean-kept and masked-kept MAEs both drop for DCRNN/STGCN under hub dropout, but the *gap* also shrinks, since DCRNN's bidirectional diffusion redistributes information effectively even when hub inputs are absent.

C.5 Node-degree stratification

Table 14 reports Δ_{sensor} stratified by node degree quartile (Q1 = lowest degree, Q4 = highest). Nodes in each quartile are defined by their adjacency row-sum degree in the METR-LA graph. Only kept sensors (not dropped) are included in the MAE computation. Reported values are mean over 3 model seeds.

GWNet is the only backbone with a strongly monotonic degree→fragility pattern. MTGNNLight's weak positive relationship ($1.25\times$) and STGCN's intermediate ratio ($1.50\times$) show that some degree sensitivity exists in fixed-topology models too, but neither reaches GWNet's dense-adaptive-graph level ($1.83\times$), and only GWNet's increase is monotonic across Q1→Q4.

C.6 Mask-aware recovery: FP/FN sensitivity

The mask-aware adjacency variant zeroes out adjacency rows/columns for detected failed sensors. In silent-failure scenarios, the detector is imperfect: false positives (healthy sensors flagged as failed) and false negatives (failed sensors missed) can both occur. Table 15 reports MAE under the perfect mask vs. two realistic detector operating points.

Imperfect masks increase MAE relative to perfect detection: the mean penalty is $+0.044$ at FP5%/FN10% and $+0.077$ at FP10%/FN20%. The latter has substantial seed variation ($+0.049$–$+0.134$). We report these paired penalties directly; converting them to recovery percentages using the multi-mask baseline in Table 5 would mix protocols.

C.7 Mask-aware dropout-ratio sweep

The mask-aware GWNet variant (Section 5) is reported in the main text at a single 30% random-mask operating point. To address stability across imperfect-detector scenarios, we sweep five dropout ratios and add one structured pattern. All cells use 3 GWNet seeds $\times$ 5 mask seeds; structured pattern uses the top-30% nodes by adjacency degree (one mask per seed).

The mask-aware recovery is in the 70–76% band across the 10–40% sweep (the 5% row's nominal 109% reflects an absolute $\Delta_{\text{sensor}}^{\text{mask-aware}}$ within seed noise of zero). Hub-dropout, where 30% of *high-degree* nodes fail simultaneously, is recovered at 71%—comparable to the random-30% main-text result—supporting the argument that the mechanism generalizes beyond the random-uniform mask used in the headline claim.

C.8 LOCF and mean imputation baselines

Table 17 compares three imputation strategies for dropped sensors: *zero-mask* (set dropped sensor channels to 0), *LOCF* (last observed value, i.e., the last input timestep value is carried forward for the entire window), and *mean* (per-node mean computed over the test split).

LOCF essentially eliminates the zero-mask degradation for all four backbones. Mean imputation performs similarly to or worse than zero-masking, because the test-split mean is influenced by the training distribution and creates a biased proxy in shifted traffic conditions. The LOCF result shows that the architectural fragility ranking we measure (GWNet $>$ STGCN $>$ DCRNN) is specific to the zero-masking failure mode; any system with temporal carry-forward (including simple telemetry holdover) would largely eliminate the architectural gap.

D Cross-City Transfer Analysis

D.1 Normalization conventions

Table 18 reports cross-city evaluation under both normalization conventions. *Source-stat* normalizes and denormalizes with METR-LA training statistics; *target-stat* uses PEMS-BAY training statistics for denormalization only (PEMS-BAY statistics are not available at deployment time, so source-stat is the operationally correct zero-shot metric; target-stat is reported for comparability with the broader traffic forecasting literature).

The source-stat improvement (PEMS-BAY $<$ METR-LA in normalized space) for all backbones reflects lower traffic variance on PEMS-BAY highway sensors, not better generalization. Target-stat MAE correctly accounts for this scale difference and reveals the true transfer gap.

D.2 Subset-size sensitivity

To test whether the GWNet transfer gap depends on how many PEMS-BAY sensors are used, we evaluate with 150-node coverage: 150 PEMS-BAY sensors are selected and the remaining 57 input slots are zero-padded (same protocol as sensor dropout). Table 19 reports city transfer MAE under both coverages.

The backbone ranking DCRNN $<$ STGCN $<$ GWNet is preserved at both coverage levels. GWNet's MAE increases by **41%** when moving from full 207-node to 150-node coverage ($5.30 \rightarrow 7.49$ mph); DCRNN decreases marginally (-2%) and STGCN decreases marginally (-3%). The large GWNet penalty arises because its source-city node embeddings route information through 57 zero-padded positions: inactive input slots inject systematic zero signals into the adaptive adjacency pathways, compounding the city-transfer gap. DCRNN and STGCN with target-city subgraph adjacency are unaffected by coverage reduction because zero-padded nodes are disconnected in the graph. Note: absolute MAE values differ from Table 2 due to different random subset draws; rankings are consistent.

D.3 Source-only vs. target adjacency

The main Table 2 uses a *matched structural constraint* (source-only adjacency) as the canonical cross-city comparison, so that no backbone benefits from access to target-city topology that others lack. This appendix reports the full comparison: source-only normalized MAE (main table), normal target-adj normalized MAE, and the original target-adj *mph* values for readers who prefer absolute units. GWNet and MTGNNLight are source-tied by construction (they learn or compute their own adjacency from source node embeddings); GRU uses no adjacency.

The source-only column (main table) tells the cleaner mechanistic story: DCRNN retains a 49% advantage over GWNet under the fair source-only constraint (0.180 vs 0.268), while STGCN's apparent advantage over GWNet completely disappears ($0.249 \approx 0.268$). STGCN's city-transfer advantage in the target-adj column (0.202) arises from access to the target-city adjacency matrix, not from architectural generalization. DCRNN's bidirectional diffusion generalizes better even when confined to source topology, supporting its designation as the most transfer-robust backbone in this study.

D.4 Limited target-data adaptation

We relax the frozen rule for four canonical-bank backbones in a few-shot probe, fine-tuning the METR-LA checkpoints on $k \in \{50, 200, 800\}$ target windows for 30 steps. The 207-node PEMS-BAY subset is held fixed and inputs use target normalization. Table 21 includes the $k = 0$ starting point. The ordering does not change: DCRNN remains ahead, while GWNet improves only modestly. This supports the limited-adaptation comparison shown, rather than a claim about unrestricted fine-tuning. Its fixed-subset $k = 0$ values differ from Table 18, which averages five subsets; target-normalized input is also distinct from the source-normalized main-table setting.

D.5 PEMS04-source second city pair (P18)

To test whether DCRNN's transfer advantage is METR-LA-specific, we train all four backbones (DCRNN, GWNet, GWNet[Strong], GRU) on PEMS04 [Guo et al., 2019] (307 sensors, California District 4 freeway, 16,992 timesteps) with the same frozen training protocol and evaluate zero-shot on METR-LA and PEMS-BAY, using 5 random 307-node target subsets (seeds 42–46). The source PEMS04 adjacency is used for all backbones at inference, matching the P16 source-only fairness control.

DCRNN remains the best-generalizing backbone in both PEMS04-source directions, mirroring the METR-LA-source and the PEMS-BAY $\rightarrow$ METR-LA reverse-transfer finding in Section 6. Combined, the advantage holds over **four city-pair directions** on three distinct cities, ruling out METR-LA-specific confounds. Interestingly, GWNet[Strong] is *worse* than default GWNet on PEMS04$\rightarrow$METR-LA (12.58 vs 11.39 mph), indicating that extra adaptive-embedding capacity does not help when the source topology itself mis-routes—if anything, it amplifies the problem.

D.6 Cross-city zero-padding sensitivity

The cross-city eval in `experiments/stgnn_shift_eval_v5_pems04.py` (lines 87–91) uses index-repetition padding when target N ¡ source N: for PEMS04 (307) $\rightarrow$ METR-LA (207) the `keep` list is the 207 unique target nodes followed by 100 copies of node index 0, and MAE is averaged over all 307 prediction slots. The duplicate slots feed a single repeated input, which can either help (smoothing) or hurt (artificial concentration) the reported MAE. We re-evaluate every PEMS04 checkpoint and recompute MAE only over the 207 *unique* target nodes (no-pad), and compare to the existing 307-slot padded MAE.

The padding bias is small for the fixed-graph backbones DCRNN (-0.15 mph) and STGCN (-0.12 mph) but larger for GWNet, MTGNN, and GRU (-0.66, -0.73, -0.73 mph): index-repetition padding flatters the adaptive and graph-free models on PEMS04 $\rightarrow$ METR-LA by roughly 6–7% of their already-large MAE. Crucially, the *ranking* is unchanged: DCRNN remains best in both columns, and the gap to the next-best model (STGCN, ≈ 7 vs. MTGNN, ≥ 10) is preserved. The PEMS04 $\rightarrow$ PEMS-BAY direction is unaffected since target $>$ source (subsample only, no padding).

E Temporal Shift Analysis

E.1 Absolute-unit weekday/weekend comparison

Table 24 pairs normalized and masked-mph results for the same three frozen checkpoints per model and the same test windows. MegaCRN and STAEformer change sign: their weekend error is lower in masked mph. Normalized MAE includes all targets, while the physical-unit metric excludes zero-valued targets. The comparison therefore changes both scaling and target masking; the observed reversal cannot be attributed solely to per-node standardization.

E.2 Per-horizon decomposition (P19)

Table 25 reports normalized MAE at horizons h=1, h=6, and h=12 under clean, 30% sensor-dropout, and cross-city (source-stat) evaluation (3 seeds, mean).

Under clean inference and sensor dropout, all backbones show the expected near-monotone MAE growth with horizon. Under cross-city transfer the story splits: DCRNN and STGCN retain normal growth (+46% and +33% from h=1 to h=12), whereas GWNet, GWNet[Strong], MTGNNLight, and GRU are nearly flat (+2%–+7%). For the adaptive-graph models, the transfer error is therefore paid *up-front* as a static structural mis-routing that saturates within the first prediction step—consistent with the mask-aware adjacency intervention (Section 5) recovering 75% of the dropout gap without any temporal modification.

E.3 Temporal covariate ablation

To test whether the normalized weekday/weekend gap of MegaCRN and STAEformer reflects an over-reliance on their frozen time-of-day (TOD) and day-of-week (DOW) embeddings, we run

two inference-time interventions across three seeds per model: (i) *randomize*: replace TOD/DOW channels with uniform noise; (ii) *swap*: swap covariates between weekday and weekend samples.

STAEformer shows partial covariate dependence; MegaCRN's gap is unchanged, so its normalized gap is not attributable to the frozen covariate channel alone. The residual mechanism—memory-bank dynamics or encoder/decoder conditioning—is out of scope for inference-time interventions and is flagged as open. These interventions concern the normalized metric and do not establish a higher weekend error in masked mph (Table 24).

F Routing Concentration: Mechanism and Replication

F.1 Adaptive adjacency density sweep

Table 27 reports the anchor-point density sweep ($k \in \{10, 20, \text{full}\}$) alongside GWNet[fixed] and MTGNNLight references. Table 28 extends this to the full k-grid $k \in \{5, 10, 15, 20, 30, \text{full}{=}207\}$.

All evaluations use frozen GWNet[adaptive] checkpoints (3 seeds); top-k filtering is applied at inference only, with row renormalization. Sanity check: k=full reproduces registry values within 10^{-5} MAE (verified).

The relative fragility trend is monotonically increasing across all six k values (5/5 consecutive pairs), supporting the association between denser adaptive connectivity and higher dropout fragility within this checkpoint. The absolute Δ_{sensor} values at k=5–20 are similar (0.072–0.074), with the gap widening at k=30–full. As noted in Section 5.2, inference-time sparsification is not a practical intervention because it degrades in-distribution accuracy; the finding is presented as mechanism evidence, not as a deployment recommendation.

F.2 Routing-sparsity spectrum across adaptive models

Table 29 reports the per-model adjacency concentration and sensor-dropout delta for the four adaptive-graph models in our bank (METR-LA test set; three seeds). max_mass is the mean over rows and samples of the largest entry in each adjacency row; eff_k is $\exp(\text{row-entropy})$ and measures effective support size.

STAEformer is excluded from the Pearson because its spatial mixing is head-stratified multi-head attention rather than a single row-stochastic adjacency: a max_mass extracted from any one head is not commensurable with the per-row probability used in the other four backbones, so the proxy-isomorphism assumption underlying the correlation does not hold. The four-backbone Pearson is therefore reported on the row-stochastic subset where the proxy is identically defined.

Under the conservative ranking that treats MegaCRN's negative delta as an adjacency-smoothing artifact (Section 5.3), max_mass and Δ_{sensor} are monotonic across all four models.

F.2.1 Seed-level variation and rank-correlation diagnostics

Per-seed max_mass values for the four adaptive backbones are AGCRN $\{0.0077, 0.0076, 0.0100\}$ (std 0.0014), MegaCRN $\{0.0064, 0.0093, 0.0097\}$ (std 0.0018), MTGNN-Light $\{0.1586, 0.1607, 0.1596\}$ (std 0.0011), and GWNet $\{0.1638, 0.2773, 0.2475\}$ (std 0.0588). Three of the four backbones have per-seed std below the smallest non-tied inter-family gap of 0.07 (MTGNN 0.16 vs. GWNet 0.23); GWNet's larger seed spread is the dominant source of within-family variability.

Per-seed Pearson against Δ_{sensor} is $\{+0.92, +0.99, +0.98\}$ across the three seeds (mean $+0.96$, std 0.04), suggesting that the max_mass relation is not an artifact of seed averaging despite GWNet's larger within-seed spread. Spearman over the four seed-mean values is $\rho_S{=}+0.80$; the single rank exchange swaps AGCRN (0.0085) and MegaCRN (0.0085), whose max_mass values differ by less than 10^{-3}, well below either backbone's per-seed std. Treating the two memory-meta backbones as tied on the proxy yields rank correlation $\rho_S{=}+1.0$ across the three distinguishable groups $\{\text{tied AGCRN/MegaCRN}, \text{MTGNN-Light}, \text{GWNet}\}$.

F.2.2 Leave-one-out and exact permutation analysis

Using the unrounded saved max_mass values and the routing-spectrum deltas in Table 29, the four-model Pearson is $+0.978827$. Table 30 gives all leave-one-out results. Removing GWNet leaves $+0.960752$, so the positive association does not disappear when that model is excluded. Enumerating all $4!{=}24$ permutations of the four deltas, and counting $|\rho_{\mathrm{perm}}| \geq |\rho_{\mathrm{obs}}|$, gives $p{=}2/24{=}0.0833$. The architecture-level sample remains four models.

F.3 Six-architecture extension and native-source summaries

GTS [Shang et al., 2021] and DGCRN [Li et al., 2021] extend the four-backbone comparison with link-predictor and input-conditioned graph learning. Their reported METR-LA max_mass values are 0.288 and 0.325, above GWNet's 0.230. The six-architecture Pearson is $+0.974$ with exact permutation $p = 0.003$; removing GWNet gives $+0.973$, and the smallest leave-one-out correlation is $+0.961$. Table 31 summarizes the native-source measurements. The sign is positive on all three datasets, while the strength varies and PEMS04 does not reach $p < 0.05$. These six-model summaries differ from the original four-model PEMS04 replication below; the two sample sizes should not be conflated.

F.4 PEMS04-native routing-concentration replication

To address whether the routing-concentration relation generalizes beyond a single source city, we re-train the four adaptive-graph backbones on PEMS04 (307 sensors, chronological 70/10/20 split) using the same training configuration as the canonical METR-LA bank (Section 3.2). max_mass is then recomputed from each PEMS04-trained checkpoint via the same per-architecture adjacency proxy (Section 5.2), and Δ_{sensor} is measured on PEMS04 test data (3 model seeds $\times$ 5 mask seeds, 30% zero-mask, MAE on kept sensors only).

Two findings support the shared-mechanism hypothesis. (i) Both source cities separate the low max_mass of AGCRN/MegaCRN from the higher values of MTGNN/GWNet. (ii) MegaCRN's METR-LA-specific negative Δ_{sensor} (-0.005) becomes positive on PEMS04 ($+0.057$), consistent with the adjacency-mediated weekday-prior smoothing diagnosis in Section 5.3—the smoothing prior exists in METR-LA but not in the PEMS04 weekday distribution, while the routing-concentration mechanism is shared.

F.5 Theory sketch: first-order exposure bound

Setup. Let a single message-passing layer produce node representations $h_i = \sum_j A_{ij} W x_j$ where $A \in \mathbb{R}^{N \times N}$ is row-stochastic and W is a linear map. Perturbing the inputs at nodes in $\mathcal{I} \subseteq [N]$ by zero-masking, the change in h_i is $\Delta h_i = -\sum_{j \in \mathcal{I}} A_{ij} W x_j$.

Exposure bound. Taking norms and bounding input magnitudes by $\|x\|_\infty$:

$$\|\Delta h_i\|_2 \leq \|W\|_2 \cdot \|x\|_\infty \cdot \sum_{j \in \mathcal{I}} A_{ij}.$$

For any row i, let $m_i = \max_j A_{ij}$. Then $\sum_{j \in \mathcal{I}} A_{ij} \leq |\mathcal{I}| m_i$, so

$$\|\Delta h_i\|_2 \leq \|W\|_2 \cdot \|x\|_\infty \cdot |\mathcal{I}| m_i.$$

Averaging over target nodes yields

$$\frac{1}{N} \sum_i \|\Delta h_i\|_2 \leq \|W\|_2 \cdot \|x\|_\infty \cdot |\mathcal{I}| \cdot \text{max_mass}(A).$$

Interpretation. The bound says that concentrated rows have larger worst-case exposure when the dropped set includes high-mass neighbors. It is deliberately local: it does not prove full-horizon MAE behavior and does not cover nonlinear recurrence, temporal convolutions, or decoder amplification. It

also should not be read as an exact expected-error result under iid dropout. If each sensor is dropped independently with probability p, then for a row-stochastic A,

$$\mathbb{E}_{\mathcal{I}}\left[\sum_{j\in\mathcal{I}} A_{ij}\right] = p\sum_{j} A_{ij} = p,$$

which is independent of m_i. Thus max_mass(A) is best viewed as a tail-risk or worst-case exposure proxy. This is the role it plays in Table 29: the empirical ρ=+0.979 on METR-LA and ρ=+0.910 on PEMS04 show that the proxy tracks sensor-dropout fragility across adaptive backbones. The mask-aware intervention (Section 5) targets the same exposure term by zeroing and renormalizing routes attached to known dropped sensors.

G Model Ablations

G.1 GWNet capacity variants (P17 and P21)

We train GWNet[Strong] with hidden dim 128, adaptive embed dim 20, and early-stopping patience 30 (otherwise identical to the standard config). Table 33 compares it to the default GWNet and DCRNN across all shift axes. We additionally report GWNet[Best] (P21), the best configuration identified by in-distribution MAE across a 12-config Stage-1 grid (hidden $\in \{128, 256\}$, embed $\in \{20, 32\}$, lr $\in$ {1e-3, 5e-4, 2e-4}, dropout $\in \{0.1, 0.3\}$); the winning setting is hidden 256, embed 32, lr 5e-4, patience 30.

Doubling hidden dimension and adaptive embedding closes 34% of the in-distribution MAE gap to DCRNN (7.85 $\rightarrow$ 7.42 mph) and halves the sensor-dropout Δ (+0.088 $\rightarrow$ +0.050), matching the sparse MTGNNLight baseline. However, the cross-city MAE is effectively unchanged (4.42 $\rightarrow$ 4.46 mph), the source-only adjacency gap to DCRNN persists (0.262 vs 0.180), and the degree-stratified hub-fragility signature remains monotonic (1.72$\times$ Q4/Q1, still far from DCRNN's 0.95$\times$).

The full 12-config sweep GWNet[Best] (hidden 256, embed 32, lr 5e-4, patience 30) further reduces the in-distribution gap (7.22 $\pm$ 0.04 mph, closing 63% of the gap to DCRNN) and the sensor-dropout fragility (+0.042 $\pm$ 0.002), yet Δ_{sensor} remains 2.1$\times$ DCRNN's +0.020—confirming P21. The source-only city-transfer normalized MAE (0.262 $\pm$ 0.009) is identical to GWNet[Strong]'s (0.262) and still 46% above DCRNN's 0.180. Capacity attenuates but does not eliminate the architectural fragility, supporting the mechanism interpretation in Section 5.

G.2 MegaCRN memory-bank ablation

To test whether MegaCRN's meta-memory bank absorbs missing sensors as a form of implicit regularization, we zero-mask and re-route its attention/memory paths at inference in four modes. *full*: the unmodified model; *memzero*: query the memory bank with a zero vector so the prototype fall-back is fixed regardless of input; *graphonly*: zero out the attention output keeping the adjacency pathway; *attnonly*: use identity adjacency while keeping memory attention. We report Δ_{sensor} means over three seeds and five dropout ratios $r \in \{0.1, 0.2, 0.3, 0.4, 0.5\}$.

memzero deepens rather than flattens the U-shape, refuting the memory-bank regularization hypothesis. **attnonly** (identity adjacency) eliminates Δ_{sensor} completely, indicating that cross-node flow through the adjacency is the dominant driver in this ablation. Per-seed σ at r=0.2 is 0.031, approximately equal to the mean—the apparent robustness is seed-fragile. The mechanism is adjacency-mediated smoothing: zero-diffused predictions drift toward a weekday-mean prior that accidentally tracks the test set.

H Architecture-Selection Decision Tree

Table 35 reports the conservative 2$\times$2$\times$2 recommendation table over the deployment profile. The tree is generated by `experiments/decision_tree_artifact.py` from the same per-model normalized fragility vectors used in the main paper. The conservative ranking demotes flagged *(model, axis)* pairs where low apparent fragility is an artifact (*(megacrn, sensor)*; see Section 5.3). The temporal

axis uses the original normalized gaps. Its weekend-related recommendations are conditional on that metric; physical-error comparisons are given separately in Table 24.

Under these normalized profiles, four of the eight cells reach DCRNN, reflecting its uniformly low fragility across axes. MegaCRN is recommended only under the single-shift city-transfer profile; STAEformer wins the sensor-only cell; AGCRN wins the two weekend-exposed cells without city transfer. The tree and supporting scripts are included in the repository artifact (`stgnn-stress`) so that practitioners can reproduce the recommendation and the underlying rankings on new frozen checkpoints.

Table 6: Pre-registered hypotheses and outcomes. Confirmed (✓), partially confirmed, or refuted (×) by experiment.

Prediction	**Outcome**	**Result**
GWNet fails hardest under city transfer (topology overfitting)	GWNet is worst under sensor dropout, not city transfer; GRU is worst at city transfer	×
Graph-based models are more robust than GRU to sensor dropout	GRU is nearly as robust as DCRNN at 30%; adaptive graph hurts, fixed graph helps	Partial ×
All models degrade on PEMS-BAY vs. METR-LA	Source-stat MAE improves on PEMS-BAY (simpler traffic); target-stat reveals real gaps	×
Adaptive adjacency drives sensor-dropout fragility ($\geq$30% reduction when ablated)	43.1% reduction confirmed	✓
Temporal shift magnitude differs across architectures	All architectures within one std of each other	×
STGCN (fixed spectral adj) $\Delta_{\text{sensor}} \leq$ DCRNN (fixed diffusion adj)	STGCN $+0.078 >$ DCRNN $+0.020$; but both $<$ GWNet $+0.088$. Adaptive adj is the dominant driver.	×
P11–P13 added prior to structured / coverage experiments:		
[P11] GWNet transfer gap persists (GWNet worst) across 150- and 207-node PEMS-BAY coverage	Confirmed: ranking preserved; GWNet +41% MAE at 150 nodes vs. -2% for DCRNN	✓
[P12] Hub dropout raises GWNet Δ_{sensor} relative to uniform random (dense routing)	Confirmed: GWNet $+45\%$ ($+0.127$ vs. $+0.088$); DCRNN lower ($+0.008$ vs. random $+0.021$)	✓
[P13] Mask-aware recovery meaningful with FP $\leq 5\%$, FN $\leq 10\%$ detection	Partial: error increases under imperfect detection; high variance at FP=10%/FN=20%	Partial ✓
P14–P16 added prior to inductive-baseline and capacity-matched experiments:		
[P14] MTGNNLight (sparse cosine-sim) shows lower Δ_{sensor} than GWNet (dense product)	Confirmed: MTGNNLight $+0.051$, GWNet $+0.088$ (42% lower)	✓
[P15] GWNet[CM] (doubled patience) shows same Δ_{sensor} as standard GWNet	Confirmed: $+0.088$ vs $+0.088$ (identical); fragility is architectural not training artifact	✓
[P16] Source-only adj control narrows but does not eliminate DCRNN's transfer advantage	Confirmed: DCRNN 0.180 vs GWNet 0.268 (49% gap remains under fair comparison)	✓
P17–P19 added prior to stronger-GWNet, second-city-pair, and per-horizon experiments:		
[P17] GWNet[Strong] (hidden 128, embed 20) still shows $\Delta_{\text{sensor}}>2\times$ DCRNN and unchanged city MAE	Confirmed: $+0.050$ vs $+0.020$ ($2.5\times$); city 4.46 vs 4.42 mph	✓
[P18] DCRNN is best-generalizing on ≥ 1 PEMS04-source direction (PEMS04$\rightarrow$METR-LA, PEMS04$\rightarrow$PEMS-BAY)	Confirmed on *both*: DCRNN 7.01/2.65 vs next-best GRU 11.03/GWNet 4.58	✓
[P19] GWNet's per-horizon city-transfer MAE is flatter than DCRNN's (static mis-routing, not accumulation)	Confirmed: GWNet $+4\%$ h1$\rightarrow$h12 growth vs DCRNN $+46\%$	✓
P21 added prior to full-sweep best-config experiment:		
[P21] GWNet[Best] (12-config sweep: hidden 256, embed 32, lr 5e-4) still shows $\Delta_{\text{sensor}}>2\times$ DCRNN	Confirmed: $+0.042$ vs $+0.020$ ($2.1\times$); in-dist 7.22 mph; optimal training cannot eliminate routing fragility	✓

Table 7: Key supplementary checks behind the main findings. Each row points to the corresponding appendix experiment.

Experiment	Key result	Ref.
GWNet[Best] 12-config sweep (P21)	$\Delta_{\text{sensor}} = +0.042$ (2.1× DCRNN); the gap persists after tuning	G.1
PEMS04 cross-city (P18)	DCRNN best in both directions: 7.01/2.65 mph vs next-best 11.03/4.58 mph	D.5
Source-adj vs target-adj	STGCN's apparent advantage shrinks (0.249 src-only vs 0.202 target-adj)	D.3
Hub dropout	GWNet +45% (+0.127 vs. matched +0.088); DCRNN −62% (+0.008)	C.4
Per-horizon city MAE (P19)	GWNet: +4% h1→h12 growth vs DCRNN +46%	E.2

PEMS04 cross-city values are denormalized mph; all Δ values are normalized.

Table 8: Estimand-level crosswalk: which numbers are cross-family-comparable.

Estimand	Source	Unit	Normalization	Cross-family?
Clean MAE	T.2, T.3	mph (canon.) / masked (ext.)	per-family	No
Δ_{sensor}	T.2, T.3	normalized	source-stat	Yes (within-family)
Cross-city MAE	T.2, T.3	normalized	source / target (both)	Yes (matched-access)
Δ_{temp}	T.2, T.3, T.24	normalized / masked mph	per-model	Metric-dependent
Routing concentration	T.29, App. F.4	unitless $[0, 1]$	per-row	Yes (proxy-matched, n=4)

Table 9: **GWNet is most fragile in this three-model comparison; the gap grows nonlinearly.** Δ_{sensor} mean over 3 seeds across dropout ratios 10–50%. GWNet/DCRNN ratio (bottom) quantifies relative fragility.

Backbone	10%	20%	30%	40%	50%
DCRNN	+0.005	+0.012	+0.020	+0.033	+0.044
GWNet	+0.013	+0.044	+0.088	+0.149	+0.189
GRU	+0.001	+0.005	+0.025	+0.073	+0.088
GWNet/DCRNN	2.5×	3.8×	4.3×	4.6×	4.3×

Table 10: Physical-unit zero-fill severity comparison, healthy-sensor split. GTS and DGCRN extend the concentration range; routing-mass values are rounded reported values. DCRNN uses a fixed graph.

Backbone	Max mass	10%	20%	30%	40%	50%
DCRNN	—	+0.07	+0.21	+0.39	+0.60	+0.81
MTGNN-Light	0.16	+0.19	+0.54	+0.99	+1.54	+2.22
GWNet	0.23	+0.32	+0.96	+1.65	+2.67	+3.47
GTS	0.29	+0.41	+0.96	+1.75	+2.53	+3.26
DGCRN	0.32	+0.38	+1.51	+2.85	+4.92	+6.34

Table 11: Additional sensor corruptions on the canonical bank and GWNet[Strong] control: 30% affected channels, healthy-sensor split. Entries are reported MAE increases in mph relative to clean inputs.

Backbone	Zero	Stale	Noise	Bias	Intermittent
DCRNN	+0.39	+0.18	+0.28	+1.00	+0.21
GRU	+0.88	+0.58	+0.20	+1.02	+0.25
STGCN	+1.50	+0.32	+1.34	+4.24	+0.80
MTGNN-Light	+0.99	+0.30	+0.29	+2.12	+0.52
GWNet	+1.65	+0.28	+0.16	+1.96	+0.73
GWNet[Strong]	+1.49	+0.39	+0.29	+3.12	+0.78

Table 12: Multi-mask sensor dropout: Δ_{sensor} mean and std over 5 random masks (seeds 42–46), then averaged over 3 model seeds. Most values are consistent with primary-mask results in Table 2; GRU is the exception noted in the protocol.

Backbone	Δ_{sensor} (multi-mask mean)	Seed std	vs. Table 2
DCRNN (fixed diffusion)	$+0.021$	±0.002	$+0.020$ (consistent)
GRU (graph-free)	$+0.044$	±0.002	$+0.025$ (seed-42 was low-variance mask)
MTGNNLight (sparse cosine-sim)	$+0.051$	±0.012	$+0.051$ (consistent)
STGCN (fixed spectral)	$+0.079$	±0.006	$+0.078$ (consistent)
GWNet (adaptive adj)	$+0.092$	±0.030	$+0.088$ (consistent; high mask variance)
GWNet[CM] (patience=30)	$+0.088$	±0.017	$+0.088$ (P15 confirmed identical)

Table 13: Structured vs. uniform sensor dropout (Δ_{sensor}, mean over 3 seeds, 30% drop rate). Hub: top-k degree sensors dropped. Contiguous: BFS cluster from highest-degree seed. GWNet ordering is preserved (>STGCN>DCRNN); structured patterns amplify GWNet's fragility but reduce DCRNN/STGCN's apparent sensitivity, because hub dropout keeps peripheral (easier-to-predict) sensors.

Backbone	Random (uniform)	Hub dropout	Contiguous dropout
DCRNN (fixed diffusion)	$+0.021$	$+0.008$	$+0.005$
STGCN (fixed spectral)	$+0.079$	$+0.026$	$+0.022$
GWNet (adaptive adj)	$+0.088$	$+0.127$	$+0.096$

Table 14: Sensor-dropout Δ_{sensor} by node-degree quartile (30% zero-mask, kept sensors only, 3-seed mean). Mean node degrees: Q1 $\bar{d} = 1.83$, Q2 $\bar{d} = 3.32$, Q3 $\bar{d} = 4.48$, Q4 $\bar{d} = 5.98$.

Backbone	Q1 (low)	Q2	Q3	Q4 (high)	Q4/Q1
DCRNN	$+0.019$	$+0.026$	$+0.018$	$+0.018$	$0.95\times$
MTGNNLight	$+0.044$	$+0.052$	$+0.050$	$+0.055$	$1.25\times$
STGCN	$+0.059$	$+0.089$	$+0.074$	$+0.089$	$1.50\times$
GWNet	$+0.066$	$+0.076$	$+0.085$	$+0.121$	$1.83\times$

Table 15: Mask-aware GWNet sensitivity to imperfect detection (3 model seeds). FP is the fraction of healthy sensors erroneously zeroed in the adjacency; FN is the fraction of failed sensors missed. Values are the normalized-MAE increase relative to perfect detection under the same primary mask, reported as mean $\pm$ population std and median across seeds.

Detector scenario	FP / FN	Mean $\pm$ std	Median
Perfect mask	0%/0%	$+0.000 \pm 0.000$	$+0.000$
Conservative detector	5%/10%	$+0.044 \pm 0.017$	$+0.045$
Noisy detector	10%/20%	$+0.077 \pm 0.040$	$+0.049$

Table 16: Mask-aware GWNet recovery is stable across dropout ratios and structured patterns. "Standard" = silent zero-mask; "mask-aware" = adjacency rows/cols zeroed and renormalized for dropped sensors; recovery $= 1 - \Delta^{\text{mask-aware}}_{\text{sensor}} / \Delta^{\text{standard}}_{\text{sensor}}$. Script: `experiments/mask_aware_dropout_sweep.py`; data: `results/polish_v15/mask_aware_ratio_sweep.json`.

Cell	$\Delta^{\text{std.}}_{\text{sensor}}$	$\Delta^{\text{mask-aware}}_{\text{sensor}}$	Recovery
Random 5%	$+0.004 \pm 0.002$	$+0.000 \pm 0.001$	$109\% \pm 29$
Random 10%	$+0.019 \pm 0.006$	$+0.005 \pm 0.002$	$76\% \pm 6$
Random 20%	$+0.051 \pm 0.013$	$+0.015 \pm 0.002$	$70\% \pm 5$
Random 30% (main)	$+0.092 \pm 0.030$	$+0.023 \pm 0.009$	$75\% \pm 3$
Random 40%	$+0.145 \pm 0.026$	$+0.035 \pm 0.006$	$75\% \pm 3$
Hub-30% (structured)	$+0.116 \pm 0.037$	$+0.034 \pm 0.001$	71%

Table 17: Sensor-dropout Δ under three imputation strategies (30% drop rate, seed=42, 3 model seeds). LOCF improvement: fraction of zero-mask gap closed by LOCF. Negative improvement indicates worse than zero-mask.

Backbone	Δ_{zero}	Δ_{LOCF}	Δ_{mean}	**LOCF improvement**
DCRNN	$+0.020$	≈ 0	$+0.025$	$\sim 102\%$
MTGNNLight	$+0.051$	≈ 0	$+0.077$	$\sim 100\%$
STGCN	$+0.078$	$+0.003$	$+0.079$	$\sim 97\%$
GWNet	$+0.088$	≈ 0	$+0.109$	$\sim 101\%$

Table 18: Cross-city MAE under two normalization conventions. Source-stat: METR-LA train mean/std for both normalization and denormalization (lower = PEMS-BAY traffic is statistically simpler in normalized space). Target-stat: PEMS-BAY train statistics for denormalization (interpretable mph units). Mean $\pm$ population std over 5 random 207-node subsets and 3 model seeds.

Backbone	**Clean MAE (METR-LA, norm)**	**Source-stat MAE (norm)**	**Target-stat MAE (mph)**
DCRNN (fixed diffusion)	0.359	0.168	2.74 ± 0.01
STGCN (fixed spectral)	0.388	0.209	3.27 ± 0.02
GWNet (adaptive adj)	0.427	0.268	4.42 ± 0.15
GRU (graph-free)	0.408	0.278	4.73 ± 0.19

Table 19: Cross-city transfer MAE (target-stat, mph) under variable sensor coverage. 150-node: 150 PEMS-BAY sensors active, 57 input slots zero-padded to 207. 207-node: full model capacity (different subset draws from main table; see text). Mean $\pm$ std over 3 random PEMS-BAY subsets, 3 model seeds.

Backbone	**150-node coverage**	**207-node (full)**
DCRNN (fixed diffusion)	4.25 ± 0.03	4.33 ± 0.05
STGCN (fixed spectral)	4.94 ± 0.25	5.07 ± 0.33
GWNet (adaptive adj)	7.49 ± 1.08	5.30 ± 0.25

Table 20: Full cross-city transfer comparison. *Source-only (norm)*: all models constrained to METR-LA adjacency; canonical main-table values. *Target-adj (norm)*: DCRNN/STGCN use PEMS-BAY adjacency (GWNet/MTGNNLight/GRU unchanged). *Target-adj (mph)*: same target-adj evaluation, denormalized using PEMS-BAY statistics. Mean $\pm$ population std over 5 PEMS-BAY subsets, 3 model seeds.

Backbone	**Source-only (norm) [main table]**	**Target-adj (norm)**	**Target-adj (mph)**
DCRNN (fixed diffusion)	0.180 ± 0.001	0.167 ± 0.002	2.74 ± 0.01
MTGNNLight (cosine-sim)	0.244 ± 0.004	0.244 ± 0.004	4.15 ± 0.11
STGCN (fixed spectral)	0.249 ± 0.008	0.202 ± 0.005	3.27 ± 0.02
GRU (graph-free)	0.278 ± 0.009	0.278 ± 0.009	4.73 ± 0.19
GWNet (dense adaptive)	0.268 ± 0.006	0.268 ± 0.006	4.42 ± 0.15

Table 21: Limited target-data adaptation: target-test MAE in mph on one fixed 207-node PEMS-BAY subset, using target normalization. This is a separate probe from the five-subset source-normalized main comparison.

Model	$k = 0$	$k = 50$	$k = 200$	$k = 800$
DCRNN	2.69	2.69	2.66	2.67
MTGNN-Light	4.13	3.82	3.79	3.78
GWNet	4.22	4.06	4.13	4.11
GRU	4.44	4.25	4.21	4.18

Table 22: PEMS04-source cross-city transfer (3 seeds $\times$ 5 target subsets, mean $\pm$ std). PEMS04 in-dist MAE in native flow units; target MAE in target-stat mph. DCRNN is best in *both* new directions by $> 37\%$ margin.

Backbone	**PEMS04 in-dist**	**$\rightarrow$ METR-LA (mph)**	**$\rightarrow$ PEMS-BAY (mph)**
DCRNN	26.19 ± 0.02	$\mathbf{7.01 \pm 0.09}$	$\mathbf{2.65 \pm 0.02}$
GWNet	33.47 ± 0.45	11.39 ± 0.62	4.58 ± 0.16
GWNet[Strong]	32.62 ± 0.17	12.58 ± 0.32	4.61 ± 0.02
GRU	25.81 ± 0.06	11.03 ± 0.01	4.68 ± 0.03

Table 23: Cross-city MAE (mph) on METR-LA target with the existing index-repetition padding vs. a no-pad variant that scores only the 207 unique target nodes. PEMS04 $\rightarrow$ PEMS-BAY (N=325) is unaffected since target $>$ source (subsample only). 3 PEMS04 seeds $\times$ 5 target subsets. Script: `experiments/cross_city_no_pad_sensitivity.py`; data: `results/polish_v15/cross_city_no_pad_sensitivity.json`.

Backbone	**Padded MAE (mph)**	**No-pad MAE (mph)**	**Δ (pad $-$ nopad)**
DCRNN	7.014 ± 0.085	7.166 ± 0.088	-0.152
STGCN	7.176 ± 0.169	7.295 ± 0.158	-0.118
GWNet	11.390 ± 0.623	12.051 ± 0.422	-0.661
MTGNN	10.292 ± 0.090	11.020 ± 0.083	-0.728
GRU	11.026 ± 0.008	11.756 ± 0.012	-0.730

Table 24: Weekday/weekend gap under two reporting conventions. The same checkpoints and test windows are used in both columns; normalized MAE uses all targets, while masked mph excludes zero targets. Negative gaps mean lower weekend error. Mean $\pm$ population std over three seeds.

Model	**Normalized/plain gap**	**Masked-mph gap**
AGCRN	$+0.061 \pm 0.008$	$+0.750 \pm 0.013$
MegaCRN	$+0.734 \pm 0.019$	-0.594 ± 0.051
STAEformer	$+0.750 \pm 0.003$	-0.612 ± 0.002

Table 25: Per-horizon normalized MAE on METR-LA at h=1, 6, 12. Clean and 30% sensor dropout computed on the METR-LA test set; city-src computed on the 5-subset PEMS-BAY evaluation. Δh: relative growth from h=1 to h=12.

	Clean			**Masked 30%**			**City-src**		
Backbone	h_1	h_6	h_{12}	h_1	h_6	h_{12}	h_1	h_6	h_{12}
DCRNN	0.251	0.356	0.448	0.356	0.449	0.527	0.133	0.160	0.194
MTGNNLight	0.291	0.370	0.450	0.371	0.444	0.515	0.237	0.240	0.253
STGCN	0.296	0.385	0.466	0.438	0.513	0.578	0.173	0.199	0.230
GRU	0.331	0.403	0.474	0.375	0.435	0.499	0.263	0.269	0.282
GWNet	0.363	0.423	0.485	0.464	0.516	0.568	0.261	0.264	0.272
GWNet[Strong]	0.333	0.401	0.468	0.390	0.457	0.522	0.254	0.257	0.260

Table 26: Weekday $\rightarrow$ weekend Δ_{temp} (normalized) under covariate interventions. Script: `experiments/temporal_covariate_ablation.py`.

Model	**Clean**	**Randomize**	**Swap**	**Reduction (swap)**
MegaCRN	0.7336	0.7254	0.7336	0.0%
STAEformer	0.7495	0.7212	0.6556	12.5%

Table 27: Density sweep anchor points: relative fragility increases monotonically with adaptive connectivity density. Rel. fragility $= \Delta_{\text{sensor}}/\text{MAE}_{\text{in-dist}}$. Mean $\pm$ std over 3 seeds; Δ_{sensor} averaged over 5 random 30% masks.

Variant	In-dist MAE	Δ_{sensor} (30%)	Rel. fragility
GWNet[fixed]	8.27 ± 0.08	$+0.050 \pm 0.010$	0.60%
GWNet[k=10]	9.03 ± 0.42	$+0.073 \pm 0.030$	0.80%
GWNet[k=20]	8.85 ± 0.34	$+0.074 \pm 0.032$	0.84%
GWNet[k=full]	7.85 ± 0.11	$+0.092 \pm 0.030$	1.17%
MTGNNLight (ref)	6.88 ± 0.11	$+0.051 \pm 0.012$	0.74%

Table 28: Full k-grid density sweep for GWNet[adaptive] on METR-LA. Mean $\pm$ std over 3 seeds. Δ_{sensor}: averaged over 5 random 30% zero-masks (seeds 42–46). Rel. fragility $= \Delta_{\text{sensor}}/\text{MAE}_{\text{in-dist}}$. Note: $k<$full disrupts embeddings trained for dense routing, causing in-distribution degradation at low k; the clean-performance cost at k=5 is $+17\%$ relative to k=full.

k	In-dist MAE	Δ_{sensor} (30%)	Rel. fragility
5	9.21 ± 0.50	$+0.072 \pm 0.031$	0.78%
10	9.03 ± 0.42	$+0.073 \pm 0.030$	0.80%
15	8.94 ± 0.38	$+0.073 \pm 0.031$	0.81%
20	8.85 ± 0.34	$+0.074 \pm 0.032$	0.84%
30	8.66 ± 0.30	$+0.078 \pm 0.033$	0.89%
full = 207	7.85 ± 0.11	$+0.092 \pm 0.030$	1.17%

Table 29: Routing-sparsity spectrum vs. sensor-dropout fragility. Pearson correlation of max_mass and Δ_{sensor} across four adaptive models: $\rho = +0.979$. Script: `experiments/routing_sparsity_spectrum.py`. Δ_{sensor} values are the routing-spectrum estimates used for this correlation.

Model	Family	max_mass	eff_k	density	Δ_{sensor}
AGCRN	dense-symmetric	0.008	≈ 200	1.00	$+0.011$
MegaCRN	memory-meta	0.008	≈ 200	1.00	-0.005
MTGNN-Light	sparse-top-k	0.160	—	sparse	$+0.051$
GWNet	dense-bilinear	0.230	≈ 114	1.00	$+0.092$

Table 30: Leave-one-out Pearson correlations for the original four-model routing-spectrum estimates. The full-sample Pearson is $+0.978827$; the exact absolute-value-tail permutation test over all 24 permutations gives $p = 0.0833$.

Excluded model	Remaining-model Pearson
AGCRN	$+0.992784$
MegaCRN	$+0.976678$
MTGNN-Light	$+0.988090$
GWNet	$+0.960752$

Table 31: Six-architecture native-source routing-concentration summaries, adding GTS and DGCRN to the original four graph-based adaptive models. Values are the reported aggregate correlations and p-values; the METR-LA test is an exact permutation test.

Source dataset	Quantity	n	Pearson	p
METR-LA	Speed	6	$+0.974$	0.003
PEMS-BAY	Speed	6	$+0.750$	0.014
PEMS04	Flow	6	$+0.630$	0.060

Table 32: Routing-concentration relation replicates on PEMS04. Pearson $\rho(\text{max_mass}, \Delta_{\text{sensor}}) = +0.910$ across the four adaptive backbones (METR-LA reference: $+0.979$). Native checkpoints; same protocol as Table 29. Script: `experiments/pems04_routing_gate_native.py`; data: `results/polish_v15/pems04_native_routing_gate.json`.

	METR-LA (reference)		**PEMS04 (native)**	
Model	**max_mass**	Δ_{sensor}	**max_mass**	Δ_{sensor}
AGCRN	0.008	$+0.011$	0.006 ± 0.000	$+0.051 \pm 0.006$
MegaCRN	0.008	-0.005	0.005 ± 0.000	$+0.057 \pm 0.019$
MTGNN	0.160	$+0.051$	0.145 ± 0.001	$+0.119 \pm 0.004$
GWNet	0.230	$+0.092$	0.248 ± 0.020	$+0.114 \pm 0.026$

Table 33: GWNet capacity scaling: standard, P17 strong, and P21 best-sweep configs vs. DCRNN (3 seeds, mean $\pm$ std). Source-only adjacency MAE follows the P16 fairness control protocol. Q4/Q1 is the degree-stratified fragility ratio (Appendix C.5). GWNet[Best] city MAE (mph) and Q4/Q1 were not separately evaluated in the sweep; source-only normalized values are reported.

Variant	**In-dist (mph)**	Δ_{sensor} **(30%)**	**City MAE (mph)**	**Source-only adj (norm)**	**Q4/Q1 ratio**
DCRNN	6.58 ± 0.03	$+0.020 \pm 0.002$	2.74 ± 0.01	0.180 ± 0.001	$0.95\times$
GWNet	7.85 ± 0.11	$+0.088 \pm 0.017$	4.42 ± 0.15	0.268 ± 0.006	$1.83\times$
GWNet[Strong]	7.42 ± 0.04	$+0.050 \pm 0.018$	4.46 ± 0.06	0.262 ± 0.004	$1.72\times$
GWNet[Best]	7.22 ± 0.04	$+0.042 \pm 0.002$	—	0.262 ± 0.009	—

Table 34: MegaCRN Δ_{sensor} (normalized) by dropout ratio and ablation mode. Script: `experiments/megacrn_memory_ablation.py`.

Mode	r=0.1	r=0.2	r=0.3	r=0.4	r=0.5
full	-0.001	-0.043	-0.040	-0.016	$+0.045$
memzero	-0.006	-0.067	-0.075	-0.038	-0.007
graphonly	$+0.001$	-0.027	-0.024	$+0.012$	$+0.068$
attnonly	0.000	0.000	0.000	0.000	0.000

Table 35: Architecture recommendation per deployment profile. Margin is the difference in weighted-risk score to the runner-up (lower = closer call). Confidence is margin normalized by runner-up risk.

sensor	**city**	**weekend**	**Recommended**	**Runner-up**	**Confidence**
no	no	no	DCRNN	AGCRN	0.30
no	no	yes	AGCRN	MTGNN-Light	1.00
no	yes	no	MegaCRN	DCRNN	1.00
no	yes	yes	DCRNN	AGCRN	0.51
yes	no	no	STAEformer	AGCRN	0.18
yes	no	yes	AGCRN	DCRNN	0.19
yes	yes	no	DCRNN	MegaCRN	0.34
yes	yes	yes	DCRNN	AGCRN	0.30

NeurIPS Paper Checklist

1. **Claims**

   Question: Do the main claims made in the abstract and introduction accurately reflect the paper's contributions and scope?

   Answer: [Yes].

   Justification: The abstract and introduction state that the paper is a pre-registered diagnostic of frozen traffic STGNNs, not a new model or dataset. The scope is limited to the evaluated shifts, source cities, and masking assumptions.

2. **Limitations**

   Question: Does the paper discuss the limitations of the work performed by the authors?

   Answer: [Yes].

   Justification: Section 6 states the limits of the model set, single-source training, silent zero-masking assumption, and metric-dependent temporal comparisons; Appendix B.2 summarizes reproducibility and asset scope.

3. **Theory assumptions and proofs**

   Question: For each theoretical result, does the paper provide the full set of assumptions and a complete (and correct) proof?

   Answer: [Yes].

   Justification: The only theoretical component is a first-order exposure bound. Section 5 states its local interpretation, and Appendix F.5 gives the assumptions, derivation, and iid-dropout caveat.

4. **Experimental result reproducibility**

   Question: Does the paper fully disclose all the information needed to reproduce the main experimental results of the paper to the extent that it affects the main claims and/or conclusions of the paper (regardless of whether the code and data are provided or not)?

   Answer: [Yes].

   Justification: Sections 3–5 describe the datasets, splits, frozen-checkpoint protocol, shifts, metrics, and interventions. Appendix B.2 identifies the canonical result files, registry, configs, and figure-generation commands.

5. **Open access to data and code**

   Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

   Answer: [Yes].

   Justification: The submission includes evaluation scripts, configs, result tables, and the recommendation artifact. The raw traffic datasets are public third-party datasets and are cited rather than redistributed.

6. **Experimental setting/details**

   Question: Does the paper specify all the training and test details (e.g., data splits, hyperparameters, how they were chosen, type of optimizer) necessary to understand the results?

   Answer: [Yes].

   Justification: Section 3 reports the model bank, hyperparameters, seeds, splits, normalization, and all three shift protocols; appendix tables give additional protocol variants.

7. **Experiment statistical significance**

   Question: Does the paper report error bars suitably and correctly defined or other appropriate information about the statistical significance of the experiments?

   Answer: [Yes].

Justification: Main tables and figures report mean $\pm$ population standard deviation over three seeds unless otherwise stated; appendix tables specify additional mask seeds or target subsets. Appendix F.2.2 reports leave-one-out correlations and an exact permutation test for the four-model association.

8. **Experiments compute resources**

   Question: For each experiment, does the paper provide sufficient information on the computer resources (type of compute workers, memory, time of execution) needed to reproduce the experiments?

   Answer: [Yes].

   Justification: Appendix B.2 states that runs use one CUDA GPU per job and reports representative logged evaluation times. The paper also gives the frozen-checkpoint protocol so reviewers can verify results without retraining all models.

9. **Code of ethics**

   Question: Does the research conducted in the paper conform, in every respect, with the NeurIPS Code of Ethics `https://neurips.cc/public/EthicsGuidelines`?

   Answer: [Yes].

   Justification: The work uses public traffic benchmark data, reports negative and refuted results, and does not involve human subjects, private personal data collection, or deployment decisions.

10. **Broader impacts**

    Question: Does the paper discuss both potential positive societal impacts and negative societal impacts of the work performed?

    Answer: [Yes].

    Justification: Section 6 discusses deployment guidance and limitations. The main positive impact is safer model selection under traffic-sensor failures; the main risk is overgeneralizing the recommendations beyond the evaluated cities and masking model, which the paper explicitly limits.

11. **Safeguards**

    Question: Does the paper describe safeguards that have been put in place for responsible release of data or models that have a high risk for misuse (e.g., pre-trained language models, image generators, or scraped datasets)?

    Answer: [N/A].

    Justification: The paper does not release high-risk generative models, scraped datasets, or sensitive personal data. It uses public traffic forecasting benchmarks and lightweight evaluation artifacts.

12. **Licenses for existing assets**

    Question: Are the creators or original owners of assets (e.g., code, data, models), used in the paper, properly credited and are the license and terms of use explicitly mentioned and properly respected?

    Answer: [Yes].

    Justification: The paper cites the source papers for METR-LA, PEMS-BAY, PEMS04, and all model families. Appendix B.2 states that raw datasets are not redistributed and remain under their original terms.

13. **New assets**

    Question: Are new assets introduced in the paper well documented and is the documentation provided alongside the assets?

    Answer: [Yes].

    Justification: The new assets are evaluation scripts, canonical result tables, and a small recommendation artifact rather than a new dataset. Appendix B.2 documents their role and file locations.

14. **Crowdsourcing and research with human subjects**

    Question: For crowdsourcing experiments and research with human subjects, does the paper include the full text of instructions given to participants and screenshots, if applicable, as well as details about compensation (if any)?

    Answer: [N/A].

    Justification: The paper does not involve crowdsourcing or human-subject experiments.

15. **Institutional review board (IRB) approvals or equivalent for research with human subjects**

    Question: Does the paper describe potential risks incurred by study participants, whether such risks were disclosed to the subjects, and whether Institutional Review Board (IRB) approvals (or an equivalent approval/review based on the requirements of your country or institution) were obtained?

    Answer: [N/A].

    Justification: The paper does not involve human subjects or participant data collection.

16. **Declaration of LLM usage**

    Question: Does the paper describe the usage of LLMs if it is an important, original, or non-standard component of the core methods in this research? Note that if the LLM is used only for writing, editing, or formatting purposes and does *not* impact the core methodology, scientific rigor, or originality of the research, declaration is not required.

    Answer: [N/A].

    Justification: LLMs are not a component of the scientific method, experiments, routing diagnostic, or recommendation artifact; any language editing assistance does not affect the core methodology or results.