Programs for a Frozen Machine

The description length of language and task in optimized prefixes

Georgii Sirotenko

Mechanistically Interpreting Multilingual LMs, WT 2025/26

The idea

- A frozen LM is a fixed machine. A soft prefix that makes it do a task is a **program** for that machine.
- The shortest such program is a model-relative **description length** of the task (Shaw et al. 2026; Cosma 2026).
- Grid: tasks {translation from English, factual recall, continuation} $\times$ output languages {ru, de, en}, Qwen2.5-1.5B base, frozen.
- Questions: how many bits does a cell cost, how are they split between *task* and *language*, do the parts compose, how far apart are programs, where does the model read them.


Two units, one distortion

- **Slots**: number k of prefix positions (capacity).
- **Bits**: prefix = diagonal Gaussian posterior; its KL to a prior fitted to the embedding matrix is the code length (bits-back; Hinton & van Camp 1993).
- Distortion: teacher-forced bits per target token, normalised per cell

$$\hat{D} = \frac{L - L_{\text{floor}}}{L_{\text{none}} - L_{\text{floor}}}, \qquad L_{\text{floor}} = \min(\text{LoRA}, \text{best prefix})$$

- Preregistered operating points $\hat{D} \leq 0.25$ and ≤ 0.10.
- 8 cells; ~32 A100 hours; every figure regenerated from CSVs.

Result 1: slots are not a description length




- Translation: one slot reaches $\hat{D} \leq 0.10$ in every language. Recall needs 2–16 and is still improving at $k = 32$.
- One trained slot beats the natural-language prompt: recall NL prompt $\hat{D}$ 0.91–0.96, one slot 0.13–0.41.
- Telling the model the language or the task saves < 1 slot on average. Continuation: floor no prefix, unmeasurable.

Result 2: description length in bits

cell	bits at $\hat{D} \leq 0.10$	bits at $\hat{D} \leq 0.25$
translation-de	436	436
translation-ru	542	542
recall-ru	2,419	2,419
recall-de	— (best 0.14)	3,343
recall-en	— (best 0.23)	7,155

- A translation program 500 bits; Russian recall 5×; English recall dearest, also on the 4,212 items shared by all three recall test sets.
- Task ordering follows the learning gap (H1); language ordering does **not** follow exposure (H1).

Result 3: task is the shared factor, language the cheap modifier




code for all 8 cells at $\hat{D} \leq 0.25$	bits
one centre per task + language deviations	33,500
eight independent programs	37,600
one centre per language + task deviations	53,500


What a language costs, what a task costs

- Given the **translation** centre: Russian 485 bits, German 662 bits. Under half a standalone program.
- Given the **recall** centre: a language costs 3,300–4,000 bits.
- Given a **language** centre: continuation 100–200 bits, translation 440–630, recall 5,300–26,200.
- Recall is the program that cannot be shared; the language-centred code pays for it three times.
- For translation alone the hierarchy does not pay (2,733 vs 1,893 bits): the shared centre is dearer than either specialised program.

Result 4: composition and distance




Zero-shot assembly of task part + language part closes 60–73% of the gap on translation, 14–32% on recall.




Same-task warm start costs 0.85 of scratch, same-language 0.95. Silhouettes 0: direction only. Zero-shot transfer = no prefix; recall prefixes break continuation.

Result 5: where the program is read



- Patching the prefix positions into **block 0 alone** recovers 70–94% of the effect for translation and continuation, 36–58% for recall (secondary peaks at blocks 17, 25).
- A translation program is copied into the token stream in the first block; a recall program is read repeatedly, deep in the network.
- Language deviation vs task centre (H5): both peak at block 0; the depth profile splits by task, not by prefix part.

Result 6: the objective is right, the search is hard



- lr 0.05 = 2 prior per step → KL overshoots by 20k (k=2) to 300k bits (k=8), then decays.
- Selecting the checkpoint by mean-posterior distortion picks the high-rate step; the mean is not the coded object (=3: mean $\hat{D}$ 0.35–0.56, samples 0.06–0.17).
- Corrected protocol (lr 0.01, select on the objective, score samples): frontier **20–71%**

Preregistered comparisons

	outcome
H1 cost orderings	task (recall translation); language (English dearest)
H2 cheap language	slots: equal; bits: task given language 2–7× language given task on recall
H3 separability	partial on translation, not on recall
H4 task-organised distance	direction , structure (silhouette 0.004 vs −0.09)
H5 depth split	by task, not by prefix part
H6 input compressibility	one vector suffices with the task prefix (exploratory)

Limitations and next steps

- Two seeds; recall budget-bound (3000 steps: $\hat{D}$ 0.043 $\rightarrow$ 0.032 and falling); continuation unmeasurable; distance matrix one seed.
- Variational protocol corrected after preregistration; both reported. Hierarchical rates are upper bounds (old selection rule).
- Research version, same code: scale axis 0.5B–7B, 20+ languages by resource level, per-column mixture prior, charge $\log_2 |k\text{-grid}|$ bits for k, step size in prior- units.
- Repo: `sirotenkogeorgii/prefix-programs`, branch `prefixlab`; `01_figures.ipynb` regenerates everything in under a minute.