Programs for a Frozen Machine

The description length of language and task in optimized prefixes

Georgii Sirotenko

Mechanistically Interpreting Multilingual LMs, WT 2025/26

The idea

- A frozen LM is a fixed machine. A soft prefix that makes it do a task is a **program** for that machine.
- The shortest such program is a model-relative **description length** of the task (Shaw et al. 2026; Cosma 2026).
- Grid: tasks {translation from English, factual recall, continuation} × output languages {ru, de, en}, Qwen2.5-1.5B base, frozen.
- Questions: how many bits does a cell cost, how are they split between *task* and *language*, do the parts compose, how far apart are programs, where does the model read them.


Two units, one distortion

- **Slots**: number k of prefix positions (capacity).
- **Bits**: prefix = diagonal Gaussian posterior; its KL to a prior fitted to the embedding matrix is the code length (bits-back; Hinton & van Camp 1993).
- Distortion: teacher-forced bits per target token, normalised per cell

$$\hat{D} = \frac{L - L_{\text{floor}}}{L_{\text{none}} - L_{\text{floor}}}, \qquad L_{\text{floor}} = \min(\text{LoRA}, \text{best prefix})$$

- Preregistered operating points $\hat{D} \leq 0.25$ and ≤ 0.10.
- 8 cells; ~36 A100 hours; every figure regenerated from CSVs.

Result 1: slots are not a description length




- Translation: one slot reaches $\hat{D} \leq 0.10$ in every language. Recall needs 2–16 and is still improving at $k = 32$.
- One trained slot beats the natural-language prompt: recall NL prompt $\hat{D}$ 0.91–0.96, one slot 0.13–0.41.
- Telling the model the language or the task saves 1.8 slots on average, 8 of them from recall-en. Continuation: floor ≈ no prefix, unmeasurable.

Result 2: description length in bits

cell	bits at $\hat{D} \leq 0.10$	bits at $\hat{D} \leq 0.25$
translation-de	436	436
translation-ru	542	542
recall-ru	2,419	2,419
recall-de	— (best 0.14)	3,343
recall-en	— (best 0.23)	7,155

- Shortest programs found: translation ≈ 500 bits; Russian recall 5× (upper bounds); English recall dearest, also on the 4,212 items shared by all three recall test sets.
- Task ordering follows the learning gap (H1 yes); language ordering does **not** follow exposure (H1 no).
- Replication seed (corrected protocol): within 4% on three cells, 17–22% on recall-de / translation-de in opposite directions; same ordering.

Result 3: neither nesting is cheaper, and sharing gives no consistent saving



Centre paid once per group, each deviation once per member; cheapest run with every member at $\hat{D} \leq 0.25$.

Three codes for the same eight cells


code (all 8 cells, $\widehat{D} \leq 0.25$)	protocol	bits
task centres + language deviations	prereg. selection	33,500
eight independent programs	prereg.	37,600
language centres + task deviations	prereg. selection	53,500
task centres + language deviations	corrected	26,700
language centres + task deviations	corrected	not reached (ru+de 8,900)
eight independent programs	corrected	17,600

- Prereg. rule: task-centred wins by 37%. Corrected: the nestings tie within 25% at matched (k, β); language-centred never gets recall-en under 0.25.
- A shared centre gives **no consistent saving**: 1.87× the independent programs on the five measurable cells; parity on translation (1,029 vs 978), 1.9× on recall (24,972 vs 12,917).


What a language costs, what a task costs

- Given the **translation** centre (604 bits): Russian 225, German 200 bits, 0.41–0.46 of a standalone program (corrected protocol; 485 / 662 under the preregistered rule).
- Given the **recall** centre (14,600 bits): a language costs 3,200–3,950 bits, more than a standalone Russian or German program.
- Given a **language** centre retrained on translation + recall (975 / 770 bits): translation 137 / 139, recall 2,251 / 2,774 (ru / de); the group is at parity with independent programs (1.14 / 0.97). Compare with the task-centred costs; the prereg. asymmetry (recall 5,300–26,200 given a language) was the optimiser.
- Recall dominates every code that contains it: 2,250–3,950 bits as a deviation from either kind of centre.
- For translation alone the hierarchy is at best at parity: 1,029 vs 978 bits (corrected), 2,733 vs 1,893 (prereg.).

Result 4: composition and distance




Zero-shot assembly of task part + language part closes 60–73% of the gap on translation, 14–32% on recall.




Same-task warm start costs 0.85 of scratch, same-language 0.95. Silhouettes ≈ 0: direction only. Zero-shot transfer = no prefix; recall prefixes break continuation.

Result 5: where the program is read



- Patching the prefix positions into **block 0 alone** recovers 70–94% of the effect for translation and continuation, 36–58% for recall (secondary peak at block 17).
- Patching block 0 alone recovers 70–87% of a translation program's effect but only 36–58% of a recall program's; the rest of recall's effect is recovered at blocks 10–11 and 17.
- H5: every probe peaks at block 0, but the **language deviation is read again at blocks 16–17** (late mass 1.9 vs early 1.6 on recall) while the task centre is not (0.5 vs 1.0): a split by part, opposite to H5's direction.

Result 6: the objective is right, the search is hard



- lr 0.05 = 2 prior σ per step: the centre KL peaks at a median 26k bits (k=2) to 144k (k=8), up to 549k, between steps 100 and 800, then decays.
- Selecting the checkpoint by mean-posterior distortion picks a high-rate step (up to 20× the final rate); the mean is not the coded object (translation, β=3: mean $\widehat{D}$ 0.35–0.56, samples 0.06–0.17).
- Corrected protocol (lr 0.01, select on the objective, score samples): frontier **20–71% lower** with 4 runs per cell instead of 9; hierarchy reruns show no overshoot (selected step within 2% of final).
- Shaw et al. (2026): 870 bits from a compiled init vs 2.8M from random init. Here the

Preregistered comparisons

	outcome
H1 cost orderings	task yes (recall far above translation); language no (English dearest)
H2 cheap language	slots: equal; bits: equal under the corrected protocol (prereg. 1.3–7.8× asymmetry does not replicate)
H3 separability	partial on translation, not on recall; a shared centre gives no consistent saving (1.87× independent on measurable cells; language groups at parity); nestings equal within 25%
H4 task-organised distance	direction yes, structure no, not significant (silhouette 0.004 vs −0.09)
H5 depth split	language deviation read early and late, task centre early: opposite to H5
H6 input compressibility	one vector suffices with the task prefix (exploratory)

Limitations and next steps

- Two seeds; recall budget-bound (3000 steps: $\widehat{D}$ 0.043 to 0.032 and falling); continuation unmeasurable; distance matrix one seed.
- Variational protocol corrected after preregistration; both reported. Both nestings rerun under it; every corrected rate still falling at 1500 steps.
- Research version, same code: scale axis 0.5B–7B, 20+ languages by resource level, per-column mixture prior, charge $\log_2 |k\text{-grid}|$ bits for k, step size in prior-σ units.
- Code and results: https://github.com/sirotenkogeorgii/prefix-programs; one notebook regenerates all figures and tables.