

GSC-X Battery Sandbox

Battery Validation V1: Multi-Dataset Predictive Battery Health Validation Using Context Memory and Early Limit Indicator

Martin Štěpánů
Independent Researcher
ORCID: 0009-0007-0409-6037
stepanumartin@gds-gsc-x.com
ID CZ: 71985981
<https://gds-gsc-x.com>
GitHub Repository
<https://github.com/sisacek66198068/GSC-X>

Related GSC-X Sandbox Portfolio

GSC-X Industrial Sandbox
GSC-X Reliability Sandbox
GSC-X Fusion Sandbox
GSC-X Spaceflight Sandbox
GSC-X Battery Sandbox
GSC-X Robotics Sandbox
GSC-X Nuclear Sandbox
GSC-X Energy Network Sandbox

Filed Patent Applications (Patent Pending)

PV 2026-216 (GSC-F)
PV 2026-236 (GSC-S)
PV 2026-241 (GSC-C)
PV 2026-242 (GSC-X)

June 21, 2026

Abstract

The GSC-X Battery Sandbox represents the battery-health and predictive-warning branch of the broader GSC-X critical-infrastructure validation ecosystem.

This study presents a multi-dataset validation campaign focused on battery degradation monitoring, state-of-health tracking, predictive warning generation, and end-of-life detection using the GSC-X executive architecture.

The validation portfolio includes NASA PCoE battery datasets, Oxford battery datasets, CALCE battery datasets, and independent Zenodo audit datasets.

Across the validated NASA subset, the GSC-X architecture successfully detected 100% of standard end-of-life battery events while maintaining meaningful early-warning lead horizons and low false-warning rates.

The primary contribution of this work is not only battery-health prediction.

The broader contribution is the demonstration that Context Memory (CM) and Early Limit Indicator (ELI) mechanisms can provide predictive resilience capabilities across multiple critical-infrastructure domains.

Together with previous Reliability Sandbox and Energy Network Sandbox validations, the Battery Sandbox forms part of an emerging critical-infrastructure resilience framework spanning predictive maintenance, battery-health monitoring, energy storage, and energy-network stabilization.

The presented results should be interpreted as a predictive battery-health validation study and not as a replacement for existing battery-management systems.

Instead, GSC-X is evaluated as a complementary executive layer capable of enhancing monitoring, early-warning generation, and operational resilience within future battery-management and energy-storage environments.

From a broader perspective, Reliability, Battery, and Energy Network validations collectively suggest the emergence of a unified predictive-resilience framework applicable to critical infrastructure, industrial systems, energy storage, and future national energy-security ecosystems.

1 Introduction

Modern societies increasingly depend on battery systems.

Electric vehicles, renewable-energy storage facilities, backup-power systems, telecommunications infrastructure, industrial automation, and critical national infrastructure all rely on large-scale battery assets.

As battery deployment continues to accelerate, the ability to detect degradation early, estimate remaining useful life, and identify approaching end-of-life conditions becomes increasingly important.

Traditional battery-management systems primarily focus on operational protection and state estimation.

The Battery Sandbox investigates a complementary question.

Can predictive executive architectures discover degradation trajectories early enough to provide meaningful operational warning before critical failure or end-of-life conditions emerge?

The Battery Sandbox therefore evaluates the GSC-X architecture as a predictive executive layer operating above conventional monitoring systems.

Its objective is not to replace existing battery-management systems.

Its objective is to provide additional predictive awareness through Context Memory (CM), Early Limit Indicator (ELI), degradation tracking, and predictive-warning generation.

This work also forms part of a broader critical-infrastructure validation effort.

Together with the Reliability Sandbox and Energy Network Sandbox, the Battery Sandbox contributes to a unified resilience framework addressing predictive maintenance, battery health, energy storage, and infrastructure continuity.

In this context, battery-health prediction is not viewed as an isolated problem.

It is viewed as one component of a larger resilience ecosystem supporting future energy systems and critical national infrastructure.

The long-term objective of the Battery Sandbox is therefore not merely battery diagnostics.

The broader objective is the development of predictive resilience architectures capable of improving reliability, operational continuity, and energy security across increasingly complex technological infrastructures.

2 GSC-X Battery Executive Architecture

The Battery Sandbox evaluates the GSC-X architecture as a predictive executive stabilization and monitoring layer operating above conventional battery-management systems.

The architecture is centered around two executive-state variables:

- Context Memory (CM)
- Early Limit Indicator (ELI)

CM represents accumulated operational context and degradation history.

Rather than evaluating battery state solely from instantaneous measurements, CM preserves information about historical system behavior, persistence of degradation trends, and recovery dynamics.

ELI serves as a predictive instability detector.

Instead of waiting for conventional threshold violations, ELI attempts to identify approaching degradation boundaries before critical operational limits are reached.

The Battery Sandbox combines these executive variables with:

- State-of-Health Monitoring
- Capacity-Loss Tracking
- Predictive Warning Generation
- End-of-Life Detection
- Battery Metastability Monitoring
- Multi-Dataset Validation

The resulting architecture is intended to function as a complementary executive layer that enhances monitoring and predictive awareness without replacing existing battery-management infrastructure.

3 Validation Portfolio

Battery Validation V1 was designed as a multi-dataset validation campaign.

The objective was to evaluate whether predictive warning mechanisms remain effective across different battery datasets, collection methodologies, degradation profiles, and operating environments.

The validation portfolio currently includes the datasets summarized in Table 1.

Table 1: Battery Validation Portfolio

Dataset	Status
NASA PCoE Battery Dataset	Complete
Oxford Battery Dataset	Complete
CALCE Battery Dataset	Partial
Independent Zenodo Audit	Complete
Stanford Severson Dataset	Postponed

The validation strategy intentionally emphasizes cross-dataset reproducibility.

Rather than optimizing performance for a single benchmark, the Battery Sandbox investigates whether predictive-warning behavior can remain robust across multiple independent battery datasets.

This approach follows the broader philosophy used throughout the GSC-X validation ecosystem, where reproducibility across domains is considered more important than isolated performance on a single benchmark.

The Battery Sandbox therefore complements previous validation efforts in Reliability, Energy Networks, Fusion, Industrial Systems, Robotics, Spaceflight, and Nuclear Digital Twins.

Together these branches contribute toward a broader predictive-resilience framework for critical infrastructure systems.

4 NASA PCoE Validation

The NASA Prognostics Center of Excellence (PCoE) battery dataset represents the primary validation benchmark within Battery Validation V1.

The dataset contains controlled degradation trajectories of lithium-ion battery cells monitored throughout their operational lifetime.

Battery Validation V1 focused on identifying degradation progression, generating predictive warnings, and detecting approaching end-of-life conditions before conventional threshold-based failure criteria were reached.

A complete audit of the available battery records was performed before validation.

The audit classified cells according to data quality, degradation consistency, and suitability for predictive analysis.

The resulting classification is summarized in Table 2.

Table 2: NASA Battery Audit Summary

Category	Count
Standard Aging Cells	27
Nonstandard Cells	6
Invalid Baseline Cells	2
Too Short for Validation	1
Total Audited Cells	38

Two cells were excluded from standard validation due to invalid baseline behavior:

- B0033
- B0041

One additional cell was excluded because the available trajectory was too short to provide meaningful predictive evaluation.

The remaining standard-aging subset formed the primary benchmark used throughout Battery Validation V1.

The NASA validation campaign therefore represents a carefully curated predictive-maintenance benchmark rather than a simple application of algorithms to raw battery records.

This audit process was designed to ensure that predictive-warning performance was evaluated on physically meaningful degradation trajectories.

5 NASA Predictive Warning Results

The strongest results obtained within Battery Validation V1 originated from the NASA battery benchmark.

The predictive-warning layer based on Context Memory (CM) and Early Limit Indicator (ELI) successfully identified all validated standard end-of-life events.

The principal performance metrics are summarized in Table 3.

Table 3: NASA Predictive Warning Results

Metric	Result
Validated Standard Cells	27
End-of-Life Detection Rate	100%
Coverage	100%
False Warnings	4
Mean Warning Lead	18.784%
Median Warning Lead	22.222%

The results indicate that the executive-state architecture successfully identified all validated end-of-life trajectories within the benchmark subset.

More importantly, warnings were generated sufficiently early to provide meaningful operational lead time rather than merely detecting degradation immediately before failure.

This distinction is important.

The objective of Battery Validation V1 is not failure detection.

The objective is predictive awareness.

A warning generated shortly before failure provides limited operational value.

A warning generated with meaningful lead time creates opportunities for maintenance scheduling, operational planning, and asset-management optimization.

The observed warning horizons therefore represent one of the most significant outcomes of the Battery Sandbox validation effort.

The combination of Context Memory and Early Limit Indicator appears capable of identifying degradation trajectories before traditional threshold violations occur.

These results support the hypothesis that executive-state variables can enhance predictive monitoring beyond conventional reactive approaches.




Figure 1: Illustrative NASA battery degradation trajectory showing State-of-Health evolution together with the Early Limit Indicator (ELI). The figure demonstrates how executive-state variables can provide predictive awareness before conventional end-of-life thresholds are reached.

6 Oxford Battery Validation

To reduce dependence on a single benchmark source, Battery Validation V1 also incorporated validation using independent Oxford battery datasets.

The purpose of the Oxford validation was to determine whether the predictive behaviors observed within NASA trajectories remained observable in an unrelated dataset collected under

different experimental conditions.

Oxford validation was successfully completed.

The resulting behavior remained broadly consistent with the NASA observations.

Although the Oxford datasets differ from NASA in collection methodology and degradation characteristics, the executive-state variables continued to demonstrate useful predictive behavior.

The Oxford validation therefore provides an important independent confirmation that the Battery Sandbox is not exclusively dependent on a single benchmark source.

Cross-dataset reproducibility remains one of the central objectives of the broader GSC-X validation philosophy.




Figure 2: Multi-cell NASA battery validation illustrating State-of-Health trajectories across several battery cells. The figure highlights the consistency of degradation tracking used within Battery Validation V1.

Table 4: NASA Validation Highlights

Metric	Result
Audited Cells	38
Standard Aging Cells	27
Coverage	100%
EOL Detection	100%
False Warnings	4
Mean Lead Horizon	18.784%
Median Lead Horizon	22.222%

7 CALCE Battery Validation

Battery Validation V1 also incorporated the CALCE battery dataset.

The CALCE branch focused primarily on data auditing, structure verification, and evaluation of long-term degradation records.

Particular attention was devoted to the PL21 and PL23 battery groups as well as MATLAB MCOS-derived table structures encountered during dataset processing.

At the time of publication, CALCE validation remains partially completed.

The available results nevertheless indicate that the dataset provides an additional independent source for future validation expansion.

The CALCE branch is therefore retained within the Battery Sandbox roadmap as a continuing validation effort rather than a completed benchmark.

The long-term objective is to extend predictive-warning evaluation across a wider range of battery chemistries, operating conditions, and degradation pathways.

8 Independent Zenodo Audit

In addition to the primary validation datasets, Battery Validation V1 included an independent audit of publicly available battery-related datasets and validation resources distributed through the Zenodo platform.

The purpose of this audit was not to optimize performance metrics.

Instead, the objective was to evaluate data quality, reproducibility potential, documentation completeness, and suitability for future predictive-health studies.

The audit confirmed that publicly available battery datasets vary substantially in structure, metadata quality, and accessibility.

Nevertheless, the reviewed resources provide valuable opportunities for future validation expansion and independent reproduction of Battery Sandbox results.

The inclusion of independent audit activities reflects a broader principle used throughout the GSC-X validation ecosystem.

Validation should not rely exclusively on a single benchmark source.

Instead, confidence increases when predictive behaviors remain observable across multiple independently collected datasets.

The Zenodo audit therefore serves as an additional reproducibility layer supporting the long-term development of Battery Validation V1.

9 Stanford Severson Dataset

Battery Validation V1 also investigated the Stanford Severson battery dataset as a potential future validation benchmark.

During the audit process, available resources primarily consisted of JavaScript bundles and hidden API endpoints associated with the public interface.

Direct access to complete validation-ready battery trajectories could not be established during the current validation cycle.

Consequently, Stanford validation was postponed rather than partially executed.

This decision follows the general validation philosophy adopted throughout the GSC-X project.

Incomplete validation is considered less valuable than transparent reporting of limitations.

Future work will revisit the Stanford dataset once complete and reproducible access pathways become available.

The Stanford branch therefore remains part of the Battery Sandbox roadmap rather than part of the completed validation portfolio.

10 Battery Operating Status

The current completion status of Battery Validation V1 is summarized in Table 5.

Table 5: Battery Validation V1 Completion Status

Validation Branch	Status
NASA PCoE	Complete
Oxford Battery Dataset	Complete
CALCE Dataset	Partial
Zenodo Audit	Complete
Stanford Dataset	Postponed
Overall Completion	85–90%

The Battery Sandbox has therefore reached a level sufficient for public validation reporting while still retaining opportunities for future expansion.

The completed validation branches already provide independent evidence across multiple datasets, while unfinished branches remain available for future validation cycles.

11 Discussion

Battery Validation V1 demonstrates that executive-state architectures can provide meaningful predictive awareness within battery-health monitoring environments.

The results suggest that Context Memory and Early Limit Indicator are capable of identifying degradation trajectories before conventional threshold-based approaches would typically generate warnings.

The importance of these findings extends beyond battery systems themselves.

Within the broader GSC-X ecosystem, Battery Validation V1 complements previous Reliability Sandbox and Energy Network Sandbox results.

The Reliability Sandbox demonstrated predictive warning capabilities for rotating machinery, turbofan engines, and industrial-health monitoring systems.

The Energy Network Sandbox demonstrated predictive stabilization, cascade suppression, and critical-infrastructure persistence within electrical networks.

The Battery Sandbox occupies a natural position between these two domains.

Batteries are simultaneously reliability assets and energy assets.

They are components whose health directly influences the resilience of future energy infrastructures.

Consequently, the combined results of Reliability, Battery, and Energy Network validations suggest the emergence of a broader predictive-resilience framework.

Rather than viewing predictive maintenance, battery monitoring, and energy-network stabilization as independent disciplines, the GSC-X validation ecosystem suggests that they may be partially unified through common executive-state principles.

This observation does not constitute proof of a universal resilience architecture.

However, the consistency of results across multiple domains provides encouraging evidence that common predictive mechanisms may exist across different classes of critical infrastructure.

From a national-infrastructure perspective, this possibility is particularly significant.

Modern societies increasingly depend on interconnected energy systems, storage systems, communication systems, industrial systems, and transportation systems.

Failures within one subsystem often propagate into others.

Predictive resilience therefore becomes increasingly valuable as system complexity grows.

The Battery Sandbox contributes to this broader objective by demonstrating that predictive-warning architectures can operate successfully within battery-health environments while remaining compatible with larger resilience frameworks.

12 Potential Operational Impact

Although Battery Validation V1 is primarily a predictive-health validation study, the observed results suggest several potential operational implications.

The ability to identify degradation trajectories before conventional end-of-life criteria are reached may provide additional operational flexibility for battery operators and asset managers.

Potential application areas include:

- Electric Vehicle Fleets
- Utility-Scale Battery Storage
- Renewable Energy Storage Systems
- Critical Infrastructure Backup Power
- Telecommunications Infrastructure
- Industrial Energy Storage
- Microgrid and Smart-Grid Environments

The primary operational value does not originate from battery replacement itself.

The primary value originates from improved decision-making.

Earlier awareness of degradation trends may allow maintenance planning, asset rotation, load redistribution, and operational optimization before critical conditions emerge.

Within larger energy systems, battery-health awareness may also contribute to broader resilience objectives.

As battery-storage deployment continues to increase, predictive degradation monitoring may become an increasingly important component of future energy-security architectures.

Battery Validation V1 therefore represents not only a battery-monitoring study but also a contribution toward predictive resilience within future energy-storage ecosystems.

Illustrative Operational Impact Assessment

The following table presents conservative engineering estimates describing potential operational benefits if predictive battery-health monitoring is integrated into large-scale battery-management environments.

Table 6: Illustrative Operational Impact Assessment

Area	Technical Effect	Potential Operational Benefit
Battery Lifetime Management	Earlier degradation awareness	Improved maintenance scheduling
Fleet Monitoring	Predictive warning generation	Reduced unexpected outages
Energy Storage Systems	State-of-health awareness	Improved asset utilization
Critical Infrastructure Backup Systems	Earlier risk identification	Improved operational resilience
Grid-Scale Storage	Predictive degradation tracking	Improved long-term planning

These estimates are presented as engineering interpretations rather than validated economic forecasts.

Future pilot studies will be required before quantitative economic conclusions can be established.




Figure 3: Conceptual illustration of predictive resilience across Reliability, Battery and Energy Network domains. The figure contrasts conventional reactive approaches with the GSC-X executive architecture based on Context Memory (CM) and Early Limit Indicator (ELI), highlighting the potential role of predictive stabilization in future critical infrastructure and energy-security environments.

Figure 3 illustrates the broader motivation behind the GSC-X validation ecosystem.

Although the Reliability Sandbox, Battery Sandbox, and Energy Network Sandbox address different technical domains, all three branches investigate the same fundamental objective: the early identification of approaching instability regimes before conventional operational limits are exceeded.

The Reliability Sandbox focuses on predictive maintenance and degradation monitoring, the Battery Sandbox addresses energy-storage health and end-of-life prediction, and the Energy Network Sandbox investigates cascade suppression and infrastructure resilience.

Together, these validation branches suggest the possibility of a unified predictive-resilience framework capable of enhancing awareness, operational continuity, and stability across future critical infrastructure systems.

While additional validation and pilot studies remain necessary, the consistency of results across multiple independent domains provides encouraging evidence that executive-state architectures based on Context Memory (CM) and Early Limit Indicator (ELI) may represent a promising direction for future resilience-oriented technologies.

13 Limitations

Several limitations should be acknowledged.

First, Battery Validation V1 does not currently include complete Stanford Severson validation.

Second, CALCE validation remains partially completed.

Third, no hardware-in-the-loop battery-management experiments have yet been performed.

Fourth, no commercial battery-management system integration has been evaluated within the present validation cycle.

Consequently, the results presented in this work should be interpreted as validation evidence within publicly available datasets rather than proof of operational performance in deployed industrial environments.

Future validation phases will address these limitations through additional datasets, hardware-in-the-loop studies, and pilot-scale deployment opportunities.

14 Conclusion

Battery Validation V1 demonstrates that executive-state architectures based on Context Memory (CM) and Early Limit Indicator (ELI) can provide meaningful predictive awareness within battery-health monitoring environments.

Across the validated NASA subset, the GSC-X architecture successfully detected 100% of standard end-of-life battery events while maintaining useful predictive warning horizons and low false-warning rates.

Additional validation using Oxford datasets, CALCE auditing activities, and independent Zenodo audits further supports the reproducibility-oriented philosophy adopted throughout the GSC-X ecosystem.

The broader significance of these findings extends beyond battery monitoring alone.

When considered together with previous Reliability Sandbox and Energy Network Sandbox validations, the Battery Sandbox contributes to an emerging predictive-resilience framework spanning predictive maintenance, energy storage, infrastructure continuity, and operational stability.

These results do not imply the existence of a universal resilience law.

However, they provide encouraging evidence that common executive-state principles may remain useful across multiple classes of critical infrastructure.

Battery Validation V1 therefore represents both a battery-health validation study and a contribution toward the broader objective of predictive resilience for future technological and energy systems.

From a broader infrastructure perspective, Battery Validation V1 complements the previously validated Reliability Sandbox and Energy Network Sandbox.

Together these branches form a unified predictive-resilience ecosystem addressing asset health, energy storage, and energy-network stability.

This combination may be particularly relevant for future critical-infrastructure protection, national energy-security programs, and large-scale energy-transition initiatives.

15 Future Work

Future development of the Battery Sandbox will focus on:

- Completion of CALCE validation
- Completion of Stanford Severson validation
- Battery Digital Twin development
- Hardware-in-the-Loop battery studies
- Real-time Battery Management System integration
- Utility-scale energy-storage validation

- Grid-storage resilience studies
- Industrial pilot projects
- Cross-validation with Energy Network Sandbox environments
- Integration with existing Battery Management Systems (BMS)
- Integration with SCADA and Energy Management Systems

The long-term objective is to evaluate whether predictive executive architectures can function as complementary resilience layers for future battery-management and energy-storage ecosystems.

Acknowledgements

The author acknowledges the use of publicly available datasets including NASA PCoE, Oxford Battery Degradation datasets, CALCE resources, and publicly available validation repositories.

The author also acknowledges the use of AI-assisted analytical tools, including ChatGPT and Gemini, as research assistants supporting data analysis, interpretation, validation planning, and manuscript preparation.

Reproducibility and Public Repository

Validation artifacts, reports, benchmark summaries, and public project documentation are available at:

<https://github.com/sisacek66198068/GSC-X>

Interactive Demonstrator

An interactive Battery Sandbox presenting the validation results, benchmark portfolio, and battery-health demonstrations described in this study is available at:

<https://battery.gds-gsc-x.com>

References

- [1] Martin Štěpánů. *GSC-X: Generative Stability Control Executive Architecture*. Zenodo. DOI: 10.5281/zenodo.20156104
- [2] Martin Štěpánů. *GDS: Gravitational Dynamical System*. Zenodo. DOI: 10.5281/zenodo.20037474
- [3] Martin Štěpánů. *Regenerative Metastability*. Zenodo. DOI: 10.5281/zenodo.20688368