

# SAFETY DATA SHEET

Version 6.6  
Revision Date 16.07.2021  
Print Date 11.06.2022

## SECTION 1: Identification of the hazardous chemical and of the supplier

### 1.1 Product identifiers

Product name : Ethylenediamine

Product Number : E26266  
Brand : Sigma-Aldrich  
CAS-No. : 107-15-3

### 1.2 Other means of identification

1,2-Diaminoethane

### 1.3 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : For R&D use only. Not for pharmaceutical, household or other uses.

### 1.4 Details of the supplier of the safety data sheet

Company : SIGMA-ALDRICH (M) SDN BHD  
Level 3, Menara Sunway Annexe,  
Jalan Lagoon Timur, Bandar Sunway,  
46150 PETALING JAYA, SELANGOR  
MALAYSIA

Telephone : +60 (603)03-563-53321  
Fax : +60 (603)03-563-54116

### 1.5 Emergency telephone

Emergency Phone # : 1-800-815-308 (CHEMTREC) \* + 62 0800  
140 1253 (Customer Call Centre)

## Section 2: Hazard identification

### 2.1 GHS Classification

Classification according to CLASS regulations 2013  
Flammable liquids (Category 3), H226  
Acute toxicity, Oral (Category 4), H302  
Acute toxicity, Dermal (Category 4), H312  
Skin corrosion/irritation (Category 1B), H314  
Serious eye damage/eye irritation (Category 1), H318  
Respiratory sensitization (Category 1), H334  
Skin sensitization (Category 1), H317

For the full text of the H-Statements mentioned in this Section, see Section 16.

### 2.2 GHS Label elements, including precautionary statements

Labelling according to CLASS regulations 2013  
Pictogram



Signal word	Danger
Hazard statement(s)	
H226	Flammable liquid and vapor.
H302 + H312	Harmful if swallowed or in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Precautionary statement(s)	
Prevention	
P210	Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P261	Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
P264	Wash skin thoroughly after handling.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P285	In case of inadequate ventilation wear respiratory protection.
Response	
P303 + P361 + P353	IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P310	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/ physician.
P305 + P351 + P338 + P310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.
P342 + P311	If experiencing respiratory symptoms: Call a POISON CENTER or doctor/ physician.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

### 2.3 Other hazards

Rapidly absorbed through skin.  
Lachrymator.

## SECTION 3: Composition and information of the ingredients of the hazardous chemical

Substance / Mixture : Substance

### 3.1 Substances

Synonyms : 1,2-Diaminoethane

Formula : C<sub>2</sub>H<sub>8</sub>N<sub>2</sub>

Molecular weight : 60.10 g/mol

CAS-No. : 107-15-3

EC-No. : 203-468-6

Index-No. : 612-006-00-6

#### Hazardous ingredients

Component	Classification	Concentration
-----------	----------------	---------------

<b>ethylenediamine</b> Included in the Candidate List of Substances of Very High Concern (SVHC) according to Regulation (EC) No. 1907/2006 (REACH)		
	Flam. Liq. 3; Acute Tox. 4; 1B; 1; Resp. Sens. 1; Skin Sens. 1; H226, H302, H312, H314, H318, H334, H317	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

## SECTION 4: First aid measures

### 4.1 Description of first-aid measures

#### General advice

First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

#### If inhaled

After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

#### In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

#### In case of eye contact

After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist. Remove contact lenses.

#### If swallowed

After swallowing: make victim drink water (two glasses at most), avoid vomiting (risk of perforation). Call a physician immediately. Do not attempt to neutralise.

### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

### 4.3 Indication of any immediate medical attention and special treatment needed

No data available

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Water Foam Carbon dioxide (CO<sub>2</sub>) Dry powder

#### Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

### 5.2 Special hazards arising from the substance or mixture

Carbon oxides

Nitrogen oxides (NO<sub>x</sub>)

Flash back possible over considerable distance., Container explosion may occur under fire conditions., Vapors may form explosive mixture with air.

Combustible.

Vapors are heavier than air and may spread along floors.

Forms explosive mixtures with air at elevated temperatures.

Development of hazardous combustion gases or vapours possible in the event of fire.

### **5.3 Advice for firefighters**

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

### **5.4 Further information**

Remove container from danger zone and cool with water. Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

---

## **SECTION 6: Accidental release measures**

### **6.1 Personal precautions, protective equipment and emergency procedures**

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

### **6.2 Environmental precautions**

Do not let product enter drains. Risk of explosion.

### **6.3 Methods and materials for containment and cleaning up**

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

### **6.4 Reference to other sections**

For disposal see section 13.

---

## **SECTION 7: Handling and storage**

### **7.1 Precautions for safe handling**

#### **Advice on safe handling**

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

#### **Advice on protection against fire and explosion**

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

#### **Hygiene measures**

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

### **7.2 Conditions for safe storage, including any incompatibilities**

#### **Storage conditions**

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Keep locked up or in an area accessible only to qualified or authorized persons.

Air and moisture sensitive. Handle and store under inert gas.

### **7.3 Specific end use(s)**

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

## SECTION 8: Exposure controls and personal protection

### 8.1 Control parameters

#### Ingredients with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
ethylenediamine	107-15-3	TWA	10 ppm 25 mg/m <sup>3</sup>	Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.
	Remarks	Skin		

### 8.2 Exposure controls

#### Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

#### Personal protective equipment

##### Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Tightly fitting safety goggles

##### Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.7 mm

Break through time: 480 min

Material tested: Butoject® (KCL 898)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

Splash contact

Material: Chloroprene

Minimum layer thickness: 0.65 mm

Break through time: 240 min

Material tested: KCL 720 Camapren®

##### Body Protection

Flame retardant antistatic protective clothing.

##### Respiratory protection

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

## Control of environmental exposure

Do not let product enter drains. Risk of explosion.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

a) Appearance	Form: liquid Color: colorless
b) Odor	amine-like
c) Odor Threshold	No data available
d) pH	12.2 at 100 g/l at 20 °C
e) Melting point/freezing point	Melting point/range: 8.5 °C
f) Initial boiling point and boiling range	118 °C
g) Flash point	38 °C - closed cup - DIN 51755 Part 1
h) Evaporation rate	No data available
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	Upper explosion limit: 17 %(V) Lower explosion limit: 2 %(V)
k) Vapor pressure	12 hPa at 20 °C
l) Vapor density	2.07 - (Air = 1.0)
m) Density	0.899 g/mL at 25 °C
Relative density	No data available
n) Water solubility	1,000 g/l - miscible
o) Partition coefficient: n-octanol/water	log Pow: -2.04 - Bioaccumulation is not expected., (Lit.)
p) Autoignition temperature	405 °C - DIN 51794
q) Decomposition temperature	> 120 °C -
r) Viscosity	Viscosity, kinematic: No data available Viscosity, dynamic: 1.265 - 1.725 mPa.s at 25 °C
s) Explosive properties	No data available
t) Oxidizing properties	No data available

### 9.2 Other safety information

Relative vapor density	2.07 - (Air = 1.0)
------------------------	--------------------

---

## **SECTION 10: Stability and reactivity**

### **10.1 Reactivity**

Vapor/air-mixtures are explosive at intense warming.

### **10.2 Chemical stability**

The product is chemically stable under standard ambient conditions (room temperature) .  
Absorbs carbon dioxide (CO<sub>2</sub>) from air.

### **10.3 Possibility of hazardous reactions**

No data available

### **10.4 Conditions to avoid**

Air Exposure to moisture.  
Heating.

### **10.5 Incompatible materials**

Aluminum, Lead, magnesium, Zinc, zinc alloys, Copper, Copper alloys, Iron, brass, bronze

### **10.6 Hazardous decomposition products**

In the event of fire: see section 5

---

## **SECTION 11: Toxicological information**

### **11.1 Information on toxicological effects**

#### **Acute toxicity**

LD50 Oral - Rat - male and female - 866 mg/kg  
(OECD Test Guideline 401)

LC50 Inhalation - Rat - male - 4 h - 14.7 mg/l

Remarks: (ECHA)

LD50 Dermal - Rabbit - male - 560 mg/kg

Remarks: (ECHA)

#### **Skin corrosion/irritation**

Skin - Rabbit

Result: Corrosive - 15 min

Remarks: (ECHA)

Causes poorly healing wounds.

#### **Serious eye damage/eye irritation**

Eyes - Rabbit

Result: Corrosive

Remarks: (ECHA)

Causes serious eye damage.

#### **Respiratory or skin sensitization**

Maximization Test - Guinea pig

Result: positive

Remarks: (ECHA)

(Regulation (EC) No 1272/2008, Annex VI)

(Regulation (EC) No 1272/2008, Annex VI)

#### **Germ cell mutagenicity**

Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: positive

Test Type: In vitro mammalian cell gene mutation test  
Test system: Chinese hamster ovary cells  
Metabolic activation: with and without metabolic activation  
Result: negative  
Remarks: (ECHA)  
Test Type: sister chromatid exchange assay  
Test system: Chinese hamster ovary cells  
Metabolic activation: with and without metabolic activation  
Result: negative  
Remarks: (ECHA)  
Test Type: unscheduled DNA synthesis assay  
Test system: rat hepatocytes  
Metabolic activation: without metabolic activation  
Result: negative  
Remarks: (ECHA)  
Test Type: Mutagenicity (mammal cell test): chromosome aberration.  
Test system: Human lymphocytes  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 473  
Result: negative  
Remarks: (ECHA)

Test Type: dominant lethal test  
Species: Rat

Application Route: Oral

Result: negative  
Remarks: (ECHA)

**Carcinogenicity**

No data available

**Reproductive toxicity**

No data available

**Specific target organ toxicity - single exposure**

No data available

**Specific target organ toxicity - repeated exposure**

No data available

**Aspiration hazard**

No data available

**11.2 Additional Information**

Repeated dose toxicity - Mouse - male - Dermal - NOAEL (No observed adverse effect level)  
- 8.3 mg/kg  
Remarks: (ECHA)

Repeated dose toxicity - Rat - male and female - inhalation (vapor) - 6 Weeks - NOAEL (No observed adverse effect level) - 48 mg/kg - LOAEL (Lowest observed adverse effect level) - 107 mg/kg  
Remarks: (ECHA)



Repeated dose toxicity - Rat - male and female - Oral - 3 Months - NOAEL (No observed adverse effect level) - 22 mg/kg - LOAEL (Lowest observed adverse effect level) - 114 mg/kg

RTECS: KH8575000

Vomiting, Diarrhea, Abdominal pain

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Liver - Irregularities - Based on Human Evidence

---

## SECTION 12: Ecological information

### 12.1 Toxicity

Toxicity to fish	semi-static test LC50 - <i>Poecilia reticulata</i> (guppy) - 640 mg/l - 96 h (Directive 67/548/EEC, Annex V, C.1.)
Toxicity to daphnia and other aquatic invertebrates	static test EC50 - <i>Daphnia magna</i> (Water flea) - 16.7 mg/l - 48 h (Directive 67/548/EEC, Annex V, C.2.)
Toxicity to algae	static test ErC50 - <i>Pseudokirchneriella subcapitata</i> (algae) - 645 mg/l - 72 h (Directive 67/548/EEC, Annex V, C.3.)
Toxicity to bacteria	static test EC50 - Bacteria - 3.2 mg/l - 2 h Remarks: (ECHA)

### 12.2 Persistence and degradability

Biodegradability	aerobic - Exposure time 28 d Result: 95 % - Readily biodegradable. (Regulation (EC) No. 440/2008, Annex, C.4-E)
------------------	---

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

### 12.6 Other adverse effects

Avoid release to the environment.

---

## SECTION 13: Disposal information

### 13.1 Waste treatment methods

#### Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself. See [www.retrologistik.com](http://www.retrologistik.com) for processes regarding the return of chemicals and containers, or contact us there if you have further questions. According to Quality Environment Regulation (Scheduled Waste) 2005, waste need to be

sent to designated premise for recycle, treatment or disposal. Please contact Kualiti Alam for waste classification and correct disposal method.

---

## SECTION 14: Transportation information

### 14.1 UN number

ADR/RID: 1604

IMDG: 1604

IATA-DGR: 1604

### 14.2 UN proper shipping name

ADR/RID: ETHYLENEDIAMINE

IMDG: ETHYLENEDIAMINE

IATA-DGR: Ethylenediamine

### 14.3 Transport hazard class(es)

ADR/RID: 8 (3)

IMDG: 8 (3)

IATA-DGR: 8 (3)

### 14.4 Packaging group

ADR/RID: II

IMDG: II

IATA-DGR: II

### 14.5 Environmental hazards

ADR/RID: no

IMDG Marine pollutant: no

IATA-DGR: no

### 14.6 Special precautions for user

None

### 14.7 Incompatible materials

Aluminum, Lead, magnesium, Zinc, zinc alloys, Copper, Copper alloys, Iron, brass, bronze

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Notification status

**DSL:** All components of this product are on the Canadian DSL

**ENCS:** On the inventory, or in compliance with the inventory

**ISHL:** On the inventory, or in compliance with the inventory

**KECI:** On the inventory, or in compliance with the inventory

**NZIoC:** On the inventory, or in compliance with the inventory

**PICCS:** On the inventory, or in compliance with the inventory

---

## SECTION 16: Other information

### Full text of H-Statements referred to under sections 2 and 3.

H226 Flammable liquid and vapor.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

### Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of

the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See [www.sigma-aldrich.com](http://www.sigma-aldrich.com) and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact [mlsbranding@sial.com](mailto:mlsbranding@sial.com).