

SAFETY DATA SHEET

Version 6.7
Revision Date 21.01.2022
Print Date 11.06.2022

SECTION 1: Identification of the hazardous chemical and of the supplier

1.1 Product identifiers

Product name : Dichloromethane

Product Number : 270997
Brand : Sigma-Aldrich
CAS-No. : 75-09-2

1.2 Other means of identification

Methylene chloride
DCM

1.3 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : For R&D use only. Not for pharmaceutical, household or other uses.

1.4 Details of the supplier of the safety data sheet

Company : SIGMA-ALDRICH (M) SDN BHD
Level 3, Menara Sunway Annexe,
Jalan Lagoon Timur, Bandar Sunway,
46150 PETALING JAYA, SELANGOR
MALAYSIA

Telephone : +60 (603)03-563-53321
Fax : +60 (603)03-563-54116

1.5 Emergency telephone

Emergency Phone # : 1-800-815-308 (CHEMTREC) * + 62 0800
140 1253 (Customer Call Centre)

Section 2: Hazard identification

2.1 GHS Classification

Classification according to CLASS regulations 2013
Carcinogenicity (Category 2), H351
Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Labelling according to CLASS regulations 2013

Pictogram



Signal word : Warning

Hazard statement(s)
H336 : May cause drowsiness or dizziness.

H351	Suspected of causing cancer.
Precautionary statement(s)	
Prevention	
P201	Obtain special instructions before use.
P261	Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
P281	Use personal protective equipment as required.
Response	
P304 + P340 + P312	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
Storage	
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.

2.3 Other hazards - none

SECTION 3: Composition and information of the ingredients of the hazardous chemical

Substance / Mixture : Substance

3.1 Substances

Synonyms : Methylene chloride
DCM

Formula : CH₂Cl₂
Molecular weight : 84.93 g/mol
CAS-No. : 75-09-2
EC-No. : 200-838-9
Index-No. : 602-004-00-3

Hazardous ingredients

Component	Classification	Concentration
Dichloromethane		
	Carc. 2; H351 Concentration limits: 20 %: STOT SE 3, H336;	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Call in physician.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Consult a physician.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing media**

Water Foam Carbon dioxide (CO₂) Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Hydrogen chloride gas

Combustible.

Development of hazardous combustion gases or vapours possible in the event of fire.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent material (e.g. Chemisorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Tightly closed. Keep in a well-ventilated place. Keep locked up or in an area accessible only to qualified or authorized persons.

Heat sensitive. Handle and store under inert gas.

Storage class

Storage class (TRGS 510): 6.1D: Non-combustible, acute toxic Cat.3 / toxic hazardous materials or hazardous materials causing chronic effects

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls and personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
Dichloromethane	75-09-2	TWA	50 ppm	Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

Derived No Effect Level (DNEL)

Application Area	Routes of exposure	Health effect	Value
Workers	Inhalation	Acute systemic effects	706 mg/m ³
Workers	Inhalation	Long-term systemic effects	353 mg/m ³
Workers	Skin contact	Long-term systemic effects	4750mg/kg BW/d
Consumers	Ingestion	Long-term systemic effects	0.06mg/kg BW/d
Consumers	Inhalation	Long-term systemic effects	88.3 mg/m ³
Consumers	Skin contact	Long-term systemic effects	2395mg/kg BW/d
Consumers	Inhalation	Acute systemic effects	353 mg/m ³

Predicted No Effect Concentration (PNEC)

Compartment	Value
Soil	0.583 mg/kg
Sea water	0.194 mg/l
Fresh water	0.54 mg/l
Sea sediment	1.61 mg/kg

Fresh water sediment	4.47 mg/kg
Onsite sewage treatment plant	26 mg/l
Aquatic intermittent release	0.27 mg/l

8.2 Exposure controls

Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact

Material: Viton®

Minimum layer thickness: 0.7 mm

Break through time: 120 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Body Protection

protective clothing

Respiratory protection

required when vapours/aerosols are generated.

Control of environmental exposure

Do not let product enter drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- | | |
|--|----------------------------------|
| a) Appearance | Form: liquid
Color: colorless |
| b) Odor | ether-like |
| c) Odor Threshold | 250 ppm |
| d) pH | No data available |
| e) Melting point/freezing point | Melting point/range: -97 °C |
| f) Initial boiling point and boiling range | 39.8 - 40 °C |
| g) Flash point | - closed cup does not flash |
| h) Evaporation rate | 0.71 |
| i) Flammability (solid, gas) | No data available |

j) Upper/lower flammability or explosive limits	Upper explosion limit: 22 %(V) Lower explosion limit: 13 %(V)
k) Vapor pressure	584 hPa at 25 °C
l) Vapor density	2.93
m) Density	1.325 g/mL at 25 °C
Relative density	No data available
n) Water solubility	13.2 g/l at 25 °C
o) Partition coefficient: n-octanol/water	log Pow: 1.25 at 20 °C - Bioaccumulation is not expected.
p) Autoignition temperature	605 °C at 1,013 hPa - DIN 51794
q) Decomposition temperature	No data available
r) Viscosity	Viscosity, kinematic: No data available Viscosity, dynamic: 0.42 mPa.s at 25 °C
s) Explosive properties	No data available
t) Oxidizing properties	none

9.2 Other safety information

Relative vapor density	2.93
------------------------	------

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

Sensitivity to light

The product is chemically stable under standard ambient conditions (room temperature) .

Contains the following stabilizer(s):

2-methyl-2-butene (>0.005 - <0.015 %)

10.3 Possibility of hazardous reactions

Risk of explosion with:

Alkali metals

nitrogen oxides

nitrogen dioxide

Potassium

sodium azide

perchloric acid

Nitric acid

aluminium chloride

Amines

Oxygen

(as liquefied gas)

powdered aluminium

sodium

aromatic hydrocarbons

with
powdered aluminium
Exothermic reaction with:
Alkaline earth metals
Powdered metals
amides
alcoholates
nonmetallic oxides
potassium tert-butanolate
sodium amide
Lithium

10.4 Conditions to avoid

no information available

10.5 Incompatible materials

rubber, various plastics, Light metals, Metals, Mild steel

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male and female - > 2,000 mg/kg

(OECD Test Guideline 401)

LC50 Inhalation - Mouse - 4 h - 86 mg/l - vapor

Remarks: (ECHA)

Symptoms: Possible damages:, mucosal irritations

LD50 Dermal - Rat - male and female - > 2,000 mg/kg

(OECD Test Guideline 402)

Skin corrosion/irritation

Skin - Rabbit

Result: Irritations - 4 h

(OECD Test Guideline 404)

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Eye irritation

Remarks: (ECHA)

Risk of corneal clouding.

Respiratory or skin sensitization

Local lymph node assay (LLNA) - Mouse

Result: negative

(OECD Test Guideline 429)

Germ cell mutagenicity

Test Type: Mutagenicity (mammal cell test): chromosome aberration.

Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473
Result: positive
Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: positive

Test Type: In vivo micronucleus test
Species: Mouse
Cell type: Bone marrow
Application Route: Oral
Method: OECD Test Guideline 474
Result: negative

Carcinogenicity

Limited evidence of carcinogenicity in animal studies
Suspected human carcinogens

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

Inhalation - May cause drowsiness or dizziness. - Central nervous system

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

Repeated dose toxicity - Rat - male and female - Oral - 104 Weeks - NOAEL (No observed adverse effect level) - 6 mg/kg

Repeated dose toxicity - Rat - male and female - Inhalation - 104 Weeks

RTECS: PA8050000

Dizziness, Nausea, Vomiting, narcosis, Cough, irritant effects, Unconsciousness, Shortness of breath, respiratory paralysis, somnolence, depressed respiration, CNS disorders, inebriation

Risk of corneal clouding.

The following applies to aliphatic halogenated hydrocarbons in general: systemic effect: narcosis, cardiovascular disorders. Toxic effect on liver, kidneys.

Dichloromethane is metabolized in the body producing carbon monoxide which increases and sustains carboxyhemoglobin levels in the blood, reducing the oxygen-carrying capacity of the blood.

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish	flow-through test LC50 - Pimephales promelas (fathead minnow) - 193.00 mg/l - 96 h
------------------	--

Remarks: (ECHA)

Toxicity to daphnia and other aquatic invertebrates	static test LC50 - Daphnia magna (Water flea) - 27 mg/l - 48 h (US-EPA)
Toxicity to bacteria	static test EC50 - activated sludge - 2,590 mg/l - 40 min (OECD Test Guideline 209)

12.2 Persistence and degradability

Biodegradability	aerobic - Exposure time 28 d Result: 68 % - Readily biodegradable. (OECD Test Guideline 301D)
------------------	---

12.3 Bioaccumulative potential

Bioaccumulation	Cyprinus carpio (Carp) - 6 Weeks - 250 µg/l(Dichloromethane) Bioconcentration factor (BCF): 2 - 5.4 (OECD Test Guideline 305) Cyprinus carpio (Carp) - 6 Weeks - 25 µg/l(Dichloromethane) Bioconcentration factor (BCF): 6 - 40 (OECD Test Guideline 305)
-----------------	--

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

No data available

SECTION 13: Disposal information

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself. See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions. According to Quality Environment Regulation (Scheduled Waste) 2005, waste need to be sent to designated premise for recycle, treatment or disposal. Please contact Kualiti Alam for waste classification and correct disposal method.

SECTION 14: Transportation information

14.1 UN number

ADR/RID: 1593

IMDG: 1593

IATA-DGR: 1593

14.2 UN proper shipping name

ADR/RID: DICHLOROMETHANE

IMDG: DICHLOROMETHANE

IATA-DGR: Dichloromethane

14.3 Transport hazard class(es)

ADR/RID: 6.1

IMDG: 6.1

IATA-DGR: 6.1

14.4 Packaging group

ADR/RID: III

IMDG: III

IATA-DGR: III

14.5 Environmental hazards

ADR/RID: no

IMDG Marine pollutant: no

IATA-DGR: no

14.6 Special precautions for user

None

14.7 Incompatible materials

rubber, various plastics, Light metals, Metals, Mild steel

Other regulations

Hazchem Code : 2Z

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****Notification status****DSL:** All components of this product are on the Canadian DSL**ENCS:** On the inventory, or in compliance with the inventory**ISHL:** On the inventory, or in compliance with the inventory**KECI:** On the inventory, or in compliance with the inventory**NZIoC:** Not in compliance with the inventory**PICCS:** On the inventory, or in compliance with the inventory

SECTION 16: Other information**Full text of H-Statements referred to under sections 2 and 3.**

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.