

Experiment No : 4

AIM

Familiarization of LINUX Commands.

CO2

Perform system administration task.

Procedure

1. read
command to accept single line of input

\$ read

Output

```
vboxuser@ubuntu: ~/sample1
vboxuser@ubuntu:~/sample1$ read
hello world
vboxuser@ubuntu:~/sample1$ echo $REPLY
hello world
vboxuser@ubuntu:~/sample1$
```

- 1.1) read [variable names]
to read contents of a line into variables.

\$ read v1 v2 v3

Output

```
vboxuser@ubuntu: ~/sample1
vboxuser@ubuntu:~/sample1$ read v1 v2 v3
hi hello world
vboxuser@ubuntu:~/sample1$ echo "$v1[$v2][$v3]"
[hi][hello][world]
vboxuser@ubuntu:~/sample1$
```

- 1.2) read -p [user command prompt]
to prompt user to enter values.

\$ read -p "Enter your name"

Output

```
dell@dell-VirtualBox:~$ read -p "enter your name"
enter your name sisira
dell@dell-VirtualBox:~$ echo my name is $REPLY
my name is sisira
dell@dell-VirtualBox:~$
```

1.3) read -n [specified character limit] [user command prompt]

to prompt the user to enter values and is restricted to the character limit specified by user.

\$ read -n 5 "Enter 5 characters only "

Output

```
vboxuser@ubuntu: ~/sample1
vboxuser@ubuntu:~/sample1$ read -n 5 -p "Enter 5 characters only "
Enter 5 characters only hellovboxuser@ubuntu:~/sample1$
```

1.4) read -s -p [user command prompt]

to prompt user to enter values which is secured and invisible to the user.

\$ read -s -p "Enter your password "

Output


```
vboxuser@ubuntu: ~/sample1
vboxuser@ubuntu:~/sample1$ read -s -p "Enter your password "
Enter your password vboxuser@ubuntu:~/sample1$
```

2. echo

to display the contents read by '\$ read' command.

```
$ echo $REPLY
```

Output




```
vboxuser@ubuntu: ~/sample1
vboxuser@ubuntu:~/sample1$ read
hello world
vboxuser@ubuntu:~/sample1$ echo $REPLY
hello world
vboxuser@ubuntu:~/sample1$
```

2.1) echo [variable names]

to print the values read by 'read' command.

```
$ echo "$v1[$v2][$v3]"
```

Output




```
vboxuser@ubuntu: ~/sample1
vboxuser@ubuntu:~/sample1$ read v1 v2 v3
hi hello world
vboxuser@ubuntu:~/sample1$ echo "$v1[$v2][$v3]"
[hi][hello][world]
vboxuser@ubuntu:~/sample1$
```

3) wc [filename]

To display number of lines, number of words, number of bytes and filename.

```
$wc file.txt
```

Output




```
vboxuser@ubuntu: ~
vboxuser@ubuntu:~$ cat file.txt
hi hello
welcome to ubuntu
ubuntu is a distribution of LINUX OS
vboxuser@ubuntu:~$ wc file.txt
 3 12 64 file.txt
vboxuser@ubuntu:~$
```

3.1) `wc -l [filename]`

Displays the number of lines.

`$wc -l file.txt`


OutputA terminal window with a dark background. The prompt is 'vboxuser@ubuntu: ~'. The command 'vboxuser@ubuntu:~\$ wc -l file.txt' is entered. The output is '3 file.txt'. The prompt 'vboxuser@ubuntu:~\$' is shown again.

```
vboxuser@ubuntu: ~  
vboxuser@ubuntu:~$ wc -l file.txt  
3 file.txt  
vboxuser@ubuntu:~$
```

3.2) `wc -m [filename]`

Displays the number of characters/bytes.

`$wc -m file.txt`


OutputA terminal window with a dark background. The prompt is 'vboxuser@ubuntu: ~'. The command 'vboxuser@ubuntu:~\$ wc -m file.txt' is entered. The output is '64 file.txt'. The prompt 'vboxuser@ubuntu:~\$' is shown again.

```
vboxuser@ubuntu: ~  
vboxuser@ubuntu:~$ wc -m file.txt  
64 file.txt  
vboxuser@ubuntu:~$
```

3.3) `wc -w [filename]`

Displays the number of words.

`$wc -w file.txt`


OutputA terminal window with a dark background. The prompt is 'vboxuser@ubuntu: ~'. The command 'vboxuser@ubuntu:~\$ wc -w file.txt' is entered. The output is '12 file.txt'. The prompt 'vboxuser@ubuntu:~\$' is shown again.

```
vboxuser@ubuntu: ~  
vboxuser@ubuntu:~$ wc -w file.txt  
12 file.txt  
vboxuser@ubuntu:~$
```

3.4) `wc -L [filename]`

Displays the length of longest word.

Output




```
vboxuser@ubuntu: ~  
vboxuser@ubuntu:~$ wc -L file.txt  
36 file.txt  
vboxuser@ubuntu:~$
```

4) more [filename]

The more command is similar to cat to display the content. The only difference is that in case of large files, cat command output will scroll off your screen while more command display output one output screen at a time.

\$ more samplefile.txt

Output



```
vboxuser@ubuntu: ~  
^Z  
[1]+  Stopped                  cat > samplefile.txt  
vboxuser@ubuntu:~$ more samplefile.txt  
A computer is a machine that can be programmed to carry out sequences of arithmetic or logical operations (computation) automatically. Modern digital electronic computers can perform generic sets of operations known as programs. These programs enable computers to perform a wide range of tasks. A computer system is a nominally complete computer that includes the hardware, operating system (main software), and peripheral equipment needed and used for full operation. This term may also refer to a group of computers that are linked and function together, such as a computer network or computer cluster.  
  
A broad range of industrial and consumer products use computers as control systems. Simple special-purpose devices like microwave ovens and remote controls are included, as are factory devices like industrial robots and computer-aided design, as well as general-purpose devices like personal computers and mobile devices like smartphones. Computers power the Internet, which links billions of other computers and users.  
  
Early computers were meant to be used only for calculations. Simple manual instruments like the abacus have aided people in doing calculations since ancient times. Early in the Industrial Revolution, some mechanical devices were built to automate long, tedious tasks, such as guiding patterns for looms. More sophisticated electrical machines did specialized analog calculations in the early 20th cen
```

```
Early computers were meant to be used only for calculations. Simple manual instruments like the abacus have aided people in doing calculations since ancient times. Early in the Industrial Revolution, some mechanical devices were built to automate long, tedious tasks, such as guiding patterns for looms. More sophisticated electrical machines did specialized analog calculations in the early 20th century. The first digital electronic calculating machines were developed during World War II. The first semiconductor transistors in the late 1940s were followed
--More--(56%)
```

4.1) more +[specified number of lines] [filename]

To display the contents of file after specified number of lines.

\$ more +5 samplefile.txt

Output

```
vboxuser@ubuntu:~$ more +5 samplefile.txt
Early computers were meant to be used only for calculations. Simple manual instruments like the abacus have aided people in doing calculations since ancient times. Early in the Industrial Revolution, some mechanical devices were built to automate long, tedious tasks, such as guiding patterns for looms. More sophisticated electrical machines did specialized analog calculations in the early 20th century. The first digital electronic calculating machines were developed during World War II. The first semiconductor transistors in the late 1940s were followed by the silicon-based MOSFET (MOS transistor) and monolithic integrated circuit chip technologies in the late 1950s, leading to the microprocessor and the microcomputer revolution in the 1970s. The speed, power and versatility of computers have been increasing dramatically ever since then, with transistor counts increasing at a rapid pace (as predicted by Moore's law), leading to the Digital Revolution during the late 20th to early 21st centuries.
```

```
Conventionally, a modern computer consists of at least one processing element, typically a central processing unit (CPU) in the form of a microprocessor, along with some type of computer memory, typically semiconductor memory chips. The processing element carries out arithmetic and logical operations, and a sequencing and control unit can change the order of operations in response to stored information. Peripheral devices include input devices (keyboards, mice, joystick, etc.), output devices (monitor screens, printers, etc.), and input/output devices that
```


```
Conventionally, a modern computer consists of at least one processing element, typically a central processing unit (CPU) in the form of a microprocessor, along with some type of computer memory, typically semiconductor memory chips. The processing element carries out arithmetic and logical operations, and a sequencing and control unit can change the order of operations in response to stored information. Peripheral devices include input devices (keyboards, mice, joystick, etc.), output devices (monitor screens, printers, etc.), and input/output devices that perform both functions (e.g., the 2000s-era touchscreen). Peripheral devices allow information to be retrieved from an external source and they enable the re
--More--(98%)
```

4.2) more +/[pattern] [filename]

This option is used to search the string inside your text document. You can view all the instances by navigating through the results.

\$ more +/computer samplefile.txt

Output



```
vboxuser@ubuntu: ~  
vboxuser@ubuntu:~$ more +/user samplefile.txt  
...skipping  
A broad range of industrial and consumer products use computers as control systems. Simple special-purpose devices like microwave ovens and remote controls are included, as are factory devices like industrial robots and computer-aided design, as well as general-purpose devices like personal computers and mobile devices like smartphones. Computers power the Internet, which links billions of other computers and users.  
  
Early computers were meant to be used only for calculations. Simple manual instruments like the abacus have aided people in doing calculations since ancient times. Early in the Industrial Revolution, some mechanical devices were built to automate long, tedious tasks, such as guiding patterns for looms. More sophisticated electrical machines did specialized analog calculations in the early 20th century. The first digital electronic calculating machines were developed during World War II. The first semiconductor transistors in the late 1940s were followed by the silicon-based MOSFET (MOS transistor) and monolithic integrated circuit chip technologies in the late 1950s, leading to the microprocessor and the microcomputer revolution in the 1970s. The speed, power and versatility of computers have been increasing dramatically ever since then, with transistor counts increasing at a rapid pace (as predicted by Moore's law), leading to the Digital Revolution during the late 20th to early 21st centuries.  
  
Conventionally, a modern computer consists of at least one processing element, t  
--More-- (75%)
```

4.3) more -d [filename]

To help users to navigate through file according to the instruction. Displays “space to continue, 'q' to quit”.

\$more -d samplefile.txt

Output

```
vboxuser@ubuntu:~$ more -d samplefile.txt
A computer is a machine that can be programmed to carry out sequences of arithmetic or logical operations (computation) automatically. Modern digital electronic computers can perform generic sets of operations known as programs. These programs enable computers to perform a wide range of tasks. A computer system is a nominally complete computer that includes the hardware, operating system (main software), and peripheral equipment needed and used for full operation. This term may also refer to a group of computers that are linked and function together, such as a computer network or computer cluster.

A broad range of industrial and consumer products use computers as control systems. Simple special-purpose devices like microwave ovens and remote controls are included, as are factory devices like industrial robots and computer-aided design, as well as general-purpose devices like personal computers and mobile devices like smartphones. Computers power the Internet, which links billions of other computers and users.

Early computers were meant to be used only for calculations. Simple manual instruments like the abacus have aided people in doing calculations since ancient times. Early in the Industrial Revolution, some mechanical devices were built to automate long, tedious tasks, such as guiding patterns for looms. More sophisticated electrical machines did specialized analog calculations in the early 20th century. The first digital electronic calculating machines were developed during World War II. The first semiconductor transistors in the late 1940s were followed

--More--(56%)[Press space to continue, 'q' to quit.]
```

Result

The program has been executed and output has been verified.