

Battle.net OAuth APIs

Battle.net provides APIs for OAuth 2.0 authentication flows.

- *User Authentication* describes the authentication code flow, which allows applications to authenticate a user and perform API requests on their behalf.
- *Server Authentication* describes the client credentials flow, which allows applications to authenticate with Blizzard's servers and perform requests as a client application.

See [Using OAuth](#) for detailed information about making requests, including host names.

Hosts

For all regions except China, the API request paths follow the format `oauth.battle.net/{API path}` for OAuth requests. In China, the API request path follows the format `oauth.battlenet.com.cn/{API path}` . For more information about regions, see [Regionality and APIs](#).

APIs

Battle.net provides the following APIs for authentication. For more information about using the APIs, see [Getting Started](#).

User Authentication

[Collapse All](#)

GET

Authorization Request
`/authorize`



The authorization request is the first part of the authorization code flow, OAuth's authentication flow for performing API requests on behalf of a user. Applications can also ask for special access to user-specific data by specifying one or more "scopes."

Parameter	Type	Example Value	Description
:region	string <i>REQUIRED</i>	us	The region of the data to retrieve.
response_type	string <i>REQUIRED</i>	code	Specifies the type of authorization request being made. For an authorization code, grant this value must be <code>code</code> .
client_id	string <i>REQUIRED</i>		A string identifying the client application making this request. Labeled in API Access for an individual application as "Client ID".
redirect_uri	string <i>REQUIRED</i>	http://example.com/oauth	The callback URL registered for an application. This value must match one of the URLs specified for the application in API Access or the request will return an error.
scope	string	wow.profile sc2.profile	A space-delimited, case-sensitive list of scopes to which to request access. The user may not grant access to any or all requested scopes. See Using OAuth for a list of valid scopes.
state	string		An opaque value supplied by the client to maintain state between the request and callback. The authorization server includes this value when redirecting the user-agent back to the client. The parameter should be used for preventing cross-site request forgery.

POST

Access Token Request
`/token`



The access token request is the second part of the authorization code flow. When the first part completes, the user's browser is redirected to an application's `redirect_uri` . This redirect URI also includes an access code and (optionally) a state parameter. This request allows the application to exchange the access code for an access token to can use in subsequent API requests.

Parameter	Type	Example Value	Description
:region	string <i>REQUIRED</i>	us	The region of the data to retrieve.
grant_type	string <i>REQUIRED</i>	authorization_code	Identifies the type of authorization request being made. For a client credentials grant this value <i>must</i> be <code>authorization_code</code> .
code	string <i>REQUIRED</i>	{code}	The authorization code received from the authorization server.
redirect_uri	string <i>REQUIRED</i>	https://example.com/oauth	Must be identical to the <code>redirect_uri</code> value used in the authorization request.
client_id	string <i>REQUIRED</i>	{client_id}	A string identifying the client application making this request. Labeled in API Access for an individual application as "Client ID".

GET

User Info (header)
/userinfo

^

Returns basic information about the user associated with the current bearer token.

Parameter	Type	Example Value	Description
:region	string <i>REQUIRED</i>	us	The region of the data to retrieve.
Authorization	string <i>REQUIRED</i>	Bearer {token}	The user's bearer token. The OAuth 2.0 spec requires the Authorization header be formatted as "Bearer {token}", where {token} is the alpha-numeric authorization token returned by a previous OAuth grant flow.

GET

User Info (param)
/userinfo

^

This request is the same as **User Info (header)** but uses a search parameter in the URL rather than an HTTP header. While HTTPS encrypts traffic between the requester and Blizzard's servers at the TCP/IP layer, search parameters are inherently less secure than HTTP headers because they can be logged, copy-pasted, and otherwise easily accessed. As such, we strongly encourage users to put bearer tokens in headers.

Parameter	Type	Example Value	Description
:region	string <i>REQUIRED</i>	us	The region of the data to retrieve.
access_token	string <i>REQUIRED</i>	{token}	The user's bearer token.

Application Authentication

Collapse All

POST

Access Token Request
/token

^

This is the only request necessary for the [client credential flow](#), OAuth's authentication flow intended for application servers.

Parameter	Type	Example Value	Description
:region	string <i>REQUIRED</i>	us	The region of the data to retrieve.
grant_type	string <i>REQUIRED</i>	client_credentials	Identifies the type of authorization request being made. For a client credentials grant this value <i>must</i> be <code>client_credentials</code> .
scope	string		A space-delimited, case-sensitive list of scopes that to which to request access. The user may not grant access to any or all requested scopes. See Using OAuth for a list of valid scopes.

Token Validation

Collapse All

POST

Token Validation (POST)
/check_token

^

Verifies that a given bearer token is valid and retrieves metadata about the token, including the **client_id** used to create the token, expiration timestamp, and scopes granted to the token. We strongly recommend that developers use the more secure **POST /check_token** method.

Parameter	Type	Example Value	Description
:region	string <i>REQUIRED</i>	us	The region of the data to retrieve.
token	string <i>REQUIRED</i>	{token}	The user's bearer token.

GET

Token Validation (GET)
/check_token

^

Verifies that a given bearer token is valid and retrieves metadata about the token, including the **client_id** used to create the token, expiration timestamp, and scopes granted to the token. We strongly recommend that developers use the more secure **POST /check_token** method.

Parameter	Type	Example Value	Description
:region	string <i>REQUIRED</i>	us	The region of the data to retrieve.
token	string <i>REQUIRED</i>	{token}	The user's bearer token.



©2026 Blizzard Entertainment, Inc.
All trademarks referenced herein are the properties of their respective owners.
Do not sell or share my personal information

[Privacy](#) [Legal](#) [Terms](#) [Cookie Policy](#) [Cookie Settings](#)

