

Moving around

Login to Pelle

There are several ways to log in to *Pelle*. Similar to *Futurum*, you can use `ssh` or *ThinLinc* client. However, specially, you can use a remote desktop via website to log in UPPMAX.

No matter which method you choose, you need to set up **two factor authentication (2FA)** to use UPPMAX.

Setting up TOTP

The purpose of 2FA is to get a **Time-based One-Time Password**, or **TOTP** for short. TOTP expires every 30 seconds, and it is not sent by email. You need an application for generating such a code.

Request Uppmax Second Factor

SSH key

Using SSH keys is considered a more secure method for connection generally, as long as you can keep your keys safe. Specifically for UPPMAX, you can skip entering password and TOTP by using your SSH key.

Warning

The key generation processes below should be processed **on the client**, which in this case, is **your own computer**. Even the server should **NOT** have your private key.

Creating the key

The default options for `ssh-keygen` should be enough for normal users. However, it is recommended to use Ed25519 for generating keys, as the command below, unless you have a super old computer. I personally suggest setting a different filename for distinguish, and set a passphrase for unlock the key.

```
$ ssh-keygen -t ed25519 -C "<Comment on the key>"
```

```
ssh-keygen -t ed25519
Generating public/private ed25519 key pair.
Enter file in which to save the key (/home/kunihiro/.ssh/id_ed25519): test_ed25519
Enter passphrase for "test_ed25519" (empty for no passphrase):
Enter same passphrase again:
Your identification has been saved in test_ed25519
Your public key has been saved in test_ed25519.pub
The key fingerprint is:
SHA256:e2p6uT205VY8fh07w/Am7U06h0v2b+yIyv9nPGL02qc kunihiro@fedora-x1c
The key's randomart image is:
+--[ED25519 256]--+
|
|      S      .
|      .. .. +O
|      .o.+ =O++
|      +=o  BBo#O
|      .+o.***E600
+-----[SHA256]-----+
```

Figure 1: Generating a key located in `./test_ed25519`

`ssh-keygen` will generate two files for you: one ends with `.pub` is the **public key** and another one is the **private key**. Figure 1 here is only for demonstration, and the key had been revoked after finishing the instruction, but for you, **DO NOT LEAK YOUR PRIVATE KEY**.

Upload the key

We need to upload the public key to UPPMAX. The easiest way is to use `ssh-copy-id`. Replace `<PATH_OF_PUB_KEY>` to the actual path of your public key.

```
$ ssh-copy-id -i <PATH_OF_PUB_KEY> <USERNAME>@pelle.uppmax.uu.se
```

For Windows, there is no `ssh-copy-id`, so one has to use a slightly weird method: read the contents of the public key, and pipe it to `ssh` to send it to server.

```
PS> cat <PUB_KEY> | ssh <USERNAME>@pelle.uppmass.uu.se "mkdir -p .ssh && tee .ssh/authorized_keys"
```

This command should work for Windows 10 and newer versions.

```

~ 01:22:23
ls test*
test_ed25519  test_ed25519.pub

~ 01:22:28
ssh-copy-id -i test_ed25519.pub yifanh@pelle.uppmx.uu.se
/usr/bin/ssh-copy-id: INFO: Source of key(s) to be installed: "test_ed25519.pub"
/usr/bin/ssh-copy-id: INFO: attempting to log in with the new key(s), to filter out any that are already
installed
/usr/bin/ssh-copy-id: INFO: 1 key(s) remain to be installed -- if you are prompted now it is to install t
he new keys
(yifanh@pelle.uppmx.uu.se) Password:
(yifanh@pelle.uppmx.uu.se) Second factor (TOTP UPPMAX):

Number of key(s) added: 1

Now try logging into the machine, with: "ssh -i ./test_ed25519 'yifanh@pelle.uppmx.uu.se'"
and check to make sure that only the key(s) you wanted were added.

```

Figure 2: Uploading the key to UPPMAX

Login with key

Now you can log in to UPPMAX by specifying your private key. Replace `<PATH_OF_PRIV_KEY>` and `<USERNAME>` to your private key path and your username for login.

```
$ ssh -i <PATH_OF_PRIV_KEY> <USERNAME>@pelle.uppmass.uu.se
```

As Figure 3, will be prompted to input the passphrase of the key, but not the password and TOTP for UPPMAX.

[illegible]

Figure 3: Using the key to log in UPPMAX

SSH config

By adding the key to config file located in `.ssh/config`, one can login with the provided key by default.

```
Host *.uppmax.uu.se
IdentityFile <PATH_OF_KEY>
```

```
cat .ssh/config
Host github.com
  HostName github.com
  User git
  IdentityFile ~/.ssh/github_ed25519

Host *.uppmax.uu.se
  IdentityFile ~/.ssh/uppmax_ed25519

ssh yifanh@pelle.uppmax.uu.se

UPPMAX | System: pelle1
#####
User Guides: https://docs.uppmax.uu.se/
Write to support@uppmax.uu.se, if you have questions or comments.
Last login: Wed Apr 22 01:08:02 2026 from 185.205.50.82
yifanh@pelle1:~$
```

Figure 4: SSH config example

Projects on UPPMAX

Projects

Active Projects You Belong To

Click on the project name in the leftmost column to see more project information.

Project	PI	Project Title	Project Type	Centre	Start Date	End Date	Your Role
UPPMAX 2026/1-95	Sara Stymne	Computational Linguistics @ UU	Centre Local	UPPMAX	2026-04-01	2027-04-01	member
UPPMAX 2026/1-123	Meriem Beloucif	5LN711 & 5LN718: Machine Translation x 2	Centre Local	UPPMAX	2026-04-08	2027-01-01	member
UPPMAX 2025/2-505	Eva Pettersson	5LN709 Master's Thesis in Langua	Centre Local Compute	UPPMAX	2026-01-01	2026-12-01	member
UPPMAX 2025/3-5	Sara Stymne	5LN71X - Masterprogram i språkteknologi	Centre Local Compute	UPPMAX	2025-03-25	2026-05-01	member

Request Membership in Project

To request membership in a project, use the search function below to search for the project. You may use project name/Dnr, project title or the name of the principal investigator.

Past Project You Belonged To

Click on the project name in the leftmost column to see more project information.

Project	PI	Project Title	Project Type	Centre	Start Date	End Date	Your Role
UPPMAX 2020/2-2	Joakim Nivre	CL@UU	Centre Local Compute	UPPMAX	2020-03-27	2026-02-01	member

Figure 5: Projects page of SUPR