

Experiment No.4:

Student Database Management

You are developing a student result management system. The database should support updating records, adding new entries, searching for specific students, and sorting based on performance. Using an array of structures, implement a student database with attributes: roll no, name, program, course, subject marks, total, and average. Support operations: display, search, and sort. (Students can additionally perform modify, append.)

```
#include <stdio.h>
```

```
#include <string.h>
```

```
#define MAX 100
```

```
struct Student {
```

```
    int roll_no;
```

```
    char name[50];
```

```
    char program[30];
```

```
    char course[30];
```

```
    int marks[3];
```

```
    int total;
```

```
    float average;
```

```
};
```

```
struct Student students[MAX];
```

```
int count = 0;
```

```
// Function to add new student
```

```
void addStudent() {
```

```
    if(count >= MAX) {
```



```
printf("Database full!\n");

return;
}

printf("\nEnter details for student %d:\n", count + 1);

printf("Roll No: ");

scanf("%d", &students[count].roll_no);

printf("Name: ");

scanf(" %[^\\n]", students[count].name); // to read full name with spaces

printf("Program: ");

scanf(" %[^\\n]", students[count].program);

printf("Course: ");

scanf(" %[^\\n]", students[count].course);

printf("Enter marks for 3 subjects:\n");

students[count].total = 0;

for(int i = 0; i < 3; i++) {

    printf("Subject %d: ", i + 1);

    scanf("%d", &students[count].marks[i]);

    students[count].total += students[count].marks[i];

}

students[count].average = students[count].total / 3.0;

count++;
```



```
    printf("Student added successfully!\n");  
}
```

```
// Function to display all students
```

```
void displayStudents() {  
    if(count == 0) {  
        printf("No student records to display.\n");  
        return;  
    }  
}
```

```
printf("\nStudent Records:\n");  
for(int i = 0; i < count; i++) {  
    printf("\nRoll No: %d\n", students[i].roll_no);  
    printf("Name: %s\n", students[i].name);  
    printf("Program: %s\n", students[i].program);  
    printf("Course: %s\n", students[i].course);  
    printf("Marks: %d, %d, %d\n", students[i].marks[0], students[i].marks[1], students[i].marks[2]);  
    printf("Total: %d\n", students[i].total);  
    printf("Average: %.2f\n", students[i].average);  
}  
}
```

```
// Function to search student by roll number
```

```
void searchStudent() {  
    int roll, found = 0;  
    printf("Enter roll number to search: ");  
    scanf("%d", &roll);
```



```
for(int i = 0; i < count; i++) {  
    if(students[i].roll_no == roll) {  
        printf("\nStudent Found:\n");  
        printf("Name: %s\n", students[i].name);  
        printf("Program: %s\n", students[i].program);  
        printf("Course: %s\n", students[i].course);  
        printf("Total: %d, Average: %.2f\n", students[i].total, students[i].average);  
        found = 1;  
        break;  
    }  
}  
  
if(!found) {  
    printf("Student with roll number %d not found.\n", roll);  
}  
}
```

// Function to modify a student record

```
void modifyStudent() {  
    int roll, found = 0;  
    printf("Enter roll number to modify: ");  
    scanf("%d", &roll);  
  
    for(int i = 0; i < count; i++) {  
        if(students[i].roll_no == roll) {  
            printf("Enter new name: ");
```



```
scanf("%s", students[i].name);

printf("Enter new program: ");
scanf("%s", students[i].program);

printf("Enter new course: ");
scanf("%s", students[i].course);

printf("Enter new marks for 3 subjects:\n");
students[i].total = 0;
for(int j = 0; j < 3; j++) {
    printf("Subject %d: ", j + 1);
    scanf("%d", &students[i].marks[j]);
    students[i].total += students[i].marks[j];
}

students[i].average = students[i].total / 3.0;
printf("Record updated successfully.\n");
found = 1;
break;
}
}

if(!found) {
    printf("Student with roll number %d not found.\n", roll);
}
}
```



```
// Function to sort students by total marks

void sortStudentsByTotal() {

    struct Student temp;

    for(int i = 0; i < count - 1; i++) {

        for(int j = i + 1; j < count; j++) {

            if(students[i].total < students[j].total) {

                temp = students[i];

                students[i] = students[j];

                students[j] = temp;

            }

        }

    }

    printf("Students sorted by total marks (highest first).\n");

}
```

```
int main() {

    int choice;

    do {

        printf("\nStudent Database Menu:\n");

        printf("1. Add Student\n");

        printf("2. Display All Students\n");

        printf("3. Search Student by Roll No\n");

        printf("4. Modify Student Record\n");

        printf("5. Sort Students by Total Marks\n");

        printf("6. Exit\n");

    }
```



```
printf("Enter choice: ");  
  
scanf("%d", &choice);  
  
switch(choice) {  
    case 1: addStudent(); break;  
    case 2: displayStudents(); break;  
    case 3: searchStudent(); break;  
    case 4: modifyStudent(); break;  
    case 5: sortStudentsByTotal(); break;  
    case 6: printf("Exiting program.\n"); break;  
    default: printf("Invalid choice. Try again.\n");  
}  
  
} while(choice != 6);  
  
return 0;  
}
```