

 MINGW64:/c/Users/LENOVO/git-repo

```
LENOVO@DESKTOP-S97V08Q MINGW64 ~  
$ mkdir git-repo
```

```
LENOVO@DESKTOP-S97V08Q MINGW64 ~  
$ cd git-repo
```

```
LENOVO@DESKTOP-S97V08Q MINGW64 ~/git-repo  
$ git init  
Initialized empty Git repository in C:/Users/LENOVO/git-repo/.git/
```

```
LENOVO@DESKTOP-S97V08Q MINGW64 ~/git-repo (master)  
$ vim repo1
```

```
LENOVO@DESKTOP-S97V08Q MINGW64 ~/git-repo (master)  
$ git add repo1  
warning: in the working copy of 'repo1', LF will be replaced by CRLF the next time Git touches it
```

```
LENOVO@DESKTOP-S97V08Q MINGW64 ~/git-repo (master)  
$ git status  
On branch master
```

No commits yet

```
Changes to be committed:  
  (use "git rm --cached <file>..." to unstage)  
    new file:   repo1
```

```
LENOVO@DESKTOP-S97V08Q MINGW64 ~/git-repo (master)  
$ git commit -m "this is repo v1"  
[master (root-commit) 906102f] this is repo v1  
 1 file changed, 3 insertions(+)  
 create mode 100644 repo1
```

```
LENOVO@DESKTOP-S97V08Q MINGW64 ~/git-repo (master)  
$ git reote add origin https://github.com/Prem-pj/repo1.git  
git: 'reote' is not a git command. See 'git --help'.
```

The most similar command is
 remote

```
LENOVO@DESKTOP-S97V08Q MINGW64 ~/git-repo (master)  
$ git remote -v
```

```
LENOVO@DESKTOP-S97V08Q MINGW64 ~/git-repo (master)  
$ git remote add origin https://github.com/Prem-pj/repo1.git
```

MINGW64:/c/Users/LENOVO/git-repo

LENOVO@DESKTOP-S97V08Q MINGW64 ~/git-repo (master)

\$ git remote -v

origin https://github.com/Prem-pj/repo1.git (fetch)

origin https://github.com/Prem-pj/repo1.git (push)

LENOVO@DESKTOP-S97V08Q MINGW64 ~/git-repo (master)

\$ git push origin master

Enumerating objects: 3, done.

Counting objects: 100% (3/3), done.

Delta compression using up to 8 threads

Compressing objects: 100% (2/2), done.

Writing objects: 100% (3/3), 263 bytes | 87.00 KiB/s, done.

Total 3 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)

To https://github.com/Prem-pj/repo1.git

* [new branch] master -> master

LENOVO@DESKTOP-S97V08Q MINGW64 ~/git-repo (master)

\$ vim repo2

LENOVO@DESKTOP-S97V08Q MINGW64 ~/git-repo (master)

\$ git add repo2

warning: in the working copy of 'repo2', LF will be replaced by CRLF the next time Git touches it

LENOVO@DESKTOP-S97V08Q MINGW64 ~/git-repo (master)

\$ git status

On branch master

Changes to be committed:

(use "git restore --staged <file>..." to unstage)

new file: repo2

LENOVO@DESKTOP-S97V08Q MINGW64 ~/git-repo (master)

\$ git commit -m "this is repo2 v1"

[master 686009b] this is repo2 v1

1 file changed, 2 insertions(+)

create mode 100644 repo2

LENOVO@DESKTOP-S97V08Q MINGW64 ~/git-repo (master)

\$ git push origin master

Enumerating objects: 4, done.

Counting objects: 100% (4/4), done.

Delta compression using up to 8 threads

Compressing objects: 100% (3/3), done.

Writing objects: 100% (3/3), 319 bytes | 79.00 KiB/s, done.

Total 3 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)

To https://github.com/Prem-pj/repo1.git

906102f..686009b master -> master

LENOVO@DESKTOP-S97V08Q MINGW64 ~/git-repo (master)