

```
BookRepository.java x
1 package repository;
2
3 public class BookRepository { 4 usages new *
4     public void getAllBooks() { 1 usage new *
5         System.out.print("book is fetched");
6     }
7 }
8

Main.java x
1 package org.example;
2 import org.springframework.context.ApplicationContext;
3 import org.springframework.context.support.ClassPathXmlApplicationContext;
4 import service.BookService;
5
6 public class Main {
7     public static void main(String[] args) {
8         ApplicationContext context = new ClassPathXmlApplicationContext(("configLocation", "applicationContext.xml");
9         BookService service = context.getBean( name: "bookService", BookService.class);
10        service.displayBook();
11    }
12 }

BookService.java x
1 package service;
2
3 import repository.BookRepository;
4
5 public class BookService { 4 usages new *
6
7     private BookRepository bookRepository; 2 usages
8
9     public void setBookRepository(BookRepository bookRepository) { no usages new *
10        this.bookRepository = bookRepository;
11    }
12
13    public void displayBook() { 1 usage new *
14        System.out.println("Book Service Called");
15        bookRepository.getAllBooks();
16    }
17 }
```

</> applicationContext.xml × Main.java

```
1 <?xml version="1.0" encoding="UTF-8"?>
2
3 <beans xmlns="http://www.springframework.org/schema/beans"
4       xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
5       xsi:schemaLocation="
6         http://www.springframework.org/schema/beans
7         https://www.springframework.org/schema/beans/spring-beans.xsd">
8
9     <bean id="bookRepository"
10         class="repository.BookRepository"/>
11     <bean id="bookService"
12         class="service.BookService">
13         <property name="bookRepository"
14             ref="bookRepository"/>
15     </bean>
16
17 </beans>
```

org.example.Main ×

"C:\Program Files\Java\jdk-17\bin\java.exe" ...

Book Service Called

book is fetched

Process finished with exit code 0