

```
7 public class Employee {
8     @Id 2 usages
9     @GeneratedValue(strategy = GenerationType.IDENTITY)
10    private Integer id;
11    private String name; 3 usages
12    private double salary; 3 usages
13    public Employee() { no usages new *
14    }
15    public Employee(String name, double salary) { no usages new *
16        this.name = name;
17        this.salary = salary;
18    }
19    public Integer getId() { no usages new *
20        return id;
21    }
22    public void setId(Integer id) { no usages new *
23        this.id = id;
24    }
25    public String getName() { no usages new *
26        return name;
27    }
28    public void setName(String name) { no usages new *
29        this.name = name;
30    }
31    public double getSalary() { no usages new *
32        return salary;
33    }
```

```
1 package com.example.jpa_handson4.controller;
2 import com.example.jpa_handson4.entity.Employee;
3 import com.example.jpa_handson4.service.EmployeeService;
4 import org.springframework.beans.factory.annotation.Autowired;
5 import org.springframework.web.bind.annotation.*;
6 @RestController no usages new *
7 @RequestMapping("/employee")
8 public class EmployeeController {
9     @Autowired 1 usage
10     private EmployeeService employeeService;
11     @PostMapping no usages new *
12     public String addEmployee(@RequestBody Employee employee) {
13         employeeService.addEmployee(employee);
14         return "Employee Added Successfully";
15     }
16 }
```

```
package com.example.jpa_handson4.service;
import com.example.jpa_handson4.entity.Employee;
import com.example.jpa_handson4.repository.EmployeeRepository;
import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Service;
import org.springframework.transaction.annotation.Transactional;
@Service no usages new *
public class EmployeeService {
    @Autowired 1 usage
    private EmployeeRepository employeeRepository;
    @Transactional no usages new *
    public void addEmployee(Employee employee) {
        employeeRepository.save(employee);
    }
}
```

```
1 package com.example.jpa_handson4.repository;
2
3 import com.example.jpa_handson4.entity.Employee;
4 import org.springframework.data.jpa.repository.JpaRepository;
5
6 public interface EmployeeRepository extends JpaRepository<Employee, Integer> { no usages new *
7 |
8 }
```

My Collection / **Get data**

Save



Share

**POST**

http://localhost:8080/employee

Send Docs Params Authorization Headers (9) **Body** Scripts Settings

Cookies

☐ none ☐ form-data ☐ x-www-form-urlencoded ☒ raw ☐ binary ☐ GraphQL **JSON**

Schema

Beautify

```
1  {  
2    "name": "ram",  
3    "salary": 30000  
4  }
```

Body Cookies Headers (5) Test Results (1/1)**200 OK**

382 ms

191 B



Save Response

 **Raw**

Preview



Visualize



```
1  Employee Added Successfully
```

Query 1 x

Limit to 1000 rows

```
1 • CREATE DATABASE jpa_handson4;
2 • SHOW DATABASES;
3 • use jpa_handson4;
4 • select * from employee;
```

Result Grid

Filter Rows:

Edit: Export/Import: Wrap Cell Content:

	id	name	salary
▶	1	Siva	50000
	2	balan	20000
	3	ram	30000
•	NULL	NULL	NULL