

Project ▾

- > .mvn
- ▾ src
 - main
 - java
 - com.cognizant.orm_learn
 - model
 - Country
 - repository
 - CountryRepository
 - service
 - CountryService
 - OrmLearnApplication
 - > resources
 - > test
 - > target
 - .gitattributes
 - .gitignore
 - HELP.md
 - mvnw
 - mvnw.cmd
 - pom.xml
 - > target
 - External Libraries
 - Scratches and Consoles

CountryService.java ×

CountryRepository.java

OrmLearnApplication.java

application.properties

```
1 package com.cognizant.orm_learn.service;
2 import com.cognizant.orm_learn.model.Country;
3 import com.cognizant.orm_learn.repository.CountryRepository;
4 import org.springframework.beans.factory.annotation.Autowired;
5 import org.springframework.stereotype.Service;
6 import org.springframework.transaction.annotation.Transactional;
7 import java.util.List;
8 @Service 3 usages new *
9 public class CountryService {
10     @Autowired 1 usage
11     private CountryRepository countryRepository;
12     @Transactional 1 usage new *
13     public List<Country> getAllCountries() {
14         return countryRepository.findAll();
15     }
16 }
```

un OrmLearnApplication ×

```
1 package com.cognizant.orm_learn.repository;
2 import com.cognizant.orm_learn.model.Country;
3 import org.springframework.data.jpa.repository.JpaRepository;
4 import org.springframework.stereotype.Repository;
5 @Repository 2 usages new *
6 public interface CountryRepository
7     extends JpaRepository<Country, String> {
8 }
```

```
1 package com.cognizant.orm_learn;
2 import com.cognizant.orm_learn.model.Country;
3 import com.cognizant.orm_learn.service.CountryService;
4 import org.slf4j.Logger;
5 import org.slf4j.LoggerFactory;
6 import org.springframework.boot.SpringApplication;
7 import org.springframework.boot.autoconfigure.SpringBootApplication;
8 import org.springframework.context.ApplicationContext;
9 import java.util.List;
10 @SpringBootApplication
11 ▶ public class OrmLearnApplication {
12     private static final Logger LOGGER = LoggerFactory.getLogger(OrmLearnApplication.class); 4 usages
13     private static CountryService countryService; 2 usages
14 ▶ public static void main(String[] args) {
15     ApplicationContext context = SpringApplication.run(OrmLearnApplication.class, args);
16     countryService = context.getBean(CountryService.class);
17     LOGGER.info("Inside main");
18     testGetAllCountries();
19 }
20 private static void testGetAllCountries() { 1 usage
21     LOGGER.info("Start");
22     List<Country> countries = countryService.getAllCountries();
23     LOGGER.info("Countries = {}", countries);
24     LOGGER.info("End");
25 }
26 }
```

CountryService.java

CountryRepository.java

OrmLearnApplication.java

application.properties ×

```
1 spring.application.name=orm-learn
2 spring.datasource.url=jdbc:mysql://localhost:3306/ormlearn
3 spring.datasource.username=root
4 spring.datasource.password=1234
5 spring.datasource.driver-class-name=com.mysql.cj.jdbc.Driver
6 spring.jpa.hibernate.ddl-auto=validate
7 spring.jpa.properties.hibernate.dialect=org.hibernate.dialect.MySQLDialect
8 spring.jpa.show-sql=true
9 logging.level.org.hibernate.SQL=DEBUG
```

```
startedMain] o.h.e.t.j.p.i.JtaPlatformInitiator      : HHH000489: No JTA platform available (set 'hibernate.transaction.jta.platform' to enable JTA platform integration)
startedMain] j.LocalContainerEntityManagerFactoryBean : Initialized JPA EntityManagerFactory for persistence unit 'default'
startedMain] JpaBaseConfiguration$JpaWebConfiguration : spring.jpa.open-in-view is enabled by default. Therefore, database queries may be performed during view rendering. Ex
startedMain] o.s.b.d.a.OptionalLiveReloadServer       : LiveReload server is running on port 35729
startedMain] o.s.b.w.embedded.tomcat.TomcatWebServer   : Tomcat started on port 8080 (http) with context path '/'
startedMain] c.c.orm_learn.OrmLearnApplication         : Started OrmLearnApplication in 6.597 seconds (process running for 7.403)
startedMain] c.c.orm_learn.OrmLearnApplication         : Inside main
startedMain] c.c.orm_learn.OrmLearnApplication         : Start
startedMain] org.hibernate.SQL                          : select c1_0.co_code,c1_0.co_name from country c1_0

startedMain] c.c.orm_learn.OrmLearnApplication         : Countries = [Country{code='IN', name='India'}, Country{code='US', name='United States of America'}]
startedMain] c.c.orm_learn.OrmLearnApplication         : End
```