

```
1 package com.cognizant.spring_learn;
2 public class Country { 13 usages new *
3     private String code; 3 usages
4     private String name; 3 usages
5     public Country(){ no usages new *
6
7     }
8     public String getCode() { 1 usage new *
9         return code;
10    }
11    public void setCode(String code) { no usages new *
12        this.code = code;
13    }
14    public String getName() { no usages new *
15        return name;
16    }
17    public void setName(String name) { no usages new *
18        this.name = name;
19    }
20    @Override new *
21    public String toString() {
22        return "Country{" +
23            "code='" + code + '\'' +
24            ", name='" + name + '\'' +
25            '}';
26    }
27 }
```

```
2      <beans xmlns="http://www.springframework.org/schema/beans"
11          <property name="code" value="IN"/>
12          <property name="name" value="India"/>
13      </bean>
14      <bean id="countryUs" class="com.cognizant.spring_learn.Country">
15          <property name="code" value="US"/>
16          <property name="name" value="United States"/>
17      </bean>
18      <bean id="countryJP" class="com.cognizant.spring_learn.Country">
19          <property name="code" value="JP"/>
20          <property name="name" value="Japan"/>
21      </bean>
22      <bean id="countryDE" class="com.cognizant.spring_learn.Country">
23          <property name="code" value="DE"/>
24          <property name="name" value="Germany"/>
25      </bean>
26      <util:list id="countryList">
27          <ref bean="countryIn"/>
28          <ref bean="countryUs"/>
29          <ref bean="countryJP"/>
30          <ref bean="countryDE"/>
31      </util:list>
32  </beans>
```

```
1 package com.cognizant.spring_learn.service;
2
3 import com.cognizant.spring_learn.Country;
4 import org.springframework.context.support.ClassPathXmlApplicationContext;
5 import org.springframework.stereotype.Service;
6 import java.util.List;
7
8 @Service no usages new *
9 public class CountryService {
10     public Country getCountry(String code){ no usages new *
11         ClassPathXmlApplicationContext context = new ClassPathXmlApplicationContext( configLocation: "country.xml");
12         List<Country> countries = context.getBean( name: "countryList", List.class);
13         for(Country country : countries){
14             if(country.getCode().equalsIgnoreCase(code)){
15                 return country;
16             }
17         }
18         return null;
19     }
20 }
21
```

```
3 import com.cognizant.spring_learn.Country;
4 import com.cognizant.spring_learn.service.CountryService;
5 import org.springframework.beans.factory.annotation.Autowired;
6 import org.springframework.context.support.ClassPathXmlApplicationContext;
7 import org.springframework.web.bind.annotation.GetMapping;
8 import org.springframework.web.bind.annotation.PathVariable;
9 import org.springframework.web.bind.annotation.RequestMapping;
10 import org.springframework.web.bind.annotation.RestController;
11
12 @RestController no usages new *
13 public class CountryController {
14     @Autowired 1 usage
15     CountryService countryService;
16     @RequestMapping("/country") no usages new *
17     public Country getCountryIndia() {
18         ClassPathXmlApplicationContext context = new ClassPathXmlApplicationContext( configLocation: "country.xml");
19         Country country = context.getBean( name: "countryIn", Country.class);
20         return country;
21     }
22     @GetMapping("/countries/{code}") no usages new *
23     public Country getCountry(@PathVariable String code) {
24         return countryService.getCountry(code);
25     }
26 }
```

Pretty-print

```
{  
  "code": "US",  
  "name": "United States"  
}
```