

src &gt; Components &gt; JS BookDetails.js &gt; [🔍] default

```
1  function BookDetails() {
2    const books = [
3      { id: 1, name: "Java Programming", author: "James Gosling" },
4      { id: 2, name: "React Basics", author: "Jordan Walke" },
5      { id: 3, name: "Python Programming", author: "Guido van Rossum" }
6    ];
7
8    return (
9      <div>
10        <h2>Book Details</h2>
11        <ul>
12          {books.map(book => (
13            <li key={book.id}>
14              {book.name} - {book.author}
15            </li>
16          ))}
17        </ul>
18      </div>
19    );
20  }
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

node + - 📄 🗑️ ... | 🔄 ✕

PS C:\Users\Sivabalan\Desktop\react practice\bloggerapp&gt; npm start

You can now view **bloggerapp** in the browser.

Local: http://localhost:3000

On Your Network: http://192.168.29.148:3000

Note that the development build is not optimized.  
To create a production build, use `npm run build`.

webpack compiled **successfully**

src &gt; Components &gt; JS BlogDetails.js &gt; [🔗] default

```
1  function BlogDetails() {
2    const blogs = [
3      { id: 1, title: "React Hooks", author: "John" },
4      { id: 2, title: "Spring Boot", author: "David" }
5    ];
6
7    return (
8      <div>
9        <h2>Blog Details</h2>
10       <ul>
11         {blogs.map(blog => (
12           <li key={blog.id}>
13             {blog.title} - {blog.author}
14           </li>
15         ))}
16       </ul>
17     </div>
18   );
19 }
20
21 export default BlogDetails;
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

node + v 🗑 ... | 🔄 ✕

PS C:\Users\Sivabalan\Desktop\react practice\bloggerapp> npm start  
You can now view **bloggerapp** in the browser.

Local: http://localhost:3000  
On Your Network: http://192.168.29.148:3000

Note that the development build is not optimized.  
To create a production build, use `npm run build`.

webpack compiled **successfully**

src &gt; Components &gt; JS CourseDetails.js &gt; default

```
1  function CourseDetails() {
2    const courses = [
3      { id: 1, name: "React", duration: "2 Months" },
4      { id: 2, name: "Java", duration: "3 Months" }
5    ];
6
7    return (
8      <div>
9        <h2>Course Details</h2>
10       <ul>
11         {courses.map(course => (
12           <li key={course.id}>
13             {course.name} - {course.duration}
14           </li>
15         ))}
16       </ul>
17     </div>
18   );
19 }
20
21 export default CourseDetails;
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

📄 node + v 📄 🗑️ ... | 🔄 ✕

PS C:\Users\Sivabalan\Desktop\react practice\bloggerapp&gt; npm start

You can now view **bloggerapp** in the browser.**Local:** http://localhost:3000**On Your Network:** http://192.168.29.148:3000

Note that the development build is not optimized.  
To create a production build, use `npm run build`.

webpack compiled **successfully**

□

Tip:  
befo

+

De

+

📄

src &gt; JS App.js &gt; [🔍] default

```
1 import BookDetails from "../Components/BookDetails";
2 import BlogDetails from "../Components/BlogDetails";
3 import CourseDetails from "../Components/CourseDetails";
4
5 function App() {
6   const showBooks = true;
7   const showBlogs = true;
8   const showCourses = false;
9
10  let course;
11
12  if (showCourses) {
13    course = <CourseDetails />;
14  } else {
15    course = <h3>Courses Not Available</h3>;
16  }
17
18  return (
19    <div>
20      <h1>Blogger App</h1>
21      {showBooks && <BookDetails />}
22      <hr />
23      {showBlogs ? <BlogDetails /> : <h3>No Blogs Available</h3>}
24      <hr />
25      {course}
26    </div>
27  );
28 }
29
30 export default App;
```

# Blogger App

## Book Details

- Java Programming - James Gosling
  - React Basics - Jordan Walke
  - Python Programming - Guido van Rossum
- 

## Blog Details

- React Hooks - John
  - Spring Boot - David
- 

## Courses Not Available