



JavaScript object basics

English ▼

[↑ Overview: Objects](#)[Next →](#)

In this article, we'll look at fundamental JavaScript object syntax, and revisit some JavaScript features that we've already seen earlier in the course, reiterating the fact that many of the features you've already dealt with are objects.

Prerequisites: Basic computer literacy, a basic understanding of HTML and CSS, familiarity with JavaScript basics (see [First steps](#) and [Building blocks](#)).

Objective: To understand the basic theory behind object-oriented programming, how this relates to JavaScript ("most things are objects"), and how to start working with JavaScript objects.

Object basics

An object is a collection of related data and/or functionality (which usually consists of several variables and functions — which are called properties and methods when they are inside objects.) Let's work through an example to understand what they look like.

To begin with, make a local copy of our [oojs.html](#) file. This contains very little — a `<script>` element for us to write our source code into. We'll use this as a basis for exploring basic object

syntax. While working with this example you should have your [developer tools JavaScript console](#) open and ready to type in some commands.

As with many things in JavaScript, creating an object often begins with defining and initializing a variable. Try entering the following line below the JavaScript code that's already in your file, then saving and refreshing:

```
1 | const person = {};
```

Now open your browser's [JavaScript console](#), enter `person` into it, and press **Enter** / **Return**. You should get a result similar to one of the below lines:

```
1 | [object Object]
2 | Object { }
3 | { }
```


Congratulations, you've just created your first object. Job done! But this is an empty object, so we can't really do much with it. Let's update the JavaScript object in our file to look like this:

```
1 | const person = {
2 |   name: ['Bob', 'Smith'],
3 |   age: 32,
4 |   gender: 'male',
5 |   interests: ['music', 'skiing'],
6 |   bio: function() {
7 |     alert(this.name[0] + ' ' + this.name[1] + ' is ' + this.age + ' years old. He
8 |   },
9 |   greeting: function() {
10 |     alert('Hi! I\'m ' + this.name[0] + '.');
11 |   }
12 | };
```

After saving and refreshing, try entering some of the following into the JavaScript console on your browser devtools:

```
1 person.name
2 person.name[0]
3 person.age
4 person.interests[1]
5 person.bio()
6 person.greeting()
```

You have now got some data and functionality inside your object, and are now able to access them with some nice simple syntax!

 **Note:** If you are having trouble getting this to work, try comparing your code against our version — see [oojs-finished.html](#) (also [see it running live](#)). The live version will give you a blank screen, but that's OK — again, open your devtools and try typing in the above commands to see the object structure.

So what is going on here? Well, an object is made up of multiple members, each of which has a name (e.g. `name` and `age` above), and a value (e.g. `['Bob', 'Smith']` and `32`). Each name/value pair must be separated by a comma, and the name and value in each case are separated by a colon. The syntax always follows this pattern:

```
1 const objectName = {
2   member1Name: member1Value,
3   member2Name: member2Value,
4   member3Name: member3Value
5 };
```

The value of an object member can be pretty much anything — in our person object we've got a string, a number, two arrays, and two functions. The first four items are data items, and are referred to as the object's **properties**. The last two items are functions that allow the object to do something with that data, and are referred to as the object's **methods**.

An object like this is referred to as an **object literal** — we've literally written out the object contents as we've come to create it. This is in contrast to objects instantiated from classes, which we'll look at later on.

It is very common to create an object using an object literal when you want to transfer a series of structured, related data items in some manner, for example sending a request to the server

to be put into a database. Sending a single object is much more efficient than sending several items individually, and it is easier to work with than an array, when you want to identify individual items by name.

Dot notation

Above, you accessed the object's properties and methods using **dot notation**. The object name (person) acts as the **namespace** — it must be entered first to access anything **encapsulated** inside the object. Next you write a dot, then the item you want to access — this can be the name of a simple property, an item of an array property, or a call to one of the object's methods, for example:

```
1 | person.age
2 | person.interests[1]
3 | person.bio()
```

Sub-namespaces

It is even possible to make the value of an object member another object. For example, try changing the name member from

```
1 | name: ['Bob', 'Smith'],
```

to

```
1 | name : {
2 |   first: 'Bob',
3 |   last: 'Smith'
4 | },
```

Here we are effectively creating a **sub-namespace**. This sounds complex, but really it's not — to access these items you just need to chain the extra step onto the end with another dot. Try

these in the JS console:

```
1 | person.name.first  
2 | person.name.last
```

Important: At this point you'll also need to go through your method code and change any instances of

```
1 | name[0]  
2 | name[1]
```

to

```
1 | name.first  
2 | name.last
```

Otherwise your methods will no longer work.

Bracket notation

There is another way to access object properties — using bracket notation. Instead of using these:

```
1 | person.age  
2 | person.name.first
```

You can use

```
1 | person['age']  
2 | person['name']['first']
```

This looks very similar to how you access the items in an array, and it is basically the same thing — instead of using an index number to select an item, you are using the name associated with each member's value. It is no wonder that objects are sometimes called **associative arrays** — they map strings to values in the same way that arrays map numbers to values.

Setting object members

So far we've only looked at retrieving (or **getting**) object members — you can also **set** (update) the value of object members by simply declaring the member you want to set (using dot or bracket notation), like this:

```
1 | person.age = 45;  
2 | person['name']['last'] = 'Cratchit';
```

Try entering the above lines, and then getting the members again to see how they've changed, like so:

```
1 | person.age  
2 | person['name']['last']
```

Setting members doesn't just stop at updating the values of existing properties and methods; you can also create completely new members. Try these in the JS console:

```
1 | person['eyes'] = 'hazel';  
2 | person.farewell = function() { alert("Bye everybody!"); }
```

You can now test out your new members:

```
1 | person['eyes']  
2 | person.farewell()
```

One useful aspect of bracket notation is that it can be used to set not only member values dynamically, but member names too. Let's say we wanted users to be able to store custom value types in their people data, by typing the member name and value into two text inputs. We could get those values like this:

```
1 | let myDataName = nameInput.value;  
2 | let myDataValue = nameValue.value;
```

We could then add this new member name and value to the `person` object like this:

```
1 | person[myDataName] = myDataValue;
```

To test this, try adding the following lines into your code, just below the closing curly brace of the `person` object:

```
1 | let myDataName = 'height';  
2 | let myDataValue = '1.75m';  
3 | person[myDataName] = myDataValue;
```

Now try saving and refreshing, and entering the following into your text input:

```
1 | person.height
```

Adding a property to an object using the method above isn't possible with dot notation, which can only accept a literal member name, not a variable value pointing to a name.

What is "this"?

You may have noticed something slightly strange in our methods. Look at this one for example:

```
1  greeting: function() {  
2    alert('Hi! I\'m ' + this.name.first + '.');  
3  }
```

You are probably wondering what "this" is. The `this` keyword refers to the current object the code is being written inside — so in this case `this` is equivalent to `person`. So why not just write `person` instead? As you'll see in the [Object-oriented JavaScript for beginners](#) article, when we start creating constructors and so on, `this` is very useful — it always ensures that the correct values are used when a member's context changes (for example, two different `person` object instances may have different names, but we want to use their own name when saying their greeting).

Let's illustrate what we mean with a simplified pair of person objects:

```
1  const person1 = {  
2    name: 'Chris',  
3    greeting: function() {  
4      alert('Hi! I\'m ' + this.name + '.');  
5    }  
6  }  
7  
8  const person2 = {  
9    name: 'Deepti',  
10   greeting: function() {  
11     alert('Hi! I\'m ' + this.name + '.');  
12   }  
13 }
```

In this case, `person1.greeting()` outputs "Hi! I'm Chris."; `person2.greeting()` on the other hand outputs "Hi! I'm Deepti.", even though the method's code is exactly the same in each case. As we said earlier, `this` is equal to the object the code is inside — this isn't hugely useful when you are writing out object literals by hand, but it really comes into its own when you are dynamically generating objects (for example using constructors). It will all become clearer later on.

You've been using objects all along

As you've been going through these examples, you have probably been thinking that the dot notation you've been using is very familiar. That's because you've been using it throughout the course! Every time we've been working through an example that uses a built-in browser API or JavaScript object, we've been using objects, because such features are built using exactly the same kind of object structures that we've been looking at here, albeit more complex ones than in our own basic custom examples.

So when you used string methods like:

```
1 | myString.split(',');
```

You were using a method available on an instance of the `String` class. Every time you create a string in your code, that string is automatically created as an instance of `String`, and therefore has several common methods and properties available on it.

When you accessed the document object model using lines like this:

```
1 | const myDiv = document.createElement('div');  
2 | const myVideo = document.querySelector('video');
```


You were using methods available on an instance of the `Document` class. For each webpage loaded, an instance of `Document` is created, called `document`, which represents the entire page's structure, content, and other features such as its URL. Again, this means that it has several common methods and properties available on it.

The same is true of pretty much any other built-in object or API you've been using — `Array`, `Math`, and so on.

Note that built in objects and APIs don't always create object instances automatically. As an example, the `Notifications API` — which allows modern browsers to fire system notifications — requires you to instantiate a new object instance using the constructor for each notification you want to fire. Try entering the following into your JavaScript console:

```
1 | const myNotification = new Notification('Hello!');
```

Again, we'll look at constructors in a later article.


 **Note:** It is useful to think about the way objects communicate as **message passing** — when an object needs another object to perform some kind of action often it sends a message to another object via one of its methods, and waits for a response, which we know as a return value.

Summary

Congratulations, you've reached the end of our first JS objects article — you should now have a good idea of how to work with objects in JavaScript — including creating your own simple objects. You should also appreciate that objects are very useful as structures for storing related data and functionality — if you tried to keep track of all the properties and methods in our `person` object as separate variables and functions, it would be inefficient and frustrating, and we'd run the risk of clashing with other variables and functions that have the same names. Objects let us keep the information safely locked away in their own package, out of harm's way.

In the next article we'll start to look at object-oriented programming (OOP) theory, and how such techniques can be used in JavaScript.

 [Overview: Objects](#)

[Next](#) 

In this module

- [Object basics](#)
- [Object-oriented JavaScript for beginners](#)
- [Object prototypes](#)
- [Inheritance in JavaScript](#)

- [Working with JSON data](#)
- [Object building practice](#)
- [Adding features to our bouncing balls demo](#)

 **Last modified:** Dec 4, 2019, by [MDN contributors](#)

[Object basics](#)

[Dot notation](#)

[Bracket notation](#)

[Setting object members](#)

[What is "this"?](#)

[You've been using objects all along](#)

[Summary](#)

[In this module](#)

Related Topics

[Complete beginners start here!](#)

- ▶ [Getting started with the Web](#)

[HTML — Structuring the Web](#)

- ▶ [Introduction to HTML](#)
- ▶ [Multimedia and embedding](#)
- ▶ [HTML tables](#)
- ▶ [HTML forms](#)

[CSS — Styling the Web](#)

- ▶ [CSS first steps](#)

- ▶ [CSS building blocks](#)
- ▶ [Styling text](#)
- ▶ [CSS layout](#)

JavaScript — Dynamic client-side scripting

- ▶ [JavaScript first steps](#)
- ▶ [JavaScript building blocks](#)
- ▼ [Introducing JavaScript objects](#)
 - [Introducing JavaScript objects overview](#)
 - [Object basics](#)
 - [Object-oriented JavaScript for beginners](#)
 - [Object prototypes](#)
 - [Inheritance in JavaScript](#)
 - [Working with JSON data](#)
 - [Object building practice](#)
 - [Assessment: Adding features to our bouncing balls demo](#)
- ▶ [Asynchronous JavaScript](#)
- ▶ [Client-side web APIs](#)

Accessibility — Make the web usable by everyone

- ▶ [Accessibility guides](#)
- ▶ [Accessibility assessment](#)

Tools and testing

- ▶ [Cross browser testing](#)

Server-side website programming

- ▶ [First steps](#)

- ▶ [Django web framework \(Python\)](#)
- ▶ [Express Web Framework \(node.js/JavaScript\)](#)

Further resources

- ▶ [Common questions](#)

[How to contribute](#)



Learn the best of web development

Get the latest and greatest from MDN delivered straight to your inbox.

Sign up now