

JavaScript Object Prototypes

[< Previous](#)[Next >](#)

All JavaScript objects inherit properties and methods from a prototype.

In the previous chapter we learned how to use an **object constructor**:

Example

```
function Person(first, last, age, eyecolor) {  
  this.firstName = first;  
  this.lastName = last;  
  this.age = age;  
  this.eyeColor = eyecolor;  
}  
  
var myFather = new Person("John", "Doe", 50, "blue");  
var myMother = new Person("Sally", "Rally", 48, "green");
```

[Try it Yourself »](#)

We also learned that you can **not** add a new property to an existing object constructor:

Example

```
Person.nationality = "English";
```

[Try it Yourself »](#)

To add a new property to a constructor, you must add it to the constructor function:

Example

```
function Person(first, last, age, eyecolor) {  
  this.firstName = first;  
  this.lastName = last;  
  this.age = age;  
  this.eyeColor = eyecolor;  
  this.nationality = "English";  
}
```

Try it Yourself »

Prototype Inheritance

All JavaScript objects inherit properties and methods from a prototype:

- `Date` objects inherit from `Date.prototype`
- `Array` objects inherit from `Array.prototype`
- `Person` objects inherit from `Person.prototype`

The `Object.prototype` is on the top of the prototype inheritance chain:

`Date` objects, `Array` objects, and `Person` objects inherit from `Object.prototype`.

Adding Properties and Methods to Objects

Sometimes you want to add new properties (or methods) to all existing objects of a given type.

Sometimes you want to add new properties (or methods) to an object constructor.

Using the **prototype** Property

The JavaScript `prototype` property allows you to add new properties to object constructors:

Example

```
function Person(first, last, age, eyecolor) {  
  this.firstName = first;  
  this.lastName = last;  
  this.age = age;  
  this.eyeColor = eyecolor;  
}  
  
Person.prototype.nationality = "English";
```

[Try it Yourself »](#)

The JavaScript `prototype` property also allows you to add new methods to objects constructors:

Example

```
function Person(first, last, age, eyecolor) {  
  this.firstName = first;  
  this.lastName = last;  
  this.age = age;  
  this.eyeColor = eyecolor;  
}  
  
Person.prototype.name = function() {  
  return this.firstName + " " + this.lastName;  
};
```

[Try it Yourself »](#)

Only modify your **own** prototypes. Never modify the prototypes of standard JavaScript objects.

Copyright 1999-2019 by Refsnes Data. All Rights Reserved.