

Aim: To perform the test scripts are written in Postman.

The image displays three sequential screenshots of the Postman interface, illustrating the process of writing and running test scripts for a REST API endpoint.

**Top Screenshot:** Shows the initial setup of a GET request to `https://api.github.com/user/repos`. The **Tests** tab is active, and a single test script is written in JavaScript:

```
1 pm.test("Your login",function() {
2
3
4     var jsonData = pm.response.json();
5     pm.expect(jsonData[0].owner.login).to.eql("siva143843");
6 });
7
```

The response body is shown in JSON format:

```
1 {
2   "id": 694653916,
3   "node_id": "R_kgDQWt3A",
4   "name": "loop",
5 }
```

**Middle Screenshot:** The test script is updated to include two tests. The first test remains the same, and a second test is added:

```
1 pm.test("Your login",function() {
2
3
4     var jsonData = pm.response.json();
5     pm.expect(jsonData[0].owner.login).to.eql("siva143843");
6 });
7
8 pm.test("Repo name",function() {
9
10    var jsonData = pm.response.json();
11    pm.expect(jsonData[0].name).to.eql("loop");
12 });
13
```

**Bottom Screenshot:** Shows the execution results of the tests. The **Test Results** tab is active, displaying a summary of the test outcomes:

Test Name	Status	Message
Your login	PASS	
Repo name	FAIL	ReferenceError: to is not defined

Home Workspaces API Network Explore Search Postman

Phase3-Lesson2-APITesting New Import GET GetAllrepos Project-Variables

GET GetAllrepos

Params Authorization Headers (7) Body Pre-request Script Tests Settings

```
1 pm.test("Your login",function() {
2
3
4     var jsonData = pm.response.json();
5     pm.expect(jsonData[0].owner.login).to.eql("siva1143843");
6 });
7
8 pm.test("Repo name",function() {
9
10
11     var jsonData = pm.response.json();
12     pm.expect(jsonData[0].name).to.eql("loop");
13 });
```

Test scripts are written in JavaScript, and are run after the response is received. Learn more about [test scripts](#)

Snippets

- Get an environment variable
- Get a global variable
- Get a variable
- Get a collection variable
- Set an environment variable

Body Cookies Headers (28) Test Results (2/2)

Status: 200 OK Time: 401 ms Size: 75.28 KB Save as example

All Passed Skipped Failed

PASS Your login

PASS Repo name

Home Workspaces API Network Explore Search Postman

Phase3-Lesson2-APITesting New Import GET GetAllrepos POST New Request Project-Variables

POST New Request

Params Authorization Headers (9) Body Pre-request Script Tests Settings

Need help authorizing with GitHub API?

Type Bearer Token

The authorization header will be automatically generated when you send the request. Learn more about [authorization](#)

Token ghp\_Z8xILDVnnY91tOn37dVZ84HoxGcb4w...

Body Cookies Headers (28) Test Results

Status: 201 Created Time: 1224 ms Size: 7.3 KB Save as example

Pretty Raw Preview Visualize JSON

```
1 {
2   "id": 715606908,
3   "node_id": "R_kgDOkqDLfa",
4   "name": "postman-demo-07Nov",
5   "full_name": "siva1143843/postman-demo-07Nov",
6   "private": false,
7   "owner": {
8     "login": "siva1143843",
9     "id": 145089482,
10    "node_id": "U_kgDOOXjyg",
11    "avatar_url": "https://avatars.githubusercontent.com/u/145089482?v=4",
```

Home Workspaces API Network Explore Search Postman

Phase3-Lesson2-APITesting New Import GET GetAllrepos POST Create a repo dev QA Project-Variables Project-Variables

Project-Variables

Filter variables

Variable	Type	Initial value	Current value
<input checked="" type="checkbox"/> Base_URL	default	https://api.openweathermap.org	https://api.openweathermap.org
<input checked="" type="checkbox"/> City	default	New Delhi	New DelhiNew Delhi
<input checked="" type="checkbox"/> repoName	default		Postman-API-197
Add new variable			

Home Workspaces API Network Explore Search Postman

Phase3-Lesson2-APITesting New Import POST Create a repo

Globals

- dev
- Project-Variables
- QA

GitHub-API / Create a repo

POST https://api.github.com/user/repos

Params Authorization Headers (9) Body Pre-request Script Tests Settings

```
1
2 var json = JSON.parse(responseBody)
3 pm.environment.set("owner", json.owner.login);
```

Test scripts are written in JavaScript, and are run after the response is received. Learn more about [test scripts](#)

Snippets

- Get an environment variable
- Get a global variable
- Get a variable
- Get a collection variable
- Set an environment variable
- Set a global variable
- Set a collection variable

Body Cookies Headers (28) Test Results

Status: 201 Created Time: 1242 ms Size: 717 KB Save as example

There are no tests for this request

Write a test script to automate debugging. Learn more about

Home Workspaces API Network Explore Search Postman

Phase3-Lesson2-APITesting New Import POST Create a repo

Globals

- dev
- Project-Variables
- QA

GitHub-API / Create a repo

POST https://api.github.com/user/repos

Params Authorization Headers (9) Body Pre-request Script Tests Settings

```
1 pm.test("create owner variable", function() {
2   var json = JSON.parse(responseBody)
3   pm.environment.set("owner", json.owner.login);
4
5 });
```

Test scripts are written in JavaScript, and are run after the response is received. Learn more about [test scripts](#)

Snippets

- Get an environment variable
- Get a global variable
- Get a variable
- Get a collection variable
- Set an environment variable
- Set a global variable
- Set a collection variable

Body Cookies Headers (28) Test Results

Status: 201 Created Time: 1242 ms Size: 717 KB Save as example

There are no tests for this request

Write a test script to automate debugging. Learn more about

Home Workspaces API Network Explore Search Postman

Phase3-Lesson2-APITesting New Import POST Create a repo

Globals

- dev
- Project-Variables
- QA

GitHub-API / Create a repo

POST https://api.github.com/user/repos

Params Authorization Headers (9) Body Pre-request Script Tests Settings

```
1 pm.test("create owner variable", function() {
2   var json = JSON.parse(responseBody)
3   pm.environment.set("owner", json.owner.login);
4
5 });
```

Test scripts are written in JavaScript, and are run after the response is received. Learn more about [test scripts](#)

Snippets

- Get an environment variable
- Get a global variable
- Get a variable
- Get a collection variable
- Set an environment variable
- Set a global variable
- Set a collection variable

Body Cookies Headers (28) Test Results (1/1)

Status: 201 Created Time: 1119 ms Size: 716 KB Save as example

All Passed Skipped Failed

PASS create owner variable

HomeWorkspacesAPI NetworkExplore

Search

InviteSettingsNotificationsUpgrade

Phase3-Lesson2-APITestingNewImport

POST Create a repoGET Get a Specific RepoGET GetAllrepos

Project-Variables

Collections

APIs

Environments

History

ApiTesting-Lesson2

CollectionRun-Newman

GitHub-API

GET GetAllrepos

POST Create a repo

GET Get a Specific Repo

HTTPMethods-Demo

Lesson-EndProject

Variables\_Demo

GitHub-API / Get a Specific Repo

GEThttps://api.github.com/repos/owner/repos

Send

ParamsAuthorizationHeaders (6)BodyPre-request ScriptTestsSettings

```
1 pm.test("Status code is 200", function () {
2   pm.response.to.have.status(200);
3 });
4 pm.test("Response time is less than 600ms", function () {
5   pm.expect(pm.response.responseTime).to.be.below(600);
6 });
7
8 pm.test("Status code name has ok", function () {
9   pm.response.to.have.status("ok");
10 });
11 pm.test("Content-Type is present", function () {
12   pm.response.to.have.header("Content-Type");
13 });
```

Test scripts are written in JavaScript, and are run after the response is received. Learn more about [test scripts](#)

Snippets

Response body: Is equal to a string

Response headers: Content-Type header check

Response time is less than 200ms

Status code: Successful POST request

Status code: Code name has string

Response body: Convert XML body to a JSON Object

BodyCookiesHeaders (26)Test Results

Status: 200 OKTime: 421 msSize: 2.48 KBSave as example

PrettyRawPreviewVisualizeJSON

```
1 {
2   "id": 715625673,
3   "node_id": "R_kgDOKqeUyQ",
4   "name": "Postman-API-488",
5   "full_name": "sivaaji143843/Postman-API-488",
6   "private": false,
7   "owner": {
8     "login": "sivaaji143843",
```

Phase3-Lesson2-APITestingNewImport

POST Create a repoGET Get a Specific RepoGET GetAllrepos

Project-Variables

Collections

APIs

Environments

History

ApiTesting-Lesson2

CollectionRun-Newman

GitHub-API

GET GetAllrepos

POST Create a repo

GET Get a Specific Repo

HTTPMethods-Demo

Lesson-EndProject

Variables\_Demo

GitHub-API / Get a Specific Repo

GEThttps://api.github.com/repos/owner/repos

Send

ParamsAuthorizationHeaders (6)BodyPre-request ScriptTestsSettings

```
1 pm.test("Status code is 200", function () {
2   pm.response.to.have.status(200);
3 });
4 pm.test("Response time is less than 600ms", function () {
5   pm.expect(pm.response.responseTime).to.be.below(600);
6 });
7
8 pm.test("Status code name has OK", function () {
9   pm.response.to.have.status("OK");
10 });
11 pm.test("Content-Type is present", function () {
12   pm.response.to.have.header("Content-Type");
13 });
```

Test scripts are written in JavaScript, and are run after the response is received. Learn more about [test scripts](#)

Snippets

Response body: Is equal to a string

Response headers: Content-Type header check

Response time is less than 200ms

Status code: Successful POST request

Status code: Code name has string

Response body: Convert XML body to a JSON Object

BodyCookiesHeaders (26)Test Results (3/4)

Status: 200 OKTime: 532 msSize: 2.48 KBSave as example

AllPassedSkippedFailed

PASSStatus code is 200

PASSResponse time is less than 600ms

FAILStatus code name has ok | AssertionError: expected response to have status reason 'ok' but got 'OK'

PASSContent-Type is present

OnlineFind and replaceConsole

PostbotRunnerStart ProxyCookiesTrash

Home Workspaces API Network Explore

Phase3-Lesson2-APITesting New Import POST Create a repo GET Get a Specific Repo GET GetAllrepos Project-Variables

GET https://api.github.com/repos/owner/repos

Params Authorization Headers (6) Body Pre-request Script Tests Settings Cookies

```
1 pm.test("Status code is 200", function () {
2   pm.response.to.have.status(200);
3 });
4 pm.test("Response time is less than 600ms", function () {
5   pm.expect(pm.response.responseTime).to.be.below(600);
6 });
7
8 pm.test("Status code name has OK", function () {
9   pm.response.to.have.status("OK");
10 });
11 pm.test("Content-Type is present", function () {
12   pm.response.to.have.header("Content-Type");
13 });
```

Test Results (4/4)

All	Passed	Skipped	Failed
PASS	Status code is 200		
PASS	Response time is less than 600ms		
PASS	Status code name has OK		
PASS	Content-Type is present		

Status: 200 OK Time: 340 ms Size: 2.48 KB Save as example

Home Workspaces API Network Explore

Phase3-Lesson2-APITesting New Import POST Create a repo GET Get a Specific Repo GET GetAllrepos DEL DeleteRepo Project-Variables

DELETE https://api.github.com/repos/owner/repos

Params Authorization Headers (7) Body Pre-request Script Tests Settings Cookies

```
1 pm.test("Status code is 204", function () {
2   pm.response.to.have.status(204);
3 });
4 pm.test("Status code name has No Content", function () {
5   pm.response.to.have.status("No Content");
6 });
```

Test Results (0/2)

Status: 404 Not Found Time: 413 ms Size: 1.33 KB Save as example