



Throughput Test

2025-11-26-10-48-27

Objective

The Candela Client Capacity test is designed to measure an Access Point's client capacity and performance when handling different amounts of Real clients like android, Linux, windows, MacOS and IOS. The test allows the user to increase the number of clients in user-defined steps for each test iteration and measure the per client and the overall throughput for this test, we aim to assess the capacity of network to handle high volumes of traffic while each trial. Along with throughput other measurements made are client connection times, Station 4-Way Handshake time, DHCP times, and more. The expected behavior is for the AP to be able to handle several stations (within the limitations of the AP specs) and make sure all Clients get a fair amount of airtime both upstream and downstream. An AP that scales well will not show a significant overall throughput decrease as more Real clients are added.

Input Parameters


The below tables provides the input parameters for the test

Test Configuration	Test name	None
	Device List	DESKTOP-DDPI3HE(Windows), macoss-MacBook-Air.local(Mac), samsung1(Android)
	No of Devices	Total(3) Android(1) Windows(1) Mac(1)
	Increment	None
	Traffic Duration in minutes	1.0
	Traffic Type	UDP
	Traffic Direction	Download
	Upload Rate(Mbps)	0.0Mbps
	Download Rate(Mbps)	1.0Mbps
	Load Type	Per Client Load
	Packet Size	AUTO


Real Time Throughput: Achieved Throughput: Download : 2.34 Mbps



Per Client Avg-Throughput



RSSI Of The Clients Connected



Detailed Result Table

The below tables provides detailed information for the throughput test on each device.

Device Type	Username	SSID	MAC	Channel	Mode	Offered download rate (Mbps)	Observed Average download rate (Mbps)	Offered upload rate (Mbps)	Observed Average upload rate (Mbps)	RSSI (dBm)	Average RTT (ms)	Packet Size(Bytes)	Average Rx Drop %	Average Tx Drop %
Windows	DESKTOP-DDPI3HE	NETGEAR_2G_wpa2	e4:a4:71:93:70:e7	11	802.11abgn 20 1x1	1.0	0.67	0.0	0	-13	6	AUTO	0.02	0.0
Mac	macoss-MacBook-Air.local	NETGEAR_2G_wpa2	30:35:ad:c5:e1:be	11	802.11abgn-BE 20 2x2	1.0	0.67	0.0	0	-31	-1	AUTO	0.00	0.0
Android	samsung1	NETGEAR_2G_Open	06:e8:6f:9c:30:7f	11	802.11abgn 20	1.0	1.0	0.0	0	-35	15	AUTO	0.03	0.0

