Explainable, Safety-Aware Fall-Risk Prediction from Smart-Ring Data

A project report submitted in partial fulfilment

of the requirements for the degree of

Bachelor of Technology

in

Electronics and Computer Engineering

by

G SIVAKUMAR

23BCE1834

KRITI SAHANA V

23BCE1868



VIT®

Vellore Institute of Technology

(Deemed to be University under section 3 of UGC Act, 1956)

CHENNAI

School of Electronics Engineering

Vellore Institute of Technology, Chennai

Vandalur - Kelambakkam Road

Chennai – 600127, India

October 2026

VIT®
Vellore Institute of Technology
(Deemed to be University under section 3 of UGC Act, 1956)
CHENNAI

School of Electronics Engineering

Declaration

I hereby declare that the report titled **"Explainable, Safety-Aware Fall-Risk Prediction from Smart-Ring Data"** submitted by me, G SIVAKUMAR (23BCE1834), to the School of Electronics Engineering, Vellore Institute of Technology, Chennai, in partial fulfilment of the requirements for the award of **Bachelor of Technology** in **Electronics and Computer Engineering**, is a bonafide record of the work carried out by me under the supervision of **Dr. Sheena Christabel Pravin**.

I further declare that the work reported in this report has not been submitted and will not be submitted, either in part or in full, for the award of any other degree or diploma of this institute or of any other institute or University.

Signature of the Candidate:

Name and Reg. No.: G SIVAKUMAR (23BCE1834)

Date: ……

VIT®
Vellore Institute of Technology
(Deemed to be University under section 3 of UGC Act, 1956)
CHENNAI

School of Electronics Engineering

Certificate

This is to certify that the project report titled **"Explainable, Safety-Aware Fall-Risk Prediction from Smart-Ring Data"** submitted by G SIVAKUMAR (23BCE1834) to Vellore Institute of Technology, Chennai, in partial fulfilment of the requirement for the award of the degree of **Bachelor of Technology** in **Electronics and Computer Engineering** is a bonafide work carried out under my supervision. The project report fulfils the requirements as per the regulations of this University and, in my opinion, meets the necessary standards for submission. The contents of this report have not been submitted and will not be submitted either in full or in part, for the award of any other degree or diploma and the same is certified.

Supervisor	**Head of the Department**
Signature: ……	Signature: ……
Name: ……	Name: ……
Date: ……	Date: ……

Examiner 1	**Examiner 2**
Signature: ……	Signature: ……
Name: ……	Name: ……
Date: ……	Date: ……

(Seal of the School)

Abstract

Falls are the leading cause of injury-related harm in older adults, yet consumer wearables mostly detect a fall after it has happened, and health chatbots built on large language models (LLMs) state health numbers they cannot be trusted with. This project develops an explainable, safety-aware system that estimates daily fall risk from smart-ring data and explains it through a conversational agent.

A Flutter and Android application collects heart rate, heart-rate variability, blood oxygen, skin temperature, sleep, stress and step data from a Bluetooth smart ring and stores them in Supabase. A deterministic fall-risk engine compares each signal with the user's own 28-day median baseline, converts robust z-score deviations into strain through a dead-zone mapping, aggregates them into physiology, recovery, motion and fall-history layers, and combines the layers with weights derived from published odds ratios ($\lambda \propto \ln \mathrm{OR}$). For women, baselines are matched to the menstrual-cycle phase. Every point of the resulting Fall Risk Score is attributed to a measurement. An agent then explains the score: it routes each question to the data it needs, fuses keyword, LLM and ring fall-event signals to detect emergencies, and checks every number in its reply against the user's data.

On 11 scenarios the full agent detected all three emergencies, including one visible only through the ring's fall event, with no false alarms, and achieved a strict numeric grounding of 0.979 against 0.723 for a plain LLM. On the real PhysioNet LTMM dataset of 73 older adults, an untrained gait-instability index reached an AUC of 0.686, comparable to the clinical Timed Up and Go test (0.683). Cycle-aware baselines reduced physiology risk on normal luteal days by 43%. The work shows that an untrained, evidence-weighted engine can give transparent fall-risk estimates whose every number can be traced and verified.

Keywords: Fall-risk prediction, smart ring, explainable AI, personal baselines, LLM agents, grounding, safety fusion, gait analysis, menstrual cycle

Acknowledgements

It is my pleasure to express with a deep sense of gratitude to my project guide, **Dr. Sheena Christabel Pravin**, School of Electronics Engineering (SENSE), Vellore Institute of Technology, Chennai, for the constant guidance, continual encouragement and understanding extended to me throughout this work. The advice to go deeper into signal processing shaped the gait-analysis work in this report.

I sincerely express my gratitude to **Dr. Ravi Sankar A**, Dean, SENSE; **Dr. Mohanaprasad K**, Associate Dean (Academics), SENSE; and **Dr. Chitra K**, Associate Dean (Research), SENSE, for providing the necessary facilities and for their constant encouragement and support throughout the project.

I also extend my heartfelt thanks to **Dr. Vijayakumar P**, Head of the Department, for the continuous guidance and support during the course of this project, and to the review panel members for their feedback at each review.

I thank the creators of the PhysioNet Long Term Movement Monitoring Database for making their data openly available, which allowed the methods to be validated on real recordings.

I also take this opportunity to thank all the faculty of the School for their support and the knowledge imparted throughout the course. I thank my parents, family and friends for their support throughout the project and for the opportunity they provided me to undergo this course in such a prestigious institution.

Place: Chennai

Date:

G Sivakumar (23BCE1834)

Codes and Standards

Project Title: Explainable, Safety-Aware Fall-Risk Prediction from Smart-Ring Data

The system is a research prototype that gives screening estimates; it is not a certified medical device. The standards below guided its design, development, data handling and reporting.

1. Health Software and Risk Management

- **IEC 62304 – Medical device software: software life-cycle processes** – Guided the structured development, unit testing and traceability of the fall-risk engine and agent.
- **ISO 14971 – Application of risk management to medical devices** – Used to reason about hazards such as missed emergencies and false alarms, which shaped the tri-modal safety fusion and the asymmetric routing.
- **IEC 82304-1 – Health software: general requirements for product safety** – Informed the decision that the system gives screening estimates only and never a diagnosis.

2. Wireless Communication and Personal Health Devices

- **Bluetooth Core Specification v5.x (Bluetooth Low Energy)** – Link between the smart ring and the phone for measurements and history download.
- **ISO/IEEE 11073 – Personal health device communication** – Reference for naming and units of vital-sign data exchanged between device and application.

3. Data Protection and Security

- **ISO/IEC 27001 – Information security management systems** – Reference for protecting stored biometric data and access credentials.
- **Digital Personal Data Protection Act, 2023 (India)** – Health readings are personal data; consent, purpose limitation and deletion on logout were applied.
- **RFC 8446 (TLS 1.3) and RFC 7519 (JSON Web Token)** – Encrypted transport to Supabase and token-based user authentication.

4. Artificial Intelligence and Software Quality

- **ISO/IEC 23894 – Artificial intelligence: guidance on risk management** – Applied to the LLM components: the score is never generated by the LLM and every number is verified.
- **ISO/IEC 25010 – Systems and software quality models** – Quality attributes (reliability, maintainability, usability) used when reviewing the application.

5. Reporting of Prediction Models

- **TRIPOD statement – Transparent reporting of a multivariable prediction model** – Followed when reporting the LTMM experiments: pre-specified models, all results reported, subject-wise validation and stated limitations.

Mapping of Sustainable Development Goals (SDGs)

Project Title: Explainable, Safety-Aware Fall-Risk Prediction from Smart-Ring Data

Mapped SDG	Justification	Expected Impact
SDG 3 – Good Health and Well-being	Daily fall-risk estimates and emergency detection support older adults living independently.	Earlier warning of rising fall risk and faster escalation after a fall can reduce injury and hospital stays.
SDG 5 – Gender Equality	Cycle-aware baselines stop normal menstrual-cycle changes from being flagged as risk.	Fairer risk estimates for women, who are otherwise judged against a cycle-blind baseline.
SDG 9 – Industry, Innovation and Infrastructure	Combines a low-cost wearable, a cloud database and an explainable AI agent into one system.	A reusable, open design for trustworthy health AI on consumer hardware.
SDG 10 – Reduced Inequalities	Runs on an affordable ring and phone, with plain-language explanations of every score.	Makes continuous risk monitoring accessible beyond clinical settings.

Table of Contents

Declaration.....*i*
Certificate.....*ii*
Abstract.....*iii*
Acknowledgements.....*iv*
Codes and Standards.....*v*
Mapping of Sustainable Development Goals (SDGs).....*vii*
List of Figures.....*x*
List of Tables.....*xi*
List of Acronyms.....*xii*

1 Introduction.....1
- 1.1 Background.....1
- 1.2 Motivation.....1
- 1.3 Problem Statement.....2
- 1.4 Objectives.....2
- 1.5 Scope of the Project.....2
- 1.6 Contributions.....3
- 1.7 Organisation of the Report.....3

2 Literature Survey.....5
- 2.1 LLM Agents for Personal Health Data.....5
- 2.2 Reasoning and Self-Verification in LLMs.....5
- 2.3 Fall-Risk Factors and Personal Baselines.....6
- 2.4 Gait Analysis for Fall Risk.....6
- 2.5 Comparison of Existing Approaches.....7
- 2.6 Research Gaps Identified.....8

3 Methodology and System Design.....9
- 3.1 Overview of the Proposed System.....9
- 3.2 Smart-Ring Application.....10
  - 3.2.1 Data Acquisition.....10
  - 3.2.2 Local Storage and Cloud Synchronisation.....10
  - 3.2.3 Phone-Based Fall Detection.....10
  - 3.2.4 User Interface.....10
- 3.3 Data Sources and Datasets.....13
  - 3.3.1 PhysioNet Long Term Movement Monitoring Database.....14
  - 3.3.2 Synthetic Demonstration Cohort.....14
- 3.4 Deterministic Fall-Risk Engine.....15
  - 3.4.1 Inputs and Layers.....15
  - 3.4.2 Personal Robust Baseline.....15
  - 3.4.3 Cycle-Aware Baseline.....16
  - 3.4.4 Deviation and Dead-Zone Strain.....16
  - 3.4.5 Fall Events.....17
  - 3.4.6 Layer Aggregation.....17
  - 3.4.7 Evidence-Derived Layer Weights.....17
  - 3.4.8 Coverage-Adaptive Weights and the Final Score.....18

3.4.9 Coverage and Confidence....18
3.4.10 Additive Attribution....18
3.5 Gait Signal Processing....21
3.5.1 Version 1: Step Detection and Regularity....21
3.5.2 Version 2: Turn Removal and Initial-Contact Detection....21
3.5.3 Version 3 Features and the Gait Instability Index....22
3.5.4 Daily-Life Walking Detection....22
3.6 Explainable and Safety-Aware Agent....22
3.6.1 Confidence-Scored Routing with Safety Widening....24
3.6.2 Tri-Modal Safety Fusion....24
3.6.3 Grounded Generation....24
3.6.4 Closed-Loop Self-Verification....25
3.6.5 Personal Correlations....25
3.7 Evaluation Methodology....25
3.7.1 Real-Data Experiments on LTMM....25
3.7.2 Engine Analysis....26
3.7.3 Agent Evaluation....26
3.8 Algorithm....26
3.9 Tools and Technologies....27
4 Implementation, Results and Discussion....28
4.1 Implementation Overview....28
4.2 Evidence-Derived Layer Weights....28
4.3 Fall-Risk Engine on the Demonstration Cohort....29
4.4 Cycle-Aware Baseline Ablation....30
4.5 Gait Detector Validation....31
4.6 Experiment 1: Untrained Gait Index on Real Data....32
4.7 Experiment 2: Pre-Registered Models....34
4.8 Experiment 3: Daily-Life Walking....35
4.9 Agent Evaluation....36
4.10 Testing and Validation....38
4.11 Discussion....38
4.12 Limitations....39
5 Conclusion and Future Work....41
5.1 Summary of Work Completed....41
5.2 Major Findings....41
5.3 Conclusion....41
5.4 Future Enhancements....42
Appendix....43
Bibliography....45
Biodata....47

List of Figures

3.1 Overall architecture of the system....9
3.2 Home dashboard: ring status card and vital-sign cards....11
3.3 AI Assist: 30-day key changes and a grounded answer to “how is my overall health” 12
3.4 Fall Risk tab (left) and the “How your score is calculated” page (right)....13
3.5 Dead-zone mapping from deviation to strain....17
3.6 Engine walk-through, step 1: today’s values against the personal 28-day baseline..19
3.7 Engine walk-through, step 3: dead-zone strain for each feature....20
3.8 Engine walk-through, step 4: layer risks and evidence-derived weights....20
3.9 Engine walk-through, step 5: additive contributions summing to the score....21
3.10 Pipeline of the agent (rotated)....23
4.1 Evidence-derived layer weights, $\lambda \propto \ln$(published risk ratio)....29
4.2 21-day Fall Risk Score trajectory of each demonstration user....30
4.3 Additive attribution: contributions sum exactly to the score....30
4.4 Cycle-aware baselines suppress normal luteal changes but keep genuine strain....31
4.5 Detector validation on synthetic ground truth....32
4.6 Gait variability on real LTMM walks before and after the signal-quality fix....32
4.7 ROC curves on real LTMM data: gait indices against clinical tests....34
4.8 Per-feature AUC of the version 2 gait features (no training on labels)....34
4.9 Experiment 2: all pre-registered models (subject-wise cross-validation)....35
4.10 Experiment 3: lab and daily-life gait models....36
4.11 Emergency recall and false-alarm rate of the four versions....37
4.12 Strict numeric grounding on personal fall-risk queries....37
4.13 Demonstration: the stale-data user is told that the estimate is less reliable....38

List of Tables

2.1 Summary of the reviewed literature....7
2.2 Research gaps and how this project addresses them....8
3.1 Data sources used in the project and their purpose....13
3.2 Synthetic demonstration cohort (35 days per user)....14
3.3 Engine inputs, layers and within-layer weights....15
3.4 Evidence-derived layer weights....17
3.5 Agent evaluation scenarios....26
3.6 Software, services and hardware used in the project....27
4.1 Implemented components and their verification....28
4.2 Fall Risk Scores of the demonstration cohort....29
4.3 Layer risks (0–100) and top contributors (points)....29
4.4 Physiology-layer risk on normal luteal days, with and without the cycle-aware baseline....31
4.5 Experiment 1: discrimination of fallers and non-fallers (LTMM lab walks, n = 73) 33
4.6 Experiment 1: per-feature AUC of the version 2 gait features....33
4.7 Experiment 2: pre-registered models on the LTMM lab walks (n = 73)....35
4.8 Experiment 3: adding daily-life walking from 3-day recordings....36
4.9 Agent versions A–D on the 11 fall scenarios....36
4.10 Automated checks and their outcomes....38

List of Acronyms

Acronym	Full Form
AI	Artificial Intelligence
API	Application Programming Interface
AP	Anteroposterior (acceleration axis)
AUC	Area Under the ROC Curve
BLE	Bluetooth Low Energy
BP	Blood Pressure
CI	Confidence Interval
CV	Coefficient of Variation / Cross-Validation
FH	Fall History (layer)
FRS	Fall Risk Score
HR	Heart Rate
HRV	Heart Rate Variability
IMU	Inertial Measurement Unit
JSON	JavaScript Object Notation
LLM	Large Language Model
LTMM	Long Term Movement Monitoring (database)
MAD	Median Absolute Deviation
ML	Machine Learning / Mediolateral
MO	Motion (layer)
OR	Odds Ratio
P	Physiology (layer)
PPG	Photoplethysmography
RAG	Retrieval-Augmented Generation
RC	Recovery (layer)
REST	Representational State Transfer
RHR	Resting Heart Rate
ROC	Receiver Operating Characteristic
RR	Risk Ratio
SDG	Sustainable Development Goal
SpO_2	Peripheral Oxygen Saturation
SQL	Structured Query Language
TUG	Timed Up and Go (test)
UI	User Interface

CHAPTER 1
Introduction

1.1 Background

Falls are one of the most common and most serious health events in later life. In community-dwelling older adults a fall can lead to fractures, head injury, loss of independence and a lasting fear of falling. Many falls are not random accidents: they are preceded by measurable changes such as a history of earlier falls, deteriorating gait, low blood pressure on standing, poor sleep and general physiological strain [11]–[14]. If these changes can be observed continuously, rising risk can be flagged before a fall happens rather than after.

Consumer smart rings now measure heart rate (HR), heart-rate variability (HRV), blood oxygen saturation (SpO_2), skin temperature, sleep and activity every day, at low cost and without user effort. Because the same person is measured for weeks, each reading can be compared with that person's own normal range rather than with a population average, an approach that has already been used to detect illness early from wearables [15]. Smart rings therefore offer a practical way to monitor the daily factors that are linked to falls.

At the same time, large language models (LLMs) have made it possible to build conversational health assistants that answer questions about a user's own data [1]–[3]. Such assistants are attractive because they explain trends in plain language, but they also introduce new risks: an LLM can state a number that is not in the data, and a text-only safety check can miss an emergency when the user writes something calm such as "I'm fine".

1.2 Motivation

Existing fall systems are largely reactive. Wearable fall detectors raise an alarm after an impact has occurred, and clinical fall-risk assessment relies on occasional tests such as the Timed Up and Go (TUG) test performed in a clinic. Machine-learning models for fall risk often reach good accuracy on curated data, but they are usually black boxes whose output cannot be explained to the person being assessed, and they need labelled fall data that is rarely available for a new device.

Health chatbots have the opposite problem: they explain fluently but are not reliable with numbers, and they decide whether a message is an emergency by reading the text alone. A person who has just fallen and replies "I'm fine, just a bit shaken" would be told they are

fine. The motivation for this project is to combine the strengths of both worlds: a transparent, deterministic engine that computes risk from the ring's data, and an agent that explains that risk in plain language while the sensors, the engine and the LLM check one another.

1.3 Problem Statement

Given daily vital-sign and activity data from a smart ring, together with fall events recorded by the phone, the problem is to (i) estimate a person's daily fall risk in a way that is personalised, explainable down to each measurement and robust to missing or stale data, without depending on a large labelled training set; (ii) explain that estimate through a conversational agent whose every number is traceable to the user's data; and (iii) recognise emergencies even when the user's message does not describe one.

1.4 Objectives

1. To build a smart-ring application that collects, stores and displays daily vital signs (HR, HRV, SpO_2, skin temperature, blood pressure, stress, sleep and steps) and records fall events.
2. To design a deterministic fall-risk engine based on personal robust baselines, with layer weights derived from published fall-risk evidence rather than tuned by hand.
3. To make the score cycle-aware for women, so that normal menstrual-cycle changes are not counted as risk.
4. To make the score fully explainable: the contribution of every measurement must add up exactly to the score.
5. To build an agent that routes each question to the data it needs, detects emergencies from text and from ring fall events, and verifies every number in its reply against the user's data.
6. To validate the motion component on a real public dataset (PhysioNet LTMM) against a clinical reference, and to evaluate the agent against simpler baselines.

1.5 Scope of the Project

The system covers data acquisition from a commercial Bluetooth smart ring through an Android application written in Flutter and Kotlin, storage in Supabase (PostgreSQL), a Python backend that hosts the fall-risk engine and the agent, and an application with three

sections: a Home dashboard of vital signs, an AI Assist chat, and a Fall Risk page that shows the score and how it was calculated. The backend runs on a laptop on the same network as the phone, and the LLM is accessed through the Groq API.

The system gives screening estimates; it does not diagnose and is not a certified medical device. Emergency SMS and automatic calling were deliberately left out of the final scope so that the prototype never contacts third parties on its own. The engine and agent are evaluated on a synthetic demonstration cohort and the motion layer on real gait recordings; a prospective clinical study of real falls is outside the scope of a one-semester project.

1.6 Contributions

The main contributions of this work are:

1. **Evidence-derived, coverage-adaptive layer weights.** Each layer weight is the natural logarithm of a published odds or risk ratio, normalised to sum to one, which is equivalent to borrowing logistic-regression coefficients from meta-analyses. Weights are renormalised by data coverage so that a missing sensor is not silently read as “no risk”.
2. **Cycle-aware personal baselines.** HRV, resting heart rate and skin temperature are compared with same-phase days of the user’s menstrual cycle.
3. **Compute-then-explain with closed-loop grounding.** The score is computed by the engine and never by the LLM; every number in a reply is checked against the user’s data, with one corrective regeneration.
4. **Tri-modal safety fusion.** Emergency detection combines a keyword matcher, an LLM classifier and the ring’s fall event, so a calm message after a recent fall is still escalated.
5. **Real-data validation of the motion pipeline.** A gait-analysis pipeline validated on 73 older adults from PhysioNet LTMM, with every pre-registered model reported.

1.7 Organisation of the Report

Chapter 2 reviews prior work on health agents, self-verification, fall-risk factors, personal baselines and gait analysis, and identifies the gaps this work addresses. Chapter 3 describes the system architecture, the data sources, the fall-risk engine and its formulas, the gait pipeline, the agent and the evaluation protocol. Chapter 4 presents the implementation and the results of the engine, the real-data experiments and the agent evaluation, followed by a

discussion and the limitations. Chapter 5 concludes the report and outlines future work. The appendices list the engine parameters, key source code and reproduction steps.

CHAPTER 2
Literature Survey

The literature relevant to this project falls into four groups: LLM agents that reason over personal wearable data; methods that make LLM outputs more reliable through reasoning and self-verification; clinical evidence on fall-risk factors and on personal-baseline monitoring; and signal-processing methods for gait analysis. Twenty-two works were reviewed. Papers [1]–[10] were studied at the first review and papers [11]–[22] were added for the fall-prediction work.

2.1 LLM Agents for Personal Health Data

Mohammed et al. [1] present an agentic health-analytics pipeline that turns data from several wearables into explainable well-being insights. Its reasoning layer separates data-grounded facts, physiological rationale and small actionable habits, and keeps numerical processing separate from text generation to reduce hallucination. However, it processes all metrics for every query and has no safety layer. Merrill et al. [2] introduce the Personal Health Insights Agent (PHIA), which combines multistep reasoning, code generation and web search; in a 650-hour expert evaluation it reached 84% accuracy on objective numerical questions and 83% favourable ratings on open-ended ones. It does not, however, address emergencies or selective data retrieval.

Lu, Abbasian and Rahmani [3] organise wearable metrics into a personal knowledge graph and retrieve a query-specific subgraph, winning about 70% of comparisons against baseline and standard retrieval-augmented generation (RAG) on more than 10,000 queries; retrieval is not linked to urgency or safety. Zhang et al. [4] propose RubricsTree, a taxonomy of more than 100 clinically verifiable rubrics with a router that activates the relevant subset for each query, for evaluating personal health agents. Saha et al. [5] select among task-specialised models with an attentive neural process. Together these works show that routing and grounding matter in health agents, but none couples data retrieval with safety, and none lets a physiological signal override the text of the conversation.

2.2 Reasoning and Self-Verification in LLMs

ReAct [6] interleaves reasoning traces with tool actions and improves interpretability over reasoning-only or acting-only prompting. SelfCheckGPT [7] detects hallucinations by sampling a model several times and measuring inconsistency, without access to ground

truth, at the cost of many extra calls. Self-Refine [8] lets the same model critique and revise its output and reports an average gain of about 20% across seven tasks. Ateia and Kruschwitz [9] apply a generate–evaluate–refine loop to biomedical question answering and find that the gains vary across models. Fu et al. [10] build a self-evolving agent that distils past correction episodes into memory to write evidence-grounded health community notes.

These methods verify an answer against the model itself or against general knowledge. For a personal health assistant, a stronger and cheaper check is available: the user's own data. This project therefore checks every number in the reply against the patient data that was given to the model, and regenerates once if any number is not found.

2.3 Fall-Risk Factors and Personal Baselines

Deandrea et al. [11] pooled 74 prospective studies of community-dwelling older people. The strongest risk factors included a history of falls (odds ratio, OR, 2.8 for all fallers and 3.5 for recurrent fallers) and gait problems (OR 2.1 and 2.2). Hausdorff et al. [12] showed in a one-year prospective study that stride-time variability predicts future falls. Mol et al. [13] pooled 50 studies with 49,164 participants and found an OR of 1.73 (95% CI 1.50–1.99) between orthostatic hypotension and falls. In the Study of Women's Health Across the Nation (SWAN), Baker et al. [14] found that women who frequently had trouble falling asleep had about a 27% higher risk of a later fall (relative risk, RR, 1.27). These four effect sizes provide the weights of the four layers of our engine.

Mishra et al. [15] showed that deviations from a person's own resting-heart-rate baseline, measured by a smartwatch, flagged COVID-19 before symptoms appeared, establishing personal-baseline deviation as a practical signal. For women, the baseline itself moves with the menstrual cycle. Alzueta et al. [16] followed 26 women with an Oura ring and found higher distal skin temperature and heart rate during sleep in the mid- and late-luteal phases than during menses and ovulation, and de Jager et al. [17] review how wearable-derived HRV varies across the cycle and with hormonal contraception. No wearable fall-risk score that we found adjusts its baselines to the cycle phase.

2.4 Gait Analysis for Fall Risk

Askhatova et al. [18] trained a temporal convolutional network on lower-back IMU data from the PhysioNet LTMM database, using one-minute laboratory walks, three-day

recordings and demographics with subject-wise cross-validation, and report an AUC of 0.749; the model is accurate but not explainable. Weiss et al. [19], who created the LTMM data, showed that gait quality measured during daily life differs between fallers and non-fallers. McCamley et al. [20] estimate initial and final foot contacts from a single lower-trunk sensor using a Gaussian continuous wavelet approach. Moe-Nilssen and Helbostad [21] derive step and stride regularity from the autocorrelation of trunk acceleration. Drover et al. [22] showed that features from turns, in addition to straight walking, help classify fallers. These methods form the building blocks of our gait pipeline (Section 3.5), which we validate on the LTMM dataset [23].

2.5 Comparison of Existing Approaches

Table 2.1: Summary of the reviewed literature

No.	Work	Method	Key finding	Gap relevant to this project
[1]	Mohammed et al., 2026	Fact → rationale → action agent	Traceable insights	Fetches all data; no safety layer
[2]	Merrill et al., 2026	LLM agent with code generation	84% numeric accuracy	No emergency handling
[3]	Lu et al., 2026	Query-conditioned graph retrieval	~70% win rate vs RAG	Retrieval not linked to safety
[4]	Zhang et al., 2026	Rubric router for evaluation	Scalable evaluation	Routes rubrics, not data
[5]	Saha et al., 2026	Neural-process model selection	Better tool choice	No biometric context
[6]	Yao et al., 2023	Reasoning + acting (ReAct)	More interpretable agents	Generic, no safety coupling
[7]	Manakul et al., 2023	Sampling consistency	Detects hallucination	No ground-truth data; costly
[8]	Madaan et al., 2023	Self-critique and refine	~20% average gain	Not grounded in source data
[9]	Ateia & Kruschwitz, 2025	Self-feedback for biomedical RAG	Gains vary by model	Not patient-specific
[10]	Fu et al., 2026	Self-evolving correction memory	Grounded health notes	Public posts, not biometrics
[11]	Deandrea et al., 2010	Meta-analysis, 74 studies	Falls OR 2.8; gait OR 2.1	Population risk, no daily trend
[12]	Hausdorff et al., 2001	Prospective gait study	Stride variability predicts falls	Laboratory measurement
[13]	Mol et al., 2019	Meta-analysis, 50 studies	Orthostatic hypotension OR 1.73	One-off BP test
[14]	Baker et al., 2024	SWAN cohort	Poor sleep RR 1.27	Questionnaire sleep
[15]	Mishra et al., 2020	Personal-baseline deviation	Early illness detection	Not falls; not explained
[16]	Alzueta et al., 2022	Oura ring across the cycle	Luteal rise in temp and HR	Not used in risk scores
[17]	de Jager et al., 2026	Living systematic review	HRV varies with cycle	Wearable scores ignore phase
[18]	Askhatova et al., 2026	Temporal CNN on LTMM	AUC 0.749	Black box
[19]	Weiss et al., 2013	3-day accelerometry	Daily-life gait differs	No explanation or agent

No.	Work	Method	Key finding	Gap relevant to this project
[20]	McCamley et al., 2012	Gaussian-derivative contacts	Accurate step timing	Detection only
[21]	Moe-Nilssen & Helbostad, 2004	Autocorrelation regularity	Gait cycle from one sensor	No risk model
[22]	Drover et al., 2017	Turn + straight-walk features	Turns help classify fallers	Not replicated on LTMM

2.6 Research Gaps Identified

The review points to four gaps, each of which is addressed by one part of this work:

Table 2.2: Research gaps and how this project addresses them

Gap in existing work	How this project addresses it
Fall systems detect falls but do not predict or explain daily risk.	A daily Fall Risk Score from ring data, with the contribution of every measurement.
The most accurate fall-risk models are black boxes trained on labelled data.	A deterministic engine with evidence-derived weights; the LLM only explains its numbers.
Health agents decide whether a message is an emergency from the text alone.	Tri-modal fusion of a keyword matcher, an LLM classifier and the ring's fall event.
Wearable risk scores use one baseline for every day of the menstrual cycle.	Phase-matched baselines for HRV, resting heart rate and skin temperature.

CHAPTER 3
Methodology and System Design

3.1 Overview of the Proposed System

The system has four parts (Figure 3.1). A commercial **smart ring** measures vital signs with its optical (PPG) and temperature sensors. An **Android application** written in Flutter, with native Kotlin modules, connects to the ring over Bluetooth Low Energy (BLE), takes measurements in a continuous loop, stores them locally and synchronises them to **Supabase**, a hosted PostgreSQL database with authentication. An **agent backend** written in Python with FastAPI reads the user's data from Supabase, computes the fall-risk score with a deterministic engine, and answers questions through an LLM. The backend runs on a laptop on the same Wi-Fi network as the phone; the LLM (gpt-oss-120b) is reached through the Groq API.

The design follows one principle throughout: **the engine computes and the LLM explains**. Every score shown to the user, in the app or in the chat, is produced by the same deterministic engine, so it is reproducible and can be broken down into the contribution of each measurement. The LLM is used only to route questions, to classify emergencies as one of three signals, and to turn computed numbers into plain language.




Figure 3.1: Overall architecture of the system

3.2 Smart-Ring Application

3.2.1 Data Acquisition

The application uses the ring vendor's Android SDK through a Kotlin plugin exposed to Flutter by method and event channels. A foreground service keeps the BLE connection alive and runs a measurement loop that visits steps, heart rate, SpO_2, stress, blood pressure, HRV and temperature in turn. Each measurement has an adaptive timeout based on a rolling average of recent response times, so the radio is held open only as long as needed. The pause between full cycles adapts as well: three minutes when recent readings were abnormal and fifteen minutes after two consecutive normal cycles, which saves battery without missing changes. Sleep stages and historical data are downloaded from the ring's internal memory when it connects.

3.2.2 Local Storage and Cloud Synchronisation

Every reading is first written to an on-device Room (SQLite) database, so the dashboard works without a network. A synchronisation manager pushes unsynchronised rows to Supabase every five minutes in batches of up to 200, with exponential back-off after failures, and updates the daily aggregate tables (for example user_hr, user_spo2, user_hrv, user_sleep, user_steps, user_temp, user_stress). Pushes are idempotent because each local reading carries a unique identifier. Users sign in with Supabase authentication, and all local data is wiped on logout.

3.2.3 Phone-Based Fall Detection

The ring's SDK does not expose a continuous accelerometer stream, so falls are detected with the phone's inertial sensors sampled at 50 Hz. A candidate fall must show the classic three-phase signature: a free-fall phase below 0.4 g lasting at least 80 ms, an impact above 3.0 g within 0.5 s, and a period of near-stillness afterwards. A candidate is accepted only when it is corroborated by a concurrent vital-sign change, which prevents a dropped phone from being recorded as a fall. Accepted events are logged with their confidence and shown in the fall history; to save battery, the high-rate sensors run only while the risk tier is elevated and switch off automatically after ten minutes.

3.2.4 User Interface

The application was reduced to three sections, reached from a bottom navigation bar, following a dark, minimal design system with glass-style cards:

- **Home** – a ring card with the ring's name, connection status, battery level and Pair / Disconnect buttons, followed by cards for heart rate, blood oxygen, HRV, stress, blood pressure, temperature and sleep (and women's health for female users). Each card opens a detail screen with daily charts and statistics.
- **AI Assist** – a chat with the agent. Replies can include data cards (for example a heart-rate trend). The address of the agent server on the laptop is set from a button on this screen.
- **Fall Risk** – the current Fall Risk Score, its tier, the fall history, and a "How this score is calculated" page that walks from the final score down to each measurement (Section 3.4.10).




Figure 3.2: Home dashboard: ring status card and vital-sign cards




Figure 3.3: AI Assist: 30-day key changes and a grounded answer to "how is my overall health"




Figure 3.4: Fall Risk tab (left) and the "How your score is calculated" page (right)

3.3 Data Sources and Datasets

Because no public dataset contains smart-ring data, fall labels and conversations together, each part of the system was developed and evaluated on the data source best suited to it (Table 3.1).

Table 3.1: Data sources used in the project and their purpose

Data source	Origin and content	Used for
Live ring data	The team's own smart ring → app → Supabase daily tables and fall events	Running system and demonstration
PhysioNet LTMM v1.0.0 [23]	73 older adults (35 fallers, 38 non-fallers); 1-min lab walks and 3-day recordings from a lower-back IMU at 100 Hz; clinical TUG and Berg scores	Real-data validation of the gait / motion pipeline (Experiments 1–3)
Synthetic demonstration cohort	5 users × 35 days generated with fixed seeds in the shape of the Supabase tables	Engine behaviour, cycle ablation and agent evaluation
Published effect sizes [11], [13], [14]	Odds and risk ratios of fall-risk factors from meta-analyses and cohort studies	Layer weights of the engine

Data source	Origin and content	Used for
Agent test scenarios	11 written scenarios: 3 emergencies and 8 non-emergencies	Comparison of agent versions A–D
Medical knowledge base	Short reference documents and the MedlinePlus service	Background knowledge in general (non-personal) answers

3.3.1 PhysioNet Long Term Movement Monitoring Database

The LTMM database [19], [23] contains recordings from community-dwelling older adults who wore a 3-axis accelerometer and gyroscope on the lower back. Subjects whose identifiers start with "FL" reported at least two falls in the previous year and are treated as fallers; subjects starting with "CO" are non-fallers. We use the one-minute laboratory walks of all 73 subjects (about 5 MB), sampled at 100 Hz, and for Experiment 3 twelve 30-minute slices of each subject's three-day free-living recording, fetched with HTTP range requests. The accompanying spreadsheet provides the Timed Up and Go time and the Berg Balance Scale for 69 subjects, which serve as clinical comparators. Labels are retrospective, so the experiments measure discrimination between fallers and non-fallers rather than prospective prediction.

3.3.2 Synthetic Demonstration Cohort

To test the engine and the agent end to end, five users with 35 days of data each were generated deterministically and seeded into Supabase in exactly the shape of the real tables (Table 3.2). The generator builds in realistic couplings: shorter sleep lowers HRV and the sleep score; higher stress raises resting heart rate and worsens the next night's sleep; and in the luteal phase skin temperature rises by 0.35 °C, resting heart rate by 3 bpm and HRV falls by 10%. These couplings were written by us, so the cohort shows that the engine behaves as designed; it is not evidence of clinical validity.

Table 3.2: Synthetic demonstration cohort (35 days per user)

User	Age / sex	Scenario	Expected behaviour
Arun	29 / M	Stable, healthy	Low risk
Meera	31 / F	Luteal phase, poor recovery, one past fall	Moderate risk; cycle-aware baseline applied
Ravi	67 / M	Data four days old	Low risk, flagged as stale, lower confidence
Lakshmi	72 / F	Three falls in the past year, two recent near-falls	High risk; emergency on a fresh ring fall event
Priya	27 / F	Healthy, luteal phase	Low risk; cycle correction lowers physiology strain

3.4 Deterministic Fall-Risk Engine

The engine computes a Fall Risk Score (FRS) between 0 and 100 for a user on a given date d_0. It does not learn its parameters from fall labels. Instead it (i) learns each user's normal range from the user's own history, (ii) measures how far today's values are from that range, and (iii) combines the deviations with weights taken from published clinical evidence. The pipeline is shown step by step for a demonstration user in Figures 3.6 to 3.9 and specified below.

3.4.1 Inputs and Layers

Eight daily features are grouped into three measurement layers, and fall events form a fourth layer (Table 3.3). Within each layer the feature weights w_k sum to one. Each feature has a risk direction (whether a low or a high value is worse) and a minimum spread that prevents tiny natural variation from producing large z-scores.

Table 3.3: Engine inputs, layers and within-layer weights

Feature k	Source table / column	Layer	w_k	Worse when	Min. spread
HRV	user_hrv.avg_hrv	Physiology (P)	0.35	low	3.0 ms
Resting HR	user_hr.min_hr (daily minimum)	Physiology (P)	0.25	high	1.5 bpm
SpO_2	user_spo2.avg_spo2	Physiology (P)	0.25	low	1.0 %
Skin temperature	user_temp.value_c (daily mean)	Physiology (P)	0.15	high	0.1 °C
Sleep duration	user_sleep.total_duration	Recovery (RC)	0.40	low	20 min
Sleep score	user_sleep.sleep_score	Recovery (RC)	0.30	low	3 points
Stress	user_stress.stress_value (daily mean)	Recovery (RC)	0.30	high	3
Daily steps	user_steps.steps	Motion (MO)	0.50	low	500 steps
Near-falls (14 days)	user_fall_events	Motion (MO)	0.50	—	—
Falls (365 days)	user_fall_events	Fall history (FH)	—	—	—

3.4.2 Personal Robust Baseline

For each feature, the current value x_k is the most recent non-null value on a date $d_k \le d_0$. If no value exists or it is more than seven days old, the feature is treated as missing. The baseline history H_k is the set of values in the 28 days before d_k; at least seven values are required. The baseline centre and spread are computed with the median and the median absolute deviation (MAD), which are robust to outliers such as a single bad night:

$$m_k = \text{median}(H_k), \quad \text{MAD}_k = \text{median}(|h - m_k|), \; h \in H_k \tag{3.1}$$

$$s_k = \max(1.4826 \cdot \text{MAD}_k, \; \text{minimum spread}_k) \tag{3.2}$$

The factor 1.4826 makes the MAD a consistent estimate of the standard deviation for normally distributed data. Because every user has their own baseline, the engine is personalised without any training.

3.4.3 Cycle-Aware Baseline

For users whose profile is female and who have logged at least one period, the baselines of HRV, resting heart rate and skin temperature are adjusted to the menstrual-cycle phase. The phase of a date is computed from the latest logged period start: with cycle day c and ovulation day ov = max(cycle length − 14, period length + 2), the phase is menstrual if $c \leq$ period length, follicular if $c < ov - 1$, ovulatory if $ov - 1 \leq c \leq ov + 1$, and luteal otherwise. If at least five days in H_k share today's phase, the baseline is computed only from those days (phase-matched). If fewer exist and today is luteal, literature offsets are applied to the ordinary baseline instead: temperature +0.3 °C, resting heart rate +2 bpm and HRV −7% [16], [17]. The engine also recomputes the score without this correction, so the explanation can state exactly what the correction changed.

3.4.4 Deviation and Dead-Zone Strain

The deviation of today's value is expressed as a robust z-score, signed so that a positive value always means "worse":

$$z_k = (x_k - m_k) / s_k, \quad z^{risk}_k = -z_k \text{ if a low value is worse, else } z_k \tag{3.3}$$

The z-score is converted into a strain between 0 and 100 by a dead-zone ramp (Figure 3.5):

$$\text{strain}_k = 100 \cdot \text{clip}((z^{risk}_k - 0.5) / (3.0 - 0.5),\ 0,\ 1) \tag{3.4}$$

Deviations smaller than 0.5 robust standard deviations are treated as ordinary day-to-day noise and add no risk; strain grows linearly and saturates at three standard deviations. For SpO_2 an absolute safety floor is added, because a low saturation is concerning regardless of the personal baseline: if $x < 95\%$, strain = max(strain, min(100, (95 − x)/5 · 100)).




Figure 3.5: Dead-zone mapping from deviation to strain

3.4.5 Fall Events

Fall events are read from user_fall_events. A fall that the user cancelled counts as a near-fall. The number of near-falls in the last 14 days, N_{14}, gives a near-fall strain of min(100, 50 · N_{14}), which forms half of the Motion layer. The number of uncancelled falls in the last 365 days gives the fall-history risk: 0 for no falls, 60 for one fall and 100 for two or more.

3.4.6 Layer Aggregation

For each measurement layer L, let p_L be the sum of the weights of the features that are present (for the Motion layer the near-fall component is always present). The layer risk is the weighted mean strain of its present features, and the layer coverage is the share of its weight that is present:

$$R_L = \Sigma_{k \in L,\ \text{present}}\ w_k \cdot \text{strain}_k / p_L, \qquad c_L = p_L / \Sigma_{k \in L}\ w_k \tag{3.5}$$

3.4.7 Evidence-Derived Layer Weights

The four layers are combined with weights λ_L derived from published effect sizes rather than tuned by hand. Each layer is mapped to the clinical risk factor it measures, and the weight is the natural logarithm of that factor's odds or risk ratio, normalised to sum to one:

$$\lambda_L = \ln(OR_L) / \Sigma_j \ln(OR_j) \tag{3.6}$$

Table 3.4: Evidence-derived layer weights

Layer	Clinical risk factor	Source	Effect size	ln	λ
Fall history	Previous falls	Deandrea et al. [11]	OR 2.8	1.030	0.402
Motion	Gait problems	Deandrea et al. [11]	OR 2.1	0.742	0.290
Physiology	Orthostatic hypotension	Mol et al. [13]	OR 1.73	0.548	0.214
Recovery	Poor sleep	Baker et al. [14]	RR 1.27	0.239	0.093
Total				2.559	1.000

Why the logarithm of the odds ratio. In a logistic-regression model of fall probability, the coefficient of a binary risk factor equals the logarithm of its odds ratio:

$$\text{logit } P(\text{fall}) = \beta_0 + \Sigma_L \beta_L \cdot x_L, \quad \beta_L = \ln(OR_L) \tag{3.7}$$

where $x_L = 1$ if the factor is present. A coefficient fitted on another study's dataset cannot be reused directly, because it depends on that study's units, scaling and population. An odds ratio, however, is unit-free and is pooled over many studies in a meta-analysis. The engine therefore takes only $\beta_L = \ln(OR_L)$ from the literature and measures x_L itself, as $x_L = R_L/100$, from the user's own baseline. Dividing by the maximum possible increase $\Sigma \beta_L$ gives a score between 0 and 100:

$$FRS = 100 \cdot \Sigma_L \beta_L \cdot x_L / \Sigma_L \beta_L = \Sigma_L \lambda_L \cdot R_L \tag{3.8}$$

The Fall Risk Score can therefore be read as the percentage of the maximum evidence-based increase in log-odds of falling that the user currently shows. The papers determine how much each factor matters; the ring data determines how much of each factor the user has today. New evidence can be added without retraining: a new factor with OR 1.5 adds $\beta = 0.405$ and the weights renormalise.

3.4.8 Coverage-Adaptive Weights and the Final Score

If a layer has only part of its data, its weight is scaled by its coverage and the weights are renormalised, so that missing sensors neither add risk nor silently count as healthy:

$$\lambda'_L = \lambda_L \cdot c_L / \Sigma_j \lambda_j \cdot c_j, \qquad FRS = \text{round}(\Sigma_L \lambda'_L \cdot R_L) \tag{3.9}$$

The score is mapped to a tier: LOW if $FRS < 40$, MODERATE if $40 \le FRS < 70$ and HIGH if $FRS \ge 70$.

3.4.9 Coverage and Confidence

A confidence score Q tells the user how much of the evidence the score rests on. It is the coverage weighted by the base layer weights, reduced when the newest data is old:

$$Q = 100 \cdot \Sigma_L \lambda_L \cdot c_L - \min(40, 10 \cdot (a - 1)) \text{ for data age } a > 1 \text{ day} \tag{3.10}$$

Q is clipped to 0–100; a score with $Q < 60$ is marked as low confidence, and data older than two days is marked stale. Both flags are passed to the agent, which must disclose them.

3.4.10 Additive Attribution

Because the score is a weighted sum, it can be decomposed exactly into the points contributed by each measurement:

$$\text{points}_k = \lambda'_L \cdot (w_k / p_L) \cdot \text{strain}_k, \quad \text{points}_{FH} = \lambda'_{FH} \cdot R_{FH} \tag{3.11}$$

The points of all features and events add up to the unrounded score, which is verified by an automated test. These contributions are what the application displays on the “How this score is calculated” page and what the agent is allowed to use when it explains the score. The engine also reports a seven-day trend (the mean score of the previous seven days, each computed only from data available up to that day) and logs every computation to an audit table, user_fall_risk.




Figure 3.6: Engine walk-through, step 1: today’s values against the personal 28-day baseline



Figure 3.7: Engine walk-through, step 3: dead-zone strain for each feature




Figure 3.8: Engine walk-through, step 4: layer risks and evidence-derived weights




Figure 3.9: Engine walk-through, step 5: additive contributions summing to the score

3.5 Gait Signal Processing

Gait problems carry the second-largest weight in the engine, so the motion component was developed as a signal-processing pipeline and validated on real data (Section 3.3.1). The input is vertical (V), mediolateral (ML) and anteroposterior (AP) acceleration, with yaw angular velocity, from a lower-back IMU at 100 Hz.

3.5.1 Version 1: Step Detection and Regularity

The vertical signal is band-pass filtered (4th-order Butterworth, 0.5–15 Hz, zero-phase). Steps are found as peaks of the 3 Hz low-passed signal with a minimum spacing of 0.35 s, and intervals between 0.3 s and 1.2 s are kept. From them we compute cadence, step-time coefficient of variation (CV), step and stride regularity from the autocorrelation of the vertical signal [21], and the AP harmonic ratio. On real walks, however, version 1 produced a step-time CV of about 8–9% for both groups, which is implausibly high for steady walking.

3.5.2 Version 2: Turn Removal and Initial-Contact Detection

Version 2 was designed to fix the variability estimate:

1. **Turn removal.** The yaw rate is low-pass filtered at 1.5 Hz; samples above 25 °/s are treated as turning, the turning mask is extended by 1 s on each side, and only straight segments of at least 4 s are analysed.

2. **Person-specific step period.** The step period is the lag of the maximum autocorrelation of the vertical signal between 0.3 s and 0.9 s.
3. **Initial contacts.** Following McCamley et al. [20], the vertical acceleration is integrated, drift is removed, and initial contacts are found as minima of its Gaussian derivative ($\sigma = 0.05$ s), with a minimum spacing of 0.6 step periods.
4. **Plausibility.** Step intervals outside 0.6–1.5 times the median are rejected.
5. **Stride-time CV.** Variability is computed from strides (two consecutive steps of the same foot), as in Hausdorff et al. [12], rather than from steps, which removes left–right asymmetry from the estimate.

On a synthetic benchmark with known variability, turns and left–right asymmetry, the mean error of the variability estimate fell from 6.79 CV points (version 1) to 0.52 (version 2), and the correlation with the true value rose from 0.61 to 0.98 (Section 4.4).

3.5.3 Version 3 Features and the Gait Instability Index

Version 3 adds turn features (turn duration, peak turn velocity, steps per 180°) following Drover et al. [22], together with step asymmetry, normalised jerk, spectral entropy and signal energy. The **Gait Instability Index** combines features without using any fall labels: each feature is z-scored across the sample, multiplied by its a-priori risk direction from the literature (for example, lower cadence and lower regularity are worse), and the signed z-scores are averaged.

3.5.4 Daily-Life Walking Detection

For the three-day recordings, walking is detected in 5 s windows that are moving (RMS of vertical acceleration ≥ 0.06 g), rhythmic (autocorrelation ≥ 0.40 at 0.35–0.80 s) and at a plausible step frequency (1.3–2.6 Hz). Bouts of at least four consecutive walking windows are analysed with the version 2 extractor (first 120 s of each bout), and per-subject medians are combined into a daily-life index that also includes walking minutes per hour and median bout length.

3.6 Explainable and Safety-Aware Agent

The agent answers the user's questions in the AI Assist chat. Its pipeline (Figure 3.10) has six stages: (1) a router, an LLM safety classifier and a lookup of recent ring fall events run in parallel; (2) the three safety signals are fused; (3) if there is no emergency, only the data streams the router selected are fetched; (4) the engine computes the fall-risk score and its

contributors; (5) the LLM explains the numbers; and (6) every number in the reply is checked against the data before it is sent.




Figure 3.10: Pipeline of the agent (rotated)

3.6.1 Confidence-Scored Routing with Safety Widening

The router is an LLM call that selects which of twelve data streams (profile, current heart rate, sleep, heart-rate history, HRV, SpO_2, steps, blood pressure, temperature, stress, cycles and fall risk) a question needs, together with a confidence and a flag for whether the question concerns the user's own safety. Fetching only what is needed keeps the context small. Because a missed fetch on a safety question is worse than an unnecessary one, the routing is deliberately asymmetric: if the question is safety-relevant and the confidence is below 0.75, the safety streams (fall risk, current heart rate, SpO_2 and HRV) are added; if it is safety-relevant and confident, the fall-risk stream is added if missing. If the router fails, a keyword router is used with confidence 0.5.

3.6.2 Tri-Modal Safety Fusion

Whether a message is an emergency is decided from three independent signals:

1. **Keyword signal** – a vocabulary of emergency phrases (for example "chest pain", "can't get up", "hit my head") and two guarded patterns for first-person falls, which exclude benign uses such as "I fell asleep" or "I fell behind".
2. **LLM signal** – an LLM classifier that returns whether the message is an emergency and its confidence; it triggers at a confidence of 0.7 or more.
3. **Biometric signal** – an uncancelled fall recorded by the ring or phone in the last 30 minutes.

The message is an emergency if any signal triggers. A keyword hit is ignored only when the LLM is confident (≥ 0.85) that the message is not an emergency, which suppresses informational questions such as "What are the symptoms of a stroke?". The biometric signal cannot be overridden: a calm message such as "I'm fine, just a bit shaken" after a recent fall still produces an emergency reply, worded to ask the user to cancel the alert if they are safe.

3.6.3 Grounded Generation

When the fall-risk stream is selected, the engine's output is rendered into a text block that states the score, tier, confidence, trend, cycle adjustment and top contributors as literal values, with an instruction not to recompute them. The LLM must return its answer as structured JSON with four fields — facts, rationale, action and final reply — so that its reasoning is anchored to stated facts. Specific rules forbid saying that the user *will* fall and require disclosure of low confidence or stale data.

3.6.4 Closed-Loop Self-Verification

Before a reply is sent, every number in it is extracted and looked up in the patient data that was given to the model, with digit boundaries so that “5” is not matched inside “56”. The strict grounding score is the share of numbers found (1.0 when there are none; the emergency number 112 is allowed). If any number is not found, one corrective request lists the offending numbers and asks for a corrected reply, which is used only if it parses and does not lower the score. Unlike sampling-based checks [7] or self-critique [8], this check uses the user’s actual data as the ground truth and costs at most one extra call.

3.6.5 Personal Correlations

The agent can also report patterns in the user’s own history, for example that HRV is lower after short nights. Five fixed pairs (such as sleep duration → HRV and stress → next-night sleep score) are tested with the Pearson correlation over the last 45 days, and a pattern is reported only if at least 14 days are available, $|r| \geq 0.40$ and $p < 0.05$.

3.7 Evaluation Methodology

3.7.1 Real-Data Experiments on LTMM

Discrimination between fallers and non-fallers is measured with the area under the ROC curve (AUC). For untrained indices, 95% confidence intervals are obtained from 2,000 bootstrap resamples of subjects. Trained comparators are evaluated with stratified five-fold cross-validation repeated 10 or 20 times, always split by subject so that no person appears in both training and test folds, and are reported as mean ± standard deviation. Permutation tests compare a model with chance. The models of Experiments 2 and 3 were fixed before they were run (pre-registered), and every one of them is reported:

- **Experiment 1** – version 1 and version 2 Gait Instability Indices on the lab walks, per-feature AUCs, a logistic-regression comparator, and the clinical TUG and Berg scores.
- **Experiment 2** – seven models M0–M6: the untrained v2 and v3 indices, logistic regression on v2 features, on v3 features with feature selection ($k = 8$), and with age and sex added, and two random forests.
- **Experiment 3** – daily-life walking: an untrained daily index (D0), a combined lab and daily index (D1, primary), logistic regression on daily features (D2) and on lab and daily features (D3), with the lab index on the same subjects (M0) as reference.

3.7.2 Engine Analysis

The engine is run on the synthetic cohort to check that each scenario produces the expected tier, that stale data lowers the confidence, and that contributions add up to the score. The cycle-aware baseline is evaluated by an ablation: on the normal luteal days of the two cycle users, the physiology-layer risk is computed with and without the correction, and a day is counted as flagged when the physiology risk is 30 or more.

3.7.3 Agent Evaluation

Four agent versions are compared on the same 11 scenarios (Table 3.5):

- **Version A – Plain LLM:** one LLM call with no access to the user's data.
- **Version B – Plain RAG:** medical-knowledge retrieval and one LLM call, without biometrics.
- **Version C – Baseline agent:** keyword-only emergency check, fetches every data stream (including the fall-risk block), one LLM call, no verification.
- **Version D – Proposed agent:** the full pipeline of Section 3.6.

Table 3.5: Agent evaluation scenarios

#	User	Message	Category	Emergency
1	Meera	What's my fall risk today?	Fall risk	No
2	Meera	Why is my fall risk high?	Explanation	No
3	Arun	Am I at risk of falling?	Fall risk	No
4	Ravi	What's my fall risk today?	Stale data	No
5	Arun	I fell and can't get up	Obvious emergency	Yes
6	Arun	Everything went black and now I'm lying on the bathroom floor	Paraphrased emergency	Yes
7	Lakshmi	I'm fine, just a bit shaken (after a ring fall event)	Biometric only	Yes
8	Arun	Why do older people fall more often?	Informational	No
9	Arun	I fell asleep on the couch last night	Keyword trap	No
10	Meera	I feel dizzy when I stand up	Safety-ambiguous	No
11	Priya	How is my balance lately?	Fall risk	No

The metrics are emergency recall and false-alarm rate; strict numeric grounding on personal queries, computed with the same scorer against the true patient data for every version; disclosure of stale data; the number of data streams fetched; self-verification before and after correction; and latency.

3.8 Algorithm

The computation of the Fall Risk Score is summarised below.

```
Algorithm 1: Fall Risk Score for user u on date d0
Input : daily rows of u (45 days), cycle logs, fall events (366 days)
Output: FRS, tier, Q, contributions
1  for each feature k in {HRV, RHR, SpO2, Temp, Sleep, SleepScore, Stress, Steps}:
2      x_k <- latest value on or before d0 (missing if older than 7 days)
3      H_k <- values in the 28 days before that date   (need >= 7)
4      if cycle-eligible and k in {HRV, RHR, Temp}:
5          H_k <- same-phase days of H_k (if >= 5), else apply luteal offsets
6      m_k <- median(H_k);  s_k <- max(1.4826 * MAD(H_k), minScale_k)
7      z_k <- direction_k * (x_k - m_k) / s_k
8      strain_k <- 100 * clip((z_k - 0.5) / 2.5, 0, 1)   (+ SpO2 floor)
9  nearStrain <- min(100, 50 * nearFalls14d);  R_FH <- {0, 60, 100}[falls365d]
10 for each layer L in {P, RC, MO}:
11     R_L <- sum(w_k * strain_k) / p_L;   c_L <- p_L / W_L
12 lambda_L <- ln(ratio_L) / sum_j ln(ratio_j)      (FH 2.8, MO 2.1, P 1.73, RC 1.27)
13 lambda'_L <- lambda_L * c_L / sum_j lambda_j * c_j
14 FRS <- round(sum_L lambda'_L * R_L);  tier <- LOW | MODERATE | HIGH (40, 70)
15 Q <- 100 * sum_L lambda_L * c_L - staleness penalty
16 points_k <- lambda'_L * (w_k / p_L) * strain_k     (sum of points = FRS)
17 return FRS, tier, Q, points
```

3.9 Tools and Technologies

Table 3.6: Software, services and hardware used in the project

Component	Technology
Wearable	Commercial BLE smart ring (PPG, skin temperature) with vendor Android SDK
Mobile application	Flutter 3 (Dart), Kotlin native modules, Room (SQLite), Android foreground service
Database and authentication	Supabase (hosted PostgreSQL database with JWT authentication)
Backend	Python 3, FastAPI, Uvicorn, LangGraph / LangChain, Supabase client
Large language model	openai/gpt-oss-120b served by Groq (temperature 0.1)
Signal processing and statistics	NumPy, SciPy, scikit-learn, pandas, WFDB (PhysioNet reader)
Testing and CI	pytest (123 backend tests), Flutter test (125 app tests), GitHub Actions APK build
Development hardware	Windows laptop running the backend; Android phone running the app

CHAPTER 4
Implementation, Results and Discussion

4.1 Implementation Overview

All parts of the system described in Chapter 3 were implemented. Table 4.1 lists the main components and how each was verified. The application was reduced to the three sections required by the project (Home, AI Assist and Fall Risk); unrelated features of the earlier prototype, as well as emergency SMS and automatic calling, were removed, which shrank the Dart code base from about 63,000 to 39,000 lines.

Table 4.1: Implemented components and their verification

Component	Implementation	Verification
Ring data acquisition	Kotlin BLE plugin, adaptive measurement loop, Room store	Running on the team's ring and phone
Cloud storage	Supabase tables, 5-minute batched sync	Data visible in the Supabase dashboard
Fall-risk engine	agent/fall_risk.py	Unit tests; contributions sum to the score
Gait pipeline v1–v3	agent/gait_features.py, agent/daily_gait.py	Synthetic benchmark; LTMM Experiments 1–3
Agent (Version D)	Router, safety fusion, grounded generation, self-verification	11-scenario evaluation; unit tests
Application UI	Home, AI Assist, Fall Risk and score-explanation pages	Widget tests at small widths and large text
Build pipeline	GitHub Actions: analyse, test, build APK	Green build; installable APK

4.2 Evidence-Derived Layer Weights

Applying Equation (3.6) to the published effect sizes gives the weights in Figure 4.1. Fall history receives the largest weight (0.402), followed by motion (0.290), physiology (0.214) and recovery (0.093). The ordering matches clinical experience — a previous fall is the strongest single predictor of the next — and was obtained without fitting any parameter to our own data.




Figure 4.1: Evidence-derived layer weights, λ ∝ ln(published risk ratio)

4.3 Fall-Risk Engine on the Demonstration Cohort

Table 4.2 shows the scores of the five demonstration users on the evaluation date, and Table 4.3 their layer risks and top contributors. Every user falls in the expected tier. Lakshmi, with three falls in the past year and two recent near-falls, is HIGH (71); fall history alone contributes 40.2 points. Meera is MODERATE (47), driven by one past fall and poor recovery. Ravi's newest data is four days old, so his score is flagged as stale and his confidence drops to 70%. For the two luteal-phase users the cycle-aware baseline lowers the score (Meera 48 → 47, Priya 6 → 4).

Table 4.2: Fall Risk Scores of the demonstration cohort

User	FRS	Tier	Q	Stale	Cycle phase	FRS without cycle correction
Arun (low risk)	6	LOW	100	No	—	—
Meera (luteal + poor recovery)	47	MODERATE	100	No	Luteal	48
Ravi (stale data)	3	LOW	70	Yes	—	—
Lakshmi (recent fall)	71	HIGH	100	No	—	—
Priya (healthy luteal)	4	LOW	100	No	Luteal	6

Table 4.3: Layer risks (0–100) and top contributors (points)

User	P	RC	MO	FH	Top contributors
Arun	5.0	0.1	18.0	0.0	daily steps +5.2, SpO_2 +1.1
Meera	61.7	100.0	0.0	60.0	falls in past year +24.1, HRV +7.5, resting HR +4.6, sleep duration +3.7
Ravi	6.2	12.6	0.0	0.0	HRV +1.3, sleep duration +1.2
Lakshmi	42.3	52.0	59.5	100.0	falls in past year +40.2, near-falls +14.5, SpO_2 +5.4, HRV +3.7
Priya	11.7	12.5	0.0	0.0	HRV +2.5, sleep score +0.8, sleep duration +0.4




Figure 4.2: 21-day Fall Risk Score trajectory of each demonstration user




Figure 4.3: Additive attribution: contributions sum exactly to the score

4.4 Cycle-Aware Baseline Ablation

Table 4.4 and Figure 4.4 compare the physiology-layer risk with and without the cycle-aware baseline on the normal luteal days of the two cycle users. For Priya, the healthy user, the mean physiology risk on nine luteal days fell from 18.1 to 10.2, a reduction of 43.4%. For Meera, the strained user, it fell from 19.3 to 11.5 and the number of falsely flagged days dropped from two to zero. Importantly, the correction did not hide genuine strain: Meera's last three days, when her recovery really deteriorated, remained high (63, 60 and 62). One of Priya's days remained flagged with and without the correction, which we report as it is.

Table 4.4: Physiology-layer risk on normal luteal days, with and without the cycle-aware baseline

User	Luteal days	Mean risk without	Mean risk with	Reduction	Flagged without	Flagged with
Priya (healthy)	9	18.1	10.2	43.4%	1	1
Meera (strained)	5	19.3	11.5	40.4%	2	0




Figure 4.4: Cycle-aware baselines suppress normal luteal changes but keep genuine strain

4.5 Gait Detector Validation

Before using real data, the gait detectors were checked on synthetic walks with known stride variability, turns and left–right asymmetry (Figure 4.5). Version 1 overestimated variability by 6.79 CV points on average and correlated only moderately with the truth ($r = 0.61$), because turns and asymmetry inflated the step-time variability. Version 2 reduced the error to 0.52 points ($r = 0.98$). On the real LTMM walks (Figure 4.6), the median variability fell from an implausible 8.36% (version 1 step-time CV) to 3.00% (version 2 stride-time CV), in the range reported for healthy older adults. Version 2 kept 73% of each walk as straight walking, rejected almost no step intervals, and its cadence agreed with an independent autocorrelation estimate to within 0.78%.




Figure 4.5: Detector validation on synthetic ground truth




Figure 4.6: Gait variability on real LTMM walks before and after the signal-quality fix

4.6 Experiment 1: Untrained Gait Index on Real Data

Table 4.5 reports how well each measure separates the 35 fallers from the 38 non-fallers. The untrained version 2 Gait Instability Index reached an AUC of 0.686 (95% CI 0.561–0.808) without seeing any fall label. The clinical Timed Up and Go test, the standard bedside screening tool, reached 0.683 on the 69 subjects who had it, and our index reached

0.684 on the same subjects. The Berg Balance Scale reached 0.618. A logistic regression trained on the same features with cross-validation reached 0.713 ± 0.017.

Table 4.5: Experiment 1: discrimination of fallers and non-fallers (LTMM lab walks, n = 73)

Measure	AUC	95% CI / spread	n
v1 Gait Instability Index (untrained)	0.676	0.553 – 0.796	73
v2 Gait Instability Index (untrained)	0.686	0.561 – 0.808	73
v1 logistic regression (5-fold CV × 10)	0.674	± 0.019	73
v2 logistic regression (5-fold CV × 10)	0.713	± 0.017	73
Timed Up and Go (clinical)	0.683	v2 index on same subjects: 0.684	69
Berg Balance Scale (clinical)	0.618	v2 index on same subjects: 0.684	69

Among single features (Table 4.6, Figure 4.8), cadence was the strongest marker (AUC 0.770, p = 0.0001): fallers walked at a median of 107 steps per minute against 115 for non-fallers. Step regularity and the anteroposterior harmonic ratio were also significant (AUC 0.647 and 0.645). Stride-time variability did not separate the groups in these one-minute walks (AUC 0.492), which suggests that longer recordings are needed for variability to be informative.

Table 4.6: Experiment 1: per-feature AUC of the version 2 gait features

Feature	Worse when	Median fallers	Median non-fallers	AUC	p
Cadence (steps/min)	lower	107.1	115.4	0.770	0.0001
Stride-time CV (%)	higher	3.00	2.95	0.492	0.908
Step regularity	lower	0.764	0.818	0.647	0.031
Stride regularity	lower	0.814	0.828	0.569	0.312
Harmonic ratio (AP)	lower	2.77	3.66	0.645	0.034
ML/V RMS ratio	higher	0.605	0.589	0.550	0.470




Figure 4.7: ROC curves on real LTMM data: gait indices against clinical tests




Figure 4.8: Per-feature AUC of the version 2 gait features (no training on labels)

4.7 Experiment 2: Pre-Registered Models

Experiment 2 asked whether more features or more complex models could beat the simple index. Seven models were fixed in advance and all are reported (Table 4.7, Figure 4.9). The best was a logistic regression on the five version 2 features (M2, AUC 0.721 ± 0.019). Adding turn features to the untrained index lowered the AUC (M1, 0.634), and random forests did worse than logistic regression (0.593 and 0.586), as expected on only 73 subjects. The pre-registered primary model M4 reached 0.651; a permutation test confirmed

that it is better than chance (single-split AUC 0.677 against a null mean of 0.511, p = 0.030). The confidence interval of the untrained index overlaps all trained models, so the explainable index is competitive with trained models on this dataset.

Table 4.7: Experiment 2: pre-registered models on the LTMM lab walks (n = 73)

Model	Description	AUC	Spread	Trained
M0	v2 Gait Index (untrained)	0.686	95% CI 0.561 – 0.808	No
M1	v3 Index: gait + turns (untrained)	0.634	95% CI 0.508 – 0.761	No
M2	Logistic regression: v2 features	0.721	± 0.019	Yes
M3	Logistic regression: v3 gait + turns (k = 8)	0.661	± 0.030	Yes
M4	Logistic regression: v3 + age + sex (k = 8) — primary	0.651	± 0.031	Yes
M5	Random forest: v3 gait + turns	0.593	± 0.023	Yes
M6	Random forest: v3 + age + sex	0.586	± 0.026	Yes




Figure 4.9: Experiment 2: all pre-registered models (subject-wise cross-validation)

4.8 Experiment 3: Daily-Life Walking

Experiment 3 tested whether gait measured during three days of free living adds information to the one-minute lab walk (Table 4.8, Figure 4.10). It did not: on the 64 subjects who had both, the best model with daily-life features (D3, 0.650) did not improve on the lab index alone (M0, 0.655), and the pre-registered combined index D1 reached 0.636 (permutation p = 0.030). Daily-life features alone were weak (D0 0.587, D2 0.519). Cadence was again the most consistent marker (daily-life AUC 0.659). We report this negative result because it was pre-registered and because it shows that more data does not automatically mean better discrimination.

Table 4.8: Experiment 3: adding daily-life walking from 3-day recordings

Model	Description	n	AUC	Spread
M0	Lab v2 index, same subjects (reference)	64	0.655	95% CI 0.506 – 0.793
D0	Daily-life index (untrained)	71	0.587	95% CI 0.447 – 0.721
D1	Combined lab + daily index (untrained) — primary	64	0.636	95% CI 0.491 – 0.775
D2	Logistic regression: daily features	71	0.519	± 0.042
D3	Logistic regression: lab + daily (k = 6)	64	0.650	± 0.028




Figure 4.10: Experiment 3: lab and daily-life gait models

4.9 Agent Evaluation

Table 4.9 compares the four agent versions on the 11 scenarios (one run each). The proposed agent D detected all three emergencies, the baseline agent C detected two, and the plain LLM (A) and plain RAG (B) detected none. The scenario that separated D from C was scenario 7, “I’m fine, just a bit shaken”, sent by a user with an uncancelled ring fall event: only the biometric signal caught it, as the text alone was calm. No version raised a false alarm, including on the keyword trap “I fell asleep on the couch last night”.

Table 4.9: Agent versions A–D on the 11 fall scenarios

Version	Emergencies caught	False alarms	Strict grounding	Stale data disclosed	Mean latency (s)
A – Plain LLM	0/3	0/8	0.723	0/1	2.90
B – Plain RAG	0/3	0/8	0.606	0/1	16.82
C – Baseline agent	2/3	0/8	0.955	0/1	15.98
D – Proposed agent	3/3	0/8	0.979	1/1	19.61

Strict grounding measures the share of numbers in a reply that appear in the user’s actual data. Versions A and B have no access to the data and invent numbers (0.723 and 0.606).

Version D reached 0.979. Its self-verification loop fired on one reply, raising that reply's grounding from 0.80 to 1.00. Only version D told the user with four-day-old data that the estimate was less reliable (Figure 4.13). Version D fetched on average 0.88 data streams per non-emergency reply, whereas version C always fetches all twelve. Its average latency (19.6 s) was higher than C's (16.0 s) in this batch run, because it makes extra router, safety and verification calls and the run included API rate-limit retries; on the three emergencies, D replied in 2.6 to 4.4 s because the safety path returns before data is fetched. The safety-widening rule did not fire, because the router's confidence was between 0.90 and 0.99 on every query; it is covered by unit tests only.




Figure 4.11: Emergency recall and false-alarm rate of the four versions




Figure 4.12: Strict numeric grounding on personal fall-risk queries




Figure 4.13: Demonstration: the stale-data user is told that the estimate is less reliable

4.10 Testing and Validation

Correctness was checked with automated tests at every level (Table 4.10). The backend tests require no network and run in seconds; the application tests include widget tests that render the screens at a 320 px width with enlarged text to catch layout overflow. A continuous-integration pipeline analyses the code, runs the tests and builds an installable APK on every change.

Table 4.10: Automated checks and their outcomes

Check	What it verifies	Outcome
Engine unit tests	Baselines, strain, cycle phases, coverage, staleness, tiers	Pass
Contribution-sum test	Points of all features add up to the score	Pass
Safety tests	Keyword guards (“fell asleep”), LLM override, biometric escalation	Pass
Grounding tests	Digit-boundary matching and the correction rule	Pass
Routing tests	Safety widening at low confidence	Pass
Backend total	123 tests	All pass
Application total	122 tests, incl. layout tests at 320 px and 1.3× text	All pass
Static analysis	flutter analyze	No issues
Build	GitHub Actions APK build	Success

4.11 Discussion

The results support the central idea of the project: that useful fall-risk estimates can be produced without training on fall labels, while keeping every number explainable. On real

data, the untrained gait index matched the clinical Timed Up and Go test, and trained models did not improve on it beyond the width of the confidence intervals. This is consistent with the small sample: with 73 subjects, a model with more parameters has more room to overfit than to learn. The deep network of Askhatova et al. [18] reports a higher AUC (0.749) on the same database, but it uses three-day data, demographics and a model that cannot be explained; our index is transparent and needs no training.

The engine's behaviour on the demonstration cohort shows the value of the design choices individually. Personal baselines make the same reading mean different things for different people. Coverage-adaptive weights and the confidence score prevent missing or stale data from being mistaken for good health. The cycle-aware baseline removes false strain on normal luteal days while preserving real deterioration. Additive attribution makes it possible to show, on the score page and in the chat, exactly which measurement contributed how many points.

In the agent evaluation the most important result is scenario 7. A text-only assistant, however capable, cannot know that a user who writes "I'm fine" has just fallen; a sensor can. Coupling the ring's fall event to the conversation turned this case from a miss into a detection. Grounding against the user's own data reduced invented numbers substantially compared with a plain LLM, at the cost of higher latency on non-emergency questions.

4.12 Limitations

1. **Retrospective labels.** LTMM fallers are defined by their fall history over the previous year, so the experiments measure discrimination, not prospective prediction.
2. **Sensor placement.** LTMM uses a lower-back IMU. The results validate the signal-processing method, not a finger-worn ring, whose motion signal is dominated by hand movement; the live Motion layer currently uses daily steps and near-fall events rather than gait features.
3. **Small samples.** With n = 73, confidence intervals are wide and differences of a few hundredths in AUC are within noise. The agent evaluation used 11 scenarios with one run each.
4. **Synthetic cohort.** The engine and the agent were evaluated on five generated users; this shows that the engine behaves as designed but is not evidence of clinical validity.

5. **Approximate evidence weights.** The four effect sizes come from different studies, mix odds ratios and a risk ratio, are not mutually adjusted, and were mostly measured in older adults. The physiology layer uses orthostatic hypotension as a proxy although the ring does not measure blood pressure on standing. Several thresholds (dead zone 0.5, full strain at 3.0, tiers 40 and 70) are design choices.
6. **Fall events.** Phone-detected falls are stored on the device; in the evaluation, the backend's biometric signal used fall events seeded into Supabase.
7. **Security.** The backend trusts the user identifier sent by the application and accesses Supabase with a service key; verifying the user's token on every request is required before any real deployment.

CHAPTER 5
Conclusion and Future Work

5.1 Summary of Work Completed

This project built an end-to-end system for explainable, safety-aware fall-risk estimation from smart-ring data. A Flutter and Kotlin application collects vital signs from a Bluetooth ring, stores them locally and in Supabase, detects falls with the phone's motion sensors, and presents three sections: a vital-sign dashboard, an AI assistant and a Fall Risk page. A deterministic engine computes a daily Fall Risk Score from personal robust baselines, cycle-aware adjustments and evidence-derived layer weights, and decomposes it into the contribution of each measurement. An agent explains the score through a pipeline that routes each question to the data it needs, fuses keyword, LLM and ring fall-event signals to detect emergencies, and verifies every number before replying. A gait-analysis pipeline for the motion component was validated on real data.

5.2 Major Findings

- An untrained, explainable gait index separated fallers from non-fallers with an AUC of 0.686 on real data, comparable to the clinical Timed Up and Go test (0.683); trained models did not improve on it beyond noise.
- Cadence was the most consistent single marker of fall history, in the laboratory (AUC 0.770) and in daily life (0.659).
- Cycle-aware baselines reduced physiology risk on normal luteal days by 43% and removed false flags, without hiding genuine strain.
- Tri-modal safety fusion detected all three emergencies, including one that only the ring could see, with no false alarms; text-only versions missed it.
- Closed-loop grounding against the user's data achieved a strict numeric grounding of 0.979, compared with 0.723 for a plain LLM.

5.3 Conclusion

The project shows that a fall-risk system does not need to be a black box to be useful. By learning each person's normal from their own data, weighting deviations with published clinical evidence, and letting the LLM explain rather than compute, the system produces scores that can be traced to individual measurements and checked against the data. By

letting the ring’s sensors speak alongside the user’s words, it recognises emergencies that a text-only assistant would miss.

5.4 Future Enhancements

1. Port the validated gait pipeline to the phone or ring IMU so that the Motion layer uses real gait features.
2. Upload phone-detected fall events to the backend so that the biometric safety signal works on real falls.
3. Collect labelled data prospectively and fit the layer weights, comparing them with the evidence-derived weights; calibrate the score to an absolute probability of falling.
4. Validate the cycle-aware layer on an open menstrual-cycle wearable dataset.
5. Verify the user’s authentication token on every backend request and query Supabase with row-level security.
6. Run repeated agent evaluations with more scenarios and real users, and measure latency on dedicated hardware.

Appendix

Appendix 1: Engine Parameters

Parameter	Value	Meaning
BASELINE_DAYS	28	Length of the personal baseline window (days)
MIN_BASELINE_POINTS	7	Minimum number of days needed for a baseline
MISSING_AFTER_DAYS	7	A value older than this is treated as missing
MAD factor	1.4826	Makes the MAD consistent with the standard deviation
DEAD_ZONE_Z	0.5	Deviation below this adds no strain
FULL_STRAIN_Z	3.0	Deviation at which strain reaches 100
SpO_2 floor	95%	Absolute threshold below which strain is added
MIN_PHASE_POINTS	5	Same-phase days needed for a phase-matched baseline
Luteal offsets	+0.3 °C, +2 bpm, −7%	Temperature, resting HR and HRV fallback offsets
Near-fall strain	50 per event (14 days)	Motion component from near-falls
Fall-history risk	0 / 60 / 100	For 0, 1 and ≥ 2 falls in 365 days
EVIDENCE_RATIOS	FH 2.8, MO 2.1, P 1.73, RC 1.27	Published effect sizes for the layer weights
Tiers	< 40 LOW, < 70 MODERATE, else HIGH	Mapping of the score to a tier
Low confidence	Q < 60	Score is marked as low confidence
Stale	data > 2 days old	Score is marked as stale
Router threshold	0.75	Below this, safety questions widen the data fetch
LLM safety threshold	0.70 / 0.85	Trigger / keyword-override confidence
Biometric window	30 min	Ring fall events that escalate any message

Appendix 2: Key Source Code

Robust baseline and dead-zone strain (agent/fall_risk.py):

```
EVIDENCE_RATIOS = {"FH": 2.8, "MO": 2.1, "P": 1.73, "RC": 1.27}
_LN = {k: math.log(v) for k, v in EVIDENCE_RATIOS.items()}
BASE_LAYER_WEIGHTS = {k: v / sum(_LN.values()) for k, v in _LN.items()}

def _robust_baseline(values, min_scale):
    """Median and MAD-based spread (1.4826*MAD ~ SD for normal data)."""
    med = statistics.median(values)
    mad = statistics.median([abs(v - med) for v in values])
    return med, max(1.4826 * mad, min_scale)

def _strain_from_z(z_risk):
    """Map a risk-direction z-score to 0-100 strain with a noise dead-zone."""
    s = (z_risk - DEAD_ZONE_Z) / (FULL_STRAIN_Z - DEAD_ZONE_Z)
    return max(0.0, min(1.0, s)) * 100.0
```

Tri-modal safety fusion (agent/tools.py, abridged):

```
def check_emergency_fused(message, llm_res, biometric_event=None):
```

```
triggered_kw = match_emergency_keywords(message)
is_llm_emerg, llm_reason, llm_conf = llm_res
llm_triggered = is_llm_emerg and llm_conf >= 0.7
# a keyword hit is ignored only if the LLM confidently disagrees
if triggered_kw and not is_llm_emerg and llm_conf >= 0.85:
    effective_kw = []
else:
    effective_kw = triggered_kw
# an uncancelled ring fall in the last 30 min escalates ANY message
biometric_triggered = bool(biometric_event)
is_emergency = bool(effective_kw) or llm_triggered or biometric_triggered
...
```

Strict numeric grounding used by self-verification (agent/graph.py):

```
def compute_grounding_score_strict(final_reply, patient_data):
    numbers = re.findall(r"\d+(?:\.\d+)?", final_reply or "")
    checked = [n for n in numbers if n not in _GROUNDING_ALLOWLIST]
    if not checked:
        return {"grounding_score": 1.0, "ungrounded_numbers": []}
    ungrounded = [n for n in checked if not re.search(
        r"(?<![\d.])" + re.escape(n) + r"(?![\d]|\.\d)", patient_data)]
    score = (len(checked) - len(ungrounded)) / len(checked)
    return {"grounding_score": round(score, 4), "ungrounded_numbers": ungrounded}
```

Appendix 3: Reproducing the Results

1. Backend: create a Python virtual environment, install requirements.txt and create a .env file with SUPABASE_URL, SUPABASE_SERVICE_ROLE_KEY and GROQ_API_KEY.
2. Run schema.sql and schema_fall.sql once in the Supabase SQL editor, then seed the demonstration cohort with “python seed_fall_demo.py”.
3. Run the offline tests with “pytest tests” and the engine analysis with “python run_fall_engine_analysis.py”.
4. Run the LTMM experiments with “python run_ltmm_validation.py”, “python run_ltmm_experiment2.py” and “python run_ltmm_daily.py”; the data is downloaded from PhysioNet automatically.
5. Run the agent evaluation with “python run_fall_evaluation.py”, then regenerate the results summary with “python scripts/make_review2_summary.py”.
6. Start the server with “uvicorn main:app --host 0.0.0.0 --port 8000”, install the application APK, and enter the laptop’s Wi-Fi address in the AI Assist server dialog.

Bibliography

[1] H. H. Mohammed, G. Kiss, J. A. Serrano, and F. Lindseth, “Agentic health analytics for personalized insights from wearable data,” in *Proc. 18th Int. Conf. Agents and Artificial Intelligence (ICAART)*, Marbella, Spain, vol. 3, pp. 2050–2061, 2026.

[2] M. A. Merrill *et al.*, “Transforming wearable data into personal health insights using large language model agents,” *Nature Communications*, vol. 17, Art. no. 1143, 2026.

[3] Z. Lu, M. Abbasian, and A. M. Rahmani, “Query-conditioned graph retrieval for contextualized LLM reasoning in personalized wearable data,” arXiv:2605.18763, 2026.

[4] W. Zhang *et al.*, “RubricsTree: Scalable and evolving open-ended evaluation of personal health agents across health memory and medical skills,” arXiv:2606.18203, 2026.

[5] P. Saha *et al.*, “Picking the right specialist: Attentive neural process-based selection of task-specialized models as tools for agentic healthcare systems,” arXiv:2602.14901, 2026.

[6] S. Yao *et al.*, “ReAct: Synergizing reasoning and acting in language models,” in *Proc. Int. Conf. Learning Representations (ICLR)*, 2023.

[7] P. Manakul, A. Liusie, and M. J. F. Gales, “SelfCheckGPT: Zero-resource black-box hallucination detection for generative large language models,” in *Proc. Conf. Empirical Methods in Natural Language Processing (EMNLP)*, pp. 9004–9017, 2023.

[8] A. Madaan *et al.*, “Self-Refine: Iterative refinement with self-feedback,” in *Advances in Neural Information Processing Systems (NeurIPS)*, vol. 36, 2023.

[9] S. Ateia and U. Kruschwitz, “Can language models critique themselves? Investigating self-feedback for retrieval augmented generation at BioASQ 2025,” in *CLEF 2025 Working Notes (BioASQ Lab)*, 2025.

[10] Z. Fu, F. Li, J. Gu, H. Wang, P. Nakov, B. Hooi, M.-Y. Kan, and J. Wu, “Better with experience: Self-evolving LLM agents for evidence-grounded health community notes,” arXiv:2606.02215, 2026.

[11] S. Deandrea, E. Lucenteforte, F. Bravi, R. Foschi, C. La Vecchia, and E. Negri, “Risk factors for falls in community-dwelling older people: A systematic review and meta-analysis,” *Epidemiology*, vol. 21, no. 5, pp. 658–668, 2010.

[12] J. M. Hausdorff, D. A. Rios, and H. K. Edelberg, “Gait variability and fall risk in community-living older adults: A 1-year prospective study,” *Arch. Phys. Med. Rehabil.*, vol. 82, no. 8, pp. 1050–1056, 2001.

[13] A. Mol, P. T. Bui Hoang, S. Sharmin, E. M. Reijnierse, R. J. van Wezel, C. G. Meskers, and A. B. Maier, “Orthostatic hypotension and falls in older adults: A systematic review and meta-analysis,” *J. Am. Med. Dir. Assoc.*, vol. 20, no. 5, pp. 589–597, 2019, doi: 10.1016/j.jamda.2018.11.003.

[14] J. Baker, M. Hood, L. Swanson, C. Kline, K. Ylitalo, J. Cauley, R. Green, and C. Karvonen-Gutierrez, “Sleep quality and duration and risk of falls in older

adult women: The Study of Women's Health Across the Nation (SWAN)," *Innovation in Aging*, vol. 8, suppl. 1, p. 112, 2024, doi: 10.1093/geroni/igae098.0360.

[15] T. Mishra *et al.*, "Pre-symptomatic detection of COVID-19 from smartwatch data," *Nature Biomedical Engineering*, vol. 4, no. 12, pp. 1208–1220, 2020.

[16] E. Alzueta *et al.*, "Tracking sleep, temperature, heart rate, and daily symptoms across the menstrual cycle with the Oura ring in healthy women," *Int. J. Women's Health*, vol. 14, pp. 491–503, 2022, doi: 10.2147/IJWH.S341917.

[17] E. de Jager, B. Caulfield, E. Angelidi, B. MacNamee, and S. Holden, "Wearable-derived heart rate variability across the menstrual cycle, hormonal contraceptive use, and reproductive life stages in females: A living systematic review," *Sports Medicine*, vol. 56, no. 5, pp. 1153–1173, 2026, doi: 10.1007/s40279-025-02388-y.

[18] A. Askhatova *et al.*, "A temporal convolutional network approach for gait-based fall risk prediction to support safe sport participation in older adults," *MethodsX*, vol. 16, Art. no. 103845, 2026, doi: 10.1016/j.mex.2026.103845.

[19] A. Weiss, M. Brozgol, M. Dorfman, T. Herman, S. Shema, N. Giladi, and J. M. Hausdorff, "Does the evaluation of gait quality during daily life provide insight into fall risk? A novel approach using 3-day accelerometer recordings," *Neurorehabil. Neural Repair*, vol. 27, no. 8, pp. 742–752, 2013.

[20] J. McCamley, M. Donati, E. Grimpampi, and C. Mazzà, "An enhanced estimate of initial contact and final contact instants of time using lower trunk inertial sensor data," *Gait & Posture*, vol. 36, no. 2, pp. 316–318, 2012.

[21] R. Moe-Nilssen and J. L. Helbostad, "Estimation of gait cycle characteristics by trunk accelerometry," *J. Biomechanics*, vol. 37, no. 1, pp. 121–126, 2004.

[22] D. Drover, J. Howcroft, J. Kofman, and E. D. Lemaire, "Faller classification in older adults using wearable sensors based on turn and straight-walking accelerometer-based features," *Sensors*, vol. 17, no. 6, Art. no. 1321, 2017.

[23] J. M. Hausdorff, "Long Term Movement Monitoring Database (LTMM), version 1.0.0," PhysioNet, doi: 10.13026/C2S59C.

Biodata

[Photo – insert here]

Name: G Sivakumar (23BCE1834)

Mobile No.:

E-mail:

Permanent Address: