DS	**Session**	Arrays	**Question Information**	Level 1 Challenge 29

Problem Description:
Tina has given a boolean matrix mat[P][Q] of size P X Q to Laaysa,

She wants to modify it such that if a matrix cell mat[m][n] is 1 (or true) then make all the cells of m_th row and nth column as 1. Can you help Laaysa?

Constraints:
1 <= p, q <= 1000

Input Format:
First line of the input is the how many rows and columns in Laaysa matrix.

After that, each line will represent each row and Laaysa need to enter numbers.

Output Format:
Print the resultant matrix output in a separate lines.

Logical Test Cases

Test Case 1

INPUT (STDIN)

```
2 2
1 0
0 1
```

EXPECTED OUTPUT

```
1 1
1 1
```

Test Case 2

INPUT (STDIN)

```
3 3
0 0 0
0 1 0
0 0 1
```

EXPECTED OUTPUT

```
0 1 1
1 1 1
1 1 1
```

Mandatory Test Cases

Test Case 1

KEYWORD

```
int arr[r][c];
```

Test Case 2

KEYWORD

```
arrTemp[r][c]
```

Test Case 3

KEYWORD

```
for(m=0;m<r;m++)
```

Complexity Test Cases

Test Case 1	Test Case 2	Test Case 3
CYCLOMATIC COMPLEXITY	TOKEN COUNT	NLOC
13	325	51

Code

solution.c

```c
#include <stdio.h>

int main() {
    int r, c;
    if (scanf("%d %d", &r, &c) != 2) return 0;
    int arr[r][c];
    int arrTemp[r][c];
    int rowFlag[100] = {0}, colFlag[100] = {0};

    for (int m = 0; m < r; m++) {
        for (int n = 0; n < c; n++) {
            scanf("%d", &arr[m][n]);
            if (arr[m][n] == 1) {
                rowFlag[m] = 1;
                colFlag[n] = 1;
            }
        }
    }
    for (int m = 0; m < r; m++) {
        for (int n = 0; n < c; n++) {
            if (rowFlag[m] || colFlag[n]) arrTemp[m][n] = 1;
            else arrTemp[m][n] = 0;
            printf("%d ", arrTemp[m][n]);
        }
        printf("\n");
    }
    return 0;
}
```

Output

```
Problems  Output  Debug Console  Terminal  Ports        powershell
PS C:\C Programming> gcc solution.c -o solution
PS C:\C Programming> .\solution
3 3
1 0 0
0 0 0
0 0 0
1 1 1
1 0 0
1 0 0
PS C:\C Programming>
```