Problem Description

You are given a string which comprises of lower case alphabets (a-z), upper case alphabets (A-Z), numbers, (0-9) and special characters like **!,-.;** etc.

You are supposed to find out **which character occurs the maximum number of times and the number of its occurrence,** in the given string. If two characters occur equal number of times, you have to output the character with the lower ASCII value.

For example, if your string was: **aaaaAAAA**, your output would be: **A 4**, because **A has lower ASCII value than a.**

Input format:
The input will contain a string.

Output format:
You've to output two things which will be separated by a space:
i) The character which occurs the maximum number of times.
ii) The number of its occurrence.

Constraints:
The maximum length of the string can be **1000.**

Logical Test Cases

Test Case 1

INPUT (STDIN)

```
puppy is a dog!!!!!!!!!!!!
```

EXPECTED OUTPUT

```
! 12
```

Test Case 2

INPUT (STDIN)

```
leana is a singer!!!!!!!
```

EXPECTED OUTPUT

```
! 7
```

Mandatory Test Cases

Test Case 1

KEYWORD

```
for(i=0;i<l;i++)
```

Complexity Test Cases

Test Case 1

CYCLOMATIC COMPLEXITY

```
6
```

Test Case 2

TOKEN COUNT

```
210
```

Test Case 3

NLOC

```
35
```

Code

max_freq_char.c

```c
#include <stdio.h>
#include <string.h>

int main() {
    char str[1005];
    if (!fgets(str, sizeof(str), stdin)) return 0;

    int l = strlen(str);
    if (l > 0 && str[l - 1] == '\n') {
        str[l - 1] = '\0';
        l--;
    }

    int freq[256] = {0};
    int i;
    for(i=0;i<l;i++) {
        freq[(unsigned char)str[i]]++;
    }

    int max_freq = 0;
    char best_char = ' ';
    for (int c = 0; c < 256; c++) {
        if (freq[c] > max_freq) {
            max_freq = freq[c];
            best_char = (char)c;
        }
    }

    printf("%c %d\n", best_char, max_freq);
    return 0;
}
```

Output

