DS	**Session**	Sorting	**Question Information**	Level 1 Challenge 11

Problem Description:
Tina owns a match making company, which even to her surprise is an extreme hit. She says that her success rate cannot be matched (Yes, letterplay!) in the entire match-making industry. She follows an extremely simple algorithm to determine if two people are matches for each other. Her algorithm is not at all complex, and makes no sense - not even to her. But she uses it anyway.

Let's say say that on a given day she decides to select n people - that is, n boys and n girls. She gets the list of n boys and n girls in a random order initially. Then, she arranges the list of girls in ascending order on the basis of their height and boys in descending order of their heights. A girl Ai can be matched to a boy on the same index only, that is, Bi and no one else. Likewise, a girl standing on Ak can be only matched to a boy on the same index Bk and no one else.

Now to determine if the pair would make an ideal pair, she checks if the modulo of their heights is 0, i.e., Ai % Bi == 0 or Bi % Ai == 0. Given the number of boys and girls, and their respective heights in non-sorted order, determine the number of ideal pairs Tina can find.

Constraints:
1 <= Test Cases <= 10^2
1 <= N <= 10^4
1 <= A i , B i <= 10^5

Input Format:
The first line contains number of test cases. Then, the next line contains an integer, n, saying the number of boys and girls. The next line contains the height of girls, followed by the height of boys.

Output Format:
Print the number of ideal pairs in a separate lines

Logical Test Cases

Test Case 1

INPUT (STDIN)

```
2
4
1 6 9 12
4 12 3 9
4
2 2 2 2
2 2 2 2
```

EXPECTED OUTPUT

```
2
4
```

Test Case 2

INPUT (STDIN)

```
2
4
3 6 9 12
4 12 16 9
4
1 1 1 1
2 2 2 2
```

EXPECTED OUTPUT

```
3
4
```

Mandatory Test Cases

Test Case 1

KEYWORD

```
for(int i = 0;i<n;i++)
```

Complexity Test Cases

Test Case 1

CYCLOMATIC COMPLEXITY

```
7
```

Test Case 2

TOKEN COUNT

```
210
```

Test Case 3

NLOC

```
23
```

Code

solution.c

```c
#include <stdio.h>
#include <stdlib.h>

int cmpAsc(const void *a, const void *b) { return (*(int*)a - *(int*)b); }
int cmpDesc(const void *a, const void *b) { return (*(int*)b - *(int*)a); }

int main() {
    int t;
    if (scanf("%d", &t) != 1) return 0;
    while (t--) {
        int n;
        scanf("%d", &n);
        int a[n], b[n];
        for (int i = 0; i < n; i++) scanf("%d", &a[i]);
        for (int i = 0; i < n; i++) scanf("%d", &b[i]);

        qsort(a, n, sizeof(int), cmpAsc);
        qsort(b, n, sizeof(int), cmpDesc);

        int count = 0;
        for (int i = 0; i < n; i++) {
            if (a[i] % b[i] == 0 || b[i] % a[i] == 0) count++;
        }
        printf("%d\n", count);
    }
    return 0;
}
```

Output

Problems Output Debug Console Terminal Ports powershell

```
PS C:\C Programming> gcc solution.c -o solution
PS C:\C Programming> .\solution
1
4
3 6 9 12
4 12 3 9
2
PS C:\C Programming>
```