

Status	Finished
Started	Thursday, 1 January 2026, 1:09 AM
Completed	Thursday, 1 January 2026, 1:34 AM
Duration	25 mins 27 secs

Question **1**

Correct

A single line L with a set of space separated values indicating distance travelled and time taken is passed as the input. The program must calculate the average speed S (with precision upto 2 decimal places) and print S as the output.

Note: The distance and time taken will follow the format DISTANCE@TIMETAKEN. DISTANCE will be in kilometers and TIMETAKEN will be in hours.

Input Format:

The first line contains L.

Output Format:

The first line contains the average speed S.

Boundary Conditions:

Length of L will be from 3 to 100.

Example Input/Output 1:

Input:

60@2 120@3

Output:

36.00 kmph

Explanation:

Total distance = $60+120 = 180$ km.

Total time taken = $2+3 = 5$ hours.

Hence average speed = $180/5 = 36.00$ kmph

For example:

Input	Result
60@2 120@3	36.00 kmph

Answer: (penalty regime: 0 %)

```

1  #include<stdio.h>
2  #include<string.h>
3  #include<stdlib.h>
4  int main() {
5      char L[101];
6      fgets(L,sizeof(L),stdin);
7      L[strcspn(L,"\n")]=0;
8      char *token;
9      double total_distance=0.0;
10     double total_time=0.0;
11     token=strtok(L, " ");
12     while(token !=NULL) {
13         char *at_pos=strchr(token, '@');
14         if(at_pos !=NULL) {
15             *at_pos = '\0';
16             char *distance_str=token;
17             char *time_str=at_pos + 1;
18             double distance=atof(distance_str);
19             total_distance+=distance;
20             total_time+=atof(time_str);
21         }
22         token=strtok(NULL, " ");
23     }
24     double average_speed=0.0;
25     if(total_time>0) {
26         average_speed=total_distance/total_time;
27     }
28     printf("%.2lf kmph\n",average_speed);
29     return 0;
30 }
```

	Input	Expected	Got	
✓	60@2 120@3	36.00 kmph	36.00 kmph	✓

Passed all tests! ✓

Question **2**

Correct

The program must accept two numbers X and Y and then print their HCF/GCD.

Input Format:

The first line denotes the value of X.

The second line denotes the value of Y.

Output Format:

The first line contains the HCF of X and Y.

Boundary Conditions:

$1 \leq X \leq 999999$

$1 \leq Y \leq 999999$

Example Input/Output 1:

Input:

30

40

Output:

10

Example Input/Output 2:

Input:

15

10

Output:

5

For example:

Input	Result
30	10
40	

Answer: (penalty regime: 0 %)

```
1  #include<stdio.h>
2  int gcd(int a,int b) {
3      if(b==0)
4          return a;
5      return gcd(b,a%b);
6  }
7  int main() {
8      int x,y;
9      scanf("%d\n",&x);
10     scanf("%d",&y);
11     int result=gcd(x,y);
12     printf("%d\n",result);
13     return 0;
14 }
```

	Input	Expected	Got	
✓	30 40	10	10	✓

Passed all tests! ✓

Question **3**

Correct

A string S is passed as input. S will contain two integer values separated by one of these alphabets - A, S, M, D where

- A or a is for addition
- S or s is for subtraction
- M or m is for multiplication
- D or d is for division

The program must perform the necessary operation and print the result as the output. (Ignore any floating point values just print the integer result.)

Input Format:

The first line contains S.

Output Format:

The first line contains the resulting integer value.

Boundary Conditions:

Length of S is from 3 to 100.

Example Input/Output 1:

Input:

5A11

Output:

16

Explanation:

As the alphabet is A, 5 and 11 are added giving 16.

Example Input/Output 2:

Input:

120D6

Output:

20

Example Input/Output 3:

Input:

1405d10

Output:

140

For example:

Input	Result
5A11	16
120D6	20
1405d10	140

Answer: (penalty regime: 0 %)

```

1  #include<stdio.h>
2  int main() {
3      char s[101];
4      int n1,n2;
5      char op;
6      int result=0;
7      if(scanf("%s",s)!=1){
8          return 1;
9      }
10     if(sscanf(s,"%d%c%d",&n1,&op,&n2)!=3) {
11         return 1;
12     }
13     if(op=='A' || op=='a') {
14         result=n1+n2; }
15     else if(op=='S' || op=='s') {
16         result=n1-n2; }
17     else if(op=='M' || op=='m') {

```

```
18         result=n1*n2; }
19     else if(op=='D' || op=='d') {
20         if(n2!=0) {
21             result=n1/n2;
22         } else {
23             return 1;
24         }
25     }
26     else {
27         printf("Invalid Operator");
28     }
29     printf("%d",result);
30     return 0;
31
32 }
```



	Input	Expected	Got	
✓	5A11	16	16	✓
✓	120D6	20	20	✓
✓	1405d10	140	140	✓

Passed all tests! ✓

