

Status	Finished
Started	Saturday, 22 November 2025, 10:18 AM
Completed	Saturday, 22 November 2025, 10:32 AM
Duration	14 mins 42 secs

Question **1**

Correct

The name and mileage of certain cars is passed as the input. The format is CARNAME@MILEAGE and the input is as a single line, with each car information separated by a space. The program must print the car with the lowest mileage. (Assume no two cars will have the lowest mileage)

Input Format:

The first line contains the CARNAME@MILEAGE separated by a space.

Output Format:

The first line contains the name of the car with the lowest mileage.

Boundary Conditions:

The length of the input string is between 4 to 10000.

The length of the car name is from 1 to 50.

Example Input/Output 1:

Input:

Zantro@16.15 Zity@12.5 Gamry@9.8

Output:

Gamry

For example:

Input	Result
Zantro@16.15 Zity@12.5 Gamry@9.8	Gamry

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 #include<string.h>
3 #include<stdlib.h>
4
5 int main() {
6     char input[10000];
```

```

7   fgets(input, sizeof(input), stdin);
8   char *token;
9   char car[100], lowestCar[100];
10  float mileage, lowestMileage=99999.0;
11
12  token = strtok(input, " ");
13  while (token != NULL) {
14      sscanf(token, "%[^@]@%f", car, &mileage);
15
16      if(mileage<lowestMileage)
17      {
18          lowestMileage=mileage;
19          strcpy(lowestCar, car);
20      }
21      token = strtok(NULL, " ");
22  }
23  printf("%s", lowestCar);
24  return 0;
25 }
```

	Input	Expected	Got	
✓	Zantro@16.15 Zity@12.5 Gamry@9.8	Gamry	Gamry	✓

Passed all tests! ✓

Question **2**

Correct

A certain number of people attended a meeting which was to begin at 10:00 am on a given day. The arrival time in HH:MM format of those who attended the meeting is passed as the input in a single line, with each arrival time by a space. The program must print the count of people who came late (after 10:00 am) to the meeting.

Input Format:

The first line contains the arrival time separated by a space.

Output Format:

The first line contains the count of late comers.

Boundary Conditions:

The length of the input string is between 4 to 10000.

The time HH:MM will be in 24 hour format (HH is hours and MM is minutes).

Example Input/Output 1:

Input:

10:00 9:55 10:02 9:45 11:00

Output:

2

Explanation:

The 2 people were those who came at 10:02 and 11:00

For example:

Input	Result
10:00 9:55 10:02 9:45 11:00	2

Answer: (penalty regime: 0 %)

```

1  #include<stdio.h>
2  #include<string.h>
3  #include<stdlib.h>
4
5  int main() {
6      char input[100000];
7      fgets(input, sizeof(input), stdin);
8
9      char *token;
10     int lateCount = 0;
11     int h,m;
12
13     token = strtok(input, " ");
14     while(token != NULL) {
15         sscanf(token, "%d:%d", &h,&m);
16
17         int totalMinutes = h*60+m;
18         int meetingStart = 10*60;
19
20         if(totalMinutes > meetingStart)
21             lateCount++;
22
23         token = strtok(NULL, " ");
24     }
25     printf("%d", lateCount);
26     return 0;
27 }

```

	Input	Expected	Got	
✓	10:00 9:55 10:02 9:45 11:00	2	2	✓

Passed all tests! ✓

Question **3**

Correct

A single line consisting of a set of integers, each separated by space is passed as input to the program. The program must print the sum of all the integers present.

Input Format:

The first line contains the integer values (Each separated by a space)

Output Format:

The first line contains the sum of all the integers.

Boundary Conditions:

The length of the input string is between 3 to 10000

The value of the integer values will be from -99999 to 99999

Example Input/Output 1:

Input:

100 -99 98 5

Output:

104

Example Input/Output 2:

Input:

100 200 -300 500 -450 -50

Output:

0

For example:

Input	Result
100 -99 98 5	104
100 200 -300 500 -450 -50	0

Answer: (penalty regime: 0 %)

```

1  #include<stdio.h>
2  #include<stdlib.h>
3  #include<string.h>
4
5  int main() {
6      char input[10000];
7      fgets(input, sizeof(input), stdin);
8      char *token;
9      int sum=0, num;
10
11     token = strtok(input, " ");
12     while(token !=NULL) {
13         num = atoi(token);
14         sum+=num;
15         token = strtok(NULL, " ");
16     }
17     printf("%d", sum);
18     return 0;
19 }
```

	Input	Expected	Got	
✓	100 -99 98 5	104	104	✓
✓	100 200 -300 500 -450 -50	0	0	✓

Passed all tests! ✓