

Status	Finished
Started	Thursday, 13 November 2025, 12:38 PM
Completed	Thursday, 13 November 2025, 2:38 PM
Duration	2 hours

Question **1**

Correct

A single line L with a set of space separated values indicating distance travelled and time taken is passed as the input. The program must calculate the average speed S (with precision upto 2 decimal places) and print S as the output.

Note: The distance and time taken will follow the format DISTANCE@TIMETAKEN. DISTANCE will be in kilometers and TIMETAKEN will be in hours.

Input Format:

The first line contains L.

Output Format:

The first line contains the average speed S.

Boundary Conditions:

Length of L will be from 3 to 100.

Example Input/Output 1:

Input:

60@2 120@3

Output:

36.00 kmph

Explanation:

Total distance = 60+120 = 180 km.

Total time taken = 2+3 = 5 hours.

Hence average speed = 180/5 = 36.00 kmph

For example:

Input	Result
60@2 120@3	36.00 kmph

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 #include<string.h>
3 #include<stdlib.h>
4 int main() {
5     char L[101];
6     fgets(L,sizeof(L),stdin);
7     L[strcspn(L,"\n")]=0;
8     char *token;
9     double total_distance=0.0;
10    double total_time=0.0;
11    token=strtok(L, " ");
12    while (token !=NULL) {
```

```
13     char *at_pos=strchr(token, '@');
14     if (at_pos !=NULL) {
15         *at_pos = '\0';
16         char *distance_str=token;
17         char *time_str=at_pos + 1;
18         double distance=atof(distance_str);
19         total_distance+=distance;
20         total_time+=atof(time_str);
21     }
22     token=strtok(NULL, " ");
23 }
24 double average_speed=0.0;
25 if(total_time>0){
26     average_speed=total_distance/total_time;
27 }
28 printf("%.2lf kmph\n",average_speed);
29 return 0;
30 }
```

	Input	Expected	Got	
✓	60@2 120@3	36.00 kmph	36.00 kmph	✓

Passed all tests! ✓

Question **2**

Correct

The program must accept two numbers X and Y and then print their HCF/GCD.

Input Format:

The first line denotes the value of X.

The second line denotes the value of Y.

Output Format:

The first line contains the HCF of X and Y.

Boundary Conditions:

1 <= X <= 999999

1 <= Y <= 999999

Example Input/Output 1:

Input:

30

40

Output:

10

Example Input/Output 2:

Input:

15

10

Output:

5

For example:

Input	Result
30	10
40	

Answer: (penalty regime: 0 %)

```
1  #include<stdio.h>
2  int gcd(int a,int b) {
3      if(b==0)
4          return a;
5      return gcd(b,a%b);
6  }
7  int main() {
8      int x,y;
9      scanf("%d\n",&x);
10     scanf("%d",&y);
11     int result=gcd(x,y);
12     printf("%d\n",result);
13     return 0;
```

```
14 |}  
15 |
```

[]

	Input	Expected	Got	
✓	30 40	10	10	✓

Passed all tests! ✓

//

Question **3**

Incorrect

A string S is passed as input. S will contain two integer values separated by one of these alphabets - A, S, M, D where

- A or a is for addition
- S or s is for subtraction
- M or m is for multiplication
- D or d is for division

The program must perform the necessary operation and print the result as the output. (Ignore any floating point values just print the integer result.)

Input Format:

The first line contains S.

Output Format:

The first line contains the resulting integer value.

Boundary Conditions:

Length of S is from 3 to 100.

Example Input/Output 1:

Input:

5A11

Output:

16

Explanation:

As the alphabet is A, 5 and 11 are added giving 16.

Example Input/Output 2:

Input:

120D6

Output:

20

Example Input/Output 3:

Input:

1405d10

Output:

140

For example:

Input	Result
5A11	16
120D6	20
1405d10	140

Answer: (penalty regime: 0 %)

```

1  #include<stdio.h>
2  #include<string.h>
3  #include<stdlib.h>
4  int main() {
5      char S[101];
6      fgets(S,sizeof(S),stdin);
7      S[strcspn(S, "\n")]=0;
8      int num1,num2;
9      char operator = ' ';
10     int len=strlen(S);
11     int op_pos=-1;
12     for(int i = 0; i< len; i++) {
13         if(S[i]=='A' || S[i] == 'a' || S[i]=='s' || S[i]=='S' || S[i]=='M' || S[i]=='m' || S[i]=='D' || S[i]=='d') {
14             operator=S[i];
15             op_pos=i;
16             break;
17         }
18     }
19     if(op_pos !=-1) {
20         char num1_str[50]={0};
21         strcpy(num1_str, S+op_pos);
22         num1=atoi(num1_str);
23         char num2_str[50]={0};
24         strcpy(num2_str, S+op_pos+1);
25         num2=atoi(num2_str);
26     }
27     int result;
28     switch(operator){
29         case 'A':
30         case 'a':
31             result=num1+num2;
32             break;
33         case 'S':
34         case 's':
35             result=num1-num2;
36             break;
37         case 'M':
38         case 'm':
39             result=num1*num2;
40         case 'D':
41         case 'd':
42             if(num2 !=0) {
43                 result=num1/num2;
44             } else {
45                 result=0;
46             }
47             break;
48     }
49     printf("%d\n",result);

```

```
50 |   return 0;  
51 | }
```

	Input	Expected	Got	
⊗	5A11	16	11	⊗
⊗	120D6	20	0	⊗
⊗	1405d10	140	0	⊗

Some hidden test cases failed, too.

Your code must pass all tests to earn any marks. Try again.

Show differences