Mylan	Document Name	SUDO to Oracle User in Unix
	Document Number	MYL-UNX-SOP-OUAU- 001
	Type of document	Standard Operation Procedure
	Revision No:	1.0

Table of Contents

1. PURPOSE 2
2. SCOPE 2
3. PROCEDURE: 2
4. DEFINITIONS: 2
5. VERSION HISTORY 3

1. PURPOSE

1.1 This document defines the service account access management in Unix Servers, which describes the local system user to get access to login service account in unix servers.

2. SCOPE

2.1 We will receive Service request from Database support team for sudo to access Oracle user.

2.2 If we receive email from Database support team, we will ask them to raise a Service Request.

2.3 If the User MID is not exists in the server, we will ask them to raise smartshop request.

3. PROCEDURE:

3.1 Based on service request and 1st level Manager approval, Unix support team will validate, whether the user account already exists or not. Usually the user account will be their MID. If the User MID is not exists in the server, we will ask them to raise smartshop request.

3.2 The smartshop access request will route to 1st and 2nd level managers approval, then routed to Access Management.

3.2.1 Access Management will verify their database whether the user's Unix account already exists.

3.2.1.1 If exists, Access Management will share UID and GID for the respective MID to Unix run team and will route the smartshop service request to Unix run team to create User access.

3.2.1.2 If not, Access Management will generate UID and GID for the respective MID and will route the smartshop service request to Unix run team to create User access.

3.3 With the reference of "MYL-UNX-WI-OUAU- 001", Unix run team will create the User's MID as unix system user account with respective UID and GID. While creating user account, will add sudoers group for Oracle as user's additional group

3.4 Unix Team will force the user to change his account password after first successful login and will share the password of user via FTA.

3.5 User can login the server with their MID and the password which shared via FTA, in first successful login, unix system will prompt to user to change their unix password.

3.6 Once User logged in to the unix system, run the below command to switch it to "oracle" user.

sudo -u oracle -i

3.7 User will get prompt to enter their password to switch to service account "oracle".

4. DEFINITIONS:

MID	Mylan Identifier: Mylan Employee's access can be managed by their MID
UID	User Identifier: Unix-like operating systems identify a user by a value called a user identifier, often abbreviated to user ID or UID
GID	Group Identifier: Unix-like operating systems, every user must be a member of at least one group, the primary group which is identified by the numeric GID
MYL-UNX-WI-OUAU- 001	Oracle Account Access Management in Unix

5. VERSION HISTORY

	Prepared By	Reviewed by	Approved By
Name	Franklin K Dhas	Vinoth Sankar	Arunachalam G
Role	SME	SME	Senior Manager
Date	**02-APR-2020**	**03-APR-2020**	**06-APR-2020**
Version	**1.0**	**1.0**	**1.0**