Mylan	Document Name	Oracle Account Access Management in Unix
	Document Number	MYL-UNX-WI-OUAU- 001
	Type of document	Standard Operation Procedure
	Revision No:	1.0

Table of Contents

1. PURPOSE 2
2. SCOPE 2
3. PROCEDURE: 2
4. DEFINITIONS: 3
5. VERSION HISTORY 3

1. PURPOSE

1.1 This document describes steps to provide the local system user to get access to login Oracle service account in Unix servers.

2. SCOPE

2.1 We will receive Service request from Database support team for sudo to access Oracle user.

2.2 If we receive email from Database support team, we will ask them to raise a Service Request.

2.3 If the User MID is not exists in the server, we will ask them to raise smartshop request.

2.4 We will raise a Change request to add “zen_ora” wheels group entry in /etc/sudoers file

3. PROCEDURE:

3.1 Based on service request and 1st level Manager approval, Unix support team will validate, whether the user account already exists or not. Usually the user account will be their MID. If the User MID is not exists in the server, we will ask them to raise smartshop request.

3.2 The smartshop access request will route to 1st and 2nd level managers approval, then routed to Access Management.

3.2.1 Access Management will verify their database whether the user’s Unix account already exists.

3.2.1.1 If exists, Access Management will share UID and GID for the respective MID to Unix run team and will route the smartshop service request to Unix run team to create User access.

3.2.1.2 If not, Access Management will generate UID and GID for the respective MID and will route the smartshop service request to Unix run team to create User access.

3.3 Unix run team will create the User’s MID as unix system user account with respective UID and GID. While creating user account, will add group name “zen_ora” as user’s additional group. Unix Team will force the user to change his account password after first successful login and will share the password of user via FTA

useradd -u 5528 -g 100 -G 4570 -s /bin/bash -d /home/m520528 -c "Prosun Mandal" m520528

```
[root@u0bvdbpoc001 ~]# id m520528
id: m520528: no such user
[root@u0bvdbpoc001 ~]# useradd -u 5528 -g 100 -G 4570 -s /bin/bash -d /home/m520528 -c "Prosun Mandal" m520528
[root@u0bvdbpoc001 ~]# id m520528
uid=5528(m520528) gid=100(users) groups=100(users),4570(zen_ora)
[root@u0bvdbpoc001 ~]#
```

3.4 If user MID already exists in Unix server, Unix run Team will add the group “zen_ora” as additional group in existing user’s MID account

#usermod -a -G 4570 m520528

```
[root@u0bvdbpoc001 /]# id m520528
uid=5528(m520528) gid=5528(m520528) groups=5528(m520528)
[root@u0bvdbpoc001 /]# usermod -a -G 4570 m520528
[root@u0bvdbpoc001 /]# id m520528
uid=5528(m520528) gid=5528(m520528) groups=5528(m520528),4570(zen_ora)
[root@u0bvdbpoc001 /]#
```

3.5 If “zen_ora” group was not existing in the server,

3.5.1 Unix admin will create “zen_ora” group by executing below command in Linux servers

groupadd -g 4570 zen_ora

```
[root@u0bvdbpoc001 /]# cat /etc/group |grep -i zen_ora
[root@u0bvdbpoc001 /]# hostname;date
u0bvdbpoc001
Thu Apr  2 21:09:31 EDT 2020
[root@u0bvdbpoc001 /]# groupadd -g 4570 zen_ora
[root@u0bvdbpoc001 /]# cat /etc/group |grep -i zen_ora
zen_ora:x:4570:
[root@u0bvdbpoc001 /]#
```

3.5.2 Append below entry in “/etc/sudoers” to create wheels group

%zen_ora ALL=(oracle) ALL

```
[root@u0bvdbpoc001 ~]# grep zen_ora /etc/sudoers
%zen_ora        ALL=(oracle) ALL
[root@u0bvdbpoc001 ~]#
```

4. DEFINITIONS:

MID	Mylan Identifier: Mylan Employee's access can be managed by their MID
UID	User Identifier: Unix-like operating systems identify a user by a value called a user identifier, often abbreviated to user ID or UID
GID	Group Identifier: Unix-like operating systems, every user must be a member of at least one group, the primary group which is identified by the numeric GID
zen_ora	Wheels group for service account oracle

5. VERSION HISTORY

	Prepared By	Reviewed by	Approved By
Name	Shaik Imran Ali	Franklin K Dhas	Arunachalam G
Role	L3	SME	Senior Manager
Date	**03-APR-2020**	03-APR-2020	**03-APR-2020**
Version	**1.0**	1.0	**1.0**