

Project_Development

Project Development

1. User Creation

A ServiceNow user named EEE User was created.

Details:

User ID: EEE User

First Name: EEE

Last Name: User

Email: eeeuser@gmail.com

2. Role Creation

The following custom roles were created:

bb1

bb2

bb3

bb4

These roles were assigned to the EEE User.

3. Table Creation

A custom table was created:

Table: u_institution_details

Label: Institution Details

Fields created:

Student Roll Number – Auto Number

Student Name – Reference User

Faculty Name – Reference User

Branch – Choice

Email – String

Phone Number – String

Description – Multi String

Branch choices:

ECE

EEE

CSE

4. READ ACL

A Record READ ACL was configured for:

Table: u_institution_details

Operation: Read

Required Role: bb1

The ACL uses a script to provide access while allowing administrators full access.

```
(function () {  
    if (gs.hasRole('admin')) {  
        return true;  
    }  
  
    if (gs.hasRole('bb1')){  
        return true;  
    }  
  
    return false;  
})();
```

The data condition is:

Branch is EEE

This restricts the ACL to EEE branch records.

5. CREATE ACL

A Record CREATE ACL was configured.

Table: u_institution_details

Operation: Create

Required Role: bb2

Users with the bb2 role can create records.

6. WRITE ACL

A Record WRITE ACL was configured.

Table: u_institution_details

Operation: Write

Required Role: bb3

Users with the bb3 role can modify records.

7. DELETE ACL

A Record DELETE ACL was configured.

Table: u_institution_details

Operation: Delete

Required Role: bb4

Users with the bb4 role can delete records.

Final Access Structure

Operation

Role

READ

bb1

CREATE

bb2

WRITE

bb3

DELETE

bb4

Full Access

admin