

Script-Controlled ACL – Restrict Record Access Based on Field Value

3. Project Design – Completed Answer

3.1 Problem–Solution Fit

Problem	Target user	Solution fit	Verification
Users may see records outside their permitted branch.	EEE / authorized users	READ ACL with Branch = EEE and bb1 role.	Impersonate EEE user and open u_institution_details.list.
Different operations need different authorization.	Operational users	Separate CREATE, WRITE and DELETE ACLs using bb2/bb3/bb4.	Verify New, edit and delete capabilities.

3.2 Proposed Solution

Parameter	Answer
Problem Statement	Restrict Institution Details access so branch-specific users see permitted records while administrators retain full READ access.
Idea / Solution description	Create u_institution_details, populate ECE/EEE/CSE records, and enforce access through ServiceNow ACLs.
Novelty / Uniqueness	Combines role checks with a record field condition and script-controlled ACL.
Social Impact / Customer Satisfaction	Reduces unauthorized visibility of institutional records and makes access rules explicit and testable.
Business Model	Not specified; this is a security/configuration lab.
Scalability	The ACL pattern can be extended to additional roles, operations and record conditions.

3.3 Solution Architecture

Layer	Component	Responsibility
User	ServiceNow user / test user	Requests access.
Security	ServiceNow ACL engine	Evaluates operation, role, condition and script.
Authorization	READ ACL script	Admin → true; bb1 → true; others → false.
Data	u_institution_details	Stores records including Branch.
Verification	ServiceNow list/form	Demonstrates allowed and denied access.

3.4 READ ACL Configuration

Type = record; Operation = read; Name = u_institution_details; Active = true; Advanced = true; Requires role = bb1; Data condition = Branch is EEE.

```
(function () {  
if (gs.hasRole('admin')) { return true; }  
if (gs.hasRole('bb1')) { return true; }  
return false;  
})();
```

3.5 CREATE / WRITE / DELETE

Operation	Required role	Data condition
Create	bb2	None specified

Operation	Required role	Data condition
Write	bb3	None specified
Delete	bb4	None specified