

Script-Controlled ACL – Restrict Record Access Based on Field Value

5. Functional & Performance Testing – Completed Answer

The reference lab explicitly requires impersonation of EEE users and administrators, opening u_institution_details.list and verifying access outcomes.

5.1 UAT Test Cases

Test Case	Scenario	Test Steps	Expected Result
TC-001	bb1 user reads EEE records	Impersonate EEE User → open list	EEE branch records are viewable.
TC-002	User without bb1 reads	Impersonate user without required role → open list	Records are not viewable through configured READ ACL.
TC-003	Admin reads all	Impersonate Admin → open list	All branches are viewable.
TC-004	bb1 + bb2 create	Use cumulative-role user → New	CREATE operation is available.
TC-005	bb1 + bb2 + bb3 write	Open EEE record → edit	WRITE operation is available.
TC-006	bb1 + bb2 + bb3 + bb4 delete	Open permitted record → delete	DELETE operation is available.

5.2 Expected Access Matrix

User / Roles	READ EEE	READ other branch	CREATE	WRITE	DELETE
No required role	Deny	Deny	Deny	Deny	Deny
bb1	Allow	Deny by EEE condition	Deny	Deny	Deny
bb1 + bb2	Allow	Deny by EEE condition	Allow	Deny	Deny
bb1 + bb2 + bb3	Allow	Deny by EEE condition	Allow	Allow	Deny
bb1 + bb2 + bb3 + bb4	Allow	Deny by EEE condition	Allow	Allow	Allow
admin	Allow	Allow	Not specified	Not specified	Not specified

5.3 Performance Testing

The supplied source contains no measured response-time, throughput, concurrency, CPU, memory or load-test results. No numeric performance result is invented here. For an actual submission, record observed response time under the target ServiceNow instance and document the test environment.

5.4 Defect Register

Bug ID	Description	Severity	Status
BG-001	No specific defect is recorded in the supplied source.	—	Not recorded