Week-5 Assignment

Sivarama Krishnan. A

II-BCA-‘A’

```
use bill;
create table orders (
   order_id int primary key,
   customer_id int
);
insert into orders values
(1, 101),
(2, 102),
(3, 103),
(4, 104),
(5, 105);
create table payment (
   payment_id int auto_increment primary key,
   order_id int not null unique,
   payment_date date not null,
   payment_mode varchar(30) not null,
   payment_status varchar(20) not null default 'pending',
   transaction_amount decimal(10,2) not null,

   check (payment_mode in (
      'upi',
      'credit card',
      'debit card',
      'net banking',
      'cash on delivery'
   )),

   check (payment_status in (
```

```
    'pending',
'success',
'failed'
)),
check (transaction_amount > 0),
foreign key (order_id)
references orders(order_id)
);
insert into payment
(order_id, payment_date, payment_mode, payment_status, transaction_amount)
values
(1, '2026-10-20', 'upi', 'success', 1500.00),
(2, '2026-10-21', 'credit card', 'success', 2500.00),
(3, '2026-10-22', 'debit card', 'failed', 1200.00),
(4, '2026-10-23', 'net banking', 'pending', 3000.00),
(5, '2026-10-24', 'cash on delivery', 'pending', 800.00);
select * from payment;
select * from payment
where payment_status = 'success';
select * from payment
where payment_status = 'failed';
select * from payment
where payment_status = 'pending';
select * from payment
where order_id = 1;
update payment
set payment_status = 'success',
payment_date = '2026-10-27'
where order_id = 3
and payment_status = 'failed';
select count(*) as successful_payments
```

```
from payment
where payment_status = 'success';
select count(*) as failed_payments
from payment
where payment_status = 'failed';
select payment_mode, count(*) as total_transactions
from payment
group by payment_mode;
select payment_mode, count(*) as total_transactions
from payment
group by payment_mode
order by total_transactions desc
limit 1;
select sum(transaction_amount) as total_revenue
from payment
where payment_status = 'success';
select payment_mode,
sum(transaction_amount) as total_revenue
from payment
where payment_status = 'success'
group by payment_mode;

select avg(transaction_amount) as average_amount
from payment;

select payment_status, count(*) as total_transactions
from payment
group by payment_status;

select c.customer_id,
    c.customer_name,
```

```
    o.order_id,
    p.payment_id,
    p.payment_date,
    p.payment_mode,
    p.payment_status,
    p.transaction_amount
from payment p
join orders o on p.order_id = o.order_id
join customer c on o.customer_id = c.customer_id;

select c.customer_id,
    c.customer_name,
    p.order_id,
    p.payment_date,
    p.payment_mode,
    p.payment_status,
    p.transaction_amount
from payment p
join orders o on p.order_id = o.order_id
join customer c on o.customer_id = c.customer_id
order by c.customer_id, p.payment_date desc;

select o.order_id,
    p.payment_mode,
    p.payment_status,
    p.transaction_amount
from orders o
join payment p on o.order_id = p.order_id
where p.payment_status in ('failed', 'pending');

select
```

```
    sum(case when payment_status = 'success' then 1 else 0 end)
        as successful_transactions,
    sum(case when payment_status = 'failed' then 1 else 0 end)
        as failed_transactions,
    sum(case when payment_status = 'pending' then 1 else 0 end)
        as pending_transactions
from payment;
```