



AI&DATASKILLS

STUDENTEXERCISE·SQLJOINS

Exercise

TOPIC

QUESTIONS

LEVEL

INCLUDES

Inner · Left · Full Outer



BrightLearn^{SQLJOINS}EXERCISE

Welcome to the Exercise

This exercise gives you fifteen real SQL questions to practise the three most important joins — INNER, LEFT, and FULL OUTER. You'll work with five tables from a streaming-service business, write your own SQL, and check your answers against the

expected output.

DEFINITION

How this exercise works

Five tables. Fifteen questions across three parts. **Part A is INNER JOIN, Part B is LEFT JOIN, Part C is FULL OUTER JOIN.** Each question tells you which tables to use, the join to apply, and the expected output columns. Write your SQL in the box under each question, then run it on your own database to check. A bonus challenge at the end lets you reason about the data without writing more SQL.

★ WHAT YOU WILL PRACTISE

- **Matching rows across tables** using a common key (an INNER JOIN).
- **Keeping every row from one side** — even rows with no match (a LEFT JOIN).
- **Keeping every row from both sides** — including unmatched rows on either end (a FULL OUTER JOIN).
- **Reading expected output** to check your work — a skill every analyst needs.
- **Reasoning about missing data** — which is what the bonus questions test.

★ HOW TO SUBMIT YOUR ANSWERS

Set up the five tables in your favourite SQL environment — SQLite, PostgreSQL, MySQL, SQL Server, BigQuery, or Databricks all work. Write each query in a single .sql file numbered Q1 to Q15. Add comments above each one. Run them and screenshot the results. Submit the .sql file plus screenshots through the BrightLearn portal.



The Three Joins

Before you write a single query, make sure these three patterns are clear in your head. The same two tables joined in three different ways give you three different answers — and choosing the right one is half the skill.

01·INNERJOIN

Returns only rows where the join condition is true on BOTH sides. Unmatched rows are dropped.

```
SELECT ...  
FROM customers c  
INNER JOIN orders o ON c.customer_id = o.customer_id;
```

→ only customers who placed orders, and only orders with a matching customer.

02·LEFTJOIN

Returns every row from the LEFT table. Matching rows from the right are included; unmatched rows on the right become NULL.

```
SELECT ...  
FROM customers c  
LEFT JOIN orders o ON c.customer_id = o.customer_id;
```

→ every customer, with or without orders. Customers without orders get NULL on the order columns.

03·FULLOUTERJOIN

Returns every row from BOTH tables. Unmatched rows on either side become NULL on the other side's columns.

```
SELECT ...  
FROM customers c  
FULL OUTER JOIN orders o ON c.customer_id = o.customer_id;
```

→ every customer AND every order. Useful to find unmatched rows on either side.



★ THEMENTALPICTURE

Picture two overlapping circles. INNER JOIN is the overlap. LEFT JOIN is the left circle plus the overlap. FULL OUTER JOIN is both circles, overlap and all. Once you see this picture clearly, picking the right join becomes automatic.



The Five Tables

These are the five tables you'll be querying. Read them carefully — some rows are intentionally missing matches in other tables, which is exactly what makes the three joins produce different results.

Table1·users

1	Nomvula	Johannesburg
2	David	Cape Town
3	Anele	Durban
4	Kabelo	Pretoria
5	Lerato	Port Elizabeth

Table2·plans

10	Basic	79
11	Standard	129
12	Premium	199
13	Family	249
14	Mobile	59

Table3·subscriptions

501	1	10	2026-01-15
502	2	11	2026-02-01
503	1	12	2026-03-10
504	6	11	2026-03-20
505	3	13	2026-04-05

Table 4 • shows

701	Comedy Hour	Comedy

**BrightLearn** SQL JOINS EXERCISE

702	Crime Time	Drama
703	Tech Tales	Documentary
704	Cooking Lab	Lifestyle
706	Wild Earth	Documentary

Table 5 • viewing_sessions

901	1	701	45
902	2	703	30
903	1	702	60
904	7	701	20
905	3	705	90

⚠ **LOOK CAREFULLY —
THESE GAPS ARE ON
PURPOSE**

Some rows reference IDs that do not exist in the parent table: **subscription 504** → **user 6 (doesn't exist)**, **session 904 user 7 (doesn't exist)** → , and **session 905** → **show 705 (doesn't exist)**. Some parent rows have no children: users 4 and 5 have no subscriptions or sessions; plan 14 (Mobile) has no subscribers; shows 704 and 706 were never watched. These gaps make INNER, LEFT, and FULL OUTER joins return visibly different results — which is the whole point of the exercise.

**BrightLearn** SQL JOINS EXERCISE**Part A — INNER JOIN**

The first five questions all use INNER JOIN — return only the rows where both sides match. Notice how rows with missing matches disappear from your result set.

QUESTION01

Show every user who has a subscription. Match users to subscriptions.

TABLESTOUSE

users · subscriptions

EXPECTEDCOLUMNS

user_id, user_name, subscription_id, start_date

WRITEYOURSQLHERE

```
SELECT user_id, user_name, subscription_id, start_date
FROM user AS A
INNER JOIN subscriptions AS B
ON A.user_id = B.user_id;
```

QUESTION02

Show every subscription with its matching plan name and monthly price.

TABLESTOUSE

subscriptions · plans

EXPECTEDCOLUMNS

subscription_id, user_id, plan_name, monthly_price

WRITEYOURSQLHERE

```
SELECT subscription_id, user_id, plan_name, monthly_price
FROM subscriptions AS A
INNER JOIN plans AS B
ON A.plan_id = B.plan_id;
```



QUESTION03

Show every viewing session that has a matching show. Include the show title and genre.

TABLESTOUSE

viewing_sessions · shows

EXPECTEDCOLUMNS

session_id, user_id, show_title, genre, watch_minutes

WRITEYOURSQLHERE

```
SELECT session_id, user_id, show_title, genre, watch_minutes
FROM viewing_sessions AS A
INNER JOIN shows AS B
ON A.show_id=B.show_id;
```

QUESTION04

Show every viewing session with the user who watched it. Only show sessions with a matching user.

TABLESTOUSE

users · viewing_sessions

EXPECTEDCOLUMNS

user_name, country, session_id, show_id, watch_minutes

WRITEYOURSQLHERE

```
SELECT user_name, country, session_id, show_id, watch_minutes
FROM users AS A
INNER JOIN viewing_sessions AS B
ON A.user_id = B.user_id;
```



QUESTION05

Show users along with their subscriptions, the plan name, and the price. Use only users who have both a subscription and a valid plan.

TABLES TO USE

users · subscriptions · plans

EXPECTED COLUMNS

user_name, country, plan_name, monthly_price, start_date

WRITE YOUR SQL HERE

```
SELECT user_name, country, plan_name, monthly_price, start_date
FROM user AS A
INNER JOIN subscription AS B ON A.user_id = B.user_id
INNER JOIN plans AS C ON B.plan_id = C.plan_id;
```



Part B — LEFT JOIN

These five questions use LEFT JOIN — every row from the left-hand table is kept, even when it has no match on the right. Watch where NULL values appear in your result.

QUESTION06

Show every user and any subscriptions they have. Users without subscriptions must still appear.

TABLES TO USE

users · subscriptions

EXPECTED COLUMNS

user_id, user_name, subscription_id, start_date

WRITE YOUR SQL HERE

```
SELECT user_id, user_name, subscription_id, start_date
FROM users AS A
LEFT JOIN subscriptions AS B
ON A.user_id = user_id;
```

QUESTION 07

Show every plan and the subscriptions on it. Plans with no subscribers must still appear.

TABLES TO USE

plans · subscriptions

EXPECTED COLUMNS

plan_id, plan_name, subscription_id, user_id

WRITE YOUR SQL HERE

```
SELECT plan_id, plan_name, subscription_id, user_id
FROM plans AS A
LEFT JOIN subscriptions AS B
ON A.plan_id = B.plan_id;
```

**QUESTION 08**

Show every show and any viewing sessions on it. Shows that were never watched must still appear.

TABLES TO USE

shows · viewing_sessions

EXPECTED COLUMNS

show_id, show_title, session_id, watch_minutes

WRITE YOUR SQL HERE

```
SELECT show_id, show_title, session_id, watch_minutes
FROM shows AS A
LEFT JOIN viewing_sessions AS B
ON A.show_id = B.show_id;
```

QUESTION 9

Show every viewing session and the user who watched it. Sessions referencing users that do not exist must still appear (with NULL user details).

TABLES TO USE

viewing_sessions · users

EXPECTED COLUMNS

session_id, show_id, watch_minutes, user_id, user_name

**BrightLearn SQL JOINS EXERCISE****WRITE YOUR SQL HERE**

```
SELECT session_id, show_id, watch_minutes, user_id, user_name
FROM viewing_sessions AS A
LEFT JOIN users AS B
ON A.user_id = B.user_id;
```

QUESTION 10

Show every user, the plan they are on (if any), and the monthly price. Users without a subscription must still appear.

TABLES TO USE

users · subscriptions · plans

EXPECTED COLUMNS

user_name, country, plan_name, monthly_price

WRITE YOUR SQL HERE

```
SELECT user_name, country, plan_name, monthly_price
FROM user AS A
LEFT JOIN subscription AS B ON A.user_id = B.user_id
LEFT JOIN plans AS C ON B.plan_id = C.plan_id;
```



Part C — FULL OUTER JOIN

The final five questions use FULL OUTER JOIN — every row from both tables, matched where possible and NULL elsewhere. This is the join that reveals everything missing on both sides at once.

★ SQL DIALECT NOTE

PostgreSQL, SQL Server, Oracle, and most warehouses support FULL OUTER JOIN directly. MySQL does not — emulate it by combining a LEFT JOIN and a RIGHT JOIN with UNION. If you are practising on MySQL, write the LEFT + RIGHT + UNION pattern for these questions.

QUESTION 11

Show every user and every subscription, including users without subscriptions AND subscriptions referencing users that do not exist.

TABLES TO USE

users · subscriptions

EXPECTED COLUMNS

user_id, user_name, subscription_id, start_date

WRITE YOUR SQL HERE

```
SELECT user_id, user_name, subscription_id, start_date
FROM user AS A
FULL OUTER JOIN subscription AS B
ON A.user_id = B.user_id;
```

QUESTION 12

Show every plan and every subscription, including plans without subscribers AND any

BrightLearn · SQL Joins Exercise Page 13

**BrightLearn SQL JOINS EXERCISE**

subscription referencing a plan that does not exist.

TABLES TO USE

plans · subscriptions

EXPECTED COLUMNS

plan_id, plan_name, subscription_id, user_id

WRITE YOUR SQL HERE

```
SELECT plan_id, plan_name, subscription_id, user_id
FROM plans AS A
FULL OUTER JOIN subscriptions AS B
ON A.plan_id = B.plan_id;
```

QUESTION 13

Show every show and every viewing session, including shows that were never watched AND sessions referencing shows that do not exist.

TABLES TO USE

shows · viewing_sessions

EXPECTED COLUMNS

show_id, show_title, session_id, watch_minutes

WRITE YOUR SQL HERE

```
SELECT show_id, show_title, session_id, watch_minutes
FROM shows AS A
FULL OUTER JOIN viewing_session AS B
ON A.show_id = B.show_id;
```



BrightLearn SQL JOINS EXERCISE

QUESTION 14

Show every user and every viewing session, including users with no sessions AND sessions referencing users who do not exist.

TABLES TO USE

users · viewing_sessions

EXPECTED COLUMNS

user_id, user_name, session_id, show_id, watch_minutes

WRITE YOUR SQL HERE

```
SELECT user_id, user_name, session_id, watch_minutes
FROM users AS A
FULL OUTER JOIN viewing_sessions AS B
ON A.user_id = B.user_id;
```

QUESTION 15

Show every user, every subscription, and every plan in one query — using FULL OUTER JOIN throughout. This is the hardest question — get all gaps visible at once.

TABLES TO USE

users · subscriptions · plans

EXPECTED COLUMNS

user_id, user_name, subscription_id, plan_id, plan_name

WRITE YOUR SQL HERE

```
SELECT user_id, user_name, subscription_id, plan_id, plan_name
FROM user AS A
FULL OUTER JOIN subscriptions AS B ON A.user_id = B.user_id
FULL OUTER JOIN plans AS C ON B.plan_id = C.plan_id;
```

BrightLearn SQL JOINS EXERCISE

BrightLearn SQL JOINS EXERCISE

Bonus Challenge

Now the conceptual test. Without writing any more SQL, answer these five questions from looking at the tables — they prove you really understand how the joins work and what they reveal about your data.

BONUS01

Which users have not subscribed to any plan?

WRITE YOUR SQL HERE

Kabelo and Lerato

BONUS02

Which subscriptions reference users that do not exist in the users table?

WRITEYOURSQLHERE

Subscription_id 504

BONUS03

BrightLearn · SQL Joins Exercise Page 17



BrightLearn ^{SQLJOINS} EXERCISE

Which shows have never been watched?

WRITEYOURSQLHERE

704: Cooking Lab and 706: Wild Earth

BONUS04

Which viewing sessions reference shows that do not exist?

WRITEYOURSQLHERE

704: Cooking Lab

BONUS05

Which plans have no subscribers?

WRITE YOUR SQL HERE

Plan_id:14 (Mobile)

BrightLearn · SQL Joins Exercise Page 18

BrightLearn SQL JOINS EXERCISE

BrightLearn · SQL Joins Exercise Page 19

BrightLearn SQL JOINS EXERCISE

Self-Check & Submission

Before you submit, walk through this checklist. The students who score highest are the ones who check their own work first — because half the learning happens in the verification.

★ BEFORE YOU SUBMIT — THE CHECKLIST

- **Every query runs without errors** on your SQL environment.
- **Output columns match the spec** — same names, same order.
- **INNER JOIN questions return fewer rows** than LEFT or FULL — confirm by counting.
- **LEFT JOIN results contain NULLs** where the right-hand match was missing.
- **FULL OUTER JOIN results show NULLs on both sides** for the unmatched rows.
- **Your bonus answers reference specific IDs** from the tables — e.g. "users 4 and 5", not just "some users".

WHAT TO SUBMIT

★ YOUR SUBMISSION PACK

- **One .sql file** containing all 15 queries, each clearly labelled (-- Q1, -- Q2, etc.).
- **Screenshots** of the result of each query (or paste-in text output).
- **Bonus answers** in a separate text file or at the bottom of the .sql file.
- **A short note** describing which SQL environment you used (PostgreSQL, SQLite, etc.).

★ ONE LAST THING

The fastest way to consolidate what you've learned is to explain it to someone else. After you submit, find a classmate or a friend and walk them through one INNER JOIN, one LEFT JOIN, and one FULL OUTER JOIN from this exercise. If you can teach it, you own it.



Three joins.