MATERIAL SAFETY DATA SHEET

For R&D use only. Not for drug, household or other uses.

Click http://www.lookchem.com/cas-685/68512-91-4.html for suppliers of this product.

Composition/Information on Ingredient

Cas:
68512-91-4
Code:
M

RTECS:

Code:
X

Name:
MIXED GAS (BUTANE)

Other REC Limits:
NONE SPECIFIED

OSHA PEL:
1800 MG/M3
Code:
M

OSHA STEL:

Code:

ACGIH TLV:
1900 MG/M3
Code:
M

ACGIHSTEL:
N/P
Code:

Control Measures

Respiratory Protection:
USE NIOSH/MSHA APPROVED RESPIRATOR. AIR-SUPPLIED OR FILTERING TYPE WITH ORGANIC VAPOR CARTRIDGES ARE RECOMMENDED.

Ventilation:
6 LOCAL AND MECHANICAL EXHAUST RECOMMENDED. AVOID OPEN ELECTRICAL SOURCES NEAR PRODUCT VAPOR AREAS.

Protective Gloves:
NEOPRENE, NITRILE, OR POLYVINYL ALCOHOL

Eye Protection:
USE CHEMICAL SAFETY GOGGLES FACESHIELD

Other Protective Equipment:
Equipment EYE WASH STATION SAFETY SHOWER.

Work Hygienic Practices:
DO NOT TAKE INTERNALLY. AVOID SKIN CONTACT. WASH SKIN AFTER USING PRODUCT. DO NOT EAT, DRINK OR SMOKE IN WORK AREA.

Supplemental Safety and Health:
NONE

Health Hazards Data

LD50LC50Mixture:
ORAL LD50 (RAT) IS UNKNOWN

Route Of Entry Inds - Inhalation:
YES

Skin:
YES

Ingestion:
YES

Carcinogenicity Inds - NTP:
YES

IARC:
YES

OSHA:
YES

Health Hazards Acute And Chronic:
ACUTE:INHALATION:CENTRAL NERVOUS SYSTEM DEPRESSION, HEADACHE, NAUSEA, DIZZINESS, FATIGUE, NARCOSIS, UNCONSCIOUSNESS, ASPHYXIATION. EYE:IRRITATION. SKIN:DEFATING, IRRITATION/DERMATITIS. INGESTION: GI D ISTURBANCES, NAUSEA, VOMITING. CHRONIC:DERMATITIS, PNEUMOTITIS, PULMONARY EDEMA, AND KIDNEY DAMAGE.

Explanation Of Carcinogenicity:
BENZENE IS LISTED AS A CARCINOGEN NTP, IARC, OSHA AND EPA.

Signs And Symptions Of Overexposure:
OVEREXPOSURE MAY LEAD TO RESPIRATORY IRRITATION, NAUSEA, FATIGUE, DIZZINESS, HEADACHES, UNCONSCIOUSNESS, AND EYE IRRITATION.

Medical Cond Aggravated By Exposure:
PERSONS WITH A SKIN DISORDER SHOULD USE CAUTION WHEN HANDLING OR USING THIS PRODUCT.

First Aid:
SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION PERSISTS. INHALATION: REMOVE TO FRESH AIR & RESTORE BREATHING IF NECESSARY. GET MEDICAL ATTENTION. EYE : IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. INGESTION: GET IMMEDIATE MEDICAL ATTENTION. DO NOT INDUCE VOMITING. NOTHING BY MOUTH IF UNCONSCIOUS.

Spill Release Procedures:
MINOR: ABSORB MATERIAL WITH CLAY, VERMICULITE, OR SIMILAR ABSORBENT MATERIAL. PLACE IN DISPOSAL CONTAINERS. MAJOR: DIKE & CONTAIN SPILL. ELIMINATE SOURCES OF IGNITION. SHUT OFF LEAKS. REMOVE LIQUID BY VACUUM OR ABSORBENT.

Neutralizing Agent:
NOT APPLICABLE

Waste Disposal Methods:
S WASTE MAY BE BURNED IN AN APPROVED INCINERATOR OR DISPOSED OF IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE AND FEDERAL LAWS AND REGULATIONS.

Handling And Storage Precautions:
STORE IN A COOL, VENTILATED WORK AREA. KEEP CONTAINERS CLOSED WHEN NOT IN USE. FLAMMABLE LIQUID; EMPTY CONTAINERS CAN BE HAZARDOUS.

Other Precautions:
THE SELECTION OF PERSONAL PROTECTIVE EQUIPMENT SHOULD BE MADE BY THE MATERIAL USER BASED ON THE PARTICULAR CONDITIONS WHERE THE MATERIAL IS TO BE USED TOGETHER WITH INFORMATION CONTAINED IN THIS MSDS.

Fire and Explosion Hazard Information

Flash Point Method:
PMCC

Flash Point:

Flash Point Text:
NOT GIVEN

Autoignition Temp:

Autoignition Temp Text:
495F

Lower Limits:
N/K

Upper Limits:
N/K

Extinguishing Media:
USE CARBON DIOXIDE, FOAM, OR DRY CHEMICAL. USE WATER FOG TO COOL SRROUNDING CONTAINERS.

Fire Fighting Procedures:
WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:
VAPORS HEAVIER THAN AIR AND MAY TRAVEL A CONSIDERABLE DISTANCE TO SOURCE OF IGNITION AND FLASH BACK.

Physical/Chemical Properties

HCC:
F2

NRC/State LIC No:
N/R

Net Prop WT For Ammo:

Boiling Point:

B.P. Text:
135F,57C

Melt/Freeze Pt:

M.P/F.P Text:
N/K

Decomp Temp:

Decomp Text:
UNKNOWN

Vapor Pres:
130 MMHG

Vapor Density:
3-4

Volatile Org Content %:

Spec Gravity:
0.77

VOC Pounds/Gallon:

PH: N/R

VOC Grams/Liter:

Viscosity:
N/K

Evaporation Rate & Reference:
7

Solubility in Water:
NIL

Appearance and Odor:
CLEAR LIQUID WITH CHARATERISTIC GASOLINE ODOR

Percent Volatiles by Volume:
100

Corrosion Rate:
UNKNOWN

Reactivity Data

Stability Indicator:
YES

Stability Condition To Avoid:
HIGH HEAT, OPEN FLAMES AND OTHER SOURCES OF IGNITION

Materials To Avoid:
STRONG OXIDIZING AGENTS

Hazardous Decomposition Products:
CARBON MONOXIDE, CARBON DIOXIDE AND OTHER HYDROCARBON COMPOUNDS DURING COMBUSTION.

Hazardous Polymerization Indicator:
NO

Conditions To Avoid Polymerization:
NOT APPLICABLE

Toxicological Information

Information:N/P

MSDS Transport Information

Information:N/P

Regulatory Information

Sara Title III Information: N/P

Federal Regulatory Information: N/P

State Regulatory Information: N/P

Other Information

Other Information:N/P

LookChem
Look for Chemicals
www.lookchem.com

For R&D use only. Not for drug, household or other uses.
WARRANTY
The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Lookchem shall not be held liable for any damage resulting from handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale.