



High sulphur vacuum distillate

Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 1/5/2009

Revision date: 8/8/2018

Version: 4.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Chemical type : Substance
Trade name : High sulphur vacuum distillate
EC-No. : 274-685-1
CAS-No. : 70592-78-8
REACH registration No : 01-2119485967-14-0022
Product code : 12010070
IUPAC name : Distillates (petroleum), vacuum
Chemical name : Distillates (petroleum), vacuum

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use
Industrial/Professional use spec : Manufacture of substance
Distribution of substance
Formulation & (re)packing of substances and mixtures
Use as an intermediate
Use as a fuel
Use of the substance/mixture : Intermediates, Fuels
Function or use category : Intermediates, Fuels

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

SLOVNAFT, a.s.
Vlčie hrdlo 1
824 12 Bratislava - Slovakia
T +421-(0)2/4055-1111 - F +421-(0)2/5859-9759
slovnaftreach@slovnaft.sk - www.slovnaft.sk

1.4. Emergency telephone number

Emergency number : Podnikový dispečing 1: ++0421(0)2/4055 3344
Podnikový dispečing 2: ++0421(0)2/4055 2244
fax: ++0421(0)2/4055 8047
E-mail: podnikovydispecing1@slovnaft.sk , podnikovydispecing2@slovnaft.sk

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals-24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	National Poisons Information Service (Belfast Centre) Royal Victoria Hospital	Grosvenor Road BT12 6BA Belfast	0344 892 0111	
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH Birmingham	0344 892 0111	
United Kingdom	National Poisons Information Service (Cardiff Centre) Gwenwyn Ward, Llandough Hospital	Penarth CF64 2XX Cardiff	0344 892 0111	
United Kingdom	National Poisons Information Service Edinburgh Royal Infirmary of Edinburgh	Little France Crescent EH16 4SA Edinburgh	0344 892 0111	
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	0870 243 2241	
United Kingdom	National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre, Wolfson Unit	Claremont Place Newcastle-upon-Tyne NE1 4LP Newcastle	0344 892 0111	

High sulphur vacuum distillate

Safety Data Sheet

according to Regulation (EU) 2015/830

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (inhalation:gas) Category 4	H332
Carcinogenicity, Category 1B	H350
Reproductive toxicity, Category 2	H361
Hazardous to the aquatic environment — Acute Hazard, Category 1	H400
Hazardous to the aquatic environment — Chronic Hazard, Category 1	H410

Full text of H statements : see section 16

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Hazard statements (CLP)

: H332 - Harmful if inhaled
H350 - May cause cancer (in contact with skin, inhalation, oral)
H361 - Suspected of damaging the unborn child
H410 - Very toxic to aquatic life with long lasting effects
H400 - Very toxic to aquatic life

Precautionary statements (CLP)

: P260 - Do not breathe dust, fume, gas, mist, spray, vapours
P281 - Use personal protective equipment as required

EUH-statements

: EUH066 - Repeated exposure may cause skin dryness or cracking

2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Substance type : UVCB

Name	Product identifier	%
High sulphur vacuum distillate	(CAS-No.) 70592-78-8 (EC-No.) 274-685-1 (REACH-no) 01-2119485967-14-0022	100
SN / 231-722-6 / sulfur	(CAS-No.) 7704-34-9 (EC-No.) 231-722-6 (EC Index-No.) 016-094-00-1 (REACH-no) 01-2119487295-27-0014	0,55 – 2,3

Full text of H-statements: see section 16

3.2. Mixtures

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

: Hydrogen sulphide (H₂S) can accumulate in the headspace of product storage tanks and reach potentially hazardous concentrations. Contact with hot product may cause severe thermal burns. Aspiration : not applicable due to the physical state of oxidized bitumen.

First-aid measures after inhalation

: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If casualty is unconscious and: Not breathing. Ensure that there is no obstruction to breathing and give artificial respiration by trained personnel. If necessary, give external cardiac massage and obtain medical advice. Breathing. Place in the recovery position. Administer oxygen if necessary. Obtain medical assistance if breathing remains difficult. If there is any suspicion of inhalation of H₂S (hydrogen sulphide). Rescuers must wear breathing apparatus, belt and safety rope, and follow rescue procedures. Remove casualty to fresh air as quickly as possible. Immediately begin artificial respiration if breathing has ceased. Provision of oxygen may help. Obtain medical advice for further treatment.

High sulphur vacuum distillate

Safety Data Sheet

according to Regulation (EU) 2015/830

First-aid measures after skin contact	: Remove contaminated clothing, contaminated footwear and dispose of safely. Wash affected area with soap and water. Seek medical attention if skin irritation, swelling or redness develops and persists. When using high-pressure equipment, injection of product can occur. If high-pressure injuries occur, immediately seek professional medical attention. Do not wait for symptoms to develop. For minor thermal burns, cool the burn. Hold the burned area under cold running water for at least five minutes, or until the pain subsides. Body hypothermia must be avoided. Do not put ice on the burn. Remove non-sticking garments carefully. DO NOT attempt to remove portions of clothing glued to burnt skin but cut round them. Seek medical attention in all cases of serious burns.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If irritation, blurred vision or swelling occurs and persists, obtain medical advice from a specialist. If hot product is splashed into the eye, it should be cooled down immediately to dissipate heat, under cold running water. Immediately obtain specialist medical assessment and treatment for the casualty.
First-aid measures after ingestion	: Do not induce vomiting. Ask for medical advice. Do not give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: irritation of the respiratory tract due to excess fume, mists or vapour exposure.
Symptoms/effects after skin contact	: dry skin. Irritation may arise in case of repeated or prolonged exposure. May cause burn in case of contact with product at high temperature.
Symptoms/effects after eye contact	: Slight eye irritation. May cause burn in case of contact with product at high temperature.
Symptoms/effects after ingestion	: few or no symptoms expected. If any, nausea and diarrhoea might occur.

4.3. Indication of any immediate medical attention and special treatment needed

Never use gasoline, kerosene or other solvents for washing of contaminated skin.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Foam (trained personnel only). Water fog (trained personnel only). Dry chemical powder. Carbon dioxide. Other inert gases (subject to regulations). Sand or earth.
Unsuitable extinguishing media	: Do not use direct water jets on the burning product. they could cause splattering and spread the fire. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

5.2. Special hazards arising from the substance or mixture

Hungarian fire hazard

5.3. Advice for firefighters

Protection during firefighting	: In case of a large fire or in confined or poorly ventilated spaces, wear full fire resistant protective clothing and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
Other information	: Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide. H ₂ S, SO _x (sulfur oxides) or sulfuric acid. unidentified organic and inorganic compounds.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment	: Small spillages: normal antistatic working clothes are usually adequate. Large spillages: full body suit of chemically resistant and antistatic material. if necessary heat resistant and insulated. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. gloves made of PVA are not water-resistant, and are not suitable for emergency use. If contact with hot product is possible or anticipated, gloves should be heat-resistant and thermally insulated. Work helmet. Antistatic non-skid safety shoes or boots. if necessary heat-resistant. Goggles and /or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory protection: a half or full-face respirator with filter(s) for organic vapours/H ₂ S, or a Self-contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
Emergency procedures	: Stop or contain leak at the source, if safe to do so. Avoid direct contact with released material. Stay upwind. In case of large spillages, alert occupants in downwind areas. Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages. The feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Eliminate all ignition sources if safe to do so (e.g. electricity, sparks, fires, flares. If required, notify relevant authorities according to all applicable regulations. When the presence of dangerous amounts of H ₂ S around the spilled product is suspected or proved, additional or special actions may be warranted, including access restrictions, use of special protection equipment, procedures and personnel training. If necessary dike the product with dry earth, sand or similar non-combustible materials. Let molten material cool naturally. Large spillages may be cautiously covered with

High sulphur vacuum distillate

Safety Data Sheet

according to Regulation (EU) 2015/830

foam, if available, to limit vapour cloud formation. Do not use direct jets. When inside buildings or confined spaces, ensure adequate ventilation.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent product from entering sewers, rivers or other bodies of water, or underground spaces (tunnels, cellars, etc.). Absorb spilled product with suitable non-combustible materials. Collect free product with suitable mechanical means. Collect recovered product and other materials in suitable tanks or containers for recovery or safe disposal. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. Product less dense than water: In case of small spillages in closed waters, contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities. Product which is denser than water will sink to the bottom, and usually no intervention will be feasible. If possible, collect the product and contaminated materials with mechanical means, and store/dispose of according to relevant regulations. In special situations (to be assessed on case-by case basis, according to expert judgement and local conditions), excavations of trenches on the bottom to collect the product, or burying the product with sand may be a feasible option.

6.3. Methods and material for containment and cleaning up

For containment : recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave/current direction and speed) may significantly influence the choice of appropriate actions. For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Concentration of H₂S in tank headspaces may reach hazardous values, especially in case of prolonged storage. This situation is especially relevant for those operations which involve direct exposure to the vapours in the tank. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. As H₂S has a density greater than ambient air, a possible exception may regard the build-up of dangerous concentrations in specific spots, like trenches, depressions or confined spaces. In all these circumstances, however, the correct actions should be assessed on a case-by-case basis.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Obtain special instructions before use. Ensure that all relevant regulations regarding handling and storage facilities of flammable products are followed. Keep away from heat/sparks/open flames/hot surfaces. Do not eat, drink or smoke when using this product. A specific assessment of inhalation risks from the presence of H₂S in tank headspaces, confined spaces, product residue, tank waste and waste water, and unintentional releases must be made to help determine controls appropriate to local circumstances. Avoid contact with the hot product. Avoid release to the environment. Take precautionary measures against static electricity. Ground/bond containers, tanks and transfer/receiving equipment. The vapour is heavier than air. Beware of accumulation in pits and confined spaces. Avoid contact with skin. Precautions should be taken to avoid skin burns when handling hot product. Use adequate personal protective equipment as required. For more information regarding protective equipment and operational conditions see Exposure scenarios. Do not breathe vapours. Ensure that proper housekeeping measures are in place. Contaminated materials should not be allowed to accumulate in the workplaces and should never be kept inside the pockets. Keep away from food and beverages. Wash the hands thoroughly after handling. Change contaminated clothes at the end of working shift.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Before entering storage tanks and commencing any operation in a confined area, check the atmosphere for oxygen content, hydrogen sulphide (H ₂ S) and flammability. Empty containers may contain flammable product residues. Do not weld, solder, drill, cut or incinerate empty containers, unless they have been properly cleaned.
Storage conditions	: Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store in a well-ventilated place.
Storage area	: Use and store only outdoors or in a well-ventilated area. Storage area layout, tank design, equipment and operating procedures must comply with the relevant European, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Store separately from oxidising agents.
Special rules on packaging	: If the product is supplied in containers: Keep only in the original container or in a suitable container for this kind of product. Keep containers tightly closed and properly labelled.
Packaging materials	: Recommended materials: For containers, or container linings use materials specifically approved for use with this product. Some synthetic materials may be unsuitable for containers or container linings depending on the material specification and intended use. Compatibility should be checked with the manufacturer.

High sulphur vacuum distillate

Safety Data Sheet

according to Regulation (EU) 2015/830

7.3. Specific end use(s)

Site documentation to support safe handling arrangements including the selection of engineering, administrative and personal protective equipment controls in accordance with risk-based management systems is available at each manufacturing site.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

High sulphur vacuum distillate (70592-78-8)		
EU	IOELV TWA (mg/m ³)	0.002 mg/m ³ benzo(a)pyrene
EU	IOELV STEL (mg/m ³)	0.01 mg/m ³ benzo(a)pyrene
SN / 231-722-6 / sulfur (7704-34-9)		
EU	IOELV TWA (mg/m ³)	10 mg/m ³ other fast aerosol
Slovakia	NPEL (priemerný) (mg/m ³)	10 mg/m ³ other fast aerosol

High sulphur vacuum distillate (70592-78-8)	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	4700 mg/m ³
Long-term - systemic effects, dermal	0.065 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	0.12 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	0.015 mg/kg bodyweight/day
PNEC	
PNEC (oral)	66.7 mg/kg/food : oral for predators

8.2. Exposure controls

Appropriate engineering controls	: Hydrogen sulphide may accumulate in the head space of storage tanks containing bitumen and can reach potentially hazardous concentrations. Monitoring procedures should be chosen according to the indications set by national authorities or labour contracts. Any comparison should be made only between data obtained with the same procedure. Storage and handling temperatures should be kept as low as feasible to minimize fume production. Where hot product is handled in confined spaces, effective local ventilation must be provided.
Personal protective equipment	: Gloves. Protective goggles. Protective clothing. Gas mask. Use of personal protective equipment must be consistent with good occupational hygiene practices.
Materials for protective clothing	: Protective clothing. Clothing to protect against heat and flame (EN 11612). Protective clothing. Protection against heat and flame. Limited flame spread materials, material assemblies and clothing (EN 14116).
Hand protection	: Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Gloves must be periodically inspected and changed in case of wear, perforations or contaminations.
Eye protection	: Chemical goggles or safety glasses. If splashing is likely, full head and face protection (protective shield and/or safety goggles) should be used.
Skin and body protection	: Wear fire/flame resistant/retardant clothing. Wear protective clothing for operations with hot material: heat resistant coveralls (with trousers legs over boots and sleeves over cuffs of gloves), heat resistant heavy duty antiskid boots (e. g. leather). Coveralls should be changed at the end of the work shift and cleaned as necessary to avoid transfer of product to clothes or underwear. For loading/unloading operations: wear safety helmet with integrated full face visor and neck protection.
Respiratory protection	: If exposure levels cannot be determined or estimated with adequate confidence, or an oxygen deficiency is possible, only SCBA's should be used



Thermal hazard protection	: Material handled at elevated temperature may cause thermal burns by contact with molten product.
Environmental exposure controls	: Store finished products in closed containers (e.g, bulk tanks, drums, cans). Incinerate, absorb, or adsorb vapours stripped from solution whenever necessary. Store all VOC-containing wastes in closed, secure containers (e.g, bulk tanks, intermediate bulk containers, drums). Carefully handle the substance to minimise releases.
Consumer exposure controls	: Site documentation to support safe handling arrangements including the selection of engineering, administrative and personal protective equipment controls in accordance with risk-based management systems is available at each manufacturing site.

High sulphur vacuum distillate

Safety Data Sheet

according to Regulation (EU) 2015/830

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	: Viscous.
Physical state	: Liquid
Colour	: Yellow. Dark yellow. Green-brown. Yellow-brown. Brown. Dark brown.
Odour	: oil-like odour.
Boiling point	: > 325 °C
Flash point	: 190 - 290 °C °C
Density	: 890 - 944 kg/m ³ at 20°C
Auto-ignition temperature	: > 250 °C
Viscosity, kinematic	: >= 40 mm ² /s at 50°C

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

This substance will float and can be reignited on surface water.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Contact with strong oxidizers (peroxides, chromates, etc.) may cause a fire hazard.

10.4. Conditions to avoid

They may be ignited by heat, sparks, static electricity or flames.

10.5. Incompatible materials

A mixture with nitrates or other strong oxidisers (e.g. chlorates, perchlorates, liquid oxygen) may create an explosive mass.

10.6. Hazardous decomposition products

No decomposition if stored normally.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Inhalation:gas: Harmful if inhaled.

High sulphur vacuum distillate (70592-78-8)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 inhalation rat (mg/l)	4.1 mg/l

SN / 231-722-6 / sulfur (7704-34-9)	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 inhalation rat (mg/l)	5430 mg/m ³

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation:	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer (in contact with skin, inhalation, oral).
Reproductive toxicity	: Suspected of damaging the unborn child.
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

High sulphur vacuum distillate (70592-78-8)	
Viscosity, kinematic	>= 40 mm ² /s at 50°C

SECTION 12: Ecological information

12.1. Toxicity

High sulphur vacuum distillate

Safety Data Sheet

according to Regulation (EU) 2015/830

High sulphur vacuum distillate (70592-78-8)

LC50 fish 1	79 mg/l
LC50 fish 2	0.1 mg/l
EC50 Daphnia 1	2 ml/l
EC50 Daphnia 2	0.27 mg/l
EC50 other aquatic organisms 1	0.75 ml/l

SN / 231-722-6 / sulfur (7704-34-9)

LC50 fish 1	< 5 µg/l
LC50 other aquatic organisms 2	< 5 mg/l
EC50 Daphnia 1	< 5 µg/l
EC50 Daphnia 2	< 100 mg/l

12.2. Persistence and degradability

High sulphur vacuum distillate (70592-78-8)

Persistence and degradability	Not easily bio-degradable (according to OECD-criteria).
-------------------------------	---

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Component	
High sulphur vacuum distillate (70592-78-8)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: DIRECTIVE 2008/98/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 19 November 2008 on waste and repealing certain Directives.
Waste treatment methods	: Contain and dispose of waste according to local regulations. External recovery and recycling of waste should comply with applicable local and/or national regulations. External treatment and disposal of waste should comply with applicable local and/or national regulations. Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended.
Sewage disposal recommendations	: Do not empty into drains; dispose of this material and its container in a safe way.
Waste disposal recommendations	: Clear up spills immediately and dispose of waste safely. Dispose of waste or used sacks/containers according to local regulations.
Additional information	: Clean up even minor leaks or spills if possible without unnecessary risk. (*) Hazardous waste according to Directive 91/689/EEC. The final user has the responsibility for the attribution of the most suitable code, according to the actual use(s) of the material, contaminations or alterations.
Ecology - waste materials	: hazardous waste. Avoid any discharge of the product into waste water. Disposal in high-temperature incinerator (> 1200 °C).

SECTION 14: Transport information


In accordance with ADN / ADR / IATA / IMDG / RID

ADR	RID	ADN	IMDG	IATA
14.1. UN number				
3082	3082	3082	3082	3082
14.2. UN proper shipping name				
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	Environmentally hazardous substance, liquid, n.o.s.
Transport document description				
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (DISTILLATES)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (DISTILLATES)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (DISTILLATES)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (DISTILLATES)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (DISTILLATES)

High sulphur vacuum distillate

Safety Data Sheet

according to Regulation (EU) 2015/830

ADR	RID	ADN	IMDG	IATA
(PETROLEUM), VACUUM), 9, III, (E)	(PETROLEUM), VACUUM), 9, III	(PETROLEUM), VACUUM), 9, III	(PETROLEUM), VACUUM), 9, III MARINE POLLUTANT/ ENVIRONMENTALLY HAZARDOUS	(PETROLEUM), VACUUM), 9, III
14.3. Transport hazard class(es)				
9 	9 	9	9 	9 
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes
14.6. Classification code :				
M6	M6	M6		
14.7. Hazard identification number (Kemler No.)				
90	90	9 + CMR (N1, N2, F or S)		
14.8. Additional information				
Tunnel restriction code (ADR) : E		Number of blue cones/lights (ADN) : 0	EmS-No. (Fire) : F-A EmS-No. (Spillage) : S-F	PCA packing instructions (IATA) : 964 CAO packing instructions (IATA) : 964
No supplementary information available				

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

High sulphur vacuum distillate is not on the REACH Candidate List

High sulphur vacuum distillate is not on the REACH Annex XIV List

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

3. Liquid substances or mixtures which are regarded as dangerous or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008	Distillates (petroleum), vacuum
28. Substances which appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 classified as Carcinogen category 1A or 1B (Table 3.1) or Carcinogen category 1 or 2 (Table 3.2) and listed as follows: Carcinogen category 1A (Table 3.1)/Carcinogen category 1 (Table 3.2) listed in Appendix 1 Carcinogen category 1B (Table 3.1)/Carcinogen category 2 (Table 3.2) listed in Appendix 2	Distillates (petroleum), vacuum

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL

of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC;

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006;

COMMISSION REGULATION (EU) No 605/2014 of 5 June 2014 amending, for the purposes of introducing hazard and precautionary statements in the Croatian language and its adaptation to technical and scientific progress, Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures;

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015, amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

High sulphur vacuum distillate

Safety Data Sheet

according to Regulation (EU) 2015/830

15.1.2. National regulations

Environmental Protection Act 1990 (as amended).

Health and Safety at Work Act 1974.

Consumers Protection Act 1987.

Control of Pollution Act 1974.

Environmental Act 1995.

Factories Act 1961.

Carriage of Dangerous Goods by Road and Rail (Classification, Packaging and Labelling) Regulations.

Chemicals (Hazard Information and Packaging for Supply) Regulations 2002.

Control of Substances Hazardous to Health Regulations 1994 (as amended).

Road Traffic (Carriage of Dangerous Substances in Packages) Regulations.

Merchant Shipping (Dangerous Goods and Marine Pollutants) Regulations.

Road Traffic (Carriage of Dangerous Substances in Road Tankers in Tank Containers) Regulations.

Reporting of Injuries, Diseases and Dangerous Occurrences Regulations.

Health and Safety (First Aid) Regulations 1981.

Personal Protective Equipment (EC Directive) Regulations 1992. Personal Protective Equipment at

Work Regulations 1992.

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

SDS changed items : SDS updated under EU Regulation. No.: 2015/830

Data sources : CONCAWE registration dossier.

Training advice : Before handling, storing or using the present substance for the first time, employees must be informed.

Full text of H- and EUH-statements:

Acute Tox. 4 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Carc. 1B	Carcinogenicity, Category 1B
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
H315	Causes skin irritation
H332	Harmful if inhaled
H350	May cause cancer
H361	Suspected of damaging fertility or the unborn child
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
EUH066	Repeated exposure may cause skin dryness or cracking

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product